

The background image shows a swimming pool with a light-colored tiled deck. A pergola with wooden posts is situated over the pool. The pool has a blue tile border and several circular tiles in the water. The scene is set outdoors with greenery in the background.

**BRICKFORM**

# ***Color Selection Guide***


- Color Hardener
- Overlay Colorants
- Antique Release
- Tinta' Seal
- Antique-It
- Refresh

***Defining Decorative Concrete***




# Color Selection Guide

## Top Sellers



Dover Blue + 625



Stone Gray + 615



Light Gray + 600



Medium Gray + 200



Dark Gray + 100



Ash White + 1030




Adobe Buff + 1080



Oyster White 250



Sun Buff + 1090



Smokey Beige 1010



Golden Sandstone 320




Cappuccino 735




Cream Beige 310



Sandy Buff 1070




Desert Tan + 350



Sunbaked Clay 515




Terra Cotta 700



Buff Tan 375



Brick Red + 550



Autumn Brown 425



Chestnut 400




Nutmeg 300



Walnut 810



Black 900




White 1000

For Technical Assistance  
1-800-483-9628

- Color Hardener
- Overlay Colorants
- Antique Release
- Tinta' Seal
- Antique-It
- Refresh




## Made to Order



Antique Rose 1020



Summer Beige 1035




Antique Cork 1050




Dusty Rose 525



Pecan 1060



Sandstone 325



Blush Beige 1015




Pecos Sand 1055




Copper Brown 1025



Saddle Brown 1085



Quarry Red 1065



Tile Red 500




Slate Green 825



Smokey Blue\* 650



French Gray 815



Federal Yellow 3100



Pool Blue\* 660

The colors shown are approximate representations only and Brickform does not guarantee that the final color will be an exact match. Application methods, jobsite conditions, texturing or finishing techniques such as brooming or troweling, the use of sealers, and slight color-drifts in raw materials are likely to produce variations of the colors. **The sample chips represented on this color chart were produced to compare to concrete with a flat troweled finish, sealed with BRICKFORM solvent-based sealer.**

\*Brickform Overlay Colorants not available in Smokey Blue and Pool Blue

NOTE: Tinta Seal and Refresh Color Packs are Made to Order only

+ Tinta' Seal colors that are available for use in Poly-Astic

*Defining Decorative Concrete Since 1971*

[BRICKFORM.COM](http://BRICKFORM.COM)



Prior to using Brickform products, refer to the current TIS and SDS available at [brickform.com](http://brickform.com) or by using the QR codes below.

### Color Hardener

Color Hardener is manufactured with the finest UV-resistant pigments and premium aggregates available. When properly applied and troweled into newly placed, fresh concrete, it forms a colored concrete surface that is resistant to weathering, wear, and normal abrasion.

- 90 to 120 ft<sup>2</sup> per 60 lb. bucket
- Improves abrasion resistance
- Hardens the concrete surface



### Antique Release

Antique Release is a hydrophobic powder that imparts color while serving as a bond breaker for stamping. It is made from a finely ground formula that creates beautifully antiqued concrete surfaces. During the stamping process, Antique Release is pressed into the concrete surface, creating a secondary coloring effect once washed off and sealed.

- 800 to 1000 ft<sup>2</sup> per 30 lb. bucket
- Bond breaker and Antiquing agent
- Fade-resistant



### Antique-It

Antique-It is a water-soluble antiquing agent designed to impart a secondary color or to highlight stamped concrete or textured overlays. Antique-It is easy to apply, dries fast, and provides a durable color that closely resembles the look of antique release powder. Use Antique-It on newly placed hardened concrete or to rejuvenate old unsealed stamped concrete.

- 2000 to 3000 ft<sup>2</sup> per 3 lb. container
- Unlimited effects and color combinations
- Dust free application



### Overlay Colorants

The Overlay Colorants are pre-measured bottles of Liquid Integral Colorants designed to add color to the base cement of SM Professional Grade, SM Pro PLUS and Stampable Overlay (SC-60, White Mix).



- 10 oz bottles
- Use 1 bottle per bag of Overlay
- 6 per case

\* Brickform Overlay Colorants not available in Smokey Blue and Pool Blue



### Tinta' Seal

Enhance and correct color with Tinta' Seal. Tinta' Seal mixes with Brickform solvent-based sealers to add opaque color to integrally colored, stamped, and overlaid concrete surfaces. Each pre-measured tint pack conveniently mixes in a 5-gallon pail of solvent-based sealer to create a tinted sealer.

- 1 bottle per 5 gal. of sealer
- Color matching available
- Compatible with Gem-Seal, Poly-Seal, Poly-Astic, and Gem Cure & Seal
- Not recommended for use with Gem-Guard SB
- **Made to Order Only**



### Refresh

Brickform Refresh is a solvent-based, semi-opaque stain used to impart color on unsealed, porous concrete and masonry surfaces. Refresh is great for correcting surface discoloration, upgrading existing concrete, or blending together multiple pours of integrally colored concrete. For added protection and color enhancement, Refresh can be sealed using spray-applied Brickform Gem-Seal or Poly-Seal.

- 1000-1500 ft<sup>2</sup> per 5 gal pail
- UV resistant
- Apply with acetone resistant sprayer
- **Made to Order Only**



WARRANTY: These products are not intended for public use and are intended for use by licensed contractors and installers, experienced and trained in the use of these products. They are warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of these products, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability. CAUTIONS • KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the appropriate Technical Data Sheet, Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Use only with a NIOSH approved respirator when using these products. Installation guidelines available at [brickform.com](http://brickform.com).

Distributed by:



**BRICKFORM®**  
A Division of Solomon Colors, Inc.  
4050 Color Plant Road, Springfield, IL 62702  
800-483-9628 • [brickform.com](http://brickform.com)  
An Employee-Owned Company  
©2024 Brickform. All rights reserved. Printed in U.S.A.