

SPECIFICATIONS

ENGINE

Engine Type	Kubota Diesel
Model Name	LX-1200 Engine with 3 cylinder, EPA Tier 4
Total Displacement	100.5 CU. IN.
Engine Power	25 HP
Rated Speed	2200 RPM
Low Idling Speed	1100 RPM

PERFORMANCE

Attachment Mounting System	CII (Common industry interface) or 2 Lever Quick Attach
Travel Speed (Fwd/Rev)	4.94 MPH
Ground Pressure (with Operator)	4.1 psi
Battery Capacity	12V, 60 AH
Auxiliary Hydraulic Flow	12 GAL/MIN
Auxiliary Hydraulic Pressure	2610 PSI

OPERATION

Driving Movement	Left hand dual axis hydraulic joystick.
Boom and Bucket	Right hand dual axis manual controls.
Attachment Control	Middle dual auxiliary controls.

SERVICE AND FILL CAPACITIES

Fuel Tank Capacity	9.25 gal
Hydraulic System	9.25 gal

DIMENSIONS

Overall Length (w/o Bucket)	76"
Overall Height	59"
Overall Width (w/o Bucket)	42"
Operating Weight (w/o Bucket)	3035 LBS
Rated Operating Capacity	1200
Tipping Load	2857 LBS
Wheelbase	42.9"
Hinge Pin Height	74.8"
Reach at Max Lift and 39° Dump	23.2"
Track Width	9"
Ground Clearance	14.9"
Angle of Departure	30°

LX - 1200 DIMENSIONS

