



LX-850

ENGINE

Engine Type	HONDA GX690
Model Name	Dual Cylinder (90° V type) 4 stroke forced air cooling.
Total Displacement	42.09 CU. IN.
Engine Power	25 HP
Rated Speed	3600 RPM
Low Idling Speed	2500 RPM

PERFORMANCE

Attachment Mounting System	CII (Common industry interface) or 2 Lever Quick Attach
Travel Speed (Fwd/Rev)	5.2 MPH
Ground Pressure (with Operator)	5.5 PSI
Battery Capacity	12V, 48 AH
Auxiliary Hydraulic Flow	11.3 GAL/MIN
Auxiliary Hydraulic Pressure	2610 PSI

OPERATION

Driving Movement	Left hand dual axis hydraulic joystick.
Boom and Bucket	Right hand dual axis manual controls.
Attachment Control	Middle dual auxiliary controls.

SERVICE AND FILL CAPACITIES

Fuel Tank Capacity	4.23 gal
Hydraulic System	5.82 gal



DIMENSIONS

Overall Length-Transport (W/STD Bucket Parallel to Ground)	94.5"
Overall Length (w/o Bucket)	67"
Overall Height	60.2"
Overall Width W/STD Bucket (S/T)	S: 39.3" T: 35.0"
Overall Width (w/o Bucket)	35"
Operating Weight (w/o Operator)	2426 LBS
Rated Operating Capacity	883 LBS
Tipping Load	2400 LBS
Wheelbase	28.5"
Hinge Pin Height	73.4"
Track Width	7.8"
Ground Clearance	S: 6.7" T: 5.5"
Angle of Departure	15°

