


ADVERTISING SPECIFICATIONS – PARTS MAGAZINE & DRAG SPECIALTIES MAGAZINE

PAGE SIZE: 8.375" x 10.875"

Revised June 2026



AD SIZE	Trim	Bleed	Safety	Non-Bleed
Two-Page Spread	16.75 x 10.875"	17 x 11.125"	16.25 x 10.375"	16.25 x 10.375"
Full-Page	8.375 x 10.875"	8.625 x 11.125"	7.875 x 10.375"	7.375 x 9.875"
1/2 Page	8.375 x 5.25"	8.625 x 5.5"	7.875 x 4.75"	7.375 x 4.875"
1/3 Page	2.75 x 10.875"	3 x 11.125"	2.25 x 10.375"	2.5 x 10.375"
1/4 Page	4 x 5.25"	4.25 x 5.5"	3.5 x 4.75"	3.5 x 4.875"

NOTE: Dimensions are always stated in standardized width (first) x height (second).

AD SIZE DEFINITIONS

Trim – The edge of the page, or the final visible borders of a 'bleed' ad.

Bleed – .125" on each side beyond the trim measurement of a 'bleed' ad. (That is, add .25" overall to the trim measurements.) Elements that touch the trim edge should extend at least .125" beyond trim on each side. The bleed area will be "trimmed off" in print.

Safety – Also commonly referred to as "Live Area", this is measured as .25" inside of trim on each side of a 'bleed' ad. (That is, subtract .5" overall from both the width and height trim dimensions.) This is considered the 'safe' area for critical content. All critical image, graphic and text elements not intended to bleed should be within this measurement. Artwork elements beyond the safety area risk being trimmed in the printed issue.

Non-Bleed – Non-bleed ads do not reach the trim edges of the magazine and therefore have white margins around all sides in the printed issue. The above aspects of "bleed" and "safety" do not apply to non-bleed advertisements.

DIGITAL AD FILE REQUIREMENTS

Parts Magazine and Drag Specialties Magazine are produced entirely in a digital format and are printed using state of the art computer-to-plate technology.

- » Accepted file formats: PDF (highly preferred). Other formats: EPS or TIF (w/compression).
- » Unacceptable file formats: JPG and native application formats such as QuarkXpress, InDesign, Illustrator, Photoshop, all Microsoft file formats, etc.
- » Spread ads should be submitted as a single file at "Two-Page Spread" dimensions. Do not split the file into two separate pages.
- » Please check that all images in the ad file are high-resolution (300ppi).
- » Fonts must all be embedded or else outlined (with vector artwork) or rasterized.
- » Convert all RGB color mode images and spot colors to CMYK color mode for 4-color process. Any non-CMYK colors included in the file will be automatically converted to CMYK.
- » Total ink density should not exceed 300%. Do not use "Registration" color in the artwork!
- » Trapping is the responsibility of the file provider.
- » Please include crop marks in your ad file. Crop marks should have an offset of .125".

NEW PROOF FILE REQUESTED

To help us ensure that your ad file is received intact and is printed as expected, we ask that you please also include a secondary "proof" file along with your ad file submission as follows:

- » JPG file format only. No other formats.
- » Screen resolution (72ppi) is sufficient.
- » Be sure to include the word "PROOF" in the filename to avoid any confusion.

Thank you! We will cross-check your ad file with your proof for any potential concerns.

QUESTIONS & SUBMISSION INFO

Contact: Jen Rose
 Phone: 949-813-8104
 Email: jen@emdebooks.com

Ad artwork and proof file may be submitted via email, or through our FTP site.

FTP FILE UPLOAD INSTRUCTIONS

Upload files at:
<https://www.hightail.com/u/PartsMagazine>