

Sunrise® Dot On

Clear or White Dot Removable Adhesive Vinyl



Sunrise® Dot On Vinyl has a unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation. Available in clear matte, clear gloss, white matte and white gloss finishes. Sunrise® Dot On Vinyl is commonly used for window graphics but can also be used for short-term indoor applications such as wall graphics, trade show graphics or retail graphics that require seasonal change out.

Sunrise® Dot On Vinyl is a 100µ (4 mil) printable monomeric PVC film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. Sunrise® Dot On Vinyl is available in clear matte, clear gloss, white matte and white gloss finishes.

Typical Application

- General Signage
- Retail Promotions
- Window Graphics

Ideal for indoor and short term outdoor promotion, easy tool & bubble free application, and can be removed easily within 12 months, prop 65 compliant.

Product Structure

Film	Clear Matte, Clear Gloss, White Matte or White Gloss Monomeric PVC
Adhesive	Dot Pattern Removable Polyacrylate
Release Liner	140 gsm 1 Side Siliconised PE Coated Kraft

Product Characteristics


Film Thickness	4 mil (100µ)	4.5 mil (113µ)
Adhesive Layer	0.5 mil (13µ)	(113µ)
Film/Adhesive Ratio	4:0.5	
UV Protection Factor	Not Applicable	
Outdoor Durability	Short Term	
Application Temperature	> 41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Fire Rating	B1 (DIN 4102-1) PASS (CAN/ULC-S102)	
Shelf Life	1 Year	
Storage Conditions	64°F to 77°F (18°C to 25°C) 40-65% Relative Humidity	

Installation Recommendations

Please see Sunrise® Dot On Vinyl installation instructions for further details. The surface must be clean and smooth and free of defects before application.

Certified for
HP Latex Inks

4 mil Clear or White Monomeric PVC
Matte or Gloss



Important Note:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Sunrise_{MPC} is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Sunrise_{MPC} at one of the phone numbers listed below.

Overlamine Recommendations

When using Sunrise® Dot On Vinyl, an overlamine can be used for maximum life expectancy. Products recommended for use with Sunrise® Dot On Vinyl are Sunrise_{MPC} overlamines.



LUX

Wide Format Everything!

905-760-7623 TF 800-416-3996

www.luxonline.ca