Sunrise® Reli-A-Lam Lustre



Sunrise® Reli-A-Lam Lustre is a 3 mil (75µ) monomeric soft calendared PVC laminating film with a lustre finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

Typical Application

- POP Displays •
- Architectural Renderings •
- Promotional Displays
- Event Signage •

Low sheen without loss of contrast or sharpness makes it effective for a wide range of applications.

Product Structure

Film	Lustre Monomeric Soft Calendered PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Sided PE Coated, 1 Side Siliconized Kraft

Product Characteristics

Film Thickness	3 mil (75µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	3:1
UV Protection	Yes
Outdoor Durability	5 Years (Ink Dependant)
Fire Rating	Class 0
Application Temperature	-4°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C) 50-55% Relative Humidity

Process Settings

Equipment Type & Temperature

Roller Laminator	
Room temperature to 104 °F	1ft to 8ft (0.3m to 2.5m) per minute
(40°C)	

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Sunrise_{MPC} is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Sunrise_{MPC} at one of the phone numbers listed below.

