

Sunrise® WallTac Jr. Premium Repositionable Adhesive White Vinyl



A 75 micron, printable white polymeric PVC film coated on one side with Sunrise® ultra removable adhesive. With Sunrise® adhesive technology, there is no need to worry about surface damage during graphic removal. Sunrise® WallTac Jr. Premium Vinyl can be removed and repositioned multiple times without a decrease in bond strength. It has a Class 0 fire rating, making it ideal for use on most indoor surfaces and for applications in public areas that require compliance with strict fire regulations, such as airports, hotels and hospitals.

Sunrise® WallTac Jr. Premium Vinyl is a 75µ (3 mil) printable gloss or matte white, phthalate-free polymeric PVC film, coated on one side with Sunrise® ultra removable adhesive. The adhesive is protected by a single-sided, siliconised PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. Sunrise® WallTac Jr. Premium Vinyl can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

Typical Application

- Smooth Flat Surfaces
- Point of Sale Graphics
- Interior Decor
- Decals & Stickers

Ideal for interior promotions, perfect for application in public areas that require compliance with strict fire regulations. Suitable for use on most indoor surfaces, painted walls, melamine, glass, and low surface energy substrates.

Product Structure

Film	Matte or Gloss White Polymeric PVC
Adhesive	Sunrise® ultra removable and re-positionable adhesive technology
Release Liner	88# (143gsm) 1 Side Siliconized PE Coated Kraft Paper

Product Characteristics

Film Thickness	3 mil (75µ)	3.7 mil (93µ)
Adhesive Layer	0.7 mil (µ)	(93µ)
Outdoor Durability	5 Years; 2 Years Removability	
Application Temperature	>41°F (5°C)	
Service Temperature Range	40°F to 120°F (4.4°C to 48.9°C)	
Flame Ratings	Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C) 50-55% Relative Humidity	

Installation Recommendations

The surface must be clean and smooth and free of defects before application.

Recommended for curved, textured or angled surfaces where conformability is a priority.

Overlamine Recommendations

When using Sunrise® WallTac Jr. Premium Vinyl, an overlaminate can be used for maximum life expectancy. Products recommended for use with Sunrise® WallTac Jr. Premium Vinyl are Sunrise_{MPC} overlaminates.

3 mil White Phthalate-Free Polymeric PVC Matte or Gloss

(Eco) Solvent
Latex
UV

Sunrise® Ultra removable and re-positionable adhesive

Widths up to 54 in

Years Durability

5

Interior & Exterior
(2 Year Removability Exterior)

Certified for
HP Latex Inks

Important Note:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Sunrise_{MPC} is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Sunrise_{MPC} at one of the phone numbers listed below.



LUX

Wide Format Everything!

905-760-7623 TF 800-416-3996

www.luxonline.ca