

Sunrise® WallTac Premium

Repositionable Adhesive White Vinyl



Our 6 mil (150µ), white polymeric printable PVC film with Sunrise® WallTac Premium removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned. Dimensionally stable, Sunrise® WallTac Premium Vinyl can be applied and re-positioned multiple times without stretching or tearing. And, with Sunrise® on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed. Sunrise® WallTac Premium Vinyl has a Class 0 Fire Rating for surface spread of flame, making it perfect for application in public areas that require compliance with strict fire regulations, such as airports, hotels, and hospitals

Sunrise® WallTac Premium Vinyl is a 6 mil (150µ) printable white, phthalate-free polymeric PVC film, coated on one side with Sunrise® removable adhesive. The adhesive is protected by a single-sided, siliconized PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. Sunrise® WallTac Premium Vinyl can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

Typical Application

- Smooth flat surfaces
- Point of Sale graphics
- Interior Decor
- Decals & Stickers

Installation Recommendations

- Ideal for interior wall graphic applications
- Perfect for application in public areas that require compliance with strict fire regulations
- Can be removed without leaving adhesive residue
- Ideal for removable wall decals, appliques, and wall murals
- Suitable for use on most indoor surfaces, painted walls, melamine, glass, and low surface energy substrates


Product Structure

Film	Matte or Gloss White Polymeric PVC
Adhesive	WallTac® ultra removable and re-positionable adhesive technology
Release Liner	88# (143gsm) 1 side siliconized PE coated Kraft paper


Product Characteristics

Film Thickness	6 mil (150µ)	6.9 mil
Adhesive Layer	0.9 mil (22µ)	(172µ)
Outdoor Durability	5 years; 2 years removability	
Application Temperature	>41°F (5°C)	
Service Temperature Range	20°F to 120°F (-6.7°C to 48.9°C)	
Application Temperature	> 41°F (5°C)	
Flame Ratings	Class 0 (BS 476- Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C) 50-55% Relative Humidity	


6 mil White Phthalate-Free Polymeric PVC Matte or Gloss



(Eco) Solvent Latex UV



Sunrise® ultra removable and re-positionable adhesive



Widths up to 61 in

Years Durability

5

Interior & Exterior
(2 Year Removability Exterior)

Important Note:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Sunrise_{MPC} is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Sunrise_{MPC} at one of the phone numbers listed below.

Overlamine Recommendations

When using Sunrise® WallTac Premium Vinyl, an overlamine can be used for maximum life expectancy. Products recommended for use with Sunrise® WallTac Premium Vinyl are Sunrise_{MPC} overlaminates.



LUX

Wide Format Everything!

905-760-7623 TF 800-416-3996

www.luxonline.ca