H&S Manufacturing

A Broadcast Sprayer That is Field Tested... Farmer Approved.



"Head and Shoulders above the rest."




1-800-769-2767

32506 430th Street NW, Stephen, MN 56757 Phone: 218-478-2229 Fax: 218-478-3683

www.hsmfginc.com

Broadcast Sprayer








- **A.** Mix 'n Fill Cone 15 or 35 gallon on parallel linkage for lowering when filling.
- **B.** Bottom fill for main tank and rinse tank
- **C.** Inline filters optional.
- D. Electric ball valves. Fittings are flanged with O-Rings. Flow back manifold.
- E. Optional Raven Regulator and Flow Meter
- **F.** Optional electric agitation
- **G.** Optional 200 gal. boom and tank rinse.





I. Optional rate controller

H. Standard Ace 150 hyd. pump

J. Clean outs are standard for complete rinsing of boom

- **K.** Urethane cushion wing
- **L.** Superior boom construction for years of service. Available in 90 ft. to 150 ft. widths.
- M. Wet booms available in aluminum or stainless steel 3/4" & 1" sizes
- **N.** Optional spring loaded touch down wheels. (Not shown)
- **O.** Large safety platform with fold-up steps.
- **P.** 380/90Rx50 or optional 380/90Rx46 tire with large hub and spindle for optional dual extensions.
- **Q.** Self-leveling boom uses a hydraulic accumulator along with shocks and spring to insure a smooth and level ride.
- **R.** Electric over hydraulic banks.
- **S.** All cylinders are ORB fittings, 3,000 PSI and with nitro-steel shafts.