

20 SERIES

Flows: 0.84 to 7.13 gpm (191 to 1619 L/min)
 Pressures: 25 to 50 psi (1.72 to 3.45 bar)



2009HS IMPACT SPRINKLER (/NODE/64971)

2009HS SPRINKLER DESIGN CRITERIA	psi				
	30	35	40	45	50
#6 Nozzle - Gold (3/32")					
Flow (gpm)	1.34	1.45	1.55	1.64	-
Diameter at 1.5 ft ht (ft)	58	60	62	64	-
#7 Nozzle - Lime (7/64")					
Flow (gpm)	1.84	1.99	2.12	2.25	2.37
Diameter at 1.5 ft ht (ft)	60	62	64	66	67
#8 Lavender (1/8")					
Flow (gpm)	2.42	2.62	2.79	2.97	3.12
Diameter at 1.5 ft ht (ft)	62	64	66	68	69
#9 Nozzle - Grey (9/64")					
Flow (gpm)	3.08	3.33	3.56	3.78	3.98
Diameter at 1.5 ft ht (ft)	64	66	68	70	71

Sprinkler performance may vary with actual field conditions. Stream heights range from 1.5 to 3.0 ft above the nozzle based on pressure and nozzle size. Minimum recommended riser height is 1.5 ft.