



# VN-4KUHD55

Server TV Monitor



### Features:

- 4K Ultra-HD resolution
- Using tamper-proof metal housing
- Suitable for continuous 24/7 operation
- Slim 8mm narrow bezel design
- Built-in 3D COMB filter and 3D Noise Reduction
- 6ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience

- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterupted viewing angle
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Support multiple signals, such as HDMI, DP, VGA, USB multimedia, Audio, RS232



### Technical Specification

#### Model

Model	VN-4KUHD55
-------	------------

#### Display

Screen Size	55"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	450cd/m <sup>2</sup>
Contrast	1000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	6ms
Refresh Rate	60Hz

#### Signals

Input	DP 1.2×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

#### General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	<170W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	25.2kg (55.6lb)	
Gross Weight	35kg (77.2lb)	
Bezel Width	8mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1227.2×699.6×65.0mm (48.3"×27.5"×2.6")	
Package(W×H×D)	1410×875×255mm (55.5"×34.4"×10.0")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%~85%

#### Accessory

Standard	HDMI cable, power cable, hanging bracket, remote control
Optional	Pedestal