



VN-LIUT2.61

LED Display Units



Features :

- 1000x500mm, 750x500mm and 500x500mm panel to match your design.
- Support hanging , stacked, wall-mounted, adaptng to diverse environments.
- Modules and PSU can be taken from the front totally.
- Dot by dot calibration ensures color richness and brightness uniformity.



Technical Specification

Model

Model	VN-LIUT2.61
-------	-------------

Parameters

Pixel Pitch	2.604mm
Pixel Configuration	1R1G1B
LED Type	SMD1515
Brightness (Max)	1000 nit
Color Temperature	3500K-9000K (adjustable)
Viewing Angle	H160° / V160°
Pixel Density	147,456 dots/m ²
Module Size	250mm×250mm
Module Resolution	96x96 dots
Cabinet Size	W1000mm×H500mm×D33mm
Cabinet Resolution (W×H)	384×192 dots
Cabinet Weight	10.0 kg ± 0.5
Cabinet Material	Die-casting Aluminum

Operating Temperature/ Humidity	-20°C~+50°C/10~80%RH
Storage Temperature/ Humidity	-30°C~+60°C/10~80%RH
IP Rating	Front IP20/Rear IP20
Aspect Ratio	2:1
Gray Scale	14 bit
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 110~220V (+/-10%)
Input Power (max)	400 W/m ²
Input Power (Avg)	120 W/m ²
Installation	Wall Mounted/Floor Mounted/Hanging
Maintenance	Front Maintenance
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)