Single-use Surgical Mask



BYD CARE 🧡

Product Model

FLAT FE2811

Product Introduction

BYD Single-use Surgical Mask consists of three layers of nonwoven material:

Outer Layer Polypropylene spunbond nonwoven fabric

- Middle Layer Polypropylene melt-blown nonwoven
- Inner Layer
 Polypropylene spunbond
 nonwoven fabric

MATERIALS

- Inner layer Middle layer Outer layer Ties Nose clip
 - Polypropylene melt-blown nonwoven Polypropylene spunbond nonwoven fabric Polypropylene spunbond nonwoven fabric Metal wire with plastic covering

Polypropylene spunbond nonwoven fabric

This device is not made with natural rubber latex. Non-sterile product. One-time use only.

Wearing directions



1. Ensure the side with nose clip is facing upwards before applying the mask to your face.

BYD




2. Before applying the mask to your face, make sure the white side of the mask is facing towards your face while the colored side facing outwards.



3. Pick up the mask by the upper ties, place the ties around the back of your head and attach them together with a bow.





5. Then take the bottom ties, one in each hand, and secure with a bow at the nape of your neck.



6. Once the mask is completely secured, adjust it to ensure it covers your face and mouth, and so the bottom edge is under your chin.

Single-use Surgical Mask


SOFT & EASY TO BREATHE (Non-sterile)

BYD

Indications for Use

The Single-use Surgical Masks (Model: FLAT FE2811) are intended to be worn to protect both the patient and healthcare personnel from transfer of microorganisms, body fluids and particulate material. These face masks are intended for use in infection control practices to reduce the potential exposure to blood and body fluids.

This is a single use, disposable device(s), provided non-sterile.



Product Information

Name		Parameter	
Product name		Single-use Surgical Mask	
		Polypropylene spunbond nonwoven fabric (for surgical use), polypropylene melt-blown nonwoven, metal wire with plastic covering nose clip, Polypropylene spunbond nonwoven fabric ties	
Product model		FLAT FE2811	
Size	175 mm×95 mm / 6.89in.×3.74in.		
Expiration date		2 years after production	
Packaging specification10pcs/bag; 50pcs/box; 1000pcs/case		ase	
Storage		Store in a dry, clean environment with room temperature	
BFE ≥ 98% PI	PFE ≥ 98%	Flammability: Class I	The masks are tested according to the ASTM F-2100 and 16 CFR-1610 standard.
DIE > 30/0 11	1 2 2 30 70	rannability. Class r	The masks are rested according to the ASTMT-2100 and 10 cm -1010 standard.

- 1 The mask does not eliminate the risk of contracting any diseaseor infection.
- 2 Failure to properly use and maintain this product could result in illness or even death.
- 3 Only for one-time use, please destroy and dispose according to regulations after use.
- 4 Please use within the validity period.

5 DO NOT use if package is damaged.6 Please refer to the instructions before use.7 For adult use only.

Time use limitation

If the mask becomes damaged, soiled, or breathing becomes difficult, leave the contaminated area and replace and refit with a new mask.

Important notice

To the extent permitted by law, BYD shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by BYD. Nothing in this statement will be deemed to exclude or restrict BYD's liability for death or personal injury arising from its negligence.

All information presented in this document is based on the latest data available at the time of printing. BYD reserves the right to make changes at any time without prior notice.

YY 0469-2011 standard

ASTM F-2100 Level III

Distributed by Bigfoot Inc. 7378 W Atlantic Blvd #210 Margate, FL 33063 www.BigfootPPE.com Made in China

