

# MFCF330 Multi-functional system



**ANKASH**  
Solutions, LLC

# ANKASH MFCF330 Multi-functional system

A growing segment in the printing industry is packaging. Labels are a key application that is produced in the packaging segment. These high attention seeking labels are used extensively in industries such as beverage, wine & alcohol, pharmaceutical, consumer food products, home electronics, toys and more. The robust Ankash MFCF330 multi-functional system offers a standard overprint by flexo, varnish protection, cut, slit and rewind all in one pass, making the most complex label production seem very simple.

Offered in 3 widths of 330, 420 and 520 mm widths, our MFCF330 Multi-functional system are built keeping complex label finishing and high productivity in mind. Optional features such as platform for an ink-jet station for variable data overprinting, hot/cold laminate to protect the print, cold stamping to decorate, or sheet the label can further enhance the value of your label. For your most demanding label production, deploy the MFCF 330 and offer your customers the high value, high quality labels they desire.

## Specification

	MFCF 330	MFCF 420	MFCF 520
Web feed width (max.)	330 mm	420 mm	520 mm
Unwind diameter (max.)	700 mm	700 mm	700 mm
Rewind diameter (max.)	700 mm	700 mm	700 mm
Machine speed (max.)	60 m/min.	60 m/min.	60 m/min.
User interface	Touch screen	Touch screen	Touch screen
Options	Platform for inkjet head, UV flexo press unit, Double shaft laminator, Hot lamination system, Slitting, Sheeting	Platform for inkjet head, UV flexo press unit, Double shaft laminator, Hot lamination system, Slitting, Sheeting	Platform for inkjet head, UV flexo press unit, Double shaft laminator, Hot lamination system, Slitting, Sheeting
Dimensions (LxWxH)	3,600 x 1,200 x 1,500 mm	3,600 x 1,200 x 1,500 mm	3,600 x 1,200 x 1,500 mm
Weight	3,000 kgs.	3,000 kgs.	3,000 kgs.
Power supply			
–Main machine power	13 kw	9.5 kw	12 kw
–Operational power	AC, 380V, 50 Hz, 3 phase (4 wire system)	AC, 380V, 50 Hz, 3 phase (4 wire system)	AC, 380V, 50 Hz, 3 phase (4 wire system)
Desired environment			
–Temperature			
–Relative humidity	Upto 32°C / 90°F 20–60%	Upto 32°C / 90°F 20–60%	Upto 32°C / 90°F 20–60%



8, Sparrow Dr., W. Henrietta, NY-14586, USA  
Email: info@ankash.com URL: www.ankash.com

**Marketed by**  
<Dealer name>  
<Address>  
<City>, <State>, <Postal code>, <Country>