



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

MOLY-SPRAY™ DRY FILM LUBRICANT Safety Data Sheet

SECTION 1: IDENTIFICATION

Manufacturer: Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131
Phone: 847-455-2300
Toll Free: 800 991-1106
Web: antiseize.com

Information Phone Number:

Emergency Phone Number: Infotrac 24/7 Phone: 1-800-535-5053 or 352-323-3500

Product Use: Dry film lubricant

Restriction on Use: Use only as directed

SDS Date of Preparation: February 13, 2018

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification (Hazcom 2012):

Extremely Flammable Aerosol Category 1

Gases Under Pressure – Compressed Gas

May cause damage to organs through prolonged or repeated exposure.

May cause serious Eye Irritation

May cause drowsiness or dizziness

Label Elements:



DANGER!

Hazard Phrases:

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness

Precautionary Phrases:**Prevention**

If medical advice is needed have product container or label on hand.
Read Label before use.
Wash thoroughly after handling.
Wear protective gloves, eye and face protection.
Avoid breathing mist or spray.
Use only outdoors or in a well-ventilated area.
Take off contaminated clothing and wash it before reuse.
Keep out of reach of children.
Read label before use
Keep away from heat, sparks, open flames or hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell

Storage

Store in a well-ventilated place.

Store locked up.

Protect from sunlight.

Disposal

Dispose of contents in accordance with local, regional and national regulations.

Other Hazards: None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Acetone	67-64-1	40-70
Isopropyl Alcohol	67-63-0	15-30
Glycol Ether EP	2807-30-9	8-15
Propane	74-98-6	15-25
Butane	106-97-8	5-15

The specific identity and/or exact percentage of composition has been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

Eye: Immediately flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: In case of contact, wash thoroughly with plenty of water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention.

Most Important symptoms and effects, both acute and delayed: Causes eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention required for ingestion.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Extremely flammable aerosol. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling: Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not smoke while using.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight. Do not store in subfreezing conditions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Propane	1000 ppm TWA OSHA PEL
Butane	1000 ppm STEL ACGIH TLV
Acetone	500 ppm TWA ACGIH TLV 750 ppm STEL ACGIH TLV 1000 ppm TWA OSHA PEL
Isopropyl alcohol	200 ppm TWA ACGIH TLV 400 ppm STEL ACGIH TLV 400 ppm TWA OSHA PEL

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits .

Individual Protection Measures:

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin Protection: Impervious gloves such as nitrile recommended where needed to avoid skin contact .

Eye Protection: Safety goggles recommended where needed to avoid eye contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Aerosol	Vapor Density (air = 1): Not determined
Odor: mild aromatic	Specific Gravity: 0.7
Odor Threshold: Not established	Water Solubility: Not soluble
pH: Not determined	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: Not available	Autoignition Temperature: Not available
Boiling Point: -47 °F (-44°C)	Decomposition Temperature: Not available
Flash Point: -2 °F (propellant) (-19°C)	Viscosity: Not available

Evaporation Rate: Not available	Explosion Properties: None
Flammable Limits: LEL: 1.5 % UEL: 12.0 %	Oxidizing Properties: Not oxidizing
Vapor Pressure: 233 hPa@20°C	Aerosol Fire Protection Level: Level 2 Aerosol (NFPA 30B)
VOC Content: 46.9%	Flammability (solid, gas): Extremely flammable

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Keep away from heat, sparks, flames and other sources of ignition. Dropping containers may cause bursting.

Incompatible Materials: Avoid strong oxidizing agents and acids. Concentrated oxygen.

Hazardous Decomposition Products: Thermal decomposition may produce carbon dioxide, carbon monoxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Potential Health Effects:

Eye: Causes serious eye irritation.

Skin: Contact may cause irritation and drying of the skin.

Inhalation: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Ingestion: If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Hazards: None known.

Carcinogen Status: Isopropyl Alcohol, IARC Group 3 - not classifiable

Acute Toxicity Values:

Isopropyl alcohol: Oral rat LD50: 5840 mg/kg, inhalation rat LC50 > 10000 ppm/6hr, dermal rabbit LD50: 16.4 ml/kg

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity:**

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available.

Mobility in Soil: No data available

Other Adverse Effects: None known

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, regional and national regulations. Do not puncture or incinerate containers. When contents are depleted, continue to depress button until all gas is expelled.

SECTION 14: TRANSPORT INFORMATION

DOT Proper Shipping Name: UN1950, Aerosols, 2.1, Limited Quantity

DOT Technical Name: None

DOT Hazard Class: 2.1

UN Number: UN1950

DOT Labels Required (49CFR172.101): LTD QTY

IMDG Shipping Description: UN1950, Aerosols, 2.1, FP -17 C, Limited Quantity,

ID Number: UN1950

Hazard Class: 2.1

Packing Group: None

Labels Required: None

Marking Required: Limited Quantity Mark

Placards Required: Limited Quantity and Marine Pollutant Marks On Transport Containers

SECTION 15: REGULATORY INFORMATION


Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ:

SARA Hazard Category (311/312): Fire Hazard, Pressure Hazard, Acute Health

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: isopropyl alcohol

EPA TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65:  This product can expose you to Ethyl Benzene a chemical know to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SECTION 16: OTHER INFORMATION

Revision Summary: New format to comply with OSHA Hazcom 2012

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.