

SAFETY DATA SHEET

A-7480S v2.0
en/US



1. Identification of the substance/mixture and of the company/undertaking

Product name	DuPont Acrylic Clear	
Product code	A-7480S	061218
Intended use	Coating for professional use	
	Axalta Coating Systems, LLC Applied Corporate Center 50 Applied Card Way Suite 300 US Glen Mills PA 19342	
Telephone	Product information	(800) 438-3876
	Medical emergency	(855) 274-5698
	Transportation emergency	(800) 424-9300 (CHEMTREC)

2. Hazards identification

This preparation is hazardous per the following GHS criteria

GHS-Classification

Flammable liquids	Category 1
Serious eye damage/eye irritation	Category 1
Respiratory sensitisation	Category 1
Skin sensitisation	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B

Endpoints which are "not classified", "cannot classified" and "not applicable" are not shown

GHS-Labeling



Hazard symbols

Signal word

Danger

Hazard statements

Extremely flammable liquid and vapour.
Causes serious eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.

Precautionary statements

Contaminated work clothing should not be allowed out of the workplace.
Ground/bond container and receiving equipment.
In case of inadequate ventilation wear respiratory protection.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Obtain special instructions before use.
Take precautionary measures against static discharge.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/ vapours/ spray.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician.

SAFETY DATA SHEET

A-7480S v2.0
en/US



IF exposed or concerned: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/ attention.
Immediately call a POISON CENTER or doctor/ physician.
Specific treatment (see supplemental first aid instructions on this label).
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to .?.

Other hazards which do not result in classification

May produce an allergic reaction. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

3. Composition/information on ingredients

Mixture of synthetic resins and solvents

Components

CAS-No.	Chemical Name	Concentration
67-64-1	Acetone	
68476-85-7	Liquified compressed gas	
1330-20-7	Xylene	7%
106-97-8	Butane	
123-86-4	Butyl acetate	
67-63-0	Isopropyl alcohol	
71-23-8	N-propanol	
100-41-4	Ethylbenzene	1.8%
108-65-6	Propylene glycol monomethyl ether acetate	

Non-regulated ingredients 10 - 20%

OSHA Hazardous: Yes

4. First aid measures

SAFETY DATA SHEET

A-7480S v2.0
en/US



Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical

Extinguishing media which shall not be used for safety reasons

High volume water jet

Hazardous combustion products

CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Fire and Explosion Hazards

Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

6. Accidental release measures

SAFETY DATA SHEET

A-7480S v2.0
en/US



Procedures for cleaning up spills or leaks

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

7. Handling and storage

Precautions for safe handling

Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY IGNITE EXPLOSIVELY. Vapors may spread long distances. Prevent buildup of vapors. Extinguish all pilot lights and turn off heaters, non-explosion proof electrical equipment and other sources of ignition during and after use and until all vapors are gone. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 deg F.

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. CONTENTS UNDER PRESSURE. Clean nozzle and cap container after each use. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

Storage

Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IA

8. Exposure controls/personal protection

Engineering controls and work practices

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

National occupational exposure limits

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
67-64-1	Acetone	ACGIH	15 min	STEL	750 ppm	
			8 hr	TWA	500 ppm	
		OSHA	8 hr	TWA	1,000 ppm	

SAFETY DATA SHEETA-7480S v2.0
en/US

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
		Dupont	8 & 12 hour	TWA	500 ppm	
68476-85-7	Liquified compressed gas	ACGIH	8 hr	TWA	1,000 ppm	
		OSHA	8 hr	TWA	1,000 ppm	
1330-20-7	Xylene	ACGIH	15 min	STEL	150 ppm	
			8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	100 ppm	
106-97-8	Butane	ACGIH	15 min	STEL	1,000 ppm	
123-86-4	Butyl acetate	ACGIH	15 min	STEL	200 ppm	
			8 hr	TWA	150 ppm	
		OSHA	8 hr	TWA	150 ppm	
71-23-8	N-propanol	ACGIH	8 hr	TWA	100 ppm	
		OSHA	15 min	STEL	250 ppm	
			8 hr	TWA	200 ppm	Skin
		Dupont	8 hr	TWA	200 ppm	
100-41-4	Ethylbenzene	ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	25 ppm	
108-65-6	Propylene glycol monomethyl ether acetate	Dupont	15 min	TWA	30 ppm	

** STEL = Short term exposure limit.

TWA = Time-weighted average.

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection**Eye protection**

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

Skin and body protection

Neoprene gloves and coveralls are recommended.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

SAFETY DATA SHEET

A-7480S v2.0
en/US



Environmental exposure controls

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

9. Physical and chemical properties

Appearance

Form: aerosol Colour: clear

Flash point	< 20 °F	
Ignition temperature	272 °C	
Lower Explosive Limit	1 %	
Upper Explosive Limit	13.7 %	
Evaporation rate	Slower than Ether	
Vapor pressure of principal solvent	357.2 hPa	
Water solubility	appreciable	
Vapor density of principal solvent (Air = 1)	2	
Approx. Boiling Range	-12 °C	
Approx. Freezing Range	Not applicable.	
Gallon Weight (lbs/gal)	6.12	
Specific Gravity	0.73	
Percent Volatile By Volume	90.77%	
Percent Volatile By Weight	85.21%	
Percent Solids By Volume	9.23%	
Percent Solids By Weight	14.79%	
pH (waterborne systems only)	No data available.	
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	272 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	4.9	
VOC* as packaged (lbs/gal)	4.0	

* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. Stability and reactivity

Stability

Stable

Conditions to avoid

Stable under recommended storage conditions.

Materials to avoid

None reasonably foreseeable.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Hazardous Polymerization

Will not occur.

Sensitivity to Static Discharge

Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

SAFETY DATA SHEET

A-7480S v2.0
en/US



Sensitivity to Mechanical Impact

None known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

not hazardous

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

Skin corrosion/irritation

Not classified according to GHS criteria

Serious eye damage/eye irritation

acetone	Category 2A
xylene	Category 2A
propan-2-ol	Category 2A
propan-1-ol	Category 1
ethylbenzene	Category 2B
2-methoxy-1-methylethyl acetate	Category 2A

Respiratory sensitisation

No data available.

Skin sensitisation

No data available.

Germ cell mutagenicity

propane	Category 1B
Butane (< 0,1% 1,3-butadiene)	Category 1B

SAFETY DATA SHEET

A-7480S v2.0
en/US



Carcinogenicity

propane Category 1A
Butane (< 0,1% 1,3-butadiene) Category 1A

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

Whether the hazardous chemical is listed by NTP, IARC or OSHA

ethylbenzene IARC 2B

12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute toxicity aquatic invertebrates

CAS-No.	Chemical Name	Species	Exposure time	Value	Type	Method
67-64-1	Acetone	Daphnia	2 days	10 mg/l		
123-86-4	Butyl acetate	Ceriodaphnia dubia	2 days	72.8 mg/l	EC50	
1330-20-7	Xylene	Water flea	1 days	10 mg/l	EC50	
1330-20-7	Xylene	Daphnia	1 days	10 mg/l	EC50	
67-63-0	Isopropyl alcohol	Daphnia	2 days	7,550 mg/l		
71-23-8	N-propanol	Water flea	2 days	3,642 ppm		
100-41-4	Ethylbenzene	Daphnia	48 h	1.8 mg/l	EC50	
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Daphnia	24 h	20 mg/l	EC50	
71-43-2	Benzene	Daphnia	48 h	9.2 mg/l	EC50	
82919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester	Daphnia	24 h	20 mg/l	EC50	
106-36-5	Propyl propionate	Daphnia	48 h	37.8 mg/l	EC50	
108-88-3	Toluene	Water flea	1 day	100 ppm		

SAFETY DATA SHEET

A-7480S v2.0
en/US

Acute and extended toxicity of fishes

CAS-No.	Chemical Name	Species	Exposure time	Value	Type	Method
67-64-1	Acetone	Carassius auratus (goldfish)	1 day	5,000 mg/l		
67-64-1	Acetone	Oncorhynchus mykiss (rainbow trout)	4 days	5,540 mg/l		
67-64-1	Acetone	Lepomis macrochirus (Bluegill sunfish)	4 days	8,300 mg/l		
123-86-4	Butyl acetate	Pimephales promelas (fathead minnow)	4 days	18 mg/l	LC50	
123-86-4	Butyl acetate	Lepomis macrochirus (Bluegill sunfish)	4 days	100 mg/l		
1330-20-7	Xylene	Pimephales promelas (fathead minnow)	4 days	21 mg/l	EC50	
1330-20-7	Xylene	Lepomis macrochirus (Bluegill sunfish)	4 days	22 mg/l	EC50	
1330-20-7	Xylene	Carassius auratus (goldfish)	4 days	24 mg/l	EC50	
67-63-0	Isopropyl alcohol	Pimephales promelas (fathead minnow)	0	83 mg/l		
71-23-8	N-propanol	Oncorhynchus mykiss (rainbow trout)	2 days	3,200 ppm		
71-23-8	N-propanol	Pimephales promelas (fathead minnow)	4 days	4,100 ppm		
100-41-4	Ethylbenzene	Oncorhynchus mykiss (rainbow trout)	96 h	4.2 mg/l	LC50	
108-65-6	Propylene glycol monomethyl ether acetate	Pimephales promelas (fathead minnow)	4 days	161 mg/l		
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Lepomis macrochirus (Bluegill sunfish)	96 h	0.97 mg/l	LC50	
104810-48-2	Poly(oxy-1,2-ethanediyl),.alpha.-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy phenyl	Oncorhynchus mykiss (rainbow trout)	4 days	3 ppm		
104810-48-2	Poly(oxy-1,2-ethanediyl),.alpha.-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy phenyl	Lepomis macrochirus (Bluegill sunfish)	4 days	4 ppm		
104810-47-1	Ultraviolet absorber	Oncorhynchus mykiss (rainbow trout)	4 days	3 ppm		
104810-47-1	Ultraviolet absorber	Lepomis macrochirus (Bluegill sunfish)	4 days	4 ppm		
71-43-2	Benzene	Oncorhynchus mykiss (rainbow trout)	96 h	5.9 mg/l	LC50	

SAFETY DATA SHEET

A-7480S v2.0
en/US

CAS-No.	Chemical Name	Species	Exposure time	Value	Type	Method
65-85-0	Benzoic acid	Lepomis macrochirus (Bluegill sunfish)	4 days	45 mg/l		
65-85-0	Benzoic acid	Oncorhynchus mykiss (rainbow trout)	4 days	47 mg/l		
82919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester	Lepomis macrochirus (Bluegill sunfish)	96 h	0.97 mg/l	LC50	
82919-37-7	Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester	Oncorhynchus mykiss (rainbow trout)	96 h	7.9 mg/l	LC50	
141-78-6	Ethyl acetate	Pimephales promelas (fathead minnow)	4 days	230 mg/l		
141-78-6	Ethyl acetate	Leuciscus idus (Golden orfe)	2 days	270 mg/l		
141-78-6	Ethyl acetate	Oncorhynchus mykiss (rainbow trout)	4 days	425 mg/l		
64-17-5	Ethyl alcohol	Carassius auratus (goldfish)	96 h	140 mg/l	LC50	
110-19-0	Isobutyl acetate	Pimephales promelas (fathead minnow)	96 h	62 mg/l	LC50	
78-83-1	Isobutyl alcohol	Leuciscus idus (Golden orfe)	2 days	1,220 mg/l		
78-83-1	Isobutyl alcohol	Pimephales promelas (fathead minnow)	4 days	1,600 mg/l		
108-31-6	Maleic anhydride	Lepomis macrochirus (Bluegill sunfish)	24 h	150 mg/l	LC50	
80-62-6	Methyl methacrylate	Oncorhynchus mykiss (rainbow trout)	4 days	79 mg/l		
80-62-6	Methyl methacrylate	Pimephales promelas (fathead minnow)	4 days	100 mg/l		
71-36-3	N-butyl alcohol	Carassius auratus (goldfish)	1 day	1,000 mg/kg		
71-36-3	N-butyl alcohol	Leuciscus idus (Golden orfe)	2 days	1,770 mg/kg		
97-88-1	N-butyl methacrylate	Carassius auratus (goldfish)	3 days	124 mg/l		
556-67-2	Octamethylcyclotetrasiloxane	Leuciscus idus (Golden orfe)	0	200 mg/l	LC50	
85-44-9	Phthalic anhydride	Daphnia	2 days	100 mg/l		
85-44-9	Phthalic anhydride	Leuciscus idus (Golden orfe)	2 days	313 mg/l		
85-44-9	Phthalic anhydride	Oncorhynchus mykiss (rainbow trout)	4 days	620 mg/l		
85-44-9	Phthalic anhydride	Lepomis macrochirus (Bluegill sunfish)	4 days	1,000 mg/l		
106-36-5	Propyl propionate	Oncorhynchus mykiss (rainbow trout)	96 h	10.8 mg/l	LC50	

SAFETY DATA SHEETA-7480S v2.0
en/US

CAS-No.	Chemical Name	Species	Exposure time	Value	Type	Method
108-88-3	Toluene	Pimephales promelas (fat-head minnow)	4 days	32 mg/l		
108-88-3	Toluene	Lepomis macrochirus (Bluegill sunfish)	4 days	60 ppm		
108-88-3	Toluene	Carassius auratus (goldfish)	4 days	60 ppm		

Toxicity with aquatic plants

CAS-No.	Chemical Name	Species	Exposure time	Value	Type	Method
71-23-8	N-propanol	Daphnia	4 days	1,000 mg/l		
100-41-4	Ethylbenzene	green algae (type not specified)	72 h	4.6 mg/l	EC50	
108-65-6	Propylene glycol monomethyl ether acetate	Daphnia	2 days	408 mg/l		
104810-48-2	Poly(oxy-1,2-ethanediy),.alpha.-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy phenyl	Daphnia	2 days	4 ppm		
104810-48-2	Poly(oxy-1,2-ethanediy),.alpha.-[3-[3-(2h-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy phenyl	green algae (type not specified)	3 days	9 ppm		
104810-47-1	Ultraviolet absorber	green algae (type not specified)	3 days	9 ppm		
71-43-2	Benzene	green algae (type not specified)	72 h	29 mg/l	IC50	
65-85-0	Benzoic acid	Daphnia	2 days	100 mg/l		
141-78-6	Ethyl acetate	Daphnia	2 days	230 mg/l		
78-83-1	Isobutyl alcohol	Daphnia	2 days	1,994 mg/l		
80-62-6	Methyl methacrylate	Daphnia	2 days	69 mg/l		
80-62-6	Methyl methacrylate	Algae	4 days	170 mg/l		
71-36-3	N-butyl alcohol	Daphnia	1 day	1,855 mg/kg		
106-36-5	Propyl propionate	green algae (type not specified)	96 h	340 mg/l	LC50	

Mobility

No information available.

13. Disposal considerations**Waste Disposal Method**

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

14. Transport information

SAFETY DATA SHEET

A-7480S v2.0
en/US



International transport regulations

IMDG (Sea transport)

UN number: 1950
Proper shipping name: AEROSOLS

Hazard Class: 2.1
Subsidiary Hazard Class: Not applicable.
Packing group:
Marine Pollutant: no

ICAO/IATA (Air transport)

UN number: 1950
Proper shipping name: AEROSOLS, FLAMMABLE

Hazard Class: 2.1
Subsidiary Hazard Class: Not applicable.
Packing group:

DOT

UN number: 1950
Proper shipping name: AEROSOLS

Hazard Class: 2.1
Subsidiary Hazard Class: Not applicable.
Packing group:
Marine Pollutant: no
EmS: F-D,S-U

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

TSCA Status

In compliance with TSCA Inventory requirements for commercial purposes.

DSL Status

All components of the mixture are listed on the DSL.

Photochemical Reactivity

Non-photochemically reactive

Regulatory information

CAS #	Ingredient	EPCRA					CERCLA RQ(lbs)	CAA HAP
		302	TPQ	RQ	311 - 312	313		
67-64-1	Acetone	N	NR	NR	A,C,F	N	5,000	N
68476-85-7	Liquified compressed gas	N	NR	NR	A,C,F,N,R	N	NR	N
1330-20-7	Xylene	N	NR	NR	A,C,F	Y	100	Y
106-97-8	Butane	N	NR	NR	A,C,F,N,R	N	100	N
123-86-4	Butyl acetate	N	NR	NR	A,C,F	N	NR	N
67-63-0	Isopropyl alcohol	N	NR	NR	A,C,F	N	NR	N
71-23-8	N-propanol	N	NR	NR	C,F	N	NR	N
100-41-4	Ethylbenzene	N	NR	NR	A,C,F	Y	1,000	Y
108-65-6	Propylene glycol monomethyl ether acetate	N	NR	NR	F	N	NR	N

SAFETY DATA SHEET

A-7480S v2.0
en/US



Key:

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)	
302	Extremely hazardous substances	
311/312 Categories	F = Fire Hazard R = Reactivity Hazard P = Pressure Related Hazard	A = Acute Hazard C = Chronic Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.	
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.	
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.	
TPQ	Threshold Planning Quantity.	
RQ	Reportable Quantity	
NA	not available	
NR	not regulated	

16. Other information

HMIS rating H: 2 F: 3 R: 0

Glossary of Terms:

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit.
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

Version	Changes
2.0	2, 3, 4, 5, 6, 7, 8, 9, 11, 12, 14, 15

Revision Date: 2014-05-16

(800) 438-3876
axalta.us

