

SAFETY DATA SHEET

1. Identification

Product identifier	Liquid Hardener		
Other means of identification			
Product Code	765-1285		
Recommended use	Liquid Hardener, Polymer Reaction Catalyst		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Company name	Balkamp, Inc.		
Address	2601 South Holt Road		
	Indianapolis, Indiana 46241		
	United States		
Telephone	Information	1-800-468-68	32
E-mail	msds@balkamp.com		
Contact person	Stephanie Pruitt		
Emergency phone number	Emergency	1-317-244-724	41
2. Hazard(s) identification			
Physical hazards	Flammable liquids		Category 3
	Organic peroxides		Type D
Health hazards	Acute toxicity, oral		Category 4
	Acute toxicity, inhalation		Category 2

Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 2
	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Protect from sunlight. Store at temperatures not exceeding 25°C / 77°F. Keep cool. Store away from other materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	63% of the mixture consists of component(s) of unknown acute oral toxicity. 64.5% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butanone peroxide		1338-23-4	30 to <40
2-butanone		78-93-3	1 to <5
Hydrogen peroxide		7722-84-1	1 to <5
Other components below re	portable levels		60 to <70

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Nausea, vomiting. Abdominal pain. Diarrhea. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor. Heating may cause a fire.

6. Accidental release measures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe vapors or spray mist. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Keep away from clothing and other combustible materials. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Keep only in the original container. Store in a well-ventilated place. Store away from other materials. Keep in an area equipped with sprinklers.
ivertive user level strengt a confiduate post

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
2-butanone (CAS 78-93-3)	PEL	590 mg/m3	
		200 ppm	
Hydrogen peroxide (CAS 7722-84-1)	PEL	1.4 mg/m3	
		1 ppm	
US. ACGIH Threshold Limit Values	6		
Components	Туре	Value	
2-butanone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
2-Butanone peroxide (CAS 1338-23-4)	Ceiling	0.2 ppm	
Hydrogen peroxide (CAS 7722-84-1)	TWA	1 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
2-butanone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

Components		Туре	Va	lue
2-Butanone peroxide (CAS 1338-23-4)		Ceiling	1.5	5 mg/m3
			0.2	2 ppm
Hydrogen peroxide (CAS 7722-84-1)		TWA	1.4	4 mg/m3
			1 μ	opm
ological limit values				
ACGIH Biological Exposu	re Indices			
Components	Value	Determinant	Specimen	Sampling Time
2-butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
* - For sampling details, plea	ase see the sour	ce document.		
opropriate engineering ontrols	changes per applicable, u	hour) should be used. Ve se process enclosures, lo	entilation rates sh ocal exhaust vent	Good general ventilation (typically 10 ai ould be matched to conditions. If ilation, or other engineering controls to plimite the avecure limits have not been
	changes per applicable, u maintain airb established, i	hour) should be used. Ve se process enclosures, lo orne levels below recom	entilation rates sh ocal exhaust vent mended exposur to an acceptable	ould be matched to conditions. If
	changes per applicable, u maintain airb established, shower must	hour) should be used. Ve se process enclosures, lo orne levels below recommaintain airborne levels to be available when hand	entilation rates sh ocal exhaust vent mended exposur to an acceptable ing this product.	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer
ntrols	changes per applicable, u maintain airb established, shower must s, such as perso	hour) should be used. Ve se process enclosures, lo orne levels below recommaintain airborne levels to be available when hand	entilation rates sh boal exhaust vent mended exposur to an acceptable ing this product. ent	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer level. Eye wash facilities and emergenc
dividual protection measure Eye/face protection	changes per applicable, u maintain airb established, shower must s, such as perso	hour) should be used. Ve se process enclosures, lo orne levels below recom maintain airborne levels t be available when handl onal protective equipme	entilation rates sh boal exhaust vent mended exposur to an acceptable ing this product. ent	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer level. Eye wash facilities and emergenc
dividual protection measure	changes per applicable, u maintain airb established, shower must s, such as perso Wear safety	hour) should be used. Ve se process enclosures, lo orne levels below recom maintain airborne levels t be available when handl onal protective equipme glasses with side shields	entilation rates sh boal exhaust vent mended exposur to an acceptable ing this product. ent (or goggles) and	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer level. Eye wash facilities and emergenc
dividual protection measure Eye/face protection Skin protection	changes per applicable, us maintain airb established, i shower must s, such as perso Wear safety Wear approp supplier.	hour) should be used. Ve se process enclosures, lo orne levels below recom maintain airborne levels t be available when handl onal protective equipme glasses with side shields	entilation rates sh boal exhaust vent mended exposur- to an acceptable ing this product. ent (or goggles) and gloves. Suitable g	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer level. Eye wash facilities and emergenc a face shield.
dividual protection measure Eye/face protection Skin protection Hand protection	changes per applicable, u maintain airb established, shower must s, such as perso Wear safety Wear approp supplier. Wear approp	hour) should be used. Ve se process enclosures, lo orne levels below recom maintain airborne levels t be available when handl onal protective equipme glasses with side shields priate chemical resistant g	entilation rates sh boal exhaust vent mended exposur- to an acceptable ing this product. ent (or goggles) and gloves. Suitable g clothing.	ould be matched to conditions. If ilation, or other engineering controls to e limits. If exposure limits have not beer level. Eye wash facilities and emergenc a face shield. loves can be recommended by the glov
dividual protection measure Eye/face protection Skin protection Hand protection Other	changes per applicable, u maintain airb established, i shower must s, such as perso Wear safety Wear approp supplier. Wear approp Wear positive	hour) should be used. Ve se process enclosures, lo orne levels below recom maintain airborne levels t be available when handl onal protective equipme glasses with side shields priate chemical resistant o	entilation rates sh bcal exhaust vent mended exposur- to an acceptable ing this product. ent (or goggles) and gloves. Suitable g clothing.	atus (SCBA).

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	66.2 °F (19 °C) estimated
Flash point	140.0 °F (60.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.04 hPa estimated
Vapor density	Not available.

Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	140 °F (60 °C)
Viscosity	Not available.
Other information	
Density	8.32 lbs/gal
Explosive properties	Not explosive.
Flammability class	Combustible IIIA estimated
Oxidizing properties	Not oxidizing.
Percent volatile	2.5 % estimated
Specific gravity	1
VOC	2.5 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Sunlight. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Combustible material.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Fatal if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Nausea, vomiting. Abdominal pain. Diarrhea. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Information on toxicological effects

Acute toxicity	Fatal if inhaled. Harmful if swallowed.			
Components	Species	Test Results		
2-butanone (CAS 78-93-3)				
Acute				
Dermal				
LD50	Rabbit	> 8000 mg/kg		
Inhalation				
LC50	Mouse	11000 ppm, 45 Minutes		
	Rat	11700 ppm, 4 Hours		
Oral				
LD50	Mouse	670 mg/kg		
	Rat	2300 - 3500 mg/kg		

	Species		Test Results	
2-Butanone peroxide (CAS 1338-	-23-4)			
<u>Acute</u>				
Inhalation				
LC50	Mouse		170 mg/l, 4 Hours	
	Rat		200 mg/l, 4 Hours	
Oral				
LD50	Rat		6.86 ml/kg	
* Estimates for product may	be based on a	dditional component data not shown.		
Skin corrosion/irritation	Causes sev	vere skin burns and eye damage.		
Serious eye damage/eye irritation	Causes ser	Causes serious eye damage.		
Respiratory or skin sensitizatio	on			
Respiratory sensitization	Not a respi	ratory sensitizer.		
Skin sensitization	This produce	ct is not expected to cause skin sensitization	n.	
Germ cell mutagenicity		ailable to indicate product or any compone or genotoxic.	nts present at greater than 0.1% are	
Carcinogenicity	This produc	ct is not considered to be a carcinogen by I	ARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation o	f Carcinogenicity		
OSHA Specifically Regulate Not regulated. US. National Toxicology Pr Not listed.				
	This product is not expected to cause reproductive or developmental effects.			
	This produce	ct is not expected to cause reproductive or	developmental effects.	
Reproductive toxicity Specific target organ toxicity - single exposure	This produc Not classifi		developmental effects.	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity -	Not classifi			
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure	Not classifi May cause	ed.		
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard	Not classifi May cause Not an asp	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re		
Reproductive toxicity Specific target organ toxicity -	Not classifi May cause Not an asp May cause be harmful	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re	epeated exposure.	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Chronic effects 12. Ecological information	Not classifi May cause Not an asp May cause be harmful. n The produc	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re	epeated exposure. epeated exposure. Prolonged inhalation may	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Chronic effects 12. Ecological information	Not classifi May cause Not an asp May cause be harmful. n The produc	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re	epeated exposure. epeated exposure. Prolonged inhalation may dous. However, this does not exclude the	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Chronic effects 12. Ecological information Ecotoxicity	Not classifi May cause Not an asp May cause be harmful. n The produc	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re et is not classified as environmentally hazar hat large or frequent spills can have a harm	epeated exposure. epeated exposure. Prolonged inhalation may rdous. However, this does not exclude the nful or damaging effect on the environment.	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Chronic effects 12. Ecological information Ecotoxicity <u>Components</u>	Not classifi May cause Not an asp May cause be harmful. n The produc	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re et is not classified as environmentally hazar hat large or frequent spills can have a harm Species	epeated exposure. epeated exposure. Prolonged inhalation may rdous. However, this does not exclude the nful or damaging effect on the environment.	
Reproductive toxicity Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure Aspiration hazard Chronic effects 12. Ecological information Ecotoxicity <u>Components</u> 2-butanone (CAS 78-93-3)	Not classifi May cause Not an asp May cause be harmful. n The produc	ed. damage to organs through prolonged or re iration hazard. damage to organs through prolonged or re et is not classified as environmentally hazar hat large or frequent spills can have a harm	epeated exposure. epeated exposure. Prolonged inhalation may rdous. However, this does not exclude the nful or damaging effect on the environment.	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octan	ol / water (log Kow)	
2-butanone	0.29	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	


13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

DOT	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
Subsidiary risk	-
Packing group	Not applicable.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	152
IATA	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
	5.2
Subsidiary risk	- Natannliachla
Packing group	Not applicable.
Environmental hazards	No.
	Read safety instructions, SDS and emergency procedures before handling.
Other information	.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN3105
UN proper shipping name	Organic Peroxide Type D, Liquid (Methyl Ethyl Ketone Peroxide <45%)
Transport hazard class(es)	
Class	5.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-J, S-R
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not established.
Annex II of MARPOL 73/78 and	
the IBC Code	



15. Regulatory information

US federal regulations		ct is a "Hazardoı 29 CFR 1910.12		d by the OSHA Hazard	Communication	
TSCA Section 12(b) E	xport Notification	(40 CFR 707, St	ubpt. D)			
Not regulated.						
CERCLA Hazardous S	•	CFR 302.4)	l inte d			
2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4))	Listed. Listed.			
SARA 304 Emergency	•	·	Liotod.			
Hydrogen peroxide			1000 LBS			
OSHA Specifically Re	· · · ·	es (29 CFR 1910).1001-1050)			
Not regulated.						
Superfund Amendments a	nd Reauthorizatio	on Act of 1986 (SARA)			
Hazard categories Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - Yes						
SARA 302 Extremely						
Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value	
Hydrogen peroxide	7722-84-1	1000	1000 lbs			
SARA 311/312 Hazard chemical	ous No					
SARA 313 (TRI reporti Not regulated.	ng)					
Other federal regulations						
Clean Air Act (CAA) S	ection 112 Hazard	ous Air Polluta	nts (HAPs) List			
Not regulated.						
Clean Air Act (CAA) S	ection 112(r) Acci	dental Release	Prevention (40 CFR 6	8.130)		
Not regulated.						
Safe Drinking Water A (SDWA)	Act Not regulat	ted.				
Drug Enforcemen Chemical Code N		DEA). List 2, Es	sential Chemicals (21	CFR 1310.02(b) and 1	310.04(f)(2) and	
Chemical Code N			<u></u>			
2-butanone (C	AS 78-93-3)		6714			
			6714		SDS US	

Drug Enforcement A	dministration (DEA). List 1 &	2 Exempt Chemical Mixtures (2	21 CFR 1310.12(c))	
2-butanone (CAS	\$ 78-93-3)	35 %WV		
DEA Exempt Chemi	cal Mixtures Code Number			
2-butanone (CAS		6714		
FEMA Priority Subst	tances Respiratory Health and	d Safety in the Flavor Manufact	uring Workplace	
2-butanone (CAS	\$ 78-93-3)	Low priority		
US state regulations				
US. California Controlleo	d Substances. CA Departmen	t of Justice (California Health a	nd Safety Code Section 11100)	
Not listed.				
US. California. Candidat (a))	e Chemicals List. Safer Consi	umer Products Regulations (Ca	al. Code Regs, tit. 22, 69502.3, subd.	
2-butanone (CAS 78-	93-3)			
US. Massachusetts RTK	- Substance List			
2-butanone (CAS 78-	,			
2-Butanone peroxide	· · · · · · · · · · · · · · · · · · ·			
Hydrogen peroxide (C	and Community Right-to-Kno	w Act		
2-butanone (CAS 78-		WAC		
2-Butanone peroxide				
Hydrogen peroxide (CAS 7722-84-1)				
	er and Community Right-to-Kr	now Law		
2-butanone (CAS 78-	93-3)			
2-Butanone peroxide				
Hydrogen peroxide (C	CAS 7722-84-1)			
US. Rhode Island RTK				
2-butanone (CAS 78-93-3) 2-Butanone peroxide (CAS 1338-23-4)				
Hydrogen peroxide (C				
US. California Propositio	,			
-		at Act of 1086 (Proposition 65): T	his material is not known to contain	
	tly listed as carcinogens or repr			
International Inventories				
Country(s) or region	Inventory name		On inventory (yes/no)*	

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-18-2015
Version #	01
HMIS® ratings	Health: 4* Flammability: 3 Physical hazard: 3
NFPA ratings	Health: 4 Flammability: 3 Instability: 3

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.