SAFETY DATA SHEET

GREENBASE™ HE® 150

Version 2.10

DRILLING SPECIALTIES COMPANY IP

Revision Date 2015-09-10

SECTION 1: Identification of t	he su	bstance/mixture and of the company/undertaking
Product information		
Product Name Material	:	GREENBASE™ HE® 150 1115418, 1111210, 1108744, 1101584
Use	:	Gelling Agent
Company	:	Chevron Phillips Chemical Company LP Drilling Specialties Company LLC 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:		
Asia: +800 CHEMCALL EUROPE: BIG +32.14.5 South America SOS-Co Responsible Department E-mail address Website	ational REC (+800 58454 58454 tec In	800.424.9300 or 703.527.3887 2 2436 2255) China:+86-21-22157316 5 (phone) or +32.14583516 (telefax) side Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 Product Safety and Toxicology Group SDS@CPChem.com
SECTION 2: Hazards identific	ation	
	d in ac	mixture coordance with the hazard communication standard 29 CFR in all the information as required by the standard.
Warning Physical state: Liquid OSHA Hazards Classification		or : White Odor : Mild, pleasant Moderate eye irritant
MSDS Number:100000014527		1/12

REENBASE™ HE® 1	30			
sion 2.10	F			ate 2015-09
	: Eye ir	ritation , Category 2	A	
Labeling				
Symbol(s)				
Signal Word	: Warn	ing		
Hazard Statements	: H31	9: Causes serious e	ye irritation.	
Precautionary Statements	P264 P280 Resp P305 water and e	Wear eye protect onse: + P351 + P338 II for several minutes. asy to do. Continue + P313 If eye irrit	ghly after handling. on/ face protection. F IN EYES: Rinse cautious Remove contact lenses, ir rinsing. ation persists: Get medical	fpresent
Carcinogenicity:				
IARC	equal to		t present at levels greater s probable, possible or con	
NTP		0.1% is identified a	t present at levels greater s a known or anticipated c	
ACGIH		0.1% is identified a	t present at levels greater s a carcinogen or potentia	
CTION 3: Composition/infor	nation on	ingredients		
Synonyms		312-01 hbase Acid Gelling A	gent	
Molecular formula	: Mixtu	re		
Component		CAS-No.	Weight %	
Di(Ethylene Glycol) Butyl Eth Saturated monocarboxylic a salt	ier cid, calciun	112-34-5 n Proprietary	55 - 70 0.5 - 1	
DS Number:100000014527			2/12	

GREENBASE™ HE® 150

SAFETY DATA SHEET

Version 2.10

Revision Date 2015-09-10

SECTION 4		
SECTION 4	: First ald	a measures

	General advice	:	Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
	If inhaled	:	If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
	In case of skin contact	:	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
	In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
SE	CTION 5: Firefighting measu	res	
SE	CTION 5: Firefighting measu	res	
SE	CTION 5: Firefighting measu	res :	100 °C (212 °F)
SE		:	100 °C (212 °F)
SE	Flash point	:	100 °C (212 °F)
SE	Flash point	:	100 °C (212 °F) 228 °C (442 °F)
SE	Flash point Autoignition temperature Unsuitable extinguishing	:	100 °C (212 °F) 228 °C (442 °F)

:	Standard procedure for chemical fires. Use extinguishing
	measures that are appropriate to local circumstances and the
	surrounding environment.
	:

Fire and explosion	: Normal measures for preventive fire protection.
--------------------	---

protection		
Hazardous decomposition products	:	No data available.

SECTION 6: Accidental release measures

Personal precautions	:	Use personal protective equipment.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
MSDS Number:100000014527		3/12

GREENBASE[™] HE® 150

Version 2.10

Revision Date 2015-09-10

SAFETY DATA SHEET

SECTION 7: Handling and storage

Handling

-		
Advice on safe handling	:	Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Storage		
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

บร

Ν

Ingredients	Basis	Value	Control parameters	Note
Di(Ethylene Glycol) Butyl Ether	ACGIH	TWA	10 ppm,	 Inhalable fraction and vapor
Calcium Stearate	ACGIH	TWA	10 mg/m3	A4,
* 0011 Adaption				

2014 Adoption

A4 Not classifiable as a human carcinogen

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection :	Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection :	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into
MSDS Number:100000014527	4/12

REENBASE™ HE® 1	SAFETY DATA S	SHE
rsion 2.10	Revision Date 2015	5-09
	consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and th contact time. Gloves should be discarded and replaced if th is any indication of degradation or chemical breakthrough.	
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggle	€S.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to specific work-place. Wear as appropriate:. Protective suit. Safety shoes.	the
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	
CTION 9: Physical and chen	cal properties	
Information on basic phys	cal and chemical properties	
Appearance		
Physical state	: Liquid	
Color	: White	
Odor	: Mild, pleasant	
Safety data		
Flash point	: 100 °C (212 °F)	
Lower explosion limit	: No data available	
Upper explosion limit	: No data available	
Oxidizing properties	: no	
Autoignition temperature	: 228 °C (442 °F)	
Molecular formula	: Mixture	
Molecular weight	: No data available	
рН	: 7	
Freezing point	: No data available	
Pour point	No data available	
Boiling point/boiling range	: 230 °C (446 °F)	
Vapor pressure	: 15.00 PSI at 20 °C (68 °F)	
Relative density	: 1.06	
Density	: 1,059.3 g/l	
Water solubility	: Soluble	
DS Number:100000014527	5/12	

GREENBASE™ HE® 15	SAFETY DATA SHEET		
Version 2.10	Revision Date 2015-09-10		
Partition coefficient: n- octanol/water	: No data available		
Viscosity, kinematic	: No data available		
Relative vapor density	5.6 (Air = 1.0)		
Evaporation rate	: No data available		
SECTION 10: Stability and reactive	vity		
Chemical stability	This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.		
Possibility of hazardous read	tions		
Conditions to avoid	: No data available.		
Materials to avoid	 May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc. No data available 		
Hazardous decomposition products			
Other data	: No decomposition if stored and applied as directed.		
SECTION 11: Toxicological inform	mation		
GREENBASE™ HE® 150 Acute oral toxicity	: Acute toxicity estimate: 3,443 mg/kg Method: Calculation method		
GREENBASE™ HE® 150 Acute dermal toxicity	LD50: 3,949 mg/kg Method: Acute toxicity estimate		
GREENBASE™ HE® 150 Skin irritation	: May cause skin irritation in susceptible persons.		
GREENBASE™ HE® 150 Eye irritation	: Eye irritation.		
Sensitization			
Di(Ethylene Glycol) Butyl Ether	Did not cause sensitization on laboratory animals.		
Repeated dose toxicity			
Di(Ethylene Glycol) Butyl Ether	: Species: Rat, Male and female Sex: Male and female Application Route: Oral		

SAFETY DATA SHEET

GREENBASE™ HE® 150

sion 2.10	Revision Date 2015-09
	NOEL: 250 mg/kg Lowest observable effect level: 1,000 mg/kg Method: OCED Guideline 408 Target Organs: Blood, Liver, Kidney
	Species: Rat, Male and female Sex: Male and female Application Route: inhalation (vapor) NOEL: 94 mg/m3 Method: OECD Guideline 413 Target Organs: Lungs
	Species: Rat, Male and female Sex: Male and female Application Route: Dermal NOEL: 2,000 mg/kg Target Organs: Skin
Reproductive toxicity	
Di(Ethylene Glycol) Butyl Ether	 Species: Mouse Sex: male and female Application Route: Oral Dose: 0, 720, 1340, 2050mg/kg bw Number of exposures: continuous Test period: 14 weeks Method: OECD Test Guideline 416 NOAEL Parent: 720 mg/kg NOAEL F1: 720 mg/kg NOAEL F2: 720 mg/kg Information given is based on data obtained from similar substances.
Developmental Toxicity	
Di(Ethylene Glycol) Butyl Ether	 Species: Rat Application Route: Oral diet Dose: 25, 115, 633 mg/kg/d Number of exposures: GD 0 -20 d Method: OECD Guideline 414 NOAEL Teratogenicity: 633 mg/kg NOAEL Maternal: 633 mg/kg No adverse effects expected
	Species: Rabbit Application Route: Dermal Dose: 25, 115, 633 mg/kg/d Exposure time: 4 h/d Number of exposures: GD 8 -19 d Method: OECD Guideline 414 NOAEL Teratogenicity: 1,000 mg/kg NOAEL Maternal: 1,000 mg/kg No adverse effects expected
GREENBASE™ HE® 150 Aspiration toxicity	: No aspiration toxicity classification.
CMR effects	

REENBASE™ HE® 15	SAFETY DATA SHE	
sion 2.10	Revision Date 2015-09	
Di(Ethylene Glycol) Butyl Ether	Carcinogenicity: Not available Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: Animal testing did not show any effects on fertility.	
GREENBASE™ HE® 150 Further information	: No data available.	
CTION 12: Ecological informa	tion	
Toxicity to fish		
Di(Ethylene Glycol) Butyl Ether	LC50: > 1,000 mg/l Exposure time: 96 h Species: Scophthalmus maximus (Flatfish, Flounder) semi-static test Method: OECD Test Guideline 203	
Toxicity to daphnia and othe	er aquatic invertebrates	
Di(Ethylene Glycol) Butyl Ether	 EC50: > 1,000 mg/l Exposure time: 48 h Species: Acartia tonsa (Marine Copepod) static test Method: ISO TC147/SC5/WG2 	
Toxicity to algae		
Di(Ethylene Glycol) Butyl Ether	: EC50: > 1,000 mg/l Exposure time: 72 h Species: Skeletonema costatum Growth inhibition Method: ISO 10253	
Elimination information (persis	tence and degradability)	
Biodegradability	: Expected to be biodegradable	
Ecotoxicology Assessment		
Results of PBT assessment Di(Ethylene Glycol) Butyl Ether	: This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).	
Additional ecological information	: No data available	
CTION 13: Disposal considera	itions	
The information in this SDS pe	ertains only to the product as shipped.	

REENBASE™ HE® 150	SAFETY DATA SHEE
Version 2.10	Revision Date 2015-09-10
Use material for its intended pur may meet the criteria of a hazard other State and local regulations regulated components may be n	pose or recycle if possible. This material, if it must be discarded, dous waste as defined by US EPA under RCRA (40 CFR 261) or a. Measurement of certain physical properties and analysis for necessary to make a correct determination. If this material is , federal law requires disposal at a licensed hazardous waste
Product :	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging :	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.
ECTION 14: Transport information	n
The shipping descriptions sho shipments in non-bulk packag	own here are for bulk shipments only, and may not apply to les (see regulatory definition).
Goods Regulations for additional etc.) Therefore, the information	c or international mode-specific and quantity-specific Dangerous I shipping description requirements (e.g., technical name or names, shown here, may not always agree with the bill of lading shipping shpoints for the material may vary slightly between the SDS and the
	PARTMENT OF TRANSPORTATION) ZARDOUS MATERIAL OR DANGEROUS GOODS FOR S AGENCY.
	MARITIME DANGEROUS GOODS) ZARDOUS MATERIAL OR DANGEROUS GOODS FOR S AGENCY.
IATA (INTERNATIONAL AIR TE NOT REGULATED AS A HAX TRANSPORTATION BY THIS	ZARDOUS MATERIAL OR DANGEROUS GOODS FOR
	EROUS GOODS BY ROAD (EUROPE)) ZARDOUS MATERIAL OR DANGEROUS GOODS FOR S AGENCY.
DANGEROUS GOODS (EUROP	ZARDOUS MATERIAL OR DANGEROUS GOODS FOR
OF DANGEROUS GOODS BY	ZARDOUS MATERIAL OR DANGEROUS GOODS FOR

GREENBASE™ HE® 150

Version 2.10

SAFETY DATA SHEET

Revision Date 2015-09-10

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

ECTION 15: Regulatory inforn	CTION 15: Regulatory information				
National legislation					
-					
SARA 311/312 Hazards	: Acute Health Hazard				
CERCLA Reportable Quantity	: This material does not contain any components with a CERCLA RQ.				
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.				
SARA 302 Threshold Planning Quantity	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.				
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.				
SARA 313 Ingredients	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.				
Clean Air Act					
Potential Class	roduct neither contains, nor was manufactured with a Class I or II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR ıbpt. A, App.A + B).				
This product does not contai Act Section 12 (40 CFR 61).	n any hazardous air pollutants (HAP), as defined by the U.S. Clean Air				
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).					
The following chemical(s) an Final VOC's (40 CFR 60.489	e listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or): : Di(Ethylene Glycol) Butyl Ether - 112-34-5				
DS Number:100000014527	10/12				

REENBASE™ HE®	150
sion 2.10	Revision Date 2015-09-1
	are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate
Final VOC's (40 CFR 60.48	
	. DI(Ethylene Glycol) Butyl Ether - 112-34-5
US State Regulations	
Pennsylvania Right To Kno	ow : Di(Ethylene Glycol) Butyl Ether - 112-34-5
New Jersey Right To Know	
	: Di(Ethylene Glycol) Butyl Ether - 112-34-5
California Prop. 65 Ingredients	: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.
Notification status Europe REACH United States of America Canada DSL Australia AICS New Zealand NZIoC Japan ENCS Korea KECI Philippines PICCS China IECSC	 On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Not in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory
CTION 16: Other information	אר אר
NFPA Classification	: Health Hazard: 2 Fire Hazard: 1 Reactivity Hazard: 0
Further information Legacy SDS Number	: CPC00471
Significant changes since t previous versions.	he last version are highlighted in the margin. This version replaces all
	S pertains only to the product as shipped.

GREENBASE™ HE® 150

SAFETY DATA SHEET

Version 2.10

Revision Date 2015-09-10

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

K	ey or legend to abbreviations and a	cronyms used	d in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		