

Install the Loadrite Sprint on your forklift or small wheel loader and see how you'll save time and money. This cost-effective onboard weighing system combines basic functions required to load once and load right, along with Loadrite's exceptional service and support. With only six keys the Loadrite Sprint is operator friendly and simple to use.

Install a Loadrite Sprint and reduce costs by:

- Loading accurately the first time
- Eliminating costly overload fines
- Minimizing lost product from overloading
- Reducing wear and tear on machines caused by overloading stresses

The Loadrite Sprint is ideal for small wheel loaders working on construction sites and forklifts situated in warehouses.



The Loadrite Sprint's features include:

- Large LCD display with back lighting for night and low light operation
- · Time/date display
- Only six keys so it's operator friendly and easy to use
- · Basic weighing functions
- A total function to show the total weight of a product loaded onto a truck

- A long total function to show total product moved over a shift, week or month
- Seven language options including English, Spanish and French
- Auto add function the Sprint automatically adds the lifted weight to the weighing total
- Load information such as summary reports can be produced with the Loadrite Printer or transferred to the Loadrite Material Management System (both sold separately)

Loadrite Sprint Console: The Nuts and Bolts

Note: Specifications may change due to continuous product improvement.

Power Requirements	Supply Voltage 12 to 32 VDC (ie. designed to operate on 12 or 24 volt systems). Automotive power supply transient suppression exceeds SAE specifications Supply Current 160 mA typical, 350 mA max, 3A max with printer Calibration and Data Back Up Data is stored in a permanent memory and is not affected when the main power is turned off
Display/Keyboard	Display LCD 2 lines of 8 characters, used to display operator messages, and prompts to enter product data etc The large, highly visible, backlit 5 digit numeric display shows lifted weights and totals Keyboard Waterproof tactile membrane
Physical	Dimensions W145 x L240 x D110 mm (5.7 x 9.4 x 4.3 inches) Weight 1.5 kg (3.2 lb)
Environmental	Operating Temperature -10PC to +50PC (14°F to 122°F) Storage Temperature -30PC to + 80PC (-22°F to 176°F) Protection Water and dust protected to IP54 Vibration Qualified to MIL-STD-810D

Accessories: Loadrite Printer, Loadrite Material Management System

Call your local distributor today to discuss how the Loadrite Printer will meet your specific requirements...



- Toll free telephone product support
- National and international network of factory-trained distributors
- Used in over 30 countries
- 25 years industry experience

United States and Canada

Call free 1 800 528 LOAD or 1 800 528 5623

Fax: 1 888 519 4479

Email: info@loadritescales.com

www.loadritescales.com



The manufacturer of Loadrite holds ISO 9001:2000 quality management systems certification.

