

MECHANICAL SPECIFICATIONS

PROVIDE EQUIPMENT INDICATED ON THE DRAWINGS, AND AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM. DEFINITIONS: FURNISH MEANS TO SUPPLY AND DELIVER TO PROJECT SITE, READY FOR INSTALLATION. INSTALL MEANS TO PLACE IN POSITION AND MAKE CONNECTIONS FOR SERVICE OR USE. PROVIDE MEANS TO FURNISH AND INSTALL, COMPLETE AND READY FOR INTENDED USE. WARRANTY: PROVIDE LABOR AND MATERIALS TO REPAIR OR REPLACE DEFECTIVE PARTS AND MATERIALS AS REQUIRED FOR ONE YEAR AFTER SUBSTANTIAL COMPLETION OR OWNER ACCEPTANCE OF THE COMPLETED PROJECT. PROVIDE A SEPARATE LINE ITEM DEDUCT AMOUNT ON THE PROPOSAL FORM TO DELETE WARRANTY SERVICE, AT THE OWNER'S OPTION. PROVIDE OPERATION MANUALS, MAINTENANCE MANUALS AND SCHEMATICS FOR ALL MECHANICAL EQUIPMENT INSTALLED. COORDINATION: COORDINATE WITH THE WORK OF OTHER SECTIONS, EQUIPMENT FURNISHED BY OTHERS, REQUIREMENTS OF THE OWNER, AND WITH THE CONSTRAINTS OF THE EXISTING CONDITIONS OF THE PROJECT SITE. ROOF PENETRATIONS SHALL COMPLY WITH "SMACNA" AND "NRCA" STANDARDS, AND WITH THE REQUIREMENTS OF THE EXISTING ROOFING WARRANTY, IF APPLICABLE. DO NOT PERFORM ROOFING PENETRATIONS IN A MANNER WHICH WOULD VOID OR OTHERWISE LIMIT THE EXISTING ROOF WARRANTY. DUCT DIMENSIONS: UNLESS OTHERWISE NOTED, DUCT DIMENSIONS ON THE DRAWINGS ARE INSIDE CLEAR DIMENSIONS. SHEET METAL DUCTWORK: PROVIDE SHEET METAL DUCTWORK FABRICATED AND INSTALLED IN ACCORDANCE WITH ASHRAE AND SMACNA STANDARDS, FOR 1" W.G. PRESSURE CLASS, SEAL CLASS "A". SHEET METAL SHALL BE GALVANIZED SHEET STEEL OF LOCK FORMING QUALITY, WITH G90 ZINC COATING. SHEET STEEL SHALL COMPLY WITH ASTM A653 STANDARD SPECIFICATION FOR STEEL SHEET METAL, ZINC COATED (GALVANIZED) OR ZINC-IRON ALLOY-COATED (GALVANNEALED) BY THE HOT DIP PROCESS, AND A924 STANDARD SPECIFICATION FOR GENERAL REQUIREMENTS FOR SHEET, METALLIC-COATED BY THE HOT DIP PROCESS. ALL ANGLE IRON USED FOR SUPPORT SHALL BE GALVANIZED. CONNECTIONS TO WALLS OR FLOOR SHALL BE AIR TIGHT WITH ANGLE IRON AND CAULKING. SEAL ALL DUCT SEAMS, TRANSVERSE AND LONGITUDINAL, AIR TIGHT. PROVIDE TURNING VANES AT ALL 90° ELBOWS. TRAPEZE DUCT HANGERS: PROVIDE MINIMUM 1" X 2" X 1" X 18 GAUGE CHANNELS WITH MINIMUM 1" X 18 GAUGE STRAPS TO STRUCTURAL SUPPORT. ROUND SHEET METAL DUCT: PROVIDE SPIRAL SEAM (ALL SIZES) OR SNAP LOCK (DUCT SIZES UP TO 10") GALVANIZED STEEL COMPLYING WITH SMACNA STANDARDS. SPIRAL SEAM DUCTWORK SHALL HAVE SMACNA SEAM TYPE RL-1. FIBER GLASS DUCT BOARD IS AN ACCEPTABLE ALTERNATIVE IF APPROVED BY OWNER AND THE LOCAL BUILDING CODE OFFICIAL. PRODUCT AND INSTALLATION MUST MEET NAIMA STANDARDS AND OTHER APPLICABLE CODES AND REGULATIONS. EXPOSED DUCTWORK: EXPOSED DUCTWORK SHALL BE CLEANED OF DEBRIS AND OIL, THEN WIPED DOWN WITH VINEGAR OR OTHER SURFACE PREPARING CHEMICAL TO PREPARE DUCT FOR PAINT. DUCT SEALANT: PROVIDE POLYMERIC RUBBER TYPE SEALANT FOR USE ON BOTH INTERIOR LOCATED DUCTWORK AND DUCTWORK EXPOSED TO OUTDOOR CONDITIONS. SEALER SHALL HAVE HIGH BONDING STRENGTH FOR SURE, FIRST TIME SEALING OF JOINTS IN LOW, MEDIUM, AND HIGH PRESSURE DUCT SYSTEMS. SEALER SHALL BE HIGH IN SOLID CONTENT, PROVIDE A TWO PART TAPE SEALING SYSTEM, CONSISTING OF WOVEN FIBER TAPE IMPREGNATED WITH A GYPSUM MINERAL COMPOUND, AND A MODIFIED ACRYLIC/SILICONE ACTIVATOR THAT REACTS EXOTHERMICALLY WITH THE TAPE. TWO PART TAPE SEALING SYSTEM MUST BE RATED FOR BOTH INDOOR AND OUTDOOR APPLICATION. TAPE SHALL NOT CONTAIN ASBESTOS. DUCT INSULATION: MATERIAL FOR SUPPLY AND RETURN AIR DUCT ABOVE CEILING INSIDE THE BUILDING SHALL HAVE THE EQUIVALENT THERMAL RESISTANCE OF MINIMUM R-6. THE REQUIRED R VALUES ARE FOR INSTALLED INSULATION WITH 25% COMPRESSION AT THE CORNERS. PROVIDE PINS AND WASHERS IN ACCORDANCE WITH SMACNA REQUIREMENTS AND AS REQUIRED TO PREVENT INSULATION FROM SAGGING. PROVIDE ADEQUATE INSULATION AT THE SUPPLY AIR DIFFUSERS TO PREVENT CONDENSATION. FLEXIBLE DUCT: UL #181 LISTED, CLASS 1, AND CONTAIN A 0.1 PERM RATED POLYETHYLENE INNER LINER, WITH R-8 FIBERGLASS INSULATION. FLEXIBLE DUCTS SHALL BE SECURED TO RIGID SHEET METAL COLLARS AND AIR DIFFUSERS WITH NYLON TIES OR STAINLESS STEEL WORM GEAR STRAPS. SEAL ALL CONNECTIONS AND JOINTS AIRTIGHT. SUPPORT FLEXIBLE DUCTS FROM THE BUILDINGS STRUCTURE WITH MINIMUM 1" WIDE, 18 GAUGE, GALVANIZED STEEL STRAP AT MAXIMUM 4'-0" CENTERS. PROVIDE 4" WIDE SHEET METAL SADDLES AT EACH SUPPORT EACH STRAP. SAG OF FLEXIBLE DUCT BETWEEN HANGERS SHALL NOT EXCEED 1/2" PER FOOT OF SUPPORT SPACING. RADIUS FOR TURNS OF FLEXIBLE DUCTS SHALL BE A MINIMUM OF ONE DUCT DIAMETER. FLEXIBLE DUCT RUNS SHALL NOT EXCEED 10'-0" IN LENGTH AND SHALL BE THE SAME SIZE AS THE DIFFUSER NECK CONNECTION. ROUND VOLUME DAMPERS: PROVIDE MINIMUM 20 GAUGE GALVANIZED STEEL FRAME AND BLADES, MINIMUM 3/8" SQUARE STEEL AXLE, MOLDED SYNTHETIC BEARINGS, WITH LOCKING POSITION REGULATOR. REGULATOR SHALL BE POSITIONED WITH SHEET METAL BRACKET BEYOND DUCT COVERING. WHERE POSITIONING REGULATOR IS NOT ACCESSIBLE, PROVIDE COUPLING AND EXTENSION ROD WITH REGULATOR FOR CEILING OR WALL INSTALLATION, AS REQUIRED. RECTANGULAR VOLUME DAMPERS: PROVIDE MINIMUM 16 GAUGE GALVANIZED STEEL CHANNEL FRAME, 16 GAUGE GALVANIZED STEEL BLADES, MINIMUM ½" HEXAGONAL AXLE, BOLDDED SYNTHETIC BEARINGS, WITH 3/8" SQUARE PLATED STEEL CONTROL SHAFT. LINKAGES SHALL BE CONCEALED IN THE FRAME. OPERATING SHAFT SHALL EXTEND BEYOND FRAME AND DUCT TO A LOCKING QUADRANT WITH ADJUSTABLE LEVER. MAXIMUM BLADE WIDTH SHALL NOT EXCEED 6".

HVAC GENERAL NOTES

- THE INTENT OF THESE PLANS AND SPECIFICATIONS IS TO INCLUDE ALL LABOR, EQUIPMENT, MATERIALS, AND SERVICES NECESSARY TO FURNISH, INSTALL, TEST, AND ADJUST A COMPLETE WORKABLE HEATING, VENTILATION, AND AIR CONDITIONING SYSTEM AS SHOWN, PRESCRIBED, OR REASONABLY IMPLIED BUT NOT LIMITED TO THAT EXPLICITLY INDICATED IN THE CONTRACT DOCUMENTS, BUT NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE INTENT THEREOF.
- THE ENTIRE INSTALLATION SHALL CONFORM TO THE APPLICABLE CODES AND REGULATIONS REQUIRED BY AUTHORITIES HAVING JURISDICTION. IN THE EVENT OF CONFLICT BETWEEN SPECIFICATIONS, CODES, AND REGULATIONS, THE MORE RESTRICTIVE SHALL APPLY.
- DRAWINGS FOR HVAC WORK ARE DIAGRAMATIC SHOWING THE GENERAL LOCATION, TYPE, LAYOUT, AND EQUIPMENT REQUIRED. THE DRAWINGS SHALL NOT BE SCALED FOR EXACT MEASUREMENT, REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS. PROVIDE ALL DUCTWORK, MATERIALS, CONNECTIONS, ACCESSORIES, FITTINGS, OFFSETS, TRANSITIONS, DAMPERS AS REQUIRED FOR A COMPLETE WORKABLE SYSTEM.
- ALL EQUIPMENT SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND APPROVED LISTING. ALL EQUIPMENT, PIPING AND SUPPORTS SHALL BE RESTRAINED IN ACCORDANCE WITH THE LATEST EDITION OF THE "GUIDLINES FOR SEISMIC RESTRAINTS OF MECHANICAL SYSTEMS AND PLUMBING PIPING SYSTEMS" BY THE SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION (SMACNA). ALL EQUIPMENT SHALL BE ANCHORED TO RESIST THE LATERAL FORCE REQUIREMENTS OF CHAPTER 16 OF THE 2022 CALIFORNIA BUILDING CODE.
- COORDINATE THE INSTALLATION OF THE HVAC SYSTEM WITH ALL OTHER TRADES PRIOR TO FABRICATION OR INSTALLATION. COORDINATE THE LOCATIONS OF PENETRATIONS AND FINAL LOCATION OF ALL EQUIPMENT WITH THE GENERAL CONTRACTOR. PROVIDE EQUIPMENT WEIGHTS, EQUIPMENT DIMENSIONS, PLATFORM SIZES & LOCATIONS, CURB SIZES & LOCATIONS, CONCRETE PAD SIZES AND LOCATIONS AST REQUIRED. COORDINATE LOCATIONS OF GAS & CONDENSATE LINES WITH PLUMBING CONTRACTOR. COORDINTAE LOCATIONS OF POWER, DISCONNECTS, AND CONTROL CONDUIT WITH THE ELECTRICAL CONTRACTOR. COORDINATE LOCATIONS OF ALL DIFFUSERS, REGISTERS, AND GRILLES WITH ARCHITECTURAL PLANS, ELECTRICAL LIGHTING PLANS AND ARCHITECTURAL ELEVATIONS.
- DETAILS FOR EQUIPMENT PADS, PLATFORMS, AND FLASHINGS SHALL BE AS INDICATED BY THE ARCHITECTURAL/STRUCTURAL/CIVIL DRAWINGS, UNLESS NOTED OTHERWISE.
- ALL EQUIPMENT, DUCTS, PIPING, SUPPORTS, AND OTHER DEVICES OUTSIDE OF THE BUILDING OR EXPOSED TO WEATHER, SHALL BE COMPLETELY WEATHER-PROOFED.
- OUTSIDE AIR INTAKES SHALL BE AT LEAST 10 FT. AWAY OR 3 FT. BELOW ANY VENT OR EXHAUST DISCHARGE.
- ALL DUCT SIZES ARE CLEAR INSIDE DIMENSIONS. DUCTWORK SHALL BE CONSTRUCTED, ERECTED, INSULATED AND TESTED IN ACCORDANCE CHAPTER 6 OF THE 2022 CALIFORNIA MECHANICAL CODE.
- ALL EXHAUST FANS SHALL BE EQUIPPED WITH A BACK DRAFT DAMPER.
- DUCT AND AIR TRANSFER PENETRATIONS THRU BUILDING ASSEMBLIES REQUIRING PROTECTION SHALL BE PROTECTED WITH FIRE DAMPERS, SMOKE DAMPERS, COMBINATION SMOKE/FIRE DAMPERS AND CEILING RADIATION DAMPERS IN ACCORDANCE WITH SECTION 607 OF THE CALIFORNIA MECHANICAL CODE. DUCTS NOT REQUIRING DAMPERS SHALL COMPLY WITH SECTION 714 & 717 OF THE 2022 CALIFORNIA BUILDING CODE.
- INSTALL SMOKED DETECTORS AND PROVIDE FOR SMOKE DETECTION AND AUTOMATIC SHUT-OFF OF ALL AIR HANDLING EQUIPMENT IN ACCORDANCE WITH SECTION 606 OF THE 2022 CALIFORNIA MECHANICAL CODE.
- UNLESS NOTED OTHERWISE, ALL LINE VOLTAGE WIRING, CONDUIT, FINAL CONNECTIONS, DISCONNECTS, STARTERS, AND OVER CURRENT PROTECTION DEVICES SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL CONTRACTOR AS INDICATED ON THESE MECHANICAL DRAWINGS AND/OR ELECTRICAL DRAWINGS AND/OR ELECTRICAL SECTION OF THE SPECIFICATIONS.
- INSTALL ALL LOW VOLTAGE HVAC CONTROL WIRE AND DEVICES PER PLAN. ALL WIRE SHALL BE IN CONDUIT PROVIDED AND INSTALLED BY THE ELECTIONAL CONTRACTOR UNLESS NOTEDD OTHERWISE.
- PROVIDE OWNER WITH THREE COPIES OF A CERTIFIED AIR BALANCE REPORT PREPARED IN BY A THIRD PARTY CERTIFIED BY THE AABC OR NEBB. TEST, ADJUST AND BALANCE THE HVAC SYSTEM IN ACCORDANCE WITH AABC OR NEBB PROCEDURES. PROVIDE START-UP/TEST REPORTS FOR ALL AIR HANDLING EQUIPMENT, FANS, AND REFRIGERATION EQUIPMENT. TEST AND VERIFY PROPER OPERATION OF ALL MAKE-UP AIR/EXHAUST AIR INTERLOCK SYSTEMS AND THEIR SEQUENCES OF OPERATION. BALANCE ALL AIR FLOWS WITHIN 5% OF DESIGN VALUES. PERMANENTLY MARK BALANCE POSITION OF ALL REGULATING DEVICES.
- PROVIDE OWNER WITH THREE SETS OF AS-BUILT PLANS AND OPERATIONS AND MAINTENANCE MANUALS. CLEARLY IDENTIFY ALL EQUIPMENT WITH PERMANENT PLASTIC OR METAL LABELS/TAGS (PEN MARKING NOT ACCEPTABLE).
- PROVIDE ONE YEAR WARRANTY ON ALL LABOR, PARTS AND MATERIALS.
- ANY CHANGE OR DEVIATION FROM THESE PLANS OR SPECIFICATIONS SHALL REQUIRE THE WRITTEN APPROVAL OF THE ENGINEER PRIOR TO COMMENCEMENT OF SUCH WORK. 19.0
- a) DUCTS FOR DEMAND CONTROLLED VENTILATION SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE FAN MANUFACTURER'S INSTALLATION INSTRUCTIONS, THE PROVISIONS ASHRAE 62.2, TABLE 5.3, OR THE AIRFLOW SHALL BE MEASURED AS REQUIRED BY AND IN COMPLIANCE WITH ASHRAE 62.2, 5.4.
- 1) DUCTS FOR KITCHEN COOKTOPS OR RANGES SHALL BE SHOWN OF METAL WITH A SMOOTH INTERIOR.
- a) DUCTS FOR DOMESTIC CLOTHES DRYERS SHALL BE INSTALLED IN ACCORDANCE WITH CMC 504.0.
- b) DUCTS FOR DOMESTIC CLOTHES DRYERS SHALL BE RIGID METALLIC DUCTS WITH A MINIMUM MILL THICKNESS OF 16 (0.016-INCH), SHALL HAVE A MINIMUM 4-INCH DIAMETER AND A SMOOTH INTERIOR. THE COMBINED HORIZONTAL AND VERTICAL LENGTH OF THE DUCTS OF THE DUCTS SHALL BE 14-FEET, WHICH SHALL BE REDUCED BY 2-FEET FOR EVERY 90-DEGREE ELBOW IN EXCESS OF TWO ELBOWS.
- c) LISTED CLOTHES DRYER TRANSITION DUCTS NOT MORE THAN 6-FEET IN LENGTH SHALL BE PERMITTED TO CONNECT THE DRYER TO THE EXHAUST DUCTS AS LONG AS THEY ARE NOT CONCEALED WITHIN CONSTRUCTION, AND THEY ARE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.

LEGEND

		DUCT WORK (WIDTHxDEPTH)
		LINED DUCT WORK (WIDTHxDEPTH DIMENSIONS ARE FOR I.D.)
		SUPPLY DUCT, SECTION
		RETURN DUCT, SECTION
		EXHAUST DUCT, SECTION
		RISE OR DROP IN DIRECTION OF AIR FLOW
	FLEX. CONN.	FLEXIBLE CONNECTION
		DUCT TRANSITION, ROUND AND RECTANGULAR
		SPLITTER DAMPER
		EXTRACTOR AT BRANCH DUCT
		TURNING VANES
		FLEXIBLE DUCT
		SINGLE LINE DUCT WORK
	AVD	AUTOMATIC VOLUME DAMPER
	MVD	MANUAL VOLUME DAMPER
	BDD	BACKDRAFT DAMPER
	MD	MODULATING DAMPER
	AFD	AUTOMATIC FIRE DAMPER
	AD	ACCESS DOOR
	SD	SUPPLY DIFFUSER
	RR	RETURN REGISTER
	ER	EXHAUST REGISTER
	SWR	SIDE WALL SUPPLY REGISTER
	SWE	SIDE WALL RETURN OR EXHAUST
	LD	LINEAR DIFFUSER
	DL	DOOR LOUVER
	UC	UNDER CUT DOOR
	VAV	VARIABLE AIR VOLUME
		THERMOSTAT
		DUCT SMOKE DETECTOR
	T/B	TO BELOW
	F/B	FROM BELOW
	T/A	TO ABOVE
	F/A	FROM ABOVE

SPECIAL NOTICE TO CONTRACTORS

- ALL CONTRACTORS (GENERAL CONTRACTOR AND SUB-CONTRACTORS) BIDDING THIS PROJECT ARE REQUIRED TO VISIT THE JOB SITE AND VERIFY THE EXISTING CONDITIONS PRIOR TO SUBMITTING THEIR BID. CONTRACTORS ARE TO CAREFULLY REVIEW ALL CONSTRUCTION DOCUMENTS AND NOTE ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED AT THE JOB SITE PRIOR TO SUBMISSION OF ANY BID. THE BUILDING OWNER REPRESENTATIVE LISTED BELOW MAY BE CONTACTED FOR ACCESS TO THE JOB SITE.
- CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO, GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.
- ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED SHALL BE BROUGHT TO THE ATTENTION, IN WRITING, TO THE ARCHITECT AND/OR ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION. NO WORK SHALL BE DONE ON ANY PART OF THE BUILDING BEYOND THE POINT INDICATED IN EACH SUCCESSIVE INSPECTION WITHOUT FIRST OBTAINING THE WRITTEN APPROVAL OF THE CODE OFFICIAL. NO CONSTRUCTION SHALL BE CONCEALED WITHOUT BEING INSPECTED AND APPROVED.

SCOPE OF WORK

PROVIDE MECHANICAL DESIGN FOR THE REMODEL OF ADULT DAY CARE.

MECHANICAL LIST OF DRAWINGS (LoD):

SHEET TAG	TITLE	SCALE
M 0.00	MECH GENERAL NOTES AND SPECIFICATIONS.	NTS
M 0.01	MECHANICAL CODE CHECKING.	NTS
M 1.01	MAIN FLOOR - MECHANICAL LAYOUT.	1/8"=1'-0"
M 1.02	ROOF PLAN - MECHANICAL LAYOUT.	1/8"=1'-0"
M 2.01	MECHANICAL EQUIPMENT SCHEDULE.	NTS
M 3.01	MECHANICAL EQUIPMENT DATASHEETS.	NTS
M 4.01	MECHANICAL GENERAL DETAILS.	NTS

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
MECHANICAL GENERAL
NOTES & SPECIFICATIONS

PROJ. NO. PROJ. ENGR. SCALE @ 24X36:
NTS

DRAWING NO.

REV.

M 0 . 0 0

CALIFORNIA MECHANICAL CODE CHECKING:

DUCT SIZING, THICKNESS & INSULATION

PLEASE REFER TO TABLE 506.2(1) FOR MINIMUM SHEET METAL THICKNESS FOR ROUND DUCTS

604.0 Insulation of Ducts.

604.1 General. Air ducts conveying air at temperatures exceeding 140°F (60°C) shall be insulated to maintain an insulation surface temperature of not more than 140°F (60°C). Factory-made air ducts and insulations intended for installation on the exterior of ducts shall be legibly printed with the name of the manufacturer, the thermal resistance (R) value at installed thickness, flame-spread index, and smoke developed index of the composite material. Internal duct liners and insulation shall be installed in accordance with SMACNA HVAC Duct Construction standards – Metal and Flexible. **[OSHPD 1, 1R, 2, 3, 4 & 5] Cold air ducts shall be insulated wherever necessary or to prevent condensation.**

Exceptions:

- (1) Factory-installed plenums, casings, or ductwork furnished as part of HVAC equipment tested and rated in accordance with approved energy efficiency standards.
- (2) Ducts or plenums located in conditioned spaces where heat gain or heat loss will not increase energy use.
- (3) For runouts less than 10 feet (3048 mm) in length to air terminals or air outlets, the rated R-value of insulation need not exceed R-3.5.
- (4) Backs of air outlets and outlet plenums exposed to unconditioned or indirectly conditioned spaces with face areas exceeding 5 square feet (0.5m²) need not exceed R-2; those 5 square feet (0.5m²) or smaller need to be insulated.
- (5) Ducts and plenums used exclusively for evaporative cooling systems.

E 502.4 Ducts. Ducts shall be sized, installed, and tested in accordance with Section E 502.4.1 though Section E 502.4.4.

E 502.4.1 Insulation and Ducts. Portions of the air distribution system installed in or on buildings for heating and cooling shall be R-8. Where the mean outdoor dew-point temperature in a month exceeds 60°F (16°C), vapor retarders shall be installed on conditioned-air supply ducts. Vapor retarders shall have a water vapor permeance not exceeding 0.5 perm [2.87 E-11 kg/(Pa.s.m²)] where tested in accordance with Procedure A in ASTM E96.

Insulation shall not be required where the ducts are within the conditioned space. [ASHRAE 90.2:6.4]

E 502.4.4 Duct Sizing. Duct systems shall be sized in accordance with ACCA Manual D or other methods approved by the Authority Having Jurisdiction with the velocity in the main duct not exceed 1000 feet per minute (ft/min) (5.08m/s) and the velocity in the secondary branch duct not to exceed 600 ft/min (3.048 m/s).

CONDENSATE DRAIN:

310.0 Condensate Wastes and Control.

310.1 Condensate Disposal. Condensate from air washers, air-cooling coils, condensing appliances, and the overflow from evaporative coolers and similar water-supplied equipment or similar air-conditioning equipment shall be collected and discharged to an approved plumbing fixture or disposal area. Where discharged into the drain system, equipment shall drain by means of an indirect waste pipe. The Waste pipe shall have a slope of not less than 1/8 inch per foot (10.4 mm/m) or 1 percent slope and shall be of approved corrosion-resistant material not smaller than the outlet size in accordance with Section 310.3 or Section 310.4 for air-cooling coils or condensing appliances, respectively. Condensate or wastewater shall not drain over a public way.

310.3 Condensate Waste Pipe Material and Sizing.

Condensate waste pipes from air-cooling coils shall be sized in accordance with the equipment capacity as specified in Table 310.3. The material of the piping shall comply with the pressure and temperature rating of the appliance or equipment, and shall be approved for use with the liquid being discharged.

TABLE 310.3
MINIMUM CONDENSATE WASTE PIPE SIZE

EQUIPMENT CAPACITY IN TONS OF REFRIGERATION	MINIMUM CONDENSATE PIPE DIAMETER (inches)
Up to 20	3/4
21 – 40	1
41 – 90	1 1/4
91 – 125	1 1/2
126 – 250	2

For SI units: 1 ton of refrigeration = 3.52 kW, 1 inch = 25 mm

310.3.1 Cleanouts. Condensate drain lines shall be configured or provided with a cleanout to permit the clearing of blockages and for maintenance without requiring the drain line to be cut.

310.5 Point of Discharge. Air conditioning condensate waste pipes shall connect indirectly, except where permitted in Section 310.6, to the drainage system through an air gap or air break to trapped and vented receptors, dry wells, leach pits, or the tailpiece of plumbing fixtures. A condensate drain shall be trapped in accordance with the appliance manufacturer's instructions or as approved.

310.6 Condensate Waste From Air-Conditioning Coils. Where the condensate waste from air-conditioning coils discharges by direct connection to a lavatory tailpiece or to an approved accessible inlet on a bathtub overflow, the connection shall be located in the area controlled by the same person controlling the air-conditioned space.

AIR INTAKE AND EXHAUST:

402.4 Outdoor Air Intake Protection. Required outdoor-air intakes shall be covered with a screen having not less than 1/4 of an inch (6.4 mm) openings, and shall have not more than 1/2 of an inch (12.7 mm) openings.

402.4.1 Weather Protections. Outdoor air intakes that are part of the mechanical ventilation system shall be designed to manage rain entrainment, to prevent rain intrusion, and manage water from snow in accordance with ASHRAE 62.1.

402.5 Bathroom Exhaust Fans. [HCD 1 & HCD 2] Each bathroom shall be mechanically ventilated in accordance with Division 4.5 of the California Green Building Standards Code (CALGreen).

407.2.2 Exhaust Outlets. Exhaust outlets shall be located a minimum of 10 feet (3048 mm) above adjoining grade and 10 feet (3048 mm) from doors, occupied areas, and operable windows.

Exception: Airborne infection isolation rooms shall comply with Section 414.1.

701.10.1 Minimum Screen Mesh Size. Screens shall be not less than 1/4 of an inch (6.4 mm) mesh. [NFPA 54:9.3.7.2]

311.3 Prohibited Source. Outside or return air for a heating or cooling air system shall not be taken from the following locations:

- (1) Less than 10 feet (3048 mm) in distance from an appliance vent outlet, a vent opening of a plumbing drainage system, or the discharge outlet of an exhaust fan, unless the outlet is 3 feet (914 mm) above the outside-air inlet.
- (2) Less than 10 feet (3048 mm) above the surface of an abutting public way, sidewalk, street, alley, or driveway.

GAS CLOTHES DRYER:

502.1 Exhaust Opening Protection. Exhaust openings terminating to the outdoors shall be covered with a corrosion-resistant screen having not less than 1/4 of an inch (6.4 mm) openings, and shall have not more than 1/2 of an inch (12.7 mm) openings.
Exception: Clothes dryers.

504.4 Clothes Dryers. A clothes dryer exhaust duct shall not be connected to a vent connector, gas vent, chimney, and shall not terminate into a crawl space, attic, or other concealed space. Exhaust ducts shall not be assembled with screws or other fastening means that extend into the duct and that are capable of catching lint, and that reduce the efficiency of the exhaust system.

504.4.1 Provisions for Makeup Air. Make up air shall be provided in accordance with the following:

- (1) Makeup air shall be provided for Type 1 clothes dryers in accordance with the manufacturer's instructions. [NFPA 54: 10.4.3.1] Where a closet is designed for the installation of a clothes dryer, an opening of not less than 100 square inches (0.065 m²) for makeup air shall be provided in the door or by other approved means.
- (2) Provision for makeup air shall be provided for Type 2 clothes dryers, with a free area of not less than 1 square inch (0.0006 m²) for each 1000 British thermal units per hour (Btu/g) (0.293 kW) total input rating of the dryer(s) installed [NFPA 54:10.4.3.2].

504.4.2.1 Length Limitation

Unless otherwise permitted or required by the dryer manufacturer's instructions and approved by the Authority Having Jurisdiction, domestic dryer moisture exhaust ducts shall not exceed a total combined horizontal and vertical length of 14 feet (4267 mm), including two 90 degree (1.57 rad) elbows. A length of 2 feet (610 mm) shall be deducted for each 90 degree (1.57 rad) elbow in excess of two

504.4.3.1 Exhaust Ducts for Type 2 Clothes Dryers.

Exhaust ducts for Type 2 clothes dryers shall comply with the following:

- (1) Exhaust ducts for Type 2 clothes dryers shall comply with Section 504.4. [NFPA 54:10.4.5.1]
- (2) Exhaust ducts for Type 2 clothes dryers shall be constructed of sheet metal or other noncombustible material. Such ducts shall be equivalent in strength and corrosion resistance to ducts 0.0195 of an inch (0.4953 mm) thick. [NFPA 54:10.4.5.2]
- (3) Type 2 clothes dryers shall be equipped or installed with lint-controlling means. [NFPA 54:10.4.5.3]
- (4) Exhaust ducts for Type 2 clothes dryers shall be installed with a clearance of not less than 6 inches (152 mm) from adjacent combustible material. Where exhaust ducts for Type 2 clothes dryers are installed with reduced clearances, the adjacent combustible material shall be protected in accordance with Table 303.10.1. [NFPA 54:10.4.5.4]
- (5) Where ducts pass through walls, floors, or partitions, the space around the duct shall be sealed with noncombustible material. [NFPA 54:10.4.5.4]

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- 1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- 2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- 3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- 4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
MECHANICAL CODE CHECKING.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS

DRAWING NO.

REV.

M 0 . 0 1

FACTORY-MADE AIR DUCTS

FACTORY-MADE AIR DUCTS SHALL BE LISTED AND LABELED IN ACCORDANCE WITH UL 181 AND INSTALLED IN ACCORDANCE WITH THE TERMS OF THEIR LISTING, THE MANUFACTURER'S INSTALLATION INSTRUCTIONS, AND SMACNA HVAC DUCT CONSTRUCTION STANDARDS-METAL AND FLEXIBLE.

FACTORY-MADE AIR DUCTS SHALL NOT BE USED FOR VERTICAL RISERS IN AIR-DUCT SYSTEMS SERVING MORE THAN TWO STORIES AND SHALL NOT PENETRATE A FIRE-RESISTANCE-RATED ASSEMBLY OR CONSTRUCTION.

FACTORY-MADE AIR DUCTS SHALL BE INSTALLED WITH NOT LESS THAN 4 INCHES (102 MM) OF SEPARATION FROM EARTH, EXCEPT WHERE INSTALLED AS A LINER INSIDE OF CONCRETE, TILE, OR METAL PIPE AND SHALL BE PROTECTED FROM PHYSICAL DAMAGE.

THE TEMPERATURE OF THE AIR TO BE CONVEYED IN A DUCT SHALL NOT EXCEED 250°F (121° C). FLEXIBLE AIR CONNECTORS SHALL NOT BE PERMITTED.

RECTANGULAR DUCTS

SUPPORTS FOR RECTANGULAR DUCTS SHALL BE INSTALLED ON TWO OPPOSITE SIDES OF EACH DUCT AND SHALL BE RIVETED, BOLTED, OR METAL SCREWED TO EACH SIDE OF THE DUCT AT INTERVALS SPECIFIED.

METAL DUCTS

DUCTS SHALL BE SUPPORTED AT EACH CHANGE OF DIRECTION AND IN ACCORDANCE WITH SMACNA HVAC DUCT CONSTRUCTION STANDARDS-METAL AND FLEXIBLE. RISER DUCTS SHALL BE HELD IN PLACE BY MEANS OF METAL STRAPS OR ANGLES AND CHANNELS TO SECURE THE RISER TO THE STRUCTURE.

METAL DUCTS SHALL BE INSTALLED WITH NOT LESS THAN 4 INCHES (102 MM) SEPARATION FROM EARTH. DUCTS SHALL BE INSTALLED IN A BUILDING WITH CLEARANCES THAT WILL RETAIN THE FULL THICKNESS OF FIRE-PROOFING ON STRUCTURAL MEMBERS.

COMBUSTIBLES WITHIN DUCTS OR PLENUMS

MATERIALS EXPOSED WITHIN DUCTS OR PLENUMS SHALL BE NONCOMBUSTIBLE OR SHALL HAVE A FLAME SPREAD INDEX NOT TO EXCEED 25 AND A SMOKE-DEVELOPED INDEX NOT TO EXCEED 50, WHERE TESTED AS A COMPOSITE PRODUCT IN ACCORDANCE WITH ASTM E84 OR UL 723.

EXCEPTIONS:

- 1. RETURN-AIR AND OUTSIDE-AIR DUCTS, PLENUMS, OR CONCEALED SPACES THAT SERVE A DWELLING UNIT.
- 2. AIR FILTERS IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION 311.2.
- 3. WATER EVAPORATION MEDIA IN AN EVAPORATIVE COOLER.
- 4. CHARCOAL FILTERS WHERE PROTECTED WITH AN APPROVED FIRE SUPPRESSION SYSTEM.
- 5. PRODUCTS LISTED AND LABELED FOR INSTALLATION WITHIN PLENUMS IN ACCORDANCE WITH SECTION 602.2.1 THROUGH SECTION 602.2.3.
- 6. SMOKE DETECTORS.
- 7. DUCT INSULATION, COVERINGS, AND LININGS AND OTHER SUPPLEMENTARY MATERIALS INSTALLED IN ACCORDANCE WITH SECTION 604.0.
- 8. MATERIALS IN A HAZARDOUS FABRICATION AREA INCLUDING THE AREAS ABOVE AND BELOW THE FABRICATION AREA SHARING A COMMON AIR RECIRCULATION PATH WITH THE FABRICATION AREA.



NOTES ON DUCTS MATERIAL & CONSTRUCTION:

FLEXIBLE AIR DUCTS

FLEXIBLE AIR DUCTS SHALL COMPLY WITH UL 181, AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND SMACNA HVAC DUCT CONSTRUCTION STANDARDS-METAL AND FLEXIBLE.

FLEXIBLE AIR DUCT INSTALLATIONS SHALL COMPLY WITH THE FOLLOWING:

- 1. DUCTS SHALL BE INSTALLED USING THE MINIMUM REQUIRED LENGTH TO MAKE THE CONNECTION.
- 2. HORIZONTAL DUCT RUNS SHALL BE SUPPORTED AT NOT MORE THAN 4 FEET (1219 MM) INTERVALS.
- 3. VERTICAL RISERS SHALL BE SUPPORTED AT NOT MORE THAN 6 FEET (1829 MM) INTERVALS.
- 4. SAG BETWEEN SUPPORT HANGERS SHALL NOT EXCEED 1/2 INCH (12.7 MM) PER FOOT (305 MM) OF SUPPORT SPACING.
- 5. SUPPORTS SHALL BE RIGID AND SHALL BE NOT LESS THAN 1 1/2 INCHES (38 MM) WIDE AT POINT OF CONTACT WITH THE DUCT SURFACE.
- 6. DUCT BENDS SHALL BE NOT LESS THAN ONE DUCT DIAMETER BEND RADIUS.
- 7. SCREWS SHALL NOT PENETRATE THE INNER LINER OF NONMETALLIC FLEXIBLE DUCTS UNLESS PERMITTED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.
- 8. FITTINGS FOR ATTACHING NON-METALLIC DUCTS SHALL BE BEADED AND HAVE A COLLAR LENGTH OF NOT LESS THAN 2 INCHES (51 MM) FOR ATTACHING THE DUCT.
- EXCEPTION: A BEAD SHALL NOT BE REQUIRED WHERE METAL WORM-GEAR CLAMPS ARE USED OR WHERE ATTACHING METALLIC DUCTS USING SCREWS IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.
- 9. DUCT INNER LINER SHALL BE INSTALLED AT NOT LESS THAN 1 INCH (25.4 MM) ON THE COLLAR AND PAST THE BEAD PRIOR TO THE APPLICATION OF THE TAPE AND MECHANICAL FASTENER. WHERE MASTIC IS USED INSTEAD OF TAPE, THE MASTIC SHALL BE APPLIED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.
- 10. DUCT OUTER VAPOR BARRIERS SHALL BE SECURED USING TWO WRAPS OF APPROVED TAPE. A MECHANICAL FASTENER SHALL BE PERMITTED TO BE USED IN PLACE OF, OR IN COMBINATION WITH, THE TAPE.
- 11. FLEXIBLE AIR DUCTS SHALL NOT PENETRATE A FIRE-RESISTANCE-RATED ASSEMBLY OR CONSTRUCTION.
- 12. THE TEMPERATURE OF THE AIR TO BE CONVEYED IN A FLEXIBLE AIR DUCT SHALL NOT EXCEED 250°F (121° C).
- 13. FLEXIBLE AIR DUCTS SHALL BE SEALED IN ACCORDANCE WITH SECTION 603.10.



PROJECT: ADULT DAY CARE

Ventilation Calculations:

Fresh Air Calculations

S.N.	Space Name	AREA (FT2)	TOTAL OUTDOOR AIR RATE (CFM/FT2)	TOTAL CFM
1	A-102: Nursing	384	0.15	58
2	A-103: Office Manager Room	153	0.15	23
3	A-104: Multipurpose Conference Room	388	0.50	194
4	A-105: Program Director Room	178	0.15	27
5	A-106: Physical/Occupational Therapy	596	0.50	298
6	A-107: Quite Room	150	0.15	23
7	A-108: Social Work	340	0.15	51
8	A-101: Open Hall	4,180	0.15	627
9	A-109: New Women's Restroom	265	0.15	40
10	A-110: New Men's Restroom	304	0.15	46
11	A-111: Storage	69	0.15	10
12	A-112: Pantry	382	0.15	57
13	A-113: Corridor	420	0.15	63
14	A-114: Utility	35	0.15	5
15	Corridor	160	0.15	24
16	TOTAL =	8,004	-	1,545

GENERAL NOTES:

- MECHANICAL CONTRACTOR TO COORDINATE ROUTING AND LOCATION OF MECHANICAL COMPONENTS AND EQUIPMENT WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS PRIOR TO PERFORMING WORK.
- CONTRACTOR TO CUT AND PATCH AS REQUIRED TO PERFORM THE WORK.
- ACCESS DOORS ARE REQUIRED FOR ANY COMPONENT REQUIRING ACCESS ABOVE HARD LID CEILINGS. COORDINATE SIZE, LOCATION AND FINISH WITH ARCHITECT PRIOR TO PERFORMING WORK.
- REFER TO THE DIAGRAMS THAT APPLY TO THIS SHEET WHICH PROVIDE GENERAL GUIDANCE FOR INSTALLATION THOUGH NOT ALL COMPONENTS AND ACCESSORIES MAY BE SHOWN.
- PRIOR TO INSTALLATION, CONFIRM SPECIFIC LOCATION FOR ALL THERMOSTATS / SENSORS WITH ARCHITECT. MOUNT AT 48" A.F.F. OR IN ACCORDANCE WITH ADA REQUIREMENTS. PROVIDE LOCKING COVERS.
- COORDINATE AND CONFIRM BORDER, FRAME, FINISH, AND LOCATION WITH ARCHITECT PRIOR TO ORDERING.
- ANY PENETRATIONS THROUGH WALL STUDS, FLOOR JOISTS, OR ROOF TO BE IN ACCORDANCE WITH THE LATEST ADOPTED BUILDING CODE.
- DUCT DIMENSIONS SHOWN ARE CLEAR INSIDE DIMENSIONS.
- CONTRACTOR TO CONFIRM ADEQUATE RETURN AIR PATH BACK TO MAIN AIR HANDLING UNIT.

CMC-303.8-Appliances on roofs shall be designed or enclosed so as to withstand climatic conditions in the area in which they are installed. Where enclosures are provided, each enclosure shall permit easy entry and movement, shall be of reasonable height, and shall have at least a 30 inch (762 mm) clearance between the entire service access panel(s) of the appliance and the wall of the enclosure. [NFPA 54:9.4.1.1]

CMC-303.8.4-Appliances shall be installed on a well-drained surface of the roof. At least 6 feet (1829 mm) of clearance shall be available between any part of the appliance and the edge of a roof or similar hazard, or rigidly fixed rails, guards, parapets, or other building structures at least 42 inches (1067 mm) in height shall be provided on the exposed side. [NFPA 54:9.4.2.2]

CMC-304.2-Where equipment or appliances that require service are installed on a roof having a slope of 4 units vertical in 12 units horizontal (33 percent slope) or more, a level platform of not less than 30 inches by 30 inches (762 mm by 762 mm) shall be provided at the service side of the equipment or appliance.

CMC-407.2-Outdoor air intakes shall be located at least 25 feet (7.62 m) from exhaust outlets of ventilating systems, combustion equipment stacks, medical-surgical vacuum systems, cooling towers, and areas that may collect vehicular exhaust or other noxious fumes. Plumbing vents shall be located in relation to outdoor air intakes per California Plumbing Code. The bottom of outdoor air intakes shall be located as high as practicable, but not less than 10 feet (3048 mm) above ground level. If installed above the roof, they shall be located 18 inches (457 mm) above roof level or 3 feet (914 mm) above a flat roof where heavy snowfall is anticipated.

CMC-502.2.1-Environmental air duct exhaust shall terminate not less than 3 feet (914 mm) from a property line, 10 feet (3048 mm) from a forced air inlet, 10 feet (3048 mm) above a public walkway, and 3 feet (914 mm) from openings into the building. The discharge of environmental exhaust ducts shall not be directed onto a public walkway

CMC-504.1.1-Exhaust ducts shall terminate outside the building and shall be equipped with backdraft dampers or with motorized dampers that automatically shut where the systems or spaces served are not in use. [OSHPD 1, 1R, 2, 4 & 5] Exception: Backdraft dampers are not required when the exhaust fan must operate continuously.

Exception: Where the exhaust duct does not discharge into a common exhaust plenum and one of the following:

- The exhaust fan runs continuously.
- The exhaust duct serves space(s) that are not mechanically heated or cooled.
- The space served is maintained at positive pressure.

CMC-504.4.1-Makeup air shall be provided in accordance with the following:

Makeup air shall be provided for Type 1 clothes dryers in accordance with the manufacturer's installation instructions. [NFPA 54:10.4.3.1] Where a closet is designed for the installation of a clothes dryer, an opening of not less than 100 square inches (0.065 m2) for makeup air shall be provided in the door or by other approved means.

Provision for makeup air shall be provided for Type 2 clothes dryers, with a minimum free area of 1 square inch (0.0006 m2) for each 1000 British thermal units per hour (Btu/h) (0.293 kW) total input rating of the dryer(s) installed. [NFPA 54:10.4.3.2]

CMC-504.4.2-Where a compartment or space for a Type 1 clothes dryer is provided, not less than a 4 inch diameter (102 mm) exhaust duct of approved material shall be installed in accordance with Section 504.0.

Type 1 clothes dryer exhaust ducts shall be of rigid metal and shall have smooth interior surfaces. The diameter shall be not less than 4 inches nominal (100 mm), and the thickness shall be not less than 0.016 of an inch (0.406 mm)

CMC-504.4.2.1-Unless otherwise permitted or required by the dryer manufacturer's instructions and approved by the Authority Having Jurisdiction, domestic dryer moisture exhaust ducts shall not exceed a total combined horizontal and vertical length of 14 feet (4267 mm), including two 90 degree (1.57 rad) elbows. A length of 2 feet (610 mm) shall be deducted for each 90 degree (1.57 rad) elbow in excess of two.

Exception: Where an exhaust duct power ventilator, in accordance with Section 504.4.2.3, is used, the maximum length of the dryer exhaust duct shall be permitted to be in accordance with the dryer exhaust duct power ventilator manufacturer's installation instructions.

CMC-Appendix E 502.3.1-Balancing Dampers shall be installed in branch ducts, and the axis of the damper shall be installed parallel to the direction of airflow in the main duct

CMC-Appendix E 502.4.4-Duct systems shall be sized in accordance with ACCA Manual D.

Velocity in main duct shall not exceed 1000 feet per minute.
Velocity in section branches shall not exceed 600 feet per minute.

CMC-Appendix E 503.4.6.1-Outdoor air intake and exhaust systems shall be equipment with motorized dampers that will automatically shut when the systems or spaces served are not in use.
Exceptions: Back-draft gravity dampers shall be permitted for exhaust and relief in buildings less than 3 stories in height.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS

APPEARING HEREIN CONSTITUTE THE

ORIGINAL AND UNPUBLISHED WORK OF THE

DESIGNER AND THE SAME MAY NOT BE

DUPLICATED, USED OR DISCLOSED WITHOUT

CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
**MAIN FLOOR -
MECHANICAL LAYOUT.**


PROJ. NO. PROJ. ENGR. SCALE @ 24X36"

1/8"=1'-0"

DRAWING NO.

REV.

M 1 . 0 1



GENERAL NOTES:

- MECHANICAL CONTRACTOR TO COORDINATE ROUTING AND LOCATION OF MECHANICAL COMPONENTS AND EQUIPMENT WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS PRIOR TO PERFORMING WORK.
- CONTRACTOR TO CUT AND PATCH AS REQUIRED TO PERFORM THE WORK.
- ACCESS DOORS ARE REQUIRED FOR ANY COMPONENT REQUIRING ACCESS ABOVE HARD LID CEILINGS. COORDINATE SIZE, LOCATION AND FINISH WITH ARCHITECT PRIOR TO PERFORMING WORK.
- REFER TO THE DIAGRAMS THAT APPLY TO THIS SHEET WHICH PROVIDE GENERAL GUIDANCE FOR INSTALLATION THOUGH NOT ALL COMPONENTS AND ACCESSORIES MAY BE SHOWN.
- PRIOR TO INSTALLATION, CONFIRM SPECIFIC LOCATION FOR ALL THERMOSTATS / SENSORS WITH ARCHITECT. MOUNT AT 48" A.F.F. OR IN ACCORDANCE WITH ADA REQUIREMENTS. PROVIDE LOCKING COVERS.
- COORDINATE AND CONFIRM BORDER, FRAME, FINISH, AND LOCATION WITH ARCHITECT PRIOR TO ORDERING.
- ANY PENETRATIONS THROUGH WALL STUDS, FLOOR JOISTS, OR ROOF TO BE IN ACCORDANCE WITH THE LATEST ADOPTED BUILDING CODE.
- DUCT DIMENSIONS SHOWN ARE CLEAR INSIDE DIMENSIONS.
- CONTRACTOR TO CONFIRM ADEQUATE RETURN AIR PATH BACK TO MAIN AIR HANDLING UNIT.

CMC-303.8-Appliances on roofs shall be designed or enclosed so as to withstand climatic conditions in the area in which they are installed. Where enclosures are provided, each enclosure shall permit easy entry and movement, shall be of reasonable height, and shall have at least a 30 inch (762 mm) clearance between the entire service access panel(s) of the appliance and the wall of the enclosure. [NFPA 54:9.4.1.1]

CMC-303.8.4-Appliances shall be installed on a well-drained surface of the roof. At least 6 feet (1829 mm) of clearance shall be available between any part of the appliance and the edge of a roof or similar hazard, or rigidly fixed rails, guards, parapets, or other building structures at least 42 inches (1067 mm) in height shall be provided on the exposed side. [NFPA 54:9.4.2.2]

CMC-304.2-Where equipment or appliances that require service are installed on a roof having a slope of 4 units vertical in 12 units horizontal (33 percent slope) or more, a level platform of not less than 30 inches by 30 inches (762 mm by 762 mm) shall be provided at the service side of the equipment or appliance.

CMC-407.2-Outdoor air intakes shall be located at least 25 feet (7.62 m) from exhaust outlets of ventilating systems, combustion equipment stacks, medical-surgical vacuum systems, cooling towers, and areas that may collect vehicular exhaust or other noxious fumes. Plumbing vents shall be located in relation to outdoor air intakes per California Plumbing Code. The bottom of outdoor air intakes shall be located as high as practicable, but not less than 10 feet (3048 mm) above ground level. If installed above the roof, they shall be located 18 inches (457 mm) above roof level or 3 feet (914 mm) above a flat roof where heavy snowfall is anticipated.

CMC-502.2.1-Environmental air duct exhaust shall terminate not less than 3 feet (914 mm) from a property line, 10 feet (3048 mm) from a forced air inlet, 10 feet (3048 mm) above a public walkway, and 3 feet (914 mm) from openings into the building. The discharge of environmental exhaust ducts shall not be directed onto a public walkway

CMC-504.1.1-Exhaust ducts shall terminate outside the building and shall be equipped with backdraft dampers or with motorized dampers that automatically shut where the systems or spaces served are not in use. [OSHPD 1, 1R, 2, 4 & 5] Exception: Backdraft dampers are not required when the exhaust fan must operate continuously.

Exception: Where the exhaust duct does not discharge into a common exhaust plenum and one of the following:

- The exhaust fan runs continuously.
- The exhaust duct serves space(s) that are not mechanically heated or cooled.
- The space served is maintained at positive pressure.

CMC-504.4.1-Makeup air shall be provided in accordance with the following:

Makeup air shall be provided for Type 1 clothes dryers in accordance with the manufacturer's installation instructions. [NFPA 54:10.4.3.1] Where a closet is designed for the installation of a clothes dryer, an opening of not less than 100 square inches (0.065 m2) for makeup air shall be provided in the door or by other approved means.

Provision for makeup air shall be provided for Type 2 clothes dryers, with a minimum free area of 1 square inch (0.0006 m2) for each 1000 British thermal units per hour (Btu/h) (0.293 kW) total input rating of the dryer(s) installed. [NFPA 54:10.4.3.2]

CMC-504.4.2-Where a compartment or space for a Type 1 clothes dryer is provided, not less than a 4 inch diameter (102 mm) exhaust duct of approved material shall be installed in accordance with Section 504.0.

Type 1 clothes dryer exhaust ducts shall be of rigid metal and shall have smooth interior surfaces. The diameter shall be not less than 4 inches nominal (100 mm), and the thickness shall be not less than 0.016 of an inch (0.406 mm)

CMC-504.4.2.1-Unless otherwise permitted or required by the dryer manufacturer's instructions and approved by the Authority Having Jurisdiction, domestic dryer moisture exhaust ducts shall not exceed a total combined horizontal and vertical length of 14 feet (4267 mm), including two 90 degree (1.57 rad) elbows. A length of 2 feet (610 mm) shall be deducted for each 90 degree (1.57 rad) elbow in excess of two.

Exception: Where an exhaust duct power ventilator, in accordance with Section 504.4.2.3, is used, the maximum length of the dryer exhaust duct shall be permitted to be in accordance with the dryer exhaust duct power ventilator manufacturer's installation instructions.

CMC-Appendix E 502.3.1-Balancing Dampers shall be installed in branch ducts, and the axis of the damper shall be installed parallel to the direction of airflow in the main duct

CMC-Appendix E 502.4.4-Duct systems shall be sized in accordance with ACCA Manual D.

Velocity in main duct shall not exceed 1000 feet per minute.

Velocity in section branches shall not exceed 600 feet per minute.

CMC-Appendix E 503.4.6.1-Outdoor air intake and exhaust systems shall be equipment with motorized dampers that will automatically shut when the systems or spaces served are not in use.

Exceptions: Back-draft gravity dampers shall be permitted for exhaust and relief in buildings less than 3 stories in height.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS

APPEARING HEREIN CONSTITUTE THE

ORIGINAL AND UNPUBLISHED WORK OF THE

DESIGNER AND THE SAME MAY NOT BE

DUPLICATED, USED OR DISCLOSED WITHOUT

CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

ROOF PLAN - MECHANICAL LAYOUT.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36" **1/8"=1'-0"**

DRAWING NO.

M 1 . 0 2

REV.

SCHEDULE No. 1

EXISTING ROOFTOP UNITS

TAG	(E) RTU-01	(E) RTU-02	(E) RTU-03,04	(E) RTU-05	(E) RTU-06
SERVING	CHECK PLANS	CHECK PLANS	CHECK PLANS	CHECK PLANS	CHECK PLANS
MANUFACTURER	BRYANT	CARRIER	YORK	RHEEM	GENERAL ELECTRIC
MODEL	577CPWC36060NA	48VLNC3606050	SA36G080-25G	RRNL-C060CK10E	BYC120D330
VOLTAGE (V / PH / HZ) - MCA (A) / MOCP (A)	208/230 / 3 / 60 - 20.1 / 30	208/230 / 3 / 60 - 20.1 / 30	208/230 / 3 / 60 - 25/21 / 35/30	208/230 / 3 / 60 - 32 / 45	230 / 3 / 60 - 68 / 90
COMPRESSOR RLA (A) / LRA (A)	10.4 / 73	10.4 / 73	13.7/12.6 / 74	17.9 / 110	22 / -
OUTDOOR - INDOOR FAN POWER (HP) / FLA (A)	1/5 / 1.05 - 3/4 / 6	1/5 / 1.05 - 3/4 / 6	1/4 / 4/2 - 1/3 / 3.8/3.3	1/3 / 2 - 1 / 7.6	1/2 / 3.8 - 3 / 9.2
COOLING CAPACITY (BTU/HR)	34,800	34,800	36,000	59,500	120,000
GAS INPUT / HEAT OUTPUT (BTU/HR)	60,000 / 48,000	60,000 / 48,000	80,000 / 60,000	100,000 / 81,000	225,000 TO 300,000 / 225,000
STANDARD CFM	1,200	1,200	1,200	2,000	4,000
WEIGHT (LBS)	170.4	170.4	180	532	800
WIDTH X DEPTH X HEIGHT (IN.)	48-3/16" X 32-5/8" X 46-1/8"	48-3/16" X 32-5/8" X 46-1/8"	42.4" X 41.3" X 22.4"	52-7/16" X 47-1/2" X 41"	61.3" X 46.3" X 31.5"
EER / THERMAL EFFICIENCY	11.5 / 80.6	11.5 / 80.6	- / 75	10.5 / 81	- / 75

SCHEDULE No. 2

PROGRAM DIRECTOR ROOM MECHANICAL SYSTEM

OUTDOOR / INDOOR UNIT TAG	(E) OU-01 / (E) IU-01
SERVING	PROGRAM DIRECTOR ROOM
MANUFACTURER	GOODMAN
OUTDOOR / INDOOR UNIT MODEL	AOU12RL2 / ASU12RL2
VOLTAGE (V / PH / HZ) - MCA (A) / MOCP (A)	115 / 1 / 60 - 15 / 20
RATED COOLING / HEATING INPUT POWER (KW)	1.2 / 1.21
RATED COOLING / HEATING CAPACITY (BTU/HR)	12,000 / 14,000
INDOOR UNIT MEDIUM AIR FLOW (CFM)	353
OUTDOOR / INDOOR WEIGHT (LBS)	69 / 16
OUTDOOR UNIT WIDTH X DEPTH X HEIGHT (IN.)	26" X 11-11/32" X 21-1/4"
INDOOR UNIT WIDTH X DEPTH X HEIGHT (IN.)	32-9/32" X 8-1/8" X 10-5/16"

SCHEDULE No. 4

AIR OUTLETS

TAG	DESCRIPTION	MANUFACTURER	MODEL	MOUNTING
S1	SUPPLY DIFFUSER	TITUS	24in. x 24in.	Duct Mounted
S2	SUPPLY DIFFUSER	TITUS	14in. x 6in.	Duct Mounted
R1	RETURN DIFFUSER	TITUS	24in. x 24in.	Duct Mounted
R2	RETURN GRILL	TITUS	6in. x 8in.	Duct Mounted
E1	EXHAUST AIR DIFFUSER	TITUS	14in. x 6in.	Duct Mounted

NOTES:

1. COORDINATE FINISH, COLOR, BORDER AND EXACT LOCATION WITH OWNER PRIOR TO ORDERING.
2. PROVIDE OPPOSED BLADE DAMPER ACCESSIBLE THROUGH DIFFUSER FACE FOR GYP BD. CEILING INSTALLATIONS.
3. PROVIDE DUCT TRANSITIONS AS REQUIRED.
4. RETURNS R1 ARE PROVIDED WITH PROPER FILTERS.

SCHEDULE No. 3

RESTROOM EXHAUST FANS

TAG	EF-01	EF-02
LOCATION	MEN'S RSTRM	WOMEN'S RSTRM
AIR FLOW (CFM) / SPEED (RPM)	490 / 1,530	420 / 1,528
DISCHARGE VELOCITY (FPM)	454	389
STATIC PRESSURE (IN. W.G)	1"	1"
VOLTAGE (V / PH / HZ)	230 / 1 / 60	230 / 1 / 60
POWER (W) / FLA (A)	181 / 2.4	159 / 2.4
MCA (A) / MOCP (A)	3 / 15	3 / 15
OPERATING POWER (HP)	0.24	0.21
STARTUP POWER (HP)	0.24	0.21
FAN TYPE	INLINE FAN	INLINE FAN
STATIC EFFICIENCY (%)	32	31
WEIGHT (LBS)	39	39
WIDTH X DEPTH X HEIGHT (IN.)	24" X 12" X 12"	24" X 12" X 12"
MANUFACTURER	GREENHECK	GREENHECK
MODEL	CSP-A700-VG	CSP-A700-VG

NOTES:

1. PROVIDE UL LISTING.
2. PROVIDE ENERGY STAR COMPLIANCE.
3. INTERLOCK WITH WALL SWITCH.
4. PROVIDE MOTOR WITH THERMAL OVERLOADS.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
MECHANICAL EQUIPMENT SCHEDULE.

PROJ. NO. | PROJ. ENGR. | SCALE @ 24X36:
NTS

DRAWING NO. | REV.

M 2 . 0 1

Model: CSP-A700-VG


Direct Drive Cabinet Fan

Standard Construction Features: Galvanized steel housing with duct collars. Centrifugal forward curved wheel. Direct driven motor in the air stream.

Fan Configuration	
Drive type	Direct

Performance	
Requested Volume (CFM)	490
Actual Volume (CFM)	490
Total External SP (in. wg)	1
Fan RPM	1,530
Operating Power (bhp)	0.24
Startup Power (bhp)	0.24
Air Stream Temp (F)	70
Start-up Temp (F)	70
Air Density (lbs/ft ³)	0.075
Elevation (ft)	160
Static Efficiency (%)	32
Outlet Velocity (ft/min)	454

Motor	
V/CP	230/60/1
NEC FLA (Amps)	2.4
Min Circuit Ampacity (MCA)	3
Max Overload Production (MOP)	15



— Fan curve
-- Brake horsepower curve
○ Operating Point SP
△ Operating Bhp point
— Max system curve

Sound	
Octave Bands (Hz)	LWA dBA Sones
62.5 125 250 500 1000 2000 4000 8000	
Inlet	55 57 57 46 47 44 46 39 54 39 3.3




Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 213 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA certified ratings seal applies to air performance ratings only. Performance certified is for installation type D: Ducted inlet, ducted outlet power rating does not include transmission losses. Performance ratings include the effects of a backdraft damper speed (BPS) shown is nominal. Performance is based on actual speed of fan. The sound ratings shown are loudness values in spherical zones at 3.5 m (15 ft) in a spherical free field calculated per ANSI/ISO 361. Values shown are for installation type D: ducted inlet spherical zone levels. Ratings do not include the effects of duct end correction. Ratings are based on 10 ft. of insulated duct.

Wattage is shown at free air. Wattage is approximate and may vary between motors. Fan shaft input power (bhp) is not certified. FLA is based on tables 100 or 140 of National Electric Code 2002. Actual motor FLA may vary. For sizing thermal overload, consult factory. MCA and MOP values shown only account for the motor, not accessories (damper actuator, field supplied VFD, etc.).

Version 3.5.0, June 2023

Dimensions and Weights		
Label	Value	Description
-	39	Weight w/o accessories (lbs)
A	12	Overall Height (in)
B	24	Overall Width (in)
C	12	Overall Length (in)



*All dimensions are in inches.

Page 2 of 2

Version 3.5.0, June 2023

Model: CSP-A700-VG


Direct Drive Cabinet Fan

Standard Construction Features: Galvanized steel housing with duct collars. Centrifugal forward curved wheel. Direct driven motor in the air stream.

Fan Configuration	
Drive type	Direct

Performance	
Requested Volume (CFM)	420
Actual Volume (CFM)	420
Total External SP (in. wg)	1
Fan RPM	1,528
Operating Power (bhp)	0.21
Startup Power (bhp)	0.21
Air Stream Temp (F)	70
Start-up Temp (F)	70
Air Density (lbs/ft ³)	0.075
Elevation (ft)	160
Static Efficiency (%)	31
Outlet Velocity (ft/min)	389

Motor	
V/CP	230/60/1
NEC FLA (Amps)	2.4
Min Circuit Ampacity (MCA)	3
Max Overload Production (MOP)	15



— Fan curve
-- Brake horsepower curve
○ Operating Point SP
△ Operating Bhp point
— Max system curve

Sound	
Octave Bands (Hz)	LWA dBA Sones
62.5 125 250 500 1000 2000 4000 8000	
Inlet	54 56 57 46 47 44 46 39 54 39 3.3




Greenheck Fan Corporation certifies that the model shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 213 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA certified ratings seal applies to air performance ratings only. Performance certified is for installation type D: Ducted inlet, ducted outlet power rating does not include transmission losses. Performance ratings include the effects of a backdraft damper speed (BPS) shown is nominal. Performance is based on actual speed of fan. The sound ratings shown are loudness values in spherical zones at 3.5 m (15 ft) in a spherical free field calculated per ANSI/ISO 361. Values shown are for installation type D: ducted inlet spherical zone levels. Ratings do not include the effects of duct end correction. Ratings are based on 10 ft. of insulated duct.

Wattage is shown at free air. Wattage is approximate and may vary between motors. Fan shaft input power (bhp) is not certified. FLA is based on tables 100 or 140 of National Electric Code 2002. Actual motor FLA may vary. For sizing thermal overload, consult factory. MCA and MOP values shown only account for the motor, not accessories (damper actuator, field supplied VFD, etc.).

Version 3.5.0, June 2023

Dimensions and Weights		
Label	Value	Description
-	39	Weight w/o accessories (lbs)
A	12	Overall Height (in)
B	24	Overall Width (in)
C	12	Overall Length (in)



*All dimensions are in inches.

Page 2 of 2

Version 3.5.0, June 2023

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
**MECHANICAL EQUIPMENT
DATA SHEETS.**


PROJ. NO. PROJ. ENGR. SCALE @ 24X36

NTS


DRAWING NO.

REV.


M 3 . 0 1



CONDENSATE DRAIN DETAIL









CEILING DIFFUSER CONNECTION DETAIL



TOILET EXHAUST FAN DIAGRAM

DUCTWORK SYMBOLS LEGEND



CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
MECHANICAL GENERAL DETAILS.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"
NTS

DRAWING NO.

M 4 . 0 1

REV.

ELECTRICAL SPECIFICATIONS

1.ELECTRICAL GENERAL NOTES

- A. GC SHALL VERIFY ANY THIRD PARTY INSPECTIONS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION PRIOR TO BIDDING THIS PROJECT.
- B. ALL LOW VOLTAGE WIRING TO BE IN CONDUIT UNLESS APPROVED OTHERWISE BY AUTHORITY HAVING JURISDICTION.
- C. ALL EMERGENCY LIGHTS & EXIT SIGNS ARE TO BE CONCECTED TO THE UNSWITCHED PORTION OF THE ADJACENT LIGHTING CIRCUIT. ALL EMERGENCY FIXTURES TO REMAIN ACTIVE FOR 90 MINUTE MINIMUM.
- D. ALL ELECTRICAL MATERIALS, DEVICES, APPLIANCES, AND EQUIPMENT SHALL BE LABELED AND LISTED BY A CERTIFIED TESTING LABORATORY OR AGENCY.
- E. ALL LIGHTING, DUCTWORK, SOFFITS, AND CEILING COMPONENT HEIGHTS ARE TO BE COORDINATED WITH THE ARCHITECT.
- F. ATTENTION LIGHTING SUPPLIER AND CONTRACTOR: ENSURE ALL LIGHTING EXPOSED TO PLENUM IS PLENUM RATED.
- G. COORDINATE THE MOUNTING OF ALL HIGH-BAY FIXTURES AND CEILING FANS WITH ARCHITECT PRIOR TO INSTALLATION.
- H. . VERIFY MOUNTING HEIGHTS OF ALL FIXTURES WITH ARCHITECTURAL ELEVATIONS PRIOR TO ROUGH-IN.
- I. FIRE ALARM CONTRACTOR SHALL VERIFY ALL BUILDING AND FIRE DEPARTMENT REQUIREMENTS REGARDING SHUT OFF OF ANY CCESSARY COMPONENTS UPON ACTIVATION OF THE FIRE ALARM. THIS INCLUDES, BUT IS NOT LIMITED TO:
 - a. AUDIO/MUSIC SYSTEM(S)
 - b. ROOFTOP UNITS
 - c. TANNING EQUIPMENT
 - d. EXERCISE FANS
- J. PROVIDE A SEPARATE EQUIPMENT GROUNDING CONDUCTOR (SIZE PER CEC) IN PVC TYPE CONDUIT, POWER CIRCUITS, ISOLATED GROUND CIRCUITS, OR AS SHOWN ON PLANS. CONDUIT SHALL BE SIZED PER CEC BASED ON THIN 600 VOLT COPPER SINGLE CONDUCTORS, PLUS THE EQUIPMENT GROUNDING CONDUCTOR.
- K. WIRING SHALL INCLUDE FINAL CONECTION TO ALL EQUIPMENT IN CONFORMANCE WITH EQUIPMENT SUPPLIER WIRING DIAGRAMS.
- L. CONTRACTOR IS RESPONSIBLE FOR PROVIDING COMPLETE PANELBOARD IDENTIFICATION SCHEDULES.
- M. BRANCH CIRCUIT CONDUCTORS SHALL BE MINIMUM #12 AWG UNLESS NOTED OTHERWISE IN SCHEDULES. WHERE 20A BRANCH CIRCUITS HAVE #8 AND LARGER WIRE SPECIFIED, #10 AWG WIRE SHALL BE USED FOR THE FINAL CONECTION (15 FOOT MAXIMUM).
- N. WHERE BRANCH CIRCUITS ARE GROUPED, SIZE CONDUIT AND DERATE CURRENT CARRYING CONDUCTORS PER CEC.
- O. PROVIDE HANDLE TIES ON ALL MULTIWIRE BRANCH CIRCUITS TO MEET CEC REQUIREMENTS.
- P. SUPPORT FROM STRUCTURE: NO ATTACHMENT OF ANY TYPE SHALL BE MADE TO BRIDGING OR JOIST WEB MEMBERS. UTILIZE ONLY THE TOP AND BOTTOM CHORDS FOR SUPPORTING THE ELECTRICAL SYSTEM INSTALLATIONS. REFER TO STRUCTURAL PLANS.
- Q. WHERE GROUPED CONDUITS ARE INSTALLED WITHIN THE JOIST SPACE, COORDINATE WITH SPRINKLER CONTRACTOR PRIOR TO INSTALLATION IN ORDER TO MAINTAIN REQUIRED CLEARANCES FROM SPRINKLERS.
- R. SEAL PENETRATIONS IN FIRE RATED WALLS PER CEC 300.21.
- S. ELECTRICAL EQUIPMENT, FIXTURES, DEVICES, AND OTHER ITEMS SHOWN IN THESE PLANS IN GREY HALFTONE ARE EITHER EXISTING TO REMAIN OR PART OF LANDLORD SHELL PACKAGE.
- T. PROVIDE ARC-FLASH COORDINATION STUDY PER CEC.
- U. PROVIDE (1) 1/2" CONDUIT AND (1) 4" SQUARE BOX WITH SINGLE GANG DEVICE RING FOR ALL THERMOSTAT LOCATIONS INDICATED ON MECHANICAL DRAWINGS. ROUTE CONDUIT FROM BOX TO ACCESSIBLE CEILING CAVITY. PROVIDE PLASTIC BUSHING ON EXPOSED CONDUIT ENDS, PROVIDE PULL STRING IN ALL EMPTY CONDUIT SYSTEMS. COORDINATE EXACT LOCATIONS AND MOUNTING HEIGHTS WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN.
- V. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE CONTRACTOR TO CLARIFY SCOPE OF WORK BEFORE BID OR INSTALLATION
- W. WIRING DEVICES: DEVICE MOUNTING HEIGHTS ARE FROM FINISHED FLOOR TO CENTER OF OUTLET BOX UNLESS NOTED OTHERWISE ON PLANS. COORDINATE THE STANDARD MOUNTING HEIGHTS WITH MASONRY:
 - a. SWITCHES 48" AFF
 - b. RECEPTACLES 18" AFF
 - c. VOICE/DATA 18" AFF

2. ELECTRICAL POWER NOTES

- A. ALL REQUIRED DOCUMENTATION REGARDING THE DESIGN OF FIRE DETECTION, ALARM, AND COMMUNICATIONS SYSTEMS AND THE PROCEDURES FOR MAINTENANCE, INSPECTION, AND TESTING OF FIRE DETECTION, ALARM, AND COMMUNICATIONS SYSTEMS SHALL BE MAINTAINED AT AN APPROVED, SECURED LOCATION FOR THE LIFE OF THE SYSTEM PER IFC 901.6.2.1.
- B. THE FIRE ALARM CONTROL PANEL DISCONNECTING MEANS SHALL HAVE A RED MARKING, SHALL ONLY BE ACCESSIBLE TO AUTHORIZED PERSONNEL, AND SHALL BE IDENTIFIED AS "FIRE ALARM CIRCUIT". THE LOCATION OF THE CIRCUIT DISCONNECTING MEANS SHALL BE IDENTIFIED AT THE FIRE ALARM CONTROL UNIT PER NFPA 72 4.4.1.4.2.2 AND 4.4.1.4.2.3.
- C. ROUTE ALL CONDUIT TIGHT TO DECK IN ACCORDANCE TO CEC 300.4(E)
- D. FIRE ALARM SYSTEM SHALL BE INSTALLED PER CURRENT NFPA STANDARDS.
- E. ALL ELECTRICAL THAT MAY NEED TO BE MAINTAINED WHILE ENERGIZED SHALL BE FIELD MARKED WITH ARC FLASH LABELING AND BE FULLY VISIBLE TO QUALIFIED PERSONNEL PRIOR TO EXAMINATION, ADJUSTMENT, SERVICING, OR MAINTENANCE OF EQUIPMENT.
- F. SERVICE EQUIPMENT SHALL BE LEGIBLY MARKED IN THE FIELD WITH THE MAXIMUM AVAILABLE FAULT CURRENT. THE FIELD MARKINGS SHALL INCLUDE THE DATE THE FAULT CURRENT CALCULATIONS WERE PERFORMED AND BE OF SUFFICIENT DURABILITY TO WITHSTAND THE ENVIRONMENT INVOLVED.
- G. FIRE ALARM DEVICE LOCATIONS ARE SHOWN FOR REFERENCE ONLY. THE ELECTRICAL CONTRACTOR SHALL INCLUDE A PRICE IN THE ELECTRICAL BID FOR A LANDLORD APPROVED FIRE ALARM SYSTEM, INCLUDING PLANS AND ALL ASSOCIATED DOCUMENTATION REQUIRED. THESE PLANS SHALL BE SUBMITTED TO THE LOCAL AUTHORITIES HAVING JURISDICTION BY A QUALIFIED AND LICENSED DESIGN-BUILD FIRE ALARM CONTRACTOR FOR A COMPLETE AND APPROVED FIRE ALARM SYSTEM. THE PLANS SHALL BE SIGNED AND SEALED BY THEIR LOCAL DESIGN ENGINEER AND SUBMITTED FOR PLAN REVIEW PRIOR TO RECEIVING SPECIFIC PERMITS FOR THIS WORK. THE FIRE ALARM CONTRACTOR SHALL ALSO SUBMIT ALL SHOP DRAWINGS, BATTERY CALCULATIONS, SPECIFICATION SHEETS, ETC. AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION TO THEIR LOCAL DESIGN ENGINEER FOR REVIEW AND APPROVAL.
- H. COORDINATE WITH MECHANICAL INSTALLER TO PROVIDE AND INSTALL CONDUIT AND JUNCTION BOXES FOR MECHANICAL THERMOSTATS.

3. NETWORK CABLING REQUIREMENTS

- A. EACH CAT 5 CABLE RUN MUST BE KEPT TO A MAXIMUM OF 295 FEET (90 METERS). INCLUDING PATCH CORDS, ENTIRE CHANNEL MAXIMUM LENGTH NOT TO EXCEED 328 FEET (100 METERS).
- B. MAINTAIN PAIR TWISTING AS CLOSE AS POSSIBLE TO FINAL TERMINATION POINTS WITH MAXIMUM UNTWISTED SEGMENT OF 1/2".
- C. WHERE CEESSARY, GRADUALLY BEND CABLE TO MAINTAIN THE MINIMUM BEND RADIUS OF 4 TIMES THE CABLE DIAMETER (APPROX. 1").
- D. USE LOW TO MODERATE PRESSURE TO DRESS CABLES NEATLY WITH CABLE TIES.
- E. USE LOW TO MODERATE FORCE WHEN PULLING CABLE. DO NOT EXCEED MAXIMUM OF 25 POUNDS OF FORCE.
- F. USE CABLE PULLING LUBRICANT FOR CABLE RUNS THAT MAY EXCEED 25 POUNDS OF FORCE WHEN PULLING.
- G. MAINTAIN 12" OF SEPARATION FROM POWER CABLES THAT MAY BE SOURCES OF EMI (ELECTRICAL CABLES, TRANSFORMERS, LIGHT FIXTURES, ETC.)
- H. INSTALL PROPER CABLE SUPPORTS WITH MAXIMUM OF 5 FEET OF SEPARATION.
- I. LEAVE EXCESS WIRE COILED IN THE CEILING OR NEAREST CONCEALED SPACE. MAINTAIN 5 FEET OF SLACK AT WORK OUTLET AND 10 FEET OF SLACK AT PATCH PANEL END.
- J. FURNISH AND INSTALL GROMMETS WHEN PASSING THROUGH METAL STUDS AND OTHER POTENTIAL HAZARDS.
- K. CONTRACTOR IS RESPONSIBLE FOR MEETING BOTH NATIONAL FIRE AND BUILDING CODES AND ANY LOCAL AMENDMENTS BY THE AUTHORITIES HAVING JURISDICTION AND MAINTAIN FIRESTOPS AT ALL CABLES THAT PENETRATE FIREWALLS. PLENUM RATED CABLES SHALL BE INSTALLED WHERE REQUIRED.
- L. DO NOT SPLICE OR BRIDGE CABLE AT ANY POINT.
- M. DO NOT INSTALL CABLE SUPPORTED FROM CEILING TILES.
- N. DO NOT OVER TIGHTEN (25 POUNDS PER SQUARE INCH MAXIMUM) WITH USING CABLE OR PLASTIC TIES.
- O. DO NOT USE OIL OR OTHER LUBRICANT NOT SPECIFICALLY DESIGNED FOR NETWORK CABLE PULLING.
- P. DO NOT SUPPORT CABLES DIRECTLY FROM ELECTRICAL CONDUITS OR FIXTURES

4. GENERAL FIRE ALARM NOTES

- A. THE INTENT OF THE FIRE ALARM SYSTEM DEVICES INDICATED ON THIS DRAWING ARE FOR PERFORMANCE SPECIFICATIONS AND LOCATIONS ONLY. THE SUCCESSFUL FIRE ALARM SYSTEM CONTRACTOR SHALL PROVIDE COMPLETE PERMIT DRAWINGS, INCLUDING WIRING MEANS AND METHODS, BATTERY CALCULATIONS, DEVICE CUT SHEETS, ETC. FOR THE EQUIPMENT THEY SHALL PROVIDE. PROVIDE 15% SPARE CAPACITY FOR NEW SYSTEMS. COORDINATE FINAL REQUIREMENTS WITH ALL AUTHORITIES HAVING JURISDICTION.
- B. THE FIRE ALARM SYSTEM SHALL BE MONITORED BY A UL LISTED CENTRAL STATION.
- C. FIRE ALARM CONTRACTOR SHALL SUBMIT FIRE ALARM SUBMITTALS TO THE OWNER'S REPRESENTATIVE WITHIN 30 DAYS AFTER CONTRACT IS AWARDED.
- D. WALL MOUNTED DEVICES SHALL BE 80" AFF TO BOTTOM OF DEVICE UNLESS NOTED OTHERWISE.
- E. SURFACE MOUNTING OF FIRE ALARM CONDUIT IS NOT PERMITTED IN FINISHED AREAS.
- F. BUILDING IS EQUIPPED WITH A FULLY AUTOMATIC SPRINKLER SYSTEM.
- G. REMOVE ALL EXISTING FIRE ALARM SYSTEMS FROM PREVIOUS TENANTS PRIOR TO INSTALLING NEW EQUIPMENT.
- H. ALL REQUIRED DOCUMENTATION REGARDING THE DESIGN OF FIRE DETECTION, ALARM, AND COMMUNICATIONS SYSTEMS AND THE PROCEDURES FOR MAINTENANCE, INSPECTION, AND TESTING OF FIRE DETECTION, ALARM, AND COMMUNICATIONS SYSTEMS SHALL BE MAINTAINED AT AN APPROVED, SECURED LOCATION FOR THE LIFE OF THE SYSTEM PER IFC 901.6.2.1.
- I. THE FIRE ALARM CONTROL PANEL DISCONNECTING MEANS SHALL HAVE A RED MARKING, SHALL ONLY BE ACCESSIBLE TO AUTHORIZED PERSONNEL, AND SHALL BE IDENTIFIED AS "FIRE ALARM CIRCUIT". THE LOCATION OF THE CIRCUIT DISCONNECTING MEANS SHALL BE IDENTIFIED AT THE FIRE ALARM CONTROL UNIT PER NFPA 72 4.4.1.4.2.2 AND 4.4.1.4.2.3.
- J. ROUTE ALL CONDUIT TIGHT TO DECK IN ACCORDANCE WITH CEC 300.4(E).
- K. FIRE ALARM SYSTEMS SHALL BE INSTALLED PER CURRENT NFPA STANDARDS.FIRE ALARM DEVICE LOCATIONS ARE SHOWN FOR REFERENCE ONLY. THE ELECTRICAL CONTRACTOR SHALL INCLUDE A PRICE IN THE ELECTRICAL BID FOR A LANDLORD APPROVED FIRE ALARM SYSTEM, INCLUDING PLANS AND ALL ASSOCIATED DOCUMENTATION REQUIRED. THESE PLANS SHALL BE SUBMITTED TO THE LOCAL AUTHORITIES HAVING JURISDICTION BY A QUALIFIED AND LICENSED DESIGN-BUILD FIRE ALARM CONTRACTOR FOR A COMPLETE AND APPROVED FIRE ALARM SYSTEM. THE PLANS SHALL BE SIGNED AND SEALED BY THEIR LOCAL DESIGN ENGINEER AND SUBMITTED FOR PLAN REVIEW PRIOR TO RECEIVING SPECIFIC PERMITS FOR THIS WORK. THE FIRE ALARM CONTRACTOR SHALL ALSO SUBMIT ALL SHOP DRAWINGS, BATTERY CALCULATIONS, SPECIFICATION SHEETS, ETC. AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION TO THEIR LOCAL DESIGN ENGINEER FOR REVIEW AND APPROVAL.

5.ELECTRICAL ABBREVIATIONS:

ABC ABOVE COUNTER
AFF ABOVE FINISHED FLOOR
CF CEILING FAN
CP CIRCULATING PUMP
EC ELECTRICAL CONTRACTOR
ECB ENCLOSED CIRCUIT BREAKER
EDF ELECTRIC DRINKING FOUNTAIN
EF EXHAUST FAN
GC GENERAL CONTRACTOR
GFCI GROUND FAULT CIRCUIT INTERRUPT
GR GROUND
HC HVAC CONTRACTOR
JB JUNCTION BOX
PC PLUMBING CONTRACTOR
TTB TELEPHONE TERMINATION BOARD
UC UNDERCOUNTER
UH UNIT HEATER
UNO UNLESS NOTED OTHERWISE
VIF VERIFY IN FIELD
WH WATER HEATER
WP WEATHER PROOF DEVICE
WR WEATHER RESISTANT DEVICE
GFCI GROUND FAULT CIRCUIT INTERRUPTER

INSTALLATION
RECEPTACLES
HEIGHTS:

h1: 24 in
h2: 46 in
h3: 48 in
h4: 84 in
h5: 94 in
h6: 60 in

LIST OF DRAWINGS

E0.00 ELECTRICAL SPECIFICATION.
E1.00 ELECTRICAL GENERAL NOTES.
E2.00 ELECTRICAL LIGHTING LAYOUT.
E3.00 ELECTRICAL FLOOR POWER PLAN .
E3.10 ELECTRICAL ROOF POWER PLAN .
E4.00 SINGLE LINE LAYOUT
E5.00 PANEL BOARDS SCHEDULE .

**SCOPE OF WORK:
PROVIDING LIGHTING DESIGN , POWER
DESIGN , SINGLE LINE , PANEL BOARD
SCHEDULE FOR NEW ADULT DAY CARE.
AND 2 BATHROOM AND ELECTRICAL
ROOM AND FIRE ACP , EXISTING
SERVICE WILL TAKE IN CONSIDERATION.**

CLIENT:

ADDRESS:

4 UNI

74587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS
APPEARING HEREIN CONSTITUTE THE
ORIGINAL AND UNPUBLISHED WORK OF THE
DESIGNER AND THE SAME MAY NOT BE
DUPLICATED, USED OR DISCLOSED WITHOUT
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL CEESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

ELECTRICAL SPECIFICATIONS

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS

DRAWING NO.	REV.
-------------	------

E 0 . 0 0

ELECTRICAL GENERAL NOTES

1. DO NOT SCALE DRAWINGS. VERIFY DIMENSIONS IN FIELD PRIOR TO COMMENCEMENT OF WORK.
2. WHEREVER THE WORD "PROVIDE" IS USED, IT SHALL MEAN TO "PROVIDE AND INSTALL".
3. FINAL CONCECTIONS TO EQUIPMENT SHALL BE PER MANUFACTURER'S APPROVED WIRING DIAGRAMS, DETAILS AND INSTRUCTIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO PROVIDE MATERIALS AND EQUIPMENT COMPATIBLE WITH EQUIPMENT ACTUALLY SUPPLIED.
4. IT IS THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS TO ESTABLISH A STANDARD OF QUALITY. THE ENGINEER RESERVES THE RIGHT TO APPROVE METHODS AND MATERIALS NOT REFLECTED HEREIN.
5. CONTRACTOR SHALL REVIEW ARCHITECTURAL, STRUCTURAL, MECHANICAL, AND OTHER RELATED DRAWINGS PRIOR TO BID.
6. CONTRACTOR SHALL VISIT SITE PRIOR TO BID AND VERIFY THAT CONDITIONS ARE AS INDICATED IN THE CONTRACT DOCUMENTS. CONTRACTOR SHALL INCLUDE IN HIS BID, ANY COSTS REQUIRED TO MAKE HIS WORK MEET THE CONTRACT SCOPE UTILIZING EXISTING CONDITIONS.
7. WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER TO THE SATISFACTION OF THE ARCHITECT.
8. WORK, MATERIALS AND EQUIPMENT SHALL CONFORM TO THE LATEST EDITIONS OF LOCAL, STATE AND NATIONAL CODES AND ORDINANCES.
9. PROVIDE PERMITS AND INSPECTIONS REQUIRED.
10. GUARANTEE THE INSTALLATION AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP WHICH MAY OCCUR UNDER NORMAL USAGE FOR A PERIOD OF ONE YEAR AFTER OWNER'S ACCEPTANCE. DEFECTS SHALL BE PROMPTLY REMEDIED WITHOUT COST TO THE OWNER.
11. PROVIDE RECORD DRAWINGS TO ENGINEER. DRAWINGS SHALL INCLUDE ALL ADDENDUM ITEMS, CHANGE ORDERS, ALTERATIONS, REROUTINGS, ETC.
12. VERIFY SPECIFIC LOCATION OF EQUIPMENT TO BE FURNISHED BY OTHERS PRIOR TO ROUGH-IN.
13. ELECTRICAL SYSTEMS SHALL BE TESTED FOR PROPER OPERATION. IF TESTS SHOW THAT WORK IS DEFECTIVE, CONTRACTOR SHALL MAKE CORRECTIONS NECESSARY AT NO COST TO OWNER.
14. RECESSED LIGHT FIXTURES INSTALLED IN GYP. BOARD OR PLASTER CEILINGS SHALL HAVE PLASTER FRAMES INSTALLED PRIOR TO CEILING MATERIAL.
15. RECESSED FIXTURES INSTALLED INDOORS SHALL BE THERMALLY PROTECTED.
16. SEE DIVISION 15 DRAWINGS FOR LOCATION OF MECHANICAL EQUIPMENT. PROVIDE SERVICE TO AND CONECT EQUIPMENT AS REQUIRED.
17. PROVIDE EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS.
18. ALL ELECTRICAL SYSTEMS COMPONENTS SHALL BE LISTED OR LABELED BY U.L. OR OTHER RECOGNIZED TESTING FACILITY.
19. WIRE TERMINATION PROVISIONS FOR PANELBOARDS, CIRCUIT BREAKERS, SAFETY SWITCHES, AND ALL OTHER ELECTRICAL APPARATUS SHALL BE LISTED AS SUITABLE FOR 75 DEGREE C.
20. THE FOLLOWING CONDUCTOR SIZES SHALL BE UTILIZED FOR 20 AMP CIRCUITS PERTAINING TO DISTANCES (IN FEET) INDICATED:

120VOLT, 1PH	CONDUCTOR	240 VOLT, (1PH)
0-64	#12AWG	0-129
65-106	#10AWG	130-212
107-160	#8AWG	213-321

NOTE: BASED ON 75°c COPPER CONDUCTORS INSTALLED IN EMT WITH 16AMP LOAD @ 85% P.F.

21. CONTRACTOR SHALL REVIEW ARCHITECTURAL, STRUCTURAL AND MECHANICAL DRAWINGS AND SHALL PROVIDE LIGHTS, SWITCHES, RECEPTACLES, EQUIPMENT CONCECTIONS, ETC., AND ASSOCIATED CIRCUITING IN NEW AND REMODELED AREAS, EVEN IF SUCH AREAS ARE NOT SHOWN ON ELECTRICAL DRAWINGS. LAYOUTS, FIXTURE TYPES, QUANTITIES AND SPACING SHALL BE IN ACCORDANCE WITH SIMILAR AREAS ON THIS PROJECT. CONTRACTOR SHALL INCLUDE COSTS FOR THE ABOVE IN HIS BID. IN ADDITION, CONTRACTOR SHALL PROVIDE LAYOUT DRAWINGS FOR WORK IN SUCH AREAS AND SUBMIT FOR APPROVAL PRIOR TO ROUGH-IN.
22. WIRE SHALL BE COPPER, 75 DEGREES C RATED FOR GENERAL USE, FOR WIRING WITHIN 3 INCHES OF FLUORESCENT BALLASTS WIRE SHALL BE COPPER, MINIMUM 90 DEGREES C RATED. SIZES INDICATED ARE FOR INSTALLATION IN A MAXIMUM 30 DEGREES C AMBIENT. CONDUCTOR AMPACITY SHALL BE DERATED FOR HIGHER AMBIENT INSTALLATIONS. 600 VOLT COMPACT ALUMINUM WIRE AND CABLE IN SIZES 1/0 AND LARGER MAY BE SUBSTITUTED FOR COPPER ON SERVICES AND FEEDERS IF AMPACITY IS EQUIVALENT TO OR GREATER
23. CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING EQUIPMENT WHICH IS DAMAGED DUE TO INCORRECT FIELD WIRING PROVIDED UNDER THIS SECTION OR FACTORY WIRING IN EQUIPMENT PROVIDED UNDER THIS SECTION.
24. CONTRACTOR'S FAILURE TO ORDER OR RELEASE ORDER FOR MATERIALS AND/OR EQUIPMENT WILL NOT BE ACCEPTED AS A REASON TO SUBSTITUTE ALTERNATE MATERIALS, EQUIPMENT OR INSTALLATION METHODS.
25. ELECTRICAL SYSTEMS SHALL BE COMPLETE, OPERABLE AND READY FOR CONTINUOUS OPERATION AT COMPLETION OF PROJECT.
26. RECEPTACLES WHICH ARE SHOWN WALL MOUNTED ON THE ELECTRICAL DRAWINGS ON WALLS WHICH, ON THE ARCHITECTURAL DRAWINGS AND ELEVATIONS ARE SHOWN AS GLASS OR PARTITIONS. SHALL BE FLUSH FLOOR DUPLEX RECEPTACLES MOUNTED ADJACENT TO BAS OR WALLS.
27. RECEPTACLES AT COUNTER SHALL BE MOUNTED WITH THEIR LONG AXIS HORIZONTAL AT +46" UNLESS NOTED.
28. FLUSH FLOOR RECEPTACLE OUTLETS SHALL BE WIREMOLD 862 SERIES. PROVIDE CARPET OR TILE FLANGE TO MATCH FLOOR FINISH.
29. THE COLOR OF THE DEVICES AND COVER PLATES SHALL BE AS DIRECTED BY ARCHITECT. IN DAMP OR WET LOCATIONS COVER PLATES SHALL BE STAINLESS STEEL. IN DRY LOCATIONS COVER PLATES SHALL BE SMOOTH HIGH ABUSE NYLON OR EQUIVALENT. PROVIDE COVER PLATES FOR SWITCHES, RECEPTACLES, TELEPHONE, TELEVISION, COMPUTER AND J-BOX OUTLETS AS REQUIRED.
30. ROMEX CABLE WITH A GROUNDING CONDUCTOR MAY BE USED WHERE PERMITTED BY BOTH THE N.E.C. AND LOCAL ORDINANCES.
31. DISCONCECT SWITCHES SHALL BE GENERAL DUTY TYPE. FUSIBLE SWITCHES SHALL ACCEPT CLASS 'R' FUSES ONLY AND REJECT ALL OTHERS.
32. FINAL CONCECTIONS TO VIBRATING EQUIPMENT SHALL BE WITH FLEX (LIQUIDTIGHT FOR EXTERIOR APPLICATIONS) AND APPROVED FITTINGS. DO NOT SECURE CONDUITS, DISCONCECTS OR DEVICES TO DUCTWORK OR MECHANICAL EQUIPMENT.
33. THE ENGINEER OF RECORD HAS PERFORMED SHORT CIRCUIT CALCULATIONS AND THE AIC RATINGS INDICATED FOR EACH DEVICE IS ADEQUATE TO PROTECT THE EQUIPMENT AND THE ELECTRICAL SYSTEM.

1. THE ENGINEER OF RECORD HAS PERFORMED VOLTAGE DROP CALCULATIONS AND ALL BRANCH CIRCUITS AND FEEDERS COMPLY WITH CEC 210-19(A) FPN NO4.
2. THE CONTRACTOR SHALL PROVIDE 120V CONCECTION TO NEAREST MAINTENANCE RECEPTACLE WHERE REQUIRED FOR CONDENSATE PUMPS ASSOCIATED WITH FAN COIL UNITS. COORDINATE WITH MECHANICAL CONTRACTOR.
3. THE CONTRACTOR SHALL COORDINATE THE SPECIFIC LOCATION, MOUNTING HEIGHT, ROTATION, TYPE, COLOR, ETC. OF ALL DEVICES PRIOR TO INSTALLATION.
4. CONCECTIONS TO HYDROMASSAGE BATHTUBS, JACCUZZI TUBS OR SIMILAR EQUIPMENT SHALL BE MADE IN ACCORDANCE WITH ARTICLE 680.70 OF THE CEC. PROVIDE BONDING AS REQUIRED BY ARTICLE 680.74 OF THE CEC.
5. ALL INDOOR FLUORESCENT FIXTURES THAT UTILIZE DOUBLE-ENDED LAMPS AND CONTAIN BALLAST(S) THAT CAN BE SERVICED IN PLACE OR BALLASTED LUMINARIES THAT ARE SUPPLIED FROM MULTIWIRE BRANCH CIRCUITS AND CONTAIN BALLAST(S) THAT CAN BE SERVICED IN PLACE SHALL COMPLY WITH 410.73 (G) OF THE CEC.
6. CEILING MOUNTED SMOKE AND CARBON MONOXIDE DETECTORS PER NFPA 72, SECTION R314 MUST COMPLY WITH U.L. 2075 AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS.
7. ALL SMOKE DETECTORS AND COMBINATION SMOKE/CARBON MONOXIDE DETECTORS SHALL BE HARDWIRED ON SAME CIRCUIT AND HAVE A BATTERY BACKUP SYSTEM.
8. WHEN MORE THAN EITHER ONE (1) SMOKE ALARM OR MORE THAN ONE (1) CARBON MONOXIDE ALARM IS REQUIRED TO BE INSTALLED WITHIN AN INDIVIDUAL DWELLING UNIT, ALL ALARM DEVICES SHALL BE INTERCONCECTED IN SUCH A MANNER THAT THE ACTUATION OF ONE ALARM WITH ACTIVATE ALL OF THE ALARMS IN THE INDIVIDUAL UNIT. SMOKE AND CARBON MONOXIDE ALARMS SHALL BE INSTALLED IN THE FOLLOWING LOCATIONS. (IRC SECTION R3143 AS AMENDED)

A. SMOKE ALARMS IN EACH SLEEPING ROOM.

B. SMOKE ALARMS OUTSIDE OF EACH SEPARATE SLEEPING AREA IN THE IMMEDIATE VICINITY OF THE BEDROOMS.

C. SMOKE ALARMS ON EACH ADDITIONAL STORY OF THE DWELLING INCLUDING BASEMENTS BUT NOT INCLUDING CRAWL SPACE AND UNINHABITABLE ATTICS. IN DWELLINGS OR DWELLING UNITS WITH SPLIT LEVELS AND WITHOUT AN INTERVENING DOOR BETWEEN THE ADJACENT LEVELS, A SMOKE ALARM INSTALLED ON THE UPPER LEVEL SHALL SUFFICE FOR THE ADJACENT LOWER LEVEL PROVIDED THAT THE LOWER LEVEL IS LESS THAN ONE FULL STORY BELOW THE UPPER LEVEL..

D. CARBON MONOXIDE ALARMS OUTSIDE OF SLEEPING AREAS IN THE IMMEDIATE VICINITY OF THE BEDROOMS IN DWELLING UNITS WITHIN WHICH FUEL-FIRED APPLIANCES ARE INSTALLED AND IN DWELLING UNITS THAT HAVE ATTACHED GARAGES.

E. CARBON MONOXIDE ALARMS WITHIN EACH BEDROOM WHICH CONTAINS A FUEL-FIRED APPLIANCE.
43. ALL BRANCH CIRCUITS THAT SUPPLY 125-VOLT, SINGLE PHASE, 15 AND 20 AMP BRANCH CIRCUITS SUPPLYING OUTLETS INSTALLED IN DWELLING UNIT FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DENS, BEDROOMS, SUNROOMS, RECREATION ROOMS, CLOSETS, HALLWAYS, OR SIMILAR ROOMS OR AREAS SHALL BE PROTECTED BY A LISTED ARC-FAULT CIRCUIT INTERRUPTER, COMBINATION-TYPE, INSTALLED TO PROVIDE PROTECTION OF THE BRANCH CIRCUIT. CEC ARTICLE 210.12 (A).
44. ALL ATTIC ACCESSSES SHALL BE PROVIDED WITH A SWITCHED LIGHT AND 120 VOLT GFI OUTLET AT OR NEAR THE FORCED AIR UNIT. LOCATE LIGHT SWITCH AT THE ATTIC ACCESS OPENING.

NOTES:

1. FIXTURES SHALL HAVE APPROPRIATE U.L. LABEL (i.e., DAMP OR WET) AS REQUIRED BY CODES AND ORDINANCES.
2. FIXTURES SHALL INCLUDE ALL ACCESSORIES NECESSARY FOR INSTALLATION ACCORDING TO MANUFACTURER'S SHOP DRAWINGS AND AS REQUIRED BY CODES AND LOCAL ORDINANCES.
3. PRIOR TO ORDERING ANY LIGHTING EQUIPMENT, THE CONTRACTOR SHALL COORDINATE ALL FIXTURE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILING PLANS AND CEILING CAVITY DEPTHS.
4. ALL LAMPS SHALL BE PROVIDED AND INSTALLED ACCORDING TO THE ATTACHED FIXTURE SCHEDULE AND SPECIFICATIONS ENSURE COMPATIBILITY BETWEEN FIXTURE, LAMP(S) AND BALLAST(S). (OSRAM SYLVANIA SERIES)
5. CONTRACTOR SHALL VERIFY FIXTURE VOLTAGES AND CEILING TRIM COMPATIBILITY PRIOR TO ORDERING FIXTURE.
6. PROVIDE APPROVED FIRE-RATED ENCLOSURES FOR ALL LIGHTING FIXTURES LOCATED IN FIRE-RATED CEILINGS.
7. LIGHTING FIXTURE CATALOG NUMBERS ARE SERIES TYPE ONLY. PROVIDE ALL NECESSARY HARDWARE AS REQUIRED BY THE SPECIFICATIONS, DRAWINGS, AND PROJECT CONDITIONS FOR A COMPLETE INSTALLATION.
8. ALL FIXTURES SHALL BE ORDERED WITH APPROPRIATE BALLAST(S) THAT HAVE U.L. AND CB, LABELS. ALL BALLASTS MUST CONFORM TO TITLE 24 AND/OR IECC REQUIREMENTS FOR PERFORMANCE. PROVIDE MULTIPLE BALLASTS FOR DUAL LEVEL SWITCHING AND WIRING (i.e. TANDEM) AS INDICATED ON THE PLANS.
9. UPON INITIAL ENERGIZING OF ALL NEW FLUORESCENT LAMPS, A CONTINUOUS PERIOD OF 30 HOURS SHALL OCCUR PRIOR TO DE-ENERGIZING OF LAMPS FOR MANUFACTURER REQUIRED
10. ALL FLUORESCENT BALLASTS SHALL BE ELECTRONIC TYPE. PROVIDE END OF LIFE (EOL) SHUT-DOWN PROTECTION FOR COMPACT FLUORESCENT LAMPS.
11. ENSURE COMPATIBILITY OF ALL LIGHTING SYSTEM COMPONENTS, ESPECIALLY DIMMED SYSTEMS. FIXTURES, LAMPS, BALLAST(S), AND DIMMING SYSTEMS/INDIVIDUAL CONTROLS MUST BE FACTORY CERTIFIED COMPATIBLE FOR FULL RANGE OF DIMMING COMPATIBILITY.
12. PROVIDE CLEARANCES FROM COMBUSTIBLES, A MINIMUM OF 3/4" (OTHER THAN AT POINTS OF SUPPORT) AND 3" FROM INSULATION FOR RECESSED LIGHTING FIXTURES WHICH ARE NON-IC RATED.
13. PROVIDE A MINIMUM OF TWO (2) #12 SUPPORT WIRES ATTACHED TO BUILDING FRAME IN ADDITION TO T-BAR CLIPS FOR FLUORESCENT FIXTURES RECESSED IN SUSPENDED T-BAR CEILING.
14. FIXTURES WITH EMERGENCY BATTERY BACKUP SHALL BE WIRED AHEAD OF ANY LOCAL SWITCHING IN COMPLIANCE WITH CEC ARTICLE 700.
15. EMERGENCY LIGHTING UNITS SHALL BE EQUIPPED WITH FACTORY-INSTALLED INTEGRAL TEST SWITCHES.
16. PROVIDE DOOR-TO-FRAME AND LENS-TO-DOOR GASKETING, INVERTED LENS, AND FOOD SERVICE RATING FOR ALL FIXTURES LOCATED IN FOOD SERVICE AREAS.
17. FLUORESCENT LUMINARIES THAT UTILIZE DOUBLE-ENDED LAMPS AND CONTAIN BALLAST(S) THAT CAN BE SERVICED IN PLACE, OR BALLASTED LUMINAIRES THAT ARE SUPPLIED FROM MULTI- WIRE BRANCH CIRCUITS AND CONTAIN BALLAST(S) THAT CAN BE SERVICED IN PLACE, SHALL HAVE DISCONNECTING MEANS EITHER INTERNAL OR EXTERNAL TO EACH LUMINAIRE SO TO DISCONCECT SIMULTANEOUSLY FROM THE SOURCE OF SUPPLY ALL CONDUCTORS OF THE BALLAST (INCLUDING THE GROUNDED CONDUCTOR IF ANY). IN ACCORDANCE WITH CEC ARTICLE 410, THE LINE-SIDE TERMINALS OF THE DISCONNECTING MEANS SHALL BE LOCATED SO AS TO BE ACCESSIBLE TO QUALIFIED PENSIONS BEFORE SERVICING OR MAINTAINING THE BALLAST.
18. ALL FLUORESCENT LAMPS SHALL BE OF A LOW MERCURY DESIGN, HAVE A MINIMUM CRI RATING OF 85 AND 3500K COLOR TEMPERATURE UNLESS NOTED OTHERWISE.

CLIENT:

ADDRESS:

4 UNI

94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

ELECTRICAL GENERAL NOTES

PROJ. NO.


PROJ. ENGR.

SCALE @ 24X36" NTS

DRAWING NO.

REV.

E 1 . 0 0



ELECTRICAL LEGEND	
L1	LED LIGHTING PANEL IN T-BAR CEILING, 20 WATT
L2	Spot Lights Ceiling 25.5mm Ultra Slim, 4WATT
	HEAVY DUTY JUNCTION BOX, FLUSH IN CEILING FOR EXHAUST FANS
S _{OS}	SWITCH WITH OCCUPANCY SENSOR ONE WAY LIGHTING SWITCH S ₂ = 2-POLE SWITCH S ₃ = 3-POLE SWITCH SWITCH INCLUDE OCCUPANCY SENSOR & DIMMER
	SELF CONTAINED SMOKE/CARBON MONOXIDE (120 W/BATTERY BACKUP) - CEILING MOUNTED SELF CONTAINED SMOKE DETECTOR/ANNUNCIATOR (120 W/BATTERY BACKUP) - CEILING MOUNTED
-E-	LED Emergency Exit Sign with 90 Minute Battery Backup
	EMERGENCY LIGHTING WALL MOUNTED WITH INTERNAL BACK UP BATTERY WITH MINIMUM 90 MINS AUTONOMY
DS	DAYLIGHT SENSOR

- GENERAL NOTES
- ALL JUNCTION BOXES, CONDUITS, AND AIRS SHALL BE SIZED PER CEC 2022.
 - CONNECT ALL EXIT LIGHTS AHEAD OF ANY LOCAL OR AUTOMATIC SWITCHING DEVICE.
 - PROVIDE A CONSTANT HOT FROM PANEL BOARD DIRECTLY TO ALL EMERGENCY BATTERY PACKS/BALLASTS IN EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS.
 - EMERGENCY LIGHTING FIXTURES SHALL TURN ON TO FULL BRIGHTNESS IN CASE OF POWER LOSS.
 - REFER TO ARCHITECTURAL DRAWINGS FOR EXACT LOCATION & MOUNTING HEIGHTS OF ALL LIGHTING FIXTURES SHOWN ON THIS DRAWING.
 - REFER TO DETAIL SHEET FOR SYMBOLS, SPECIFICATIONS, ABBREVIATIONS, AND LIGHTING FIXTURE SCHEDULE.
 - ALL DEVICES AND EQUIPMENT OUTSIDE THE SCOPE OF WORK ARE EXISTING TO REMAIN U.O.N.
 - CONTRACTOR SHALL PROVIDE AN ACCURATELY TYPED PANEL BOARD SCHEDULE FOR EACH PANEL BOARD.
 - ELECTRICAL CONTRACTOR SHALL NOTIFY THE ENGINEER OF ANY PROBLEMS PERTAINING TO CIRCUIT AVAILABILITY OR LOAD CAPACITY PRIOR TO INSTALLATION.
 - ALL EXTERIOR LUMINARIES AND ELECTRICAL DEVICES SHALL BE USED AS WEATHERPROOF TYPE.
 - ALL NEW CEILING OCCUPANCY SENSORS SHALL BE DUAL-TECHNOLOGY WITH 1000 SQFT COVERAGE AT 360 DEGREES U.O.N. ON THE DRAWING. COORDINATE EXACT LOCATION AND REQUIREMENTS OF ALL OCCUPANCY SENSORS SHOWN ON THIS DRAWING WITH MANUFACTURER REPRESENTATIVE PRIOR TO COMMENCEMENT OF WORK. CONTRACTOR TO PROVIDE POWER PACKS AS REQUIRED.
 - CONTRACTOR SHALL CONFIRM COMPATIBILITY OF ALL LIGHTING CONTROL DEVICES/SWITCHES/DIMMERS WITH LIGHTING FIXTURES AND BALLASTS/DRIVERS PRIOR TO SUBMITTAL.
 - FIXTURE MARKED WITH SUBSCRIPT "(E)" IS EXISTING TO REMAIN. CONTRACTOR TO MAINTAIN CONTINUITY OF BRANCH CIRCUITS.
 - ALL CONDUIT RUNS IN OPEN PLENUM SPACE SHALL BE INSTALLED IN A NEAT MANNER PERPENDICULAR OR PARALLEL TO WALLS AND PAINTED AS DIRECTED BY OWNER.

LIGHTING SCHEDULE						
ID	SYMBOL	TYPE	MAKE	MODEL	WATTAGE	DESCRIPTION
L1		2 x 4 Feet Surface Mount	Lithonia	CPX 4000LM 35K M2	20	LED Light, Dimmable, CSA Certified, IC Rated, Energ Star
L2		Spot Lights Ceiling 25.5mm Ultra Slim	ALUSSO LIGHTING	CSA	4	pot Lights Ceiling 25.5mm Ultra Slim, 4W 2600lm Led Downlights for Ceiling, Cool White 6500K IP44 Waterproof Bathroom Spotlights, Cutout Ø75-90mm
NOTES: 1. THIS PLAN SHALL BE USED IN CONJUNCTION WITH THE ELECTRICAL, MECHANICAL AND PLUMBING PLANS. COORDINATION REQUIRED. NOTIFY ARCHITECT IN CASE OF DISCEPANCIES FOUND. 2. MANUFACTURERS AND MODELS ARE SHOWN FOR CODE COMPLIANCE AND BIDDING PURPOSES ONLY. PRIOR ORDERING / INSTALLING ANY LIGHT FIXTURES CONTRACTOR SHALL PROVIDE SAMPLES AND CUT SHEETS TO OWNER FOR APPROVAL AND CONFIRM MANUFACTURER, MODEL, COLOR AND BUDGET / COSTS.						

CLIENT:

ADDRESS:

4 UNI 94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS
APPEARING HEREIN CONSTITUTE THE
ORIGINAL AND UNPUBLISHED WORK OF THE
DESIGNER AND THE SAME MAY NOT BE
DUPLICATED, USED OR DISCLOSED WITHOUT
CONSENT OF THE DESIGNER.

- NOTES:**
- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
 - THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
 - THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
 - THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:



Electrical Lighting PLAN.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"

1/8" = 1'-0"

DRAWING NO. REV.

E 2 . 0 0



SHEET NOTES:

- 3 - PROVIDE NON-FUSED NEMA 3R DISCONCECT SWITCH FOR GWH-01.

ELECTRICAL LEGEND

	NON-FUSED DISCONNECT SWITCH - SIZE AS INDICATED
	DUPLEX RECEPTACLE OUTLET W/GROUND FAULT CIRCUIT INTERRUPTER PROTECTION
	DUPLEX RECEPTACLE OUTLET W/ARC FAULT CIRCUIT INTERRUPTER PROTECTION
	DUPLEX RECEPTACLE FLOOR MOUNTED W/GROUND FAULT CIRCUIT INTERRUPTER PROTECTION
	WATER PROOF DUPLEX RECEPTACLE - WALL MOUNTED. NOTED GFCI DENOTES: GROUD FAULT PROTECTION

GENERAL NOTES

- ALL 120 VOLT, SINGLE PHASE 15 AND 20 AMPERE BRANCH CIRCUIT SUPPLYING OUTLETS INSTALLED IN DWELLING UNIT FAMILY ROOMS, DINING ROOMS, LIVING ROOMS, PARLORS, LIBRARIES, DENS, BEDROOMS, SUNROOMS, RECREATION ROOMS, CLOSETS, HALLWAYS, OR SIMILAR AREAS SHALL BE PROTECTED BY A LISTED ARC-FAULT CIRCUIT INTERRUPTER, COMBINATION TYPE INSTALLED TO PROVIDE PROTECTION OF THE BRANCH CIRCUIT. (CEC ARTICLE 210.12(A))
- IN EVERY KITCHEN, FAMILY ROOM, DINING ROOM, LIVING ROOM, PARLOR, LIBRARY, DEN, SUNROOM, BEDROOM, RECREATION ROOM OR SIMILAR ROOM OR AREA OF DWELLING UNITS RECEPTACLE OUTLETS SHALL BE INSTALLED IN ACCORDANCE WITH THE GENERAL PROVISIONS SPECIFIED IN THE FOLLOWING ARTICLES.
 - CEC ARTICLE 210.52(A) (1) SPACING. RECEPTACLES SHALL BE INSTALLED THAT NO POINT ALONG THE FLOOR LINE OF THE WALL IS MORE THAN 6-FEET FROM A RECEPTACLE.
 - CEC article 210.52(a) (2) AS AMENDED WALL SPACE. ANY WALL 24-INCHES OR MORE IN LENGTH SHALL BE PROVIDED WITH A RECEPTACLE OUTLET. WALL SPACE SHALL INCLUDE AROUND CORNERS, THE FIRST SLIDING PANEL OF A SLIDING DOOR, FIXED ROOM DIVIDERS SUCH AS A FREESTANDING BAR TYPE COUNTER. WALL SPACE NED NOT INCLUDE THE SPACE BEHIND OPERABLE DOORS. AND NEED NOT INCLUDE ENTRIES, HALLWAYS ETC. LESS THAN 5-FEET WIDE LOCATED IN BEDROOMS.
 - CEC ARTICLE 210.52(A) (3) AS AMENDED FLOOR RECEPTACLES.
- IN EVERY KITCHEN, FAMILY ROOM, DINING ROOM, LIVING ROOM, PARLOR, LIBRARY, DEN, SUNROOM, BEDROOM, RECREATION ROOM OR SIMILAR ROOM OR AREA OF DWELLING UNITS, ALL 125 VOLT 15 AND 20 AMP RECEPTACLES SHALL BE LISTED TAMPER-RESISTANT RECEPTACLES CEC 406.12)
- APPLIANCES IDENTIFIED IN 422.5(A)(1) THROUGH (A)(7) RATED 150 VOLTS OR LESS TO GROUND AND 60 AMPERES OR LESS, SINGLE-OR 3- PHASE, SHALL BE PROVIDED WITH CLASS A GFCI PROTECTION FOR PERSONNEL. MULTIPLE CLASS A GFCI (7) DISHWASHERS PROTECTIVE DEVICES SHALL BE PERMITTED BUT SHALL NOT BE REQUIRED.
- ELECTRICAL MATERIAL AND EQUIPMENT LISTED APPROVAL NO ELECTRICAL MATERIALS, APPARATUS, DEVICES, APPLIANCES, FIXTURES, OR EQUIPMENT SHALL BE SOLD OR INSTALLED UNLESS THEY ARE IN CONFORMANCE WITH THE PROVISIONS OF THIS CODE, THE LAWS OF THE STATE OF TEXAS AND ANY APPLICABLE RULES AND REGULATIONS ISSUED UNDER THE AUTHORITY OF THE STATE STATUTES. THE MAKERS NAME, TRADEMARK, OR OTHER IDENTIFICATION SYMBOL SHALL BE PLACED ON ALL ELECTRICAL MATERIALS, APPARATUS, DEVICES, APPLIANCES, FIXTURES, AND EQUIPMENT USED OR INSTALLED UNDER THE PROVISIONS OF THIS CODE. ALL ELECTRICAL MATERIALS AND EQUIPMENT SHALL BE LISTED AND LABELED FOR THE INTENDED USE AND SHALL BE INCLUDED IN A LIST PUBLISHED BY AN APPROVED AGENCY

CLIENT:

ADDRESS:

4 UNI

94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL CEESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY


PROJECT:

TITLE:

Electrical FLOOR POWER Plan .

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		1/8" = 1'-0"

DRAWING NO.	REV.
E 3 . 0 0	



SHEET NOTES:

- 1 → PROVIDE NON-FUSED NEMA 3R DISCONCECT SWITCH FOR OU-01.
- 2 → PROVIDE NON-FUSED NEMA 3R DISCONCECT SWITCH FOR RTU.

CLIENT:

ADDRESS:

4 UNI

94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS
APPEARING HEREIN CONSTITUTE THE
ORIGINAL AND UNPUBLISHED WORK OF THE
DESIGNER AND THE SAME MAY NOT BE
DUPLICATED, USED OR DISCLOSED WITHOUT
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL CECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:


Electrical ROOF POWER Plan .

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		1/8" = 1'-0"

DRAWING NO.

E 3 . 1 0

REV.




NOTE: ALL GROUNDING SHALL BE INSTALLED IN ACCORDANCE WITH ARTICLE 250-50 OF THE NATIONAL ELECTRICAL CODE, SIZE OF CONDUCTORS PER ONE-LINE

GROUNDING DETAIL

GENERAL NOTES

- A. ALL EXISTING COMPONENTS OF THIS ELECTRICAL DIAGRAM ARE TO REMAIN AS INSTALLED AND ARE SHOWN FOR REFERENCE ONLY.
- B. ALL WORK SHALL CONFORM TO THE LATEST EDITION OF THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) 70, NATIONAL ELECTRICAL CODE. ALL ITEMS ARE ON AN OR EQUAL BASIS.
- C. ALL SINGLE PHASE BRANCH CIRCUITS (RECEPTACLES, LIGHTING, ETC.; ARE 1/2" CONDUIT OR EMT WITH THIN, 90C WIRING, UNLESS NOTED OTHERWISE. ALL OTHER CONDUIT AND WIRING SHALL BE AS INDICATED ON THE PLANS. ACTUAL ROUTING AND HOME RUN GROUPINGS ARE TO BE DETERMINED IN THE FIELD.
- E. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC EXCEPT FOR DETAILS AND ELEVATIONS. DO NOT SCALE FROM DIAGRAMMATIC DRAWINGS. EXACT LOCATIONS OF DEVICES AND PANELS ARE TO BE DETERMINED AND ROUGHED-IN DURING CONSTRUCTION TO AVOID INTERFERENCE, TO MEET USER REQUIREMENTS, TO PROVIDE ADEQUATE MOUNTING, AND TO MEET CEC LINEAR ACCESS AND CLEARANCE REQUIREMENTS.
- F. BACK TO BACK MOUNTING OF RECEPTACLES IS NOT PERMITTED.
- G. IN ADDITION TO THE CEC REQUIREMENTS FOR GFCI PROTECTION FOR RECEPTACLES, THE FOLLOWING RECEPTACLES SHALL ALSO HAVE GFCI PROTECTION: (1)-ALL RECEPTACLES LOCATED WITHIN 8 FEET OF A SINK, (2)-ALL RECEPTACLES WHICH ARE PROVIDED FOR CONVENIENCE IN SERVICING HVAC EQUIPMENT REGARDLESS OF LOCATION AS REQUIRED TO ACCOMMODATE CONDUCTOR PULLING EASE, FIELD LIFE SAFETY.
- H. PROVIDE A LAMICOID NAMEPLATE (WHITE LETTERS ON BLACK BACKGROUND; ON EACH PANELBOARD, MOTOR STARTER, CONTACTOR, TRANSFORMER, ETC. LETTERS SHALL BE 0.75 INCH MAINIMUM.
- I. CONTRACTOR SHALL CUT AS REQUIRED TO INSTALL ELECTRICAL EQUIPMENT REPAIR OF FLOOR OR WALLS SHALL BE COORDINATED WITH GENERAL CONTRACTOR CONTRACTOR SHALL ALSO REPAIR ALL OPENINGS LEFT DUE TO EQUIPMENT REMOVAL.
- J. CONDUCTORS ARE COPPER UNLESS OTHERWISE SHOWN. ALL CONDUCTORS LARGER THAN #10 SHALL BE STRANDED.
- K. PANELBOARDS SHALL CONTAIN A TYPEWRITTEN DIRECTORY WITH A PLASTIC COVER AFFIXED TO THE INSIDE DOOR.

- L. ALL FIXTURES, DEVICES, CONDUIT, AND EQUIPMENT SHALL BE SECURED WITH APPROVED HANGERS AND ANCHORS AND IN ACCORDANCE WITH APPROVED STANDARDS OF INSTALLATION.
- M. ALL BREAKERS SHOWN IN THE PANELBOARD SCHEDULE SHALL BE RATED AS SHOWN FOR BOTH CIRCUIT CAPACITY AND FAULT CURRENT INTERRUPTING CAPACITY.
- N. ALL PANELBOARDS, DISCONNECT SWITCHES, MOTOR STARTERS, AND CONTACTORS SHALL BE NEMA 1, UNLESS OTHERWISE NOTED.
- O. ELECTRICAL CONTRACTOR MUST BE AVAILABLE AT TIME OF DBS INSPECTION. COORDINATE WITH GENERAL CONTRACTOR.
- P. FIELD VERIFY THE AVAILABLE FAULT CURRENT AT THE LANDLORD'S EXISTING PANEL AND PROVIDE A NEW, FULLY RATED, PANEL TO MATCH EXISTING.
- Q. CONTRACTOR TO MAKE FINAL CONCECTIONS IN EMS PANEL FOR LANDLORD PROVIDED LIGHTING CIRCUITS. 50% OF THE GENERAL LIGHTING CIRCUITS SHOULD BE ROUTED THROUGH THE CUSTOMER CONTROL ZONE .



ELECTRICAL METER FROM UTILITY
208/120V, 3Ø, 60Hz

NOTES

- CONTRACTOR TO INCLUDE IN THE CONTRACT ALL ONE TAP CHARGERS AND FEES FROM THE POWER COMPANY, AND COORDINATE WITH THE POWER COMPANY.
- PROVIDE PLAQUE STATING LOCATION OF DISCONNECTING MEANS.
- PANEL BOARD TO HAVE FULLY RATED BREAKERS UNLESS NOTED OTHERWISE.

CONTRACTOR TO PROVIDE 2" C. WITH 2# 3/0 CU. IN EACH, AND (1) EMPTY CONDUIT WITH PULL WIRE UNLESS UTILITY COMPANY STATES OTHERWISE. MINIMUM OF 36" BELOW GRADE, TO UTILITY TRANSFORMER. (CONTRACTOR MAY USE ALUMINUM WIRE ONLY FOR MAIN FEED FROM UTILITY TRANSFORMER TO MAIN SWITCH, ALL OTHER FEEDS MUST BE COPPER. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO SIZE WIRE AND GROUNDING APPROPRIATELY). IF ALUMINUM CONDUCTORS ARE USED THEN PROVIDE ANTI-OXIDANT PASTE LISTED FOR ALUMINUM CONDUCTORS AT TERMINAL WHERE ALUMINUM IS EXPOSED. PROVIDE CO/ALR LISTED TERMINALS IN WIREWAY FOR ALUMINIUM/COPPER SPLICE.

- Provide arc flash warning labels for electrical equipment such as switchboards and panelloads as required per CEC 110.16. If not already installed

2

E-1

POWER RISER DIAGRAM
SCALENTS

CLIENT:

ADDRESS:

4 UNI

94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

SINGLE LINE PLAN .

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"

NTS

DRAWING NO.

E 4 . 0 0

REV.

Location: CORRIDOR ROOM						
* LOAD SUMMARY	CL	DF	CONNECTED LOAD			DEMAND TOTAL
			A	B	C	
L Lighting	4.46	1.25	0.90	2.04	1.52	5.58
R Convenience Recept	16.83		5.71	5.00	6.12	13.41
H Heating (Space)		1.25				
C Cooling		1.00				
A HVAC		1.00				
P Process		1.00				
O Other Continuous		1.25				
K Kitchen		0.65		2.00	0.80	
N Noncontinuous	2.00	1.00				
M Motor		1.00				
Total	23.29		6.61	9.04	8.44	18.99
Total Demand Load (KVA)	18.99					
Total Demand Current (A)	45.68					
Min. Feeder Ampacity (A)	57.10					

DESCRIPTION	* WIRE	GRD	CB	KVA	A	B	C	KVA	CB	WIRE	GRD	DESCRIPTION	*
1 LIGHTING OPEN HALL	L 2X 14 AWG - #14G		15A-1P	0.36	1.56			1.20	20A-1P	2X 12 AWG - #12G		RECEPTACLES SOCIAL WORK	R 2
3 LIGHTING OPEN HALL	L 2X 14 AWG - #14G		15A-1P	0.26		1.06		0.80	20A-1P	2X 12 AWG - #12G		RECEPTACLE QUIT ROOM	R 4
5 LIGHTING OPEN HALL	L 2X 14 AWG - #14G		15A-1P	0.30			2.10	1.80	20A-1P	2X 12 AWG - #12G		RECEPTACLES PHYSICAL THERAPY	R 6
7 LIGHTING OPEN HALL	L 2X 14 AWG - #14G		15A-1P	0.32	1.32			1.00	20A-1P	2X 12 AWG - #12G		RECEPTACLES PROGRAM DIRECTOR	R 8
9 LIGHTING PANTRY& CORRIDOR	L 2X 14 AWG - #14G		15A-1P	0.16		1.36		1.20	20A-1P	2X 12 AWG - #12G		RECEPTACLES MULTIPURPOSE	R 10
11 LUGHTING OFFICE MANAGER ROOM& UTILITY ROOM	L 2X 14 AWG - #14G		15A-1P	0.06			0.26	0.20	20A-1P	2X 12 AWG - #12G		RECEPTACLES UTILITY	R 12
13 LIGHTING NURSING ROOM&STORAGE	L 2X 14 AWG - #14G		15A-1P	0.14	1.14			1.00	20A-1P	2X 12 AWG - #12G		RECEPTACLES CORRIDOR	R 14
15 LIGHTING CORRIDOR	L 2X 14 AWG - #14G		15A-1P	0.20		1.20		1.00	20A-1P	2X 12 AWG - #12G		RECEPTACLES OFFICE MANGER	R 16
17 LIGHTING MULTIPURPOSE CONFERENCE ROOM	L 2X 14 AWG - #14G		15A-1P	0.12			0.52	0.40	20A-1P	2X 12 AWG - #12G		RECEPTACLES MENS RESTROOMS	R 18
19 LIGHTING PROGRAM DIRECTOR ROOM	L 2X 14 AWG - #14G		15A-1P	0.04	0.44			0.40	20A-1P	2X 12 AWG - #12G		RECEPTACLES WOMENS RESTROOMS	R 20
21 LIGHTING PHYSICAL THERAPY	L 2X 14 AWG - #14G		15A-1P	0.20		0.80		0.60	20A-1P	2X 12 AWG - #12G		RECEPTACLES CORRIDOR	R 22
23 LIGHTING QUITE ROOM	L 2X 14 AWG - #14G		15A-1P	0.02			1.22	1.20	20A-1P	2X 12 AWG - #12G		RECEPTACLES PANTRY	R 24
25 LIGHTING SOCIAL WORK	L 2X 14 AWG - #14G		15A-1P	0.04	0.44			0.40	20A-1P	2X 12 AWG - #12G		RECEPTACLES STORAGE	R 26
27 LIGHTING MENS RESTROOM	L 2X 14 AWG - #14G		15A-1P	1.02		2.42		1.40	20A-1P	2X 12 AWG - #12G		RECEPTACLES NURSING	R 28
29 LIGHTING WOMENS RESTROOM	L 2X 14 AWG - #14G		15A-1P	1.02			2.82	1.80	20A-1P	2X 12 AWG - #12G		RECEPTACLES OPEN HALL	R 30
31 SMOKE/CARBON DETECTOR	R 2X 12 AWG - #12G		15A-1P	0.11	1.71			1.60	20A-1P	2X 12 AWG - #12G		RECEPTACLES OPEN HALL	R 32
33 EXIT SIGN /EMERGENCY IIGHT	L 2X 14 AWG - #14G		15A-1P	0.20		2.20		2.00	20A-1P	2X 12 AWG - #12G		RECEPTACLES MICROWAVE	K 34
35 RECEPTACLES FLOOR MOUNTED	R 2X 12 AWG - #12G		20A-1P	0.72			1.52	0.80	20A-1P	2X 12 AWG - #12G		RECEPTACLES FRIDGEL	K 36
(KVA)													
Total Connected Load					6.61	9.04	8.44						

EXISTING PANEL A	
PANELBOARD DESIGNATION	
SYSTEM VOLTAGE	240V, 3Φ, 3W
BUS SIZE	60
SYSTEM TYP E	NORMAL
FEEDER PROT	60A-3P C/B Bus Plug
CONDUCTOR SIZE	4 AWG - #4G CU
CONDUCTOR/PHASE	1
MAINS	60A MCB
SCCR	SERIES RATED
MCB RATING	80%
GROUND FAULT	NO
FEEDER LENGTH (FT)	50
FEEDER V. DROP (%)	0.669
FAULT CURRENT	
KAIC RATING	10
ENCLOSURE	TYPE 2

Location: CORRIDOR ROOM						
* LOAD SUMMARY	CL	DF	CONNECTED LOAD			DEMAND TOTAL
			A	B	C	
L Lighting		1.25	0.72	0.72		1.44
R Convenience Recept	1.44					1.44
H Heating (Space)	0.10	1.25		0.10		0.13
C Cooling		1.00				
A HVAC	45.46	1.00	16.30	14.58	14.58	45.46
P Process		1.00				
O Other Continuous		1.25				
K Kitchen		0.65				
N Noncontinuous	2.00	1.00				
M Motor		1.00				
Total	49.00		17.02	15.40	14.58	47.02
Total Demand Load (KVA)	47.02					
Total Demand Current (A)	113.11					
Min. Feeder Ampacity (A)	141.39					

EXISTING PANEL -B2													
PANELBOARD DESIGNATION													
SYSTEM VOLTAGE							240V, 3Φ, 3W						
BUS SIZE							150A						
SYSTEM TYPE							NORMAL						
FEEDER PROT							150A-3P C/B Bus Plug						
CONDUCTOR SIZE							1 AWG - #4G CU						
CONDUCTOR/PHASE							1						
MAINS							150A MCB						
SCCR							SERIES RATED						
MCB RATING							80%						
GROUND FAULT							NO						
FEEDER LENGTH (FT)							50						
FEEDER V. DROP (%)							0.834						
FAULT CURRENT													
KAIC RATING							10						
ENCLOSURE							TYPE 3X						

DESCRIPTION	* WIRE	GRD	CB	KVA	A	B	C	KVA	CB	WIRE	GRD	DESCRIPTION	*
1 OU-01	A 2X 12 AWG - #12G		20A-2P	1.73	3.27			1.54					A 2
3	A			1.54		3.08		1.54	30A-3P	3X 8 AWG - #8G		RTU-02	A 4
5 RTU-01	A 3X 8 AWG - #8G		30A-3P	1.54			3.08	1.54					A 6
7	A			1.54	3.46			1.92					A 8
9	A			1.92		3.83		1.92	30A-3P	3X 8 AWG - #8G		RTU-04	A 10
11 RTU-03	A 3X 8 AWG - #8G		30A-3P	1.92			3.83	1.92					A 12
13	A			1.92	7.13			5.21					A 14
15	A			2.45		7.66		5.21	90A-3P	3X 1 AWG - #1G		RTU-06	A 16
17 RTU-05	A 3X 6 AWG - #6G		45A-3P	2.45			7.66	5.21					A 18
19	A			2.45	3.17			0.72	20A-1P	2X 12 AWG - #12G		RECEPTACLES ROOF	R 20
21 GWH-01	H 2X 12 AWG - #12G		15A-2P	0.10		0.82		0.72	20A-1P	2X 12 AWG - #12G		RECEPTACLES ROOF	R 22
23 SPACE												SPACE	24
(KVA)													
Total Connected Load					17.02	15.40	14.58						

CLIENT:

ADDRESS:

4 UNI94587

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

PANEL BOARD SCHEDULE .

PROJ. NO. PROJ. ENGR. SCALE @ 24X36

NTS

DRAWING NO. REV.

E 5 . 0 0

PLUMBING SPECIFICATIONS

THE WORK INCLUDES MODIFICATION TO THE EXISTING PLUMBING SYSTEM AND PROVIDING NEW MATERIALS, FITTINGS AND ACCESSORIES NECESSARY FOR A COMPLETE FUNCTIONING PLUMBING SYSTEM. THE WORK ALSO INCLUDES ROUGH-IN AND FINAL CONNECTIONS TO FOOD SERVICE EQUIPMENT AND BEVERAGE DISPENSING EQUIPMENT PROVIDED BY OTHERS. ALL WORK SHALL BE IN ACCORDANCE WITH LOCAL CODES AND/OR ORDINANCES AND IS SUBJECT TO INSPECTION. HOOK-UP CHARGES, PERMITS AND ALL OTHER EXPENSES RELATED TO A COMPLETE AND FUNCTIONING PLUMBING SYSTEM ARE INCLUDED AS A PART OF THIS SECTION. WARRANTY: PROVIDE LABOR AND MATERIALS TO REPAIR OR REPLACE DEFECTIVE PARTS AND MATERIALS AS REQUIRED FOR ONE YEAR AFTER SUBSTANTIAL COMPLETION OR OWNER ACCEPTANCE OF THE COMPLETED PROJECT. PROVIDE A SEPARATE LINE ITEM DEDUCT AMOUNT ON THE PROPOSAL FORM TO DELETE WARRANTY SERVICE, AT THE OWNER'S OPTION. THE INTENT OF THE DRAWINGS IS TO INDICATE THE GENERAL EXTENT OF WORK REQUIRED FOR THE PROJECT. THE DRAWINGS FOR PLUMBING WORK ARE DIAGRAMMATIC, SHOWING THE GENERAL LOCATION, TYPE, FIXTURES AND EQUIPMENT REQUIRED. THE DRAWINGS SHALL NOT BE SCALED FOR EXACT MEASUREMENTS. REFER TO MANUFACTURER'S STANDARD ROUGH-IN DRAWINGS FOR PLUMBING FIXTURE INSTALLATION REQUIREMENTS. COMPLY WITH ALL APPLICABLE ADA INSTALLATION REQUIREMENTS. COORDINATE WITH THE WORK OF OTHER SECTIONS, EQUIPMENT FURNISHED BY OTHERS, AND WITH THE CONSTRAINTS OF THE EXISTING CONDITIONS OF THE PROJECT SITE. PIPING SYSTEMS - GENERAL: ALL PIPING SHALL BE RUN PARALLEL TO BUILDING LINES AND SUPPORTED AND ANCHORED AS REQUIRED TO FACILITATE EXPANSION AND CONTRACTION. ALL PIPING SHALL BE CONCEALED EXCEPT IN UNFINISHED SPACES. INSTALL AS REQUIRED TO MEET ALL CONSTRUCTION CONDITIONS AND TO ALLOW FOR INSTALLATION OF OTHER WORK SUCH AS DUCTS AND ELECTRICAL CONDUIT. AT ALL CONNECTIONS BETWEEN FERROUS PIPING AND NONFERROUS PIPING, PROVIDE AN ISOLATING DIALECTIC UNION. ALL HANGERS SHALL BE COMPATIBLE WITH PIPING MATERIAL TO PREVENT CORROSION. PROVIDE ALL FITTINGS, ACCESSORIES, OFFSETS, AND MATERIALS NECESSARY TO FACILITATE THE PLUMBING SYSTEM'S FUNCTIONING AS INDICATED BY THE DESIGN AND THE EQUIPMENT INDICATED. FIXTURES/EQUIPMENT FURNISHED BY OTHERS: PLUMBING CONTRACTOR SHALL PROVIDE UTILITY CONNECTIONS REQUIRED SUCH AS WATER, GAS, AIR, SUPPLIES, WASTE OUTLET, TRAPS, ETC. AT ALL PLUMBING TYPE FIXTURES OR EQUIPMENT FURNISHED BY OWNER, GENERAL CONTRACTOR, FOOD SERVICE CONTRACTOR, EQUIPMENT SUPPLIER, ETC. INCLUDED ARE STOP VALVES, ESCUTCHEONS, AND CHROME PLATED BRASS TUBING WITH COMPRESSION FITTINGS. SEWER AND WASTE PIPING: PROVIDE ALL DRAINS AND SEWERS WITHIN THE SPACE WITH CONNECTION TO THE EXISTING DRAINAGE SYSTEMS ON-SITE. SANITARY DRAINAGE PIPING ABOVE FLOOR SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE, FITTINGS AND CONNECTIONS. SANITARY DRAINAGE PIPING BELOW GRADE SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE WITH SOLVENT WELD FITTINGS MAY BE USED (WHERE PERMITTED BY CODE/LOCAL AUTHORITIES). ALL DRAINAGE PIPING SHALL BE UNIFORMLY PITCHED, 1/4" PER FOOT UNLESS OTHERWISE REQUIRED BY EXISTING CONDITIONS, OR INDICATED ON THE DRAWINGS. VENTS: PROVIDE A COMPLETE SYSTEM OF STANDARD WEIGHT CAST IRON NO-HUB VENT RISERS WHERE THE CEILING SPACE IS USED AS A RETURN AIR PLENUM OR USE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE (WHERE PERMITTED BY CODE/LOCAL AUTHORITIES) WHERE THERE IS A DUCTED RETURN AIR SYSTEM. DO NOT USE PVC PIPE IN RETURN AIR PLENUM SPACES. THE VENT SYSTEM SHALL BE CARRIED THROUGH THE ROOF WITH APPROPRIATE FLASHING. CONDENSATE AND INDIRECT DRAIN PIPING:PIPING ABOVE FLOOR SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE, FITTINGS AND CONNECTIONS. PIPING BELOW GRADE SHALL BE CO-EXTRUDED PVC DWV(SCHEDULE 40) PIPE WITH SOLVENT WELD FITTINGS. CLEANOUTS: PROVIDE CLEANOUTS AT THE END OF EACH HORIZONTAL RUN, AND AT THE BASE OF ALL VERTICAL WASTE AND DRAIN PIPES. CLEANOUTS SHALL BE OF THE SAME SIZE AS THE PIPES THEY SERVE, CONFORMING TO CODE REQUIREMENTS. PROVIDE SUITABLE WALL OR FLOOR CLEANOUTS WITH ACCESSORIES TO OBSCURE FROM VIEW. WATER DISTRIBUTION PIPING: LAYOUT WATER PIPING SO THAT THE ENTIRE SYSTEM CAN BE DRAINED. HOT AND COLD WATER PIPING SHALL BE 1/2" MIN. CPVC PIPE WITH SOLVENT FITTING. PROVIDE WATER HAMMER ARRESTERS AT EACH FIXTURE OR GROUP OF FIXTURES AS REQUIRED. INSTALL CHROME PLATED BRASS ESCUTCHEON PLATES AT ALL PENETRATIONS THROUGH FINISHED SURFACES (INCLUDING CABINET INTERIORS). PIPE INSULATION: INSULATE (AS ALLOWED BY CODE) ALL LISTED SERVICE PIPING AS FOLLOWS. DOMESTIC COLD/HOT WATER, HOT WATER RETURN, STORM WATER PIPING. PROVIDE 1" PREFORMED FIBERGLASS, ASJ/SS-11, FLAME SPREAD 25, SMOKE DEVELOPED 50, ASTM C-547. FOR CONDENSATE PIPING PROVIDE 1/2" THICK INSULATION OF SAME CHARACTERISTICS AS LISTED FOR 1" ABOVE. WHERE PERMITTED BY LOCAL CODES, PROVIDE 1/2" SELF-ADHESIVE UNICELLULAR FOAM PIPE INSULATION WITH PRE-FORMED PVC FITTING COVERS - EQUAL TO SELF-ADHESIVE ARMSTRONG 2000 WITH K FACTOR OF 0.27 AT 75 DEGREES MEAN TEMPERATURE. INSULATE ANY EXPOSED CONDENSATE PIPING WITH WASTE TEMPERATURE BELOW 60 DEGREES F. SHUTOFF VALVES, WITH UNIONS SHALL BE PROVIDED FOR SERVICE TO EACH PLUMBING FIXTURE, FOOD SERVICE EQUIPMENT ITEM OR OTHER EQUIPMENT ITEM, TO FACILITATE ISOLATION FOR REPAIR OR REPLACEMENT. VALVES SHALL BE EQUAL TO JENKINS #902-T BALL VALVE, CHROME-FINISHED BRONZE, TEFLON SEATS AND PACKING, 400 LB. W.O.G., SOLDER END. ACCESS PANELS SHALL BE PROVIDED WHERE CONCEALED CONTROL DEVICES, VALVES, ETC. ARE CONCEALED WITHIN WALLS. WHERE ACCESS FOR ADJUSTMENT AND MAINTENANCE IS POSSIBLE THROUGH LAY-IN SUSPENDED CEILINGS, ACCESS PANELS ARE NOT REQUIRED. PIPING SYSTEM- PVC SCHEDULE 40, SCHEDULE 80 AND CPVC PIPE WITH SOLVENT FITTINGS SHALL BE USED WHERE PERMITTED BY CODE/LOCAL AUTHORITIES. INSTALLATION: THOROUGHLY CLEAN ITEMS BEFORE INSTALLATION. CAP PIPE OPENINGS TO EXCLUDE DIRT UNTIL FIXTURES ARE INSTALLED AND FINAL CONNECTIONS HAVE BEEN MADE. PROCEED AS RAPIDLY AS CONSTRUCTION WILL PERMIT. SET FIXTURES LEVEL AND IN PROPER ALIGNMENT. INSTALL SUPPLIES IN PROPER ALIGNMENT WITH FIXTURES. INSTALL SILICONE SEALANT BETWEEN FIXTURES AND ADJACENT MATERIAL, FOR SANITARY JOINT, AND OMIT ESCUTCHEONS. REPAIR EXISTING PLUMBING SYSTEM COMPONENTS DAMAGED BY CONSTRUCTION OPERATIONS AND RESTORE TO ORIGINAL CONDITIONS. TEST WATER SYSTEM UNDER 150 PSIG HYDROSTATIC PRESSURE, FOR FOUR (4) HOURS MINIMUM. WHEN TESTING INDICATES MATERIALS OR WORKMANSHIP IS DEFICIENT, REPLACE OR REPAIR AS REQUIRED, AND REPEAT TEST UNTIL STANDARDS ARE ACHIEVED. ROOF PENETRATIONS SHALL COMPLY WITH "SMACNA" AND "NRCNA" STANDARDS, AND WITH THE REQUIREMENTS OF THE EXISTING ROOFING WARRANTY, IF APPLICABLE. DO NOT PERFORM ROOFING PENETRATIONS IN A MANNER WHICH WOULD VOID OR OTHERWISE LIMIT THE EXISTING ROOFING WARRANTY.

GENERAL NOTES

- THE INTENT OF THESE PLANS AND SPECIFICATIONS IS TO INCLUDE ALL LABOR, EQUIPMENT, MATERIALS, AND SERVICES NECESSARY TO FURNISH, INSTALL, TEST, AND ADJUST A COMPLETE WORKABLE PLUMBING INSTALLATION AS SHOWN, PRESCRIBED, OR REASONABLY IMPLIED BUT NOT LIMITED TO THAT EXPLICITLY INDICATED IN THE CONTRACT DOCUMENTS, BUT NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE INTENT THEREOF.
- THE ENTIRE INSTALLATION SHALL CONFORM TO THE REQUIREMENTS OF THE 2022 CALIFORNIA PLUMBING CODE, 2022 CALIFORNIA BUILDING CODE, 2022 CALIFORNIA ENERGY CONSERVATION CODE AND ALL OTHER APPLICABLE CODES AND REGULATIONS REQUIRED BY AUTHORITIES HAVING JURISDICTION. IN THE EVENT OF CONFLICT BETWEEN SPECIFICATIONS, CODES, AND REGULATIONS, THE MORE RESTRICTIVE SHALL APPLY.
- COORDINATE ENTIRE INSTALLATION OF THE PLUMBING SYSTEM WITH THE WORK OF OTHER TRADES PRIOR TO ANY FABRICATION OR INSTALLATION. FIELD VERIFY ALL DIMENSIONS AND CONDITIONS. REPORT ANY DISCREPANCIES, IN WRITING, TO THE ENGINEER PRIOR TO COMMENCEMENT OF WORK.
- CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS WITH ALL CHANGES NOTED THEREON AT THE COMPLETION OF THE PROJECT IN ACCORDANCE WITH THE SPECIFICATIONS. PROVIDE ONE YEAR WARRANTY ON ALL PARTS AND LABOR.
- THE DRAWINGS ARE DIAGRAMMATIC AND INTENDED TO SHOW SCOPE. CONTRACTOR SHALL COORDINATE HIS WORK WITH OTHER TRADES TO PROVIDE THE BEST ARRANGEMENT OF ALL DUCT, PIPE, CONDUIT, ETC. ALL CUTTING AND PATCHING OF THE EXISTING STRUCTURE SHALL BE PROVIDED UNDER OTHER SECTIONS OF THE WORK. PROVIDE NECESSARY REQUIREMENTS TO THE PROJECT SUPERINTENDENT.
- ALL HOT WATER PIPING AND RECIRCULATION PIPING (EXCEPT RUNOUTS 12 FT. OR SHORTER TO INDIVIDUAL FIXTURES) SHALL BE INSULATED TO MEET THE REQUIREMENTS OF THE 2022 CALIFORNIA ENERGY CONSERVATION CODE.
- CONDENSATE DRAINS SHALL BE PROVIDED FOR EACH AIR CONDITIONING UNIT. HORIZONTAL CONDENSATE DRAINS ABOVE ANY CEILING SHALL BE INSULATED WITH MIN. 3/8" THICK CLOSED CELL INSULATION.
- PIPING:
 - WASTE, VENT, AND STORM DRAIN PIPING SHALL BE CO-EXTRUDED PVC SCHEDULE 40) PIPE
 - WATER PIPE SHALL BE CPVC PIPE
 - CONDENSATE PIPING SHALL BE CO-EXTRUDED PVC (SCHEDULE 40) PIPE
 - INSIDE GAS PIPING SHALL BE BLACK IRON SCHEDULE 40 WITH MALLEABLE IRON FITTINGS. OUTSIDE SHALL BE GALVANIZED IRON SCHEDULE 40 WITH GALVANIZED FITTINGS. GAS LINE TO BE PAINTED GRAY IN COLOR. A 24 HOUR METERED GAS TEST SHALL BE REQUIRED.
 - ALL PIPING NOT ENCLOSED IN CONDITION SPACE OR AT EXTERIOR WALLS SHALL BE INSULATED.
 - PIPING: PVC SCHEDULE 40, SCHEDULE 80 AND CPVC PIPING WITH SOLVENT WELD FITTINGS SHALL BE USED WHERE PERMITTED BY CODE/LOCAL AUTHORITIES
 - ALL VENTS OR EXHAUSTS SHALL BE AT LEAST 10 FT. AWAY OR 3 FT. ABOVE ANY WINDOW, DOOR, OPENING, OR AIR INTAKE.
 - CLEANOUTS SHALL BE INSTALLED PER THE CALIFORNIA PLUMBING CODE.
 - PROVIDE WATER TIGHT FLASHINGS WHEREVER PIPES PASS THROUGH EXTERIOR WALLS, ROOFS, OR FLOORS.
 - PROVIDE ISOLATION FOR ALL PIPES THAT COME IN CONTACT WITH THE STRUCTURE.
 - LOCATION OF EXISTING UTILITIES AND POINTS OF CONNECTION ARE APPROXIMATE. CONTRACTOR SHALL VERIFY EXACT LOCATIONS AND DEPTHS OF EXISTING UTILITIES AND SERVICES PRIOR TO STARTING WORK OF THIS SECTION. IF INDICATED POINTS OF CONNECTION CANNOT BE MADE TO EXISTING UTILITIES AS FOUND, THE CONTRACTOR SHALL NOTIFY THE ENGINEER PRIOR TO INSTALLING ANY WORK WHICH MAY BE AFFECTED.
 - VALVES SHALL BE NIBCO, JENKINS, HAMMOND, RED & WHITE OR APPROVED EQUAL. SERVICE PRESSURE SHALL BE SUITABLE FOR SERVICE INTENDED. THE MAIN WATER SHUT OF VALVE SHALL BE A FULL PORT BALL TYPE AND APPROVED FOR SERVICE INTENDED. CONTRACTOR SHALL PROVIDE ALL SHUT OFF VALVES AS NECESSARY TO ISOLATE ANY EQUIPMENT, PLUMBING ITEMS, OR FIXTURES, THAT MAY NEED SERVICING OR ARE SUBJECT TO FAILURE WHETHER OR NOT SUCH VALVES ARE SHOWN ON THE DRAWINGS.
 - PROVIDE HANGERS AND SUPPORTS AS REQUIRED. PLUMBERS TAPE AND WIRE ARE NOT ACCEPTABLE.
 - CONTRACTOR IS RESPONSIBLE FOR HIS OWN TRENCHING, BACKFILL, AND COMPACTION OF TRENCHES NECESSARY TO COMPLETE HIS SCOPE OF WORK. BACKFILLED TRENCHES SHALL BE RETURNED TO THEIR ORIGINAL GRADE UNLESS NOTED OTHERWISE.
 - CONTRACTOR SHALL AFFIX A MAINTENANCE LABEL TO ALL EQUIPMENT REQUIRING ROUTINE MAINTENANCE AND SHALL PROVIDE MAINTENANCE AND OPERATIONAL MANUALS IN ACCORDANCE WITH THE SPECIFICATIONS.
 - ALL EQUIPMENT THAT REQUIRES KEYS OR SPECIAL TOOLS TO OPERATE SHALL SUPPLY THE OWNER WITH TWO OF ANY SUCH KEYS OR TOOLS FOR EACH PIECE OF EQUIPMENT THAT REQUIRE THE SAME.
 - ANY CHANGE OR DEVIATION FROM THESE PLANS OR SPECIFICATIONS SHALL REQUIRE THE APPROVAL, IN WRITING, OF THE ENGINEER PRIOR TO COMMENCEMENT OF SUCH WORK.
 - ALL PLUMBING, ELECTRICAL, AND GAS LINES SHALL BE CONCEALED WITHIN THE THE BUILDING STRUCTURE TO AS GREAT EXTENT AS POSSIBLE. ALL LINES NOT CONCEALED SHALL BE SECURED 6" OFF THE FLOOR AND 3/4" FROM THE WALLS USING STANDOFF BRACKETS
 - AN APPROVED BACKFLOW PREVENTOR SHALL BE PROPERLY INSTALLED UPSTREAM OF ANY POTENTIAL HAZARD BETWEEN THE POTABLE WATER SUPPLY AND SOURCE OF COMTAMINATION.
 - WATER SUPPLY CARBONATORS SHALL BE PROTECTED BY AN APPROVED REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTOR. THE RELIEF VALVE SHALL DRAIN IN-DIRECTLY TO A FLOOR SINK WITH A 1" MIN. AIR GAP.

PLUMBING LEGEND

SYMBOL	ABBRV	DESCRIPTION
	SS or W	NEW SEWER OR WASTE
	V	NEW VENT
	CW	NEW COLD WATER
	HW	NEW HOT WATER
	G	NEW GAS
	CD	NEW CONDENSATE DRAIN
	CA	COMPRESSED AIR
	FCO	FLOOR CLEANOUT
	WCO	WALL CLEANOUT
	FD	FLOOR DRAIN
	FS	FLOOR SINK
	TP	TRAP PRIMER & TRAP PRIMER PIPING
	SOV	SHUT-OFF VALVE
	CV	CHECK VALVE
	BFP	BACKFLOW PREVENTER W SOVS
	T & P	
	DN	PIPE DOWN
	UP	PIPE UP
	POC	POINT OF CONNECTION
	-	PLUMBING NOTE CALL-OUT
	ABV	ABOVE
	AFF	ABOVE FINISH FLOOR
	AP	ACCESS PANEL
	BEL	BELOW
	BLDG	BUILDING
	CLG	CEILING
	CONT	CONTINUATION
	EL	ELEVATION
	FIN	FINISH
	FL	FLOOR
	GR	GRADE
	NTS	NOT TO SCALE
	OC	ON CENTER
	Se %	SLOPE AT A PERCENTAGE
	SHT	SHEET
	Typ	TYPICAL
	VTR	VENT THRU ROOF

PLUMBING / GENERAL NOTES

BATHUBS AND WHIRLPOOL BATHUBS. THE MAX. HOT WATER TEMPERATURE DISCHARGING SHALL BE LIMITED TO 120 DEGREES.

BATHUBS WASTE OPENING IN FLOOR OVER CRAWL SPACES SHALL BE PROTECTED BY A METAL SCREEN NOT EXCEEDING 12" OR SOLID COVER.

SHOWERS AND TUB-SHOWERS COMBINATIONS IN ALL BUILDINGS SHALL BE PROVIDED WITH INDIVIDUAL CONTROL VALVES OF THE PRESSURE BALANCE, THERMOSTATIC, OR COMBINATION OF BOTH THAT PROVIDE SCALD AND THERMAL SHOCK PROTECTION. VALVES SHALL BE ADJUSTED TO DELIVER A MAXIMUM MIXED WATER SETTING OF 120 DEGREES FAHRENHEIT. THE WATER HEATER THERMOSTAT SHALL NOT BE CONSIDERED A SUITABLE CONTROL FOR MEETING THIS PROVISION. VERIFY AND WHERE WATER PRESSURE EXCEEDS 80 PSI AN APPROVED PRESSURE REGULATOR PRECEDED BY AN ADEQUATE STRAINER SHALL BE INSTALLED
1-INSTALL TEMPERATURE AND PRESSURE RELIEF VALVE WITH MINIMUM 3/4" DRAIN PIPE AND TERMINATE TO THE EXTERIOR OF THE BUILDING OVER WINDOW, DOOR OR VISIBLE LOCATION. DISCHARGE FROM A RELIEF VALVE INTO A WATER HEATER PAN SHALL BE PROHIBITED

2-PROVIDE (ON THE PLANS) A GAS PIPING DIAGRAM OF THE GAS PIPING SYSTEM THAT INCLUDES ALL PIPE SIZES, PIPE LENGTHS AND BTU RATINGS.

3-SUBMIT GAS LOAD CALCULATIONS IN ACCORDANCE WITH CPC TABLE 12-8 TO VERIFY THE PIPE SIZES ARE ADEQUATE FOR THE MAXIMUM DELIVERY CAPACITY OF CUBIC FEET OF GAS PER HOUR.
4- A WHOLE HOUSE HAS TEST IS REQUIRED UPON COMPLETION OF THE INSTALLATION, ALTERATION, OR REPAIR OF ANY GAS PIPING. THE CITY SHALL BE NOTIFIED WHEN GAS PIPING IS READY FOR INSPECTION.
5- 2 GPM SHOWER FIXTURE, MAX.1.5 GPM BATHROOM FAUCET, MAX. 2 GPM KITCHEN FAUCET, AND MAX 1.28 WATER CLOSET TO CONFORM TO CITY GREEN REQUIREMENTS.
BATHROOMS: PROVIDE AN EXHAUST FAN (AT LEAST 50 CFM) DUCTED TO THE OUTSIDE (MINIMUM 4" DIAMETER FLEX DUCT WITH A MAXIMUM LENGTH OF 70")WITH A MINIMUM VENTILATION RATE OF 100 CFM, IDENTIFY THE REQUIREMENT FOR A BACKDRAFT DAMPER ON THE DUCT, AN ENERGY STAR COMPLIANT EXHAUST FAN THAT IS CONTROLLED BY A HUMIDITY SENSOR THAT IS CAPABLE OF BEING ADJUSTED BETWEEN ≤ 50-PERCENT TO 80-PERCENT HUMIDITY; AND A SEPARATE SWITCH FROM THE LIGHT UNLESS THE FAN IS ALLOWED TO OPERATE WITH THE LIGHT SWITCHED OFF.
6-NOTE THAT ALL PLUMBING VENTS SHALL TERMINATE NOT LESS THAN 6" ABOVE ROOF NOR LESS THAN 1' FROM ANY VERTICAL SURFACE. VENTS SHALL TERMINATE NOT LESS THAN 10' FROM OR 3' ABOVE ANY WINDOW, DOOR OPENING AIR INTAKE, OR VENT SHAFT NOR 3' FROM LOT LINE. IF WATER PRESSURE EXCEEDS 80 PSI, AND EXPANSION TANK AND AN APPROVED PRESSURE REGULATOR SHALL BE INSTALLED.
NON-REMOVABLE BACK FLOW PRE-VENTER OR BIBB-TYPE VACUUM BREAKER WILL BE INSTALLED ON ALL EXTERIOR HOSE BIBS. HOT WATER RE-CIRCULATING SYSTEM IS INSTALLED, THE ENTIRE LENGTH OF HOT WATER PIPES SHALL BE INSULATED.

NOTES:
1-Projects which disturb less than one acre of soil shall manage storm water drainage during construction by one of the following: A. Retention basins. B. Where storm water is conveyed to a public drainage system, water shall be filtered by use of a barrier system, wattle or other approved method.
2-Site grading or drainage system will manage all surface water flows to keep water from entering buildings (swales, water collection, French drains, etc.). CGC Section 4.106.3. Exception: Additions not altering the drainage path.
3-When a shower is provided with multiple shower heads, the sum of flow to all the heads shall not exceed 1.8 gpm @ 80 psi, or the shower shall be designed so that only one head is on at a time. CGC Section 4.303.1.3.2.
4-Landscape irrigation water use shall have weather or soil based controllers. CGC Section 4.304.1.
5-The plans that a minimum of 65% of construction waste is to be recycled. CGC Section 4.408.1.
6-The contractor shall submit a Construction Waste Management Plan, per CGC Section 4.408.2.
7-The builder is to provide an operation manual (containing information for maintaining appliances, etc.) for the owner at the time of final inspection. CGC Section 4.410.1.
8-The gas fireplace(s) shall be a direct-vent sealed- combustion type. Woodstove or pellet stoves must be US EPA Phase II rated appliances. CGC Section 4.503.1.

THE WATER SAVING PERFORMANCE STANDARDS FOR A PLUMBING FIXTURE ARE THOSE ESTABLISHED BY THE AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI). CURRENT REVISION, OR THE FOLLOWING STANDARDS,WHICHEVER ARE THE MORE RESTRICTIVE
1-THE MAXIMUM FLOW FROM A SINK OR LAVATORY FAUCET OR A FAUCET AERATOR SHALL NOT EXCEED 0.5 GALLONS OF WATER PER MINUTE AT A PRESSURE OF 60 POUNDS PER SQUARE INCH WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES. 2- THE MAXIMUM VOLUME OF WATER PER FLUSH FROM A TOILET SHALL NOT EXCEED AN AVERAGE OF 1.28 GALLONS WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES
3- THE MAXIMUM VOLUME OF WATER PER FLUSH FROM A URINAL AND THE ASSOCIATED FLUSH VALVE, IF ANY, SHALL NOT EXCEED AN AVERAGE OF ONE GALLON WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES

SPECIAL NOTICE TO CONTRACTORS
1. ALL CONTRACTORS (GENERAL CONTRACTOR AND SUB-CONTRACTORS) BIDDING THIS PROJECT ARE REQUIRED TO VISIT THE JOB SITE AND VERIFY THE EXISTING CONDITIONS PRIOR TO SUBMITTING THEIR BID. CONTRACTORS ARE TO CAREFULLY REVIEW ALL CONSTRUCTION DOCUMENTS AND NOTE ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED AT THE JOB SITE PRIOR TO SUBMISSION OF ANY BID. THE BUILDING OWNER REPRESENTATIVE LISTED BELOW MAY BE CONTACTED FOR ACCESS TO THE JOB SITE.
2. CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO, GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.
3. ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED SHALL BE BROUGHT TO THE ATTENTION, IN WRITING, TO THE ARCHITECT AND/OR ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.

SCOPE OF WORK
PROVIDE PLUMBING (WATER SUPPLY, SEWER, AND GAS SUPPLY) FOR THE REMODEL OF ADULT DAY CARE.

PLUMBING LIST OF DRAWINGS (LoD):

SHEET TAG	TITLE	SCALE
P 0.00	PLUMBING GENERAL NOTES AND SPECIFICATIONS.	NTS
P 0.01	PLUMBING CODE CHECKING.	NTS
P 1.01	WATER SUPPLY LAYOUT.	1/8"=1'-0"
P 2.01	SEWER LAYOUT.	1/8"=1'-0"
P 3.01	MAIN FLOOR - GAS SUPPLY LAYOUT.	1/8"=1'-0"
P 3.02	ROOF PLAN - GAS SUPPLY LAYOUT.	1/8"=1'-0"
P 4.01	HOT WATER CALC. AND PLUMB. EQUIPMENT DATASHEET.	NTS
P 5.01	PLUMBING GENERAL DETAILS.	NTS

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:			
TITLE: PLUMBING GENERAL NOTES AND SPECIFICATIONS.			
PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: NTS	
DRAWING NO. P 0 . 0 0		REV.	

CALIFORNIA PLUMBING CODE CHECKING:

PIPE SUPPORTS:

TABLE 313.3
HANGERS AND SUPPORTS

MATERIALS	TYPES OF JOINTS	HORIZONTAL	VERTICAL
Cast	Lead and Oakum	5 feet, except 10 feet where 10 foot length are installed ^{2,3}	Base and each floor, not to exceed 15 feet
	Compression Gasket	Every other joint, unless over 4 feet then support each joint ^{2,3}	Base and each floor, not to exceed 15 feet
Cast-iron Hubless	Shielded Coupling	Every other joint, unless over 4 feet then support each joint ^{2,3,4}	Base and each floor, not to exceed 15 feet
Copper & Copper Alloys	Soldered, Brazed, Threaded, or Mechanical	1 ½ inches and smaller, 6 feet; 2 inches and larger, 10 feet	Each floor, not to exceed 10 feet ⁵
Steel Pipe for Water or DWV	Threaded or Welded	¾ inch and smaller, 10 feet; 1 inch and smaller, 12 feet	Every floor, not to exceed 25 feet ⁵
Steel Pipe for Gas	Threaded or Welded	½ inch, 6 feet; ¾ inch and 1 inch, 8 feet; 1 ½ inches and larger, 10 feet	½ inch, 6 feet; ¾ inch and 1 inch, 8 feet; 1 ½ inches every floor level
Schedule 40 PVC and ABS DWV	Solvent Cemented	All sizes, 4 feet; allow for expansion every 30 feet ³	Base and each floor; provide mid-story guides; provide for expansion every 30 feet
CPVC	Solvent Cemented	1 inch and smaller, 3 feet; 1 ½ inches and larger, 4 feet	Base and each floor; provide mid-story guides
CPVC-AL-CPVC	Solvent Cemented	½ inch, 5 feet; ¾ inch, 65 inches; 1 inch, 6 feet	Base and each floor; provide mid-story guides
Lead	Wiped or burned	Continuous Support	Not to exceed 4 feet
Steel	Mechanical	In accordance with standards acceptable to the Authority Having Jurisdiction	
PEX	Cold Expansion, Insert and Compression	1 inch and smaller, 32 inches; 1 ½ inches and larger, 4 feet	Base and each floor; provide mid-story guides
PEX-AL-PEX	Metal Insert and Metal compression	½ inch } ¾ inch } 1 inch }	All sizes 98 inches Base and each floor; provide mid-story guides
PE-AL-PE	Metal Insert and Metal compression	½ inch } ¾ inch } 1 inch }	All sizes 98 inches Base and each floor; provide mid-story guides
PE-RT	Insert and Compression	1 inch and smaller, 32 inches; 1 ½ inches and larger, 4 feet	Base and each floor; provide mid-story guides
Polypropylene (PP)	Fusion weld (socket, butt, saddle, electrofusion), threaded (metal threads only), or mechanical	1 inch and smaller, 32 inches; 1 ½ inches and larger, 4 feet	Base and each floor; provide mid-story guides

For SI units: 1 inch = 25.4 mm, 1 foot = 304.8 mm.
Notes:
1 Support adjacent to joint, not to exceed 18 inches (457 mm).
2 Brace not to exceed 40 feet (12 192 mm) intervals to prevent horizontal movement.
3 Support at each horizontal branch connection.
4 Hangers shall not be placed on the coupling.
5 Vertical water lines shall be permitted to be supported in accordance with recognized engineering principles with regard to expansion and contraction, where first approved by the Authority Having Jurisdiction.

DRAINAGE:

719.0 Cleanouts.
719.1 Locations. Cleanouts shall be placed inside the building near the connection between the building drain and the building sewer or installed outside the building at the lower end of the building drain and extended to grade.

Additional building sewer cleanouts shall be installed at intervals not to exceed 100 feet (30 480 mm) in straight runs and for each aggregate horizontal change in direction exceeding 135 degrees (2.36 rad)
719.2 No additional Cleanouts. Where a building sewer or a branch thereof does not exceed 10 feet (3048 mm) in length and is a straight-line projection from a building drain that is provided with a cleanout, no cleanout will be required at its point of connection to the building drain.

721.0 Location.
721.1 Building Sewer. Except as provided in Section 721.2, no building sewer shall be located in a lot other than the lot that is the site of the building or structure served by such sewer nor shall a building sewer be located at a point having less than the minimum distances referenced in Table 721.1..

706.0 Changes in Direction of Drainage Flow.
706.1 Approved Fittings. Changes in the direction of drainage piping shall be made by the approximate use of approved fittings and shall be of the angles presented by a one-sixteenth bend, one-eight bend, or one-sixth bend, or other approved fittings of equivalent sweep.
706.2 Horizontal to Vertical. Horizontal drainage lines, connecting with a vertical stack, shall enter through 45 degree (0.79 rad) wye branch, 60 degree (1.05 rad) wye branches, combination wye and one-eighth bend branches, sanitary tee or sanitary tapped tee branches, or other approved fittings of equivalent sweep.

706.4 Vertical to Horizontal. Vertical drainage lines connecting with horizontal drainage lines shall enter through 45 degree (0.79 rad) wye branches, combination wye and one-eighth bend branches, or other approved fittings of equivalent sweep. Branches, or other approved fittings of equivalent sweep. Branches or offsets of 60 degrees (1.05 rad) shall be permitted to be used where installed in a true vertical position.

707.4 Location. Each horizontal drainage pipe shall be provided with a cleanout at its upper terminal, and each run of piping, that's more than 100 feet (30 480 mm) in total developed length, shall be provided with a cleanout for each 100 feet (30 480 mm), or fraction thereof, in length of such piping. An additional cleanout shall be provided in a drainage line for each aggregate horizontal change in direction exceeding 135 degrees (2.36 rad). A cleanout shall be installed above the fixture connecting fitting, serving each urinal, regardless of the location of the urinal in the building.
Exceptions
(1) Cleanouts shall be permitted to be omitted on a horizontal drain line less than 5 feet (1524 mm) in length unless such line is serving sinks or urinals

TABLE 703.2: MAXIMUM UNIT LOADING AND MAXIMUM LENGTH OF DRAINAGE AND VENT PIPING

SIZE OF PIPE (inches)	1 ¼	1 ½	2	3	4	5	6	8	10	12
Maximum Units										
Drainage Piping ¹										
Vertical	1	2 ²	14 ³	48 ⁴	256	600	1380	3600	5600	8400
Horizontal	1	1	8 ³	35 ⁴	216 ⁵	428 ⁵	720 ⁵	2640 ⁵	4680 ⁵	8200 ⁵
Maximum Length										
Drainage Piping										
Vertical	45	65	85	212	300	390	510	750	—	—
Horizontal										
Vent Piping										
Horizontal and Vertical ⁴										
Maximum Units	1	8 ³	24	84	256	600	1380	3600	—	—
Maximum Lengths, (feet)	45	60	120	212	300	390	510	750		

For SI units: 1 inch = 25 mm, 1 foot = 304.8 mm
Notes:
1 Excluding trap arm.
2 Except for sinks, urinals, and dishwashers – exceeding 1 fixture unit.
3 Except for six-unit traps or water closets.
4 Only four water closets or six-unit traps allowed on a vertical pipe or stack, and not to exceed three water closets or six-unit traps on a horizontal branch or drain.
5 Based on ½ inch per foot (20.8 mm/m) slope. For ⅓ of an inch per foot (10.4 mm/m) slope, multiply horizontal fixture units by a factor of 0.8.
6 The diameter of an individual vent shall be not less than 1 ¼ inches (32 mm) nor less than one-half the diameter of the drain to which it is connected. Fixture unit load values for drainage and vent piping shall be computed from Table 702.1 and Table 702.2(2). Not to exceed one third of the total permitted length of a vent shall be permitted to be installed in a horizontal position. Where vents are increased one pipe size for their entire length, the maximum length limitations specified in this table do not apply. This table is in accordance with the requirements of Section 901.3.

707.5 Cleaning. Each cleanout shall be installed so that it opens to allow cleaning in the direction of flow of the soil or waste or at right angles thereto and, except in the case of wye branch and end-of-line cleanouts, shall be installed vertically above the flow line of the pipe.

708.0 Grade of Horizontal Drainage Piping.
708.1 General. Horizontal drainage piping shall be run in practical alignment and a uniform slope of not less than ¼ inch per foot (20.8 mm/m) or 2 percent toward the point of disposal provided that, where it is impractical due to the depth of the street sewer, to the structural features, or to the arrangement of a building or structure to obtain a slope of ¼ inch per foot (20.8 mm/m) or 2 percent, such pipe or piping 4 inches (100 mm) or larger in diameter shall be permitted to have a slope of not less than ⅛ inch per foot (10.4 mm/m) or 1 percent, where first approved by the Authority Having Jurisdiction.

TABLE 721.1 MINIMUM HORIZONTAL DISTANCE REQUIRED FROM BUILDING SEWER (feet)	
Buildings or structures ¹	2
Property line adjoining private property	Clear ²
Water supply wells	50 ³
Streams	50
On-site domestic water service line	14 ⁴
Public water main	10 ^{5,6}

WATER CONVERSION & WATER CONSUMPTION:

WATER CONSERVING PLUMBING FIXTURES AND FITTINGS	
Plumbing fixtures and fittings shall comply with the following: (2022 CBOBSC, California Plumbing Code (CPC) and Table 1401.1 of the CPC)	
4303.1.1	All Water closets: <1.28 gal/flush Tank type water closet shall be certified to the performance criteria of the U.S. EPA WaterSense Specification for Tank-type Toilets.
4303.1.2	Urinals: <0.5 gal/flush
4303.1.3.1	Single showerheads: <1.8 gpm @ 80 psi
4303.1.3.2	Multiple showerheads: combined flow rate of all showerheads and/or other water outlets controlled by a single valve shall not exceed 1.8 gpm @ 80 psi or only one shower outlet is to be in operation at a time.
4303.1.4.1	Residential Lavatory Faucets: 0.8 gpm @ 20 psi < Flow Rate <1.2 gpm @ 60 psi
4303.1.4.2	Lavatory Faucets in common and Public Use Areas (outside of dwellings or sleeping units) in residential buildings: <0.5 gpm @ 60 psi
4303.1.4.3	Metering Faucets: <0.25 gallons per cycle
4303.1.4.4	Kitchen Faucets: <1.8 gpm @ 60 psi; Maximum Flow Rate of 1.8 gpm
PLUMBING FIXTURE CERTIFICATION REQUIRED: A plumbing fixture certification must be completed and signed by either a licensed general contractor, or a plumbing subcontractor, or the building owner certifying the flow rate of the fixtures installed. A copy of the certification can be obtained from the development services department.	

407.3 Limitation of Hot water Temperature for Public Lavatories.
Hot water delivered from public-use lavatories shall be limited to a maximum temperature of 120°F (49°C) by a device that complies with ASSE 1070/ASME A112.1070/CSA B125.70. The water heater thermostat shall not be considered a control for meeting this provision.
407.5 Waste Outlet. Lavatories shall have a waste outlet and fixtures tailpiece not less than 1 ½ inches (32 mm) in diameter.

409.4 Limitation of Hot Water in Bathtubs and Whirlpool Bathtubs. The maximum hot water temperature discharging from the bathtub and whirlpool bathtub filler shall be limited to 120°F (49°C) by a device that complies with ASSE 1070/ASME A112.1070/CSA B125.70. The water heater thermostat shall not be considered a control for meeting this provision.

WATER HEATER:

501.1 Applicability.
The minimum capacity for storage water heaters shall be in accordance with the first-hour rating listed in Table 501.1 (2).

Number of Bathrooms	1 to 1.5			2 to 2.5				3 to 3.5			
Number of Bedrooms	1	2	3	2	3	4	5	3	4	5	6
First hour rating, ² Gallons	38	49	49	49	62	62	74	62	74	74	74

For SI units: 1 gallon = 3.785 L.
Notes:
1 The first-hour rating is found on the "Energy Guide" label.
2 Solar water heaters shall be sized to meet the appropriate first-hour rating as shown in the table.

504.0 Water Heater Requirements.

504.1 Location. Water heater installations in bedrooms and bathrooms shall comply with one of the following [NFPA54:10.27.1]:

- (1) Fuel-burning water heaters shall be permitted to be installed in a closet located in the bedroom or bathroom provided the closet is equipped with a listed, gasketed door assembly and a listed self-closing device. The self-closing door assembly shall meet the requirements of Section 504.1.1. The door assembly shall meet the requirements of Section 504.1.2. Combustion air for such installations shall be obtained from the outdoors in accordance with Section 506.4. The closet shall be for the exclusive use of the water heater.
- (2) Water heater shall be of the direct vent type. [NFPA 54: 10.27.1(2)]

504.2 Vent. Water heaters of other than the direct-vent type shall be located as close as practical to the chimney or gas vent.
507.2 Seismic provisions. Water heaters shall be anchored or strapped to resist horizontal displacement due to earthquake motion. Strapping shall be at points within the upper one-third (⅓) and lower one-third (⅓) of its vertical dimensions. At the lower point, a minimum distance of four (4) inches (102 mm) shall be maintained above the controls with the strapping.
507.4 Ground Support. A water heater supported from the earth shall rest on level concrete or other approved base extending not less than 3 inches (76 mm) above the adjoining ground level.
507.5 Drainage Pan. Where a water heater is located in an attic, in or on an attic ceiling assembly, floor-ceiling assembly, or floor-subfloor assembly where damage results from a leaking water heater, a watertight pan of corrosion-resistant materials shall be installed beneath the water heater with not less than ¾ of an inch (20 mm) diameter drain to an approved location. Such pan shall be not less than 1 ½ (38 mm) in depth.

507.13 Installation in Residential Garages. Appliances in residential garages and in adjacent spaces that open to the garage and are not part of the living space of a dwelling unit shall be installed so that all burners and burner-ignition devices are located not less than 18 inches (457 mm) above the floor unless listed as flammable vapor ignition resistant. [NFPA 54:9.1.10.1]

508.4.4 Lighting and Convenience Outlet. A permanent 120 V receptacle outlet and a lighting fixture shall be installed near the appliance. The switch controlling the lighting fixture shall be located at the entrance to the passageway. [NFPA 54:9.5.3]
508.2.1 Installation at roof: Clearance. Appliances shall be installed on a well-drained surface of the roof. At least 6 feet (1829 mm) of clearance shall be available between any part of the appliance, and the edge of a roof or similar hazard, or rigidly fixed rails, guards, parapets or other building structures at least 42 inches (1067 mm) in height shall be provided on the exposed side. [NFPA 54:9.4.2.2]

VENT:

906.0 Vent Termination.

906.1 Roof Termination. Each vent pipe or stack shall extend through its flashing and shall terminate vertically not less than 6 inches (152 mm) above the roof nor less than 1 foot (305 mm) from a vertical surface. ABS and PVC piping exposed to sunlight shall be protected by water based synthetic latex paints.

906.2 Clearance. Each vent shall terminate not less than 10 feet (3048 mm) from, or not less than 3 feet (914 mm) above, an openable window, door, opening, air intake, or vent shaft, or not less than 3 feet (914 mm) in every direction from a hot line, alley and street extended.

909.0 Special Venting for Island Fixtures.

909.1 General. Traps for island sinks and similar equipment shall be roughed in above the floor and shall be permitted to be vented by extending the vent as high as possible, but not less than the drainboard height and then returning it down- ward and connecting it to the horizontal sink drain immediately downstream from the vertical fixture drain. The return vent shall be connected to the horizontal drain through a wye-branch fitting and shall, in addition, be provided with a foot vent taken off the vertical fixture vent by means of a wye branch immediately below the floor and extending to the nearest partition and then through the roof to the open air, or shall be permitted to be connected to other vents at a point not less than 6 inches (152 mm) above the flood-level rim of the fixtures served. Drainage fittings shall be used on the vent below the floor level, and a slope of not less than ¼ inch per foot (20.8 mm/m) back to the drain shall be maintained. The return bend used under the drainboard shall be a one-piece fitting or an assembly of a 45 degree (0.79 rad), a 90 degree (1.57 rad), and a 45 degree (0.79 rad) elbow in the order named. Pipe sizing shall be as elsewhere required in this code.

The island sink drain, upstream of the returned vent, shall serve no other fixtures. An accessible cleanout shall be installed in the vertical portion of the foot vent.

WATER SUPPLY:

TABLE 611.4 SIZING OF RESIDENTIAL WATER SOFTENERS ⁴	
REQUIRED SIZE OF SOFTENER CONNECTION (inches)	NUMBER OF BATHROOM GROUPS SERVED ¹
¾	up to 2 ²
1	up to 4 ³

For SI units: 1 inch = 25 mm
Notes:
1 Installation of a kitchen sink and dishwasher, laundry tray, and automatic clothes washer permitted without additional size increase.
2 An additional water closet and lavatory permitted.
3 Over four bathroom groups, the softener size shall be engineered for the specific installation.
4 See also Appendix A, Recommended Rules for Sizing the Water Supply Systems, and Appendix C, Alternate Plumbing Systems, for alternate methods of sizing water supply systems.

A backflow preventer shall not be required to separate a stand-alone sprinkler syste from the water distribution system where the sprinkler system material is in accordance with the requirements of Section 604.0.

606.1 General. Valves up to and including 2 inches (50 mm) in size shall be copper alloy or other approved material. Sizes exceeding 2 inches (50 mm) shall be permitted to have cast iron or copper alloy bodies. Each gate or ball valve shall be a fullway or full-port type with working parts of the non-corrosive material. Valves carrying water used in potable water systems intended to supply drinking water shall comply with the requirements of NSF 61 and ASME A112.4.14, ASME B16.34, ASTM F1970, ASTM F2389 AWWA C500, AWWA C504, AWWA C507, IAPMO Z1157, MSS SP-67, MSS SP- 70, MSS SP-71, MSS SP-72, MSS SP-78, MSS SP-80, MSS SP-110, MSS SP-122, or NSF 359.

608.4 Pressure Relief Valves. Each pressure relief valve shall be an approved automatic type with drain, and each such relief valve shall be set at a pressure of not more than 150 psi (1034 kPa). No shutoff valve shall be installed between the relief valve and the system.

FIRESTOP PROTECTION

1404.0 Combustible Piping Installations.

1404.2 Fire-Resistance Rating. Where penetrating a fire-resistance-rated wall, partition, floor, floor-ceiling assembly, roof-ceiling assembly, or shaft enclosure, the fire-resistance rating of the assembly shall be restored to its original rating.

1404.3 Firestop Systems. Penetrations shall be protected by an approved penetration firestop system installed as tested in accordance with ASTM E119, ASTM E814, UL 263, or UL 1479 with a positive pressure differential of not less than 0.01 of an inch of water (0.002 kPa). Systems shall have and F rating of not less than 1 hour but not less than the required fire-resistance rating of the assembly being penetrated. Systems protecting floor penetrations shall have a T rating of not less than 1 hour but not less than the required fire-resistance rating of the floor penetrations shall have a T rating of not less than 1 hour but not less than the required fire-resistance rating of the floor being penetrated. Floor penetrations contained within the cavity of a wall at the location of the floor penetration do not require a T rating. No T rating shall be required for floor penetrations by piping that is not in direct contact with combustible material.

1404.6 Sleeves. Where sleeves are used, the sleeves shall be securely fastened to the fire-resistance-rated assembly. The (inside) annular space between the sleeve and the fire-resistance-rated assembly shall be firestopped in accordance with this chapter.

1405.0 Noncombustible Piping Installations.

1405.3 Firestop Systems. Penetrations shall be protected by an approved penetration firestop system installed as tested in accordance with ASTM E119, ASTM E814, UL 263, or UL 1479 with a positive pressure differential of not less than 0.01 of an inch of water (0.002 kPa). Systems shall have an F rating of not less than 1 hour but not less than the required fire-resistance rating of the assembly being penetrated. Systems protecting floor penetrations shall have a T rating of not less than 1 hour but not less than the required fire-resistance rating of the floor being penetrated. Floor penetrations contained within the cavity of a wall at a location of the floor penetration do not require a T rating. No T rating shall be required for floor penetrations by piping that is not in direct contact with combustible material.

1405.6 Sleeves. Where sleeves are used, the sleeves shall be securely fastened to the fire-resistance-rated assembly. The (inside) annular space between the sleeve and the penetrating item and the (outside) annular space between the sleeve and the fire-resistance-rated assembly shall be firestopped in accordance with this chapter.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO. DESCRIPTION DATE BY

PROJECT:


TITLE:
PLUMBING CODE CHECKING.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36

NTS

DRAWING NO. REV.

P 0 . 0 1



SCHEDULE No. 1
GAS WATER HEATER

TAG	GWH-01
LOCATION	STORAGE ROOM
MANUFACTURER	A.O. SMITH
MODEL	BSS 130
TYPE	GAS - TANK
GALLON CAPACITY (GAL)	34
GAS INPUT (MBH)	130
VOLTAGE (V / PH /HZ) - POWER (W)	120 / 1 / 60 - 200
THERMAL EFFICIENCY (%)	96
APPROXIMATE SHIPPING WEIGHT (LBS)	150
DIAMETER x HEIGHT (in.)	22" X 48-1/2"

FROM 2022 CPC - TABLE 610.3:
WATER SUPPLY FIXTURE UNITS LOADS:

FIXTURE	W.S.F.U	QTY.	TOTAL W.S.F.U
PANTRY SINK	3.0	1	3.0
SERVICE SINK	3.0	3	9.0
WATER CLOSET	2.5	15	37.5
LAVATORY	1.0	12	12.0
DRINKING FOUNTAIN	0.5	4	2.0
WASHING MACHINE	4.0	1	4.0
TOTAL UNIT A WSFU =			64.5

AS PER 2022 CPC - TABE 610.4:
THE LONGEST RUN IS APPROX. 100 FT.
AND FOR W/M PRESSURE RANGE 30-45 PSI,
THEREFORE, THE MAIN CWP TO BE NOT LESS
THAN 1-1/2" AND METER TO BE NOT LESS THAN 1"

PLUMBING SHEET NOTES

SHEET NOTES:	
1	→ DCW RISES TO FIRST FLOOR CEILING LEVEL.
2	→ DCW AND/OR DHW TO FIXTURE CONNECTION.
3	→ DCW TO IRRIGATION CONNECTION.

GENERAL NOTES:

- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
- REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
- CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
- CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
- ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
- ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
- ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
- CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
- ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT 1/4" PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT 1/8" PER FOOT.
- ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT 1/8" PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
- VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
- REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

Water Heater:

CPC-504.3-504.3.1 Listed Water Heaters

The clearances shall not be such as to interfere with combustion air, draft hood clearance and relief, and accessibility for servicing. Listed water heaters shall be installed in accordance with their listings and the manufacturer's installation instructions.

504.3.2 Unlisted Water Heaters - Unlisted water heaters shall be installed with a clearance of 12 inches (305 mm) on all sides and rear. Combustible floors under unlisted water heaters shall be protected in an approved manner. [NFPA 54:10.27.2.2]

CPC-504.4-A water heater installation shall be provided with overpressure protection using an approved, listed device installed in accordance with the terms of its listing and the manufacturer's installation instructions.

CPC-504.5-A water heater installation or a hot water storage vessel installation shall be provided with overtemperature protection by means of an approved, listed device installed in accordance with the terms of its listing and the manufacturer's installation instructions.

CPC-506.4.2-One permanent opening, commencing within 12 inches (305 mm) of the top of the enclosure, shall be provided. The appliance shall have clearances of at least 1 inch (25.4 mm) from the sides and back and 6 inches (152 mm) from the front of the appliance.

CPC-507.4-A water heater supported from the earth shall rest on level concrete or other approved base extending not less than 3 inches (76 mm) above the adjoining ground level.

CPC-507.5-Where a water heater is located in an attic, in or on an attic ceiling assembly, floor-ceiling assembly, or floor-subfloor assembly where damage results from a leaking water heater, a watertight pan of corrosion-resistant materials shall be installed beneath the water heater with not less than 3/4 of an inch (20 mm) diameter drain to an approved location. Such pan shall be not less than 11/2 inches (38 mm) in depth.

CPC-608.6-A water-heating device connected to a separate storage tank and having valves between said heater and tank shall be provided with an approved water pressure relief valve.

Water Supply:

CPC-407.2.2-The maximum flow rate of residential lavatory faucets shall not exceed 1.2 gallons (4.54 L) per minute at 60 psi. The minimum flow rate of residential lavatory faucets shall not be less than 0.8 gallons (3.03 L) per minute at 20 psi.

CPC-408.4-Showers shall have a waste outlet and fixture tailpiece not less than 2 inches (50 mm) in diameter.

CPC-411.2-The effective flush volume of all water closets shall not exceed 1.28 gallons (4.8 L) per flush when tested in accordance with ASME A112.19.2/CSA B45.1.

CPC-420.2-Sink faucets shall have a maximum flow rate of not more than 2.2 gpm at 60 psi (8.3 L/m at 414 kPa).

CPC-420.2.2-The maximum flow rate of kitchen faucets shall not exceed 1.8 gallons (6.81 L) per minute at 60 psi. Kitchen faucets may temporarily increase the flow above the maximum rate, but not to exceed 2.2 gallons (8.32 L) per minute at 60 psi, and must default to a maximum flow rate of 1.8 gallons (6.81 L) per minute at 60 psi

CPC-606.1-Valves up to and including 2 inches (50 mm) in size shall be copper alloy or other approved material. Sizes exceeding 2 inches (50 mm) shall be permitted to have cast iron or copper alloy bodies. Each gate or ball valve shall be a fullway or full-port type with working parts of the non-corrosive material.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS
APPEARING HEREIN CONSTITUTE THE
ORIGINAL AND UNPUBLISHED WORK OF THE
DESIGNER AND THE SAME MAY NOT BE
DUPLICATED, USED OR DISCLOSED WITHOUT
CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:


TITLE:
WATER SUPPLY LAYOUT.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"
1/8"=1'-0"

DRAWING NO.

P 1 . 0 1

REV.



SANITARY SHEET NOTES

SHEET NOTES:

1

→ 4" FLOOR CLEAN-OUT.

2

→ 3" FLOOR DRAIN.

3

→ 3" VENT STACK TO ABOVE.

4

→ 4" VENT STACK TO ABOVE.

5

→ 4" EXTERNAL CLEAN-OUT.

FROM 2022 CPC - TABLE 702.1:
DRAINAGE FIXTURE UNIT VALUES (DFU)

FIXTURE	D.F.U	QTY.	TOTAL D.F.U
PANTRY SINK	3.0	1	3.0
WATER CLOSET	4.0	13	52.0
LAVATORY	1.0	12	12.0
SERVICE SINK	3.0	3	9.0
UNIRAL	2.0	2	6.0
DRINKING FOUNTAIN	0.5	4	2.0
TOTAL DFU =			84.0

GENERAL NOTES:

- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
- REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
- CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
- CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
- ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
- ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
- ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
- CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
- ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT 1/4" PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT 1/8" PER FOOT.
- ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT 1/8" PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
- VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
- REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

Indirect Waste:

CMC-310.1-Condensate from air washers, air-cooling coils, condensing appliances, and the overflow from evaporative coolers and similar water-supplied equipment or similar air-conditioning equipment shall be collected and discharged to an approved plumbing fixture or disposal area. Where discharged into the drainage system, equipment shall drain by means of an indirect waste pipe. The waste pipe shall have a slope of not less than 1/8 inch per foot (10.4 mm/m) or 1 percent slope and shall be of approved corrosion-resistant material not smaller than the outlet size in accordance with Section 310.3 or Section 310.4 for air-cooling coils or condensing appliances, respectively. Condensate or wastewater shall not drain over a public way.

CMC-310.5-Air-conditioning condensate waste pipes shall connect indirectly, except where permitted in Section 310.6, to the drainage system through an air gap or air break to trapped and vented receptors, dry wells, leach pits, or the tailpiece of plumbing fixtures. A condensate drain shall be trapped in accordance with the appliance manufacturer's instructions or as approved.

CPC-801.2-Indirect waste piping shall discharge into the building drainage system through an air gap or air break as set forth in this code. Where a drainage air gap is required by this code, the minimum vertical distance as measured from the lowest point of the indirect waste pipe or the fixture outlet to the flood-level rim of the receptor shall be not less than 1 inch (25.4 mm).

Sewer:

CPC-418.3-Floor drains shall be installed in the following areas:

- Toilet rooms containing two or more water closets or a combination of one water closet and one urinal, except in a dwelling unit.
- Commercial kitchens and in accordance with Section 704.3.
- Laundry rooms in commercial buildings and common laundry facilities in multi-family dwelling buildings.
- Boiler rooms.

CPC-707.4-1- Each horizontal drainage pipe shall be provided with a cleanout at its upper terminal

Exceptions:

- Cleanouts shall be permitted to be omitted on a horizontal drain line less than 5 feet in length unless such line is serving sinks or urinals.
- each run of piping, that is more than 100 feet in total developed length.
 - A cleanout shall be provided in a drainage line for each aggregate horizontal change in direction exceeding 135 degrees.
 - A cleanout shall be installed above the fixture connection fitting, serving each urinal, regardless of the location of the urinal in the building.

CPC-707.9-Each cleanout in piping 2 inches (50 mm) or less in size shall be so installed that there is a clearance of not less than 18 inches (457 mm) by 18 inches (457 mm) in front of the cleanout. Cleanouts in piping exceeding 2 inches (50 mm) shall have a clearance of not less than 24 inches (610 mm) by 24 inches (610 mm) in front of the cleanout.

CPC-Table 721.1-no building sewer shall be located in a lot other than the lot that is the site of the building or structure served by such sewer nor shall a building sewer be located at a point having less than the minimum distances referenced in Table 721.1.

CPC-906.1-Each vent pipe or stack shall extend through its flashing and shall terminate vertically not less than 6 inches (152 mm) above the roof nor less than 1 foot (305 mm) from a vertical surface. ABS and PVC piping exposed to sunlight shall be protected by water based synthetic latex paints.

CPC-906.2-Each vent shall terminate not less than 10 feet (3048 mm) from, or not less than 3 feet (914 mm) above, an openable window, door, opening, air intake, or vent shaft, or not less than 3 feet (914 mm) in every direction from a lot line, alley and street excepted.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY


PROJECT:

TITLE:
SEWER LAYOUT.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36" 1/8"=1'-0"

DRAWING NO. REV.

P 2 . 0 1



GENERAL NOTES:

1. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
2. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
3. REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
4. CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
5. CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
6. ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
7. ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
8. ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
9. CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
10. ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT $\frac{1}{4}$ " PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT $\frac{1}{8}$ " PER FOOT.
11. ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT $\frac{1}{8}$ " PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
12. VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
13. REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

Gas:

CMC-902.14-Where the gas supply pressure is higher than that at which the appliance is designed to operate or varies beyond the design pressure limits of the appliance, a gas appliance pressure regulator shall be installed. [NFPA 54:9.1.18]

CMC-1308.6-1- Gas meters shall be located in ventilated spaces readily accessible for examination, reading, replacement, or necessary maintenance. [NFPA 54:5.7.2.1]

2- Gas meters shall not be placed where they will be subjected to damage, such as adjacent to a driveway, under a fire escape, in public passages, halls, or where they will be subject to excessive corrosion or vibration. [NFPA 54:5.7.2.2]

3- Gas meters shall not be located where they will be subjected to extreme temperatures or sudden extreme changes in temperature or in areas where they are subjected to temperatures beyond those recommended by the manufacturer. [NFPA 54:5.7.2.3]

CMC-1310.3-Piping installed aboveground shall be securely supported and located where it will be protected from physical damage. Where passing through an exterior wall, the piping shall also be protected from corrosion by coating or wrapping with an inert material approved for such applications. The piping shall be sealed around its circumference at the point of the exterior penetration to prevent the entry of water, insects, and rodents. Where piping is encased in a protective pipe sleeve, the annular spaces between the gas piping and the sleeve and between the sleeve and the wall opening shall be sealed. [NFPA 54:7.2.1]

1310.3.1 Protective Coating
Where piping is in contact with a material or an atmosphere corrosive to the piping system, the piping and fittings shall be coated with a corrosion-resistant material. Any such coating used on piping or components shall not be considered as adding strength to the system. [NFPA 54:7.2.2]

1310.3.2 Building Structure
The installation of gas piping shall not cause structural stresses within building components to exceed allowable design limits. Approval shall be obtained before any beams or joists are cut or notched. [NFPA 54:7.2.3.1 - 7.2.3.2]

1310.3.3 Gas Piping to Be Sloped
Piping for other than dry gas conditions shall be sloped not less than 1/4 inch in 15 feet (1.4 mm/m) to prevent traps. [NFPA 54:7.2.4]

CMC-1312.6-Each appliance connected to a piping system shall have an accessible, approved manual shutoff valve with a nondisplaceable valve member, or a listed gas convenience outlet. Appliance shutoff valves and convenience outlets shall serve a single appliance only. [NFPA 54:9.6.5] The shutoff valve shall be located within 6 feet (1829 mm) of the appliance it serves. [NFPA 54:9.6.5.1] Where a connector is used, the valve shall be installed upstream of the connector. A union or flanged connection shall be provided downstream from the valve to permit removal of appliance controls. [NFPA 54:9.6.5.1(A)]

Exceptions:

Shutoff valves serving decorative appliances in a fireplace shall not be located within the fireplace firebox except where the valve is listed for such use. [NFPA 54:9.6.5.1(B)]

Shutoff valves shall be permitted to be accessibly located inside wall heaters and wall furnaces listed for recessed installation where necessary maintenance is performed without removal of the shutoff valve

GAS SHEET NOTES

SHEET NOTES:

- 1 → GAS PIPE RISES TO CEILING LEVEL.
- 2 → GAS PIPE RISES TO ROOF.
- 3 → GAS PIPE RISES FROM BELOW.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:


TITLE:
MAIN FLOOR - GAS SUPPLY LAYOUT.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36:
1/8" = 1'-0"

DRAWING NO.

P 3 . 0 1

REV.



GENERAL NOTES:

1. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
2. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
3. REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
4. CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
5. CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
6. ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
7. ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
8. ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
9. CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
10. ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT $\frac{1}{4}$ " PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT $\frac{1}{8}$ " PER FOOT.
11. ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT $\frac{1}{8}$ " PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
12. VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
13. REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

Gas:

CMC-902.14-Where the gas supply pressure is higher than that at which the appliance is designed to operate or varies beyond the design pressure limits of the appliance, a gas appliance pressure regulator shall be installed. [NFPA 54:9.1.18]

CMC-1308.6-1- Gas meters shall be located in ventilated spaces readily accessible for examination, reading, replacement, or necessary maintenance.

[NFPA 54:5.7.2.1]

2- Gas meters shall not be placed where they will be subjected to damage, such as adjacent to a driveway, under a fire escape, in public passages, halls, or where they will be subject to excessive corrosion or vibration. [NFPA 54:5.7.2.2]

3- Gas meters shall not be located where they will be subjected to extreme temperatures or sudden extreme changes in temperature or in areas where they are subjected to temperatures beyond those recommended by the manufacturer. [NFPA 54:5.7.2.3]

CMC-1310.3-Piping installed aboveground shall be securely supported and located where it will be protected from physical damage. Where passing through an exterior wall, the piping shall also be protected from corrosion by coating or wrapping with an inert material approved for such applications. The piping shall be sealed around its circumference at the point of the exterior penetration to prevent the entry of water, insects, and rodents. Where piping is encased in a protective pipe sleeve, the annular spaces between the gas piping and the sleeve and between the sleeve and the wall opening shall be sealed. [NFPA 54:7.2.1]

1310.3.1 Protective Coating

Where piping is in contact with a material or an atmosphere corrosive to the piping system, the piping and fittings shall be coated with a corrosion-resistant material. Any such coating used on piping or components shall not be considered as adding strength to the system. [NFPA 54:7.2.2]

1310.3.2 Building Structure

The installation of gas piping shall not cause structural stresses within building components to exceed allowable design limits. Approval shall be obtained before any beams or joists are cut or notched. [NFPA 54:7.2.3.1 - 7.2.3.2]

1310.3.3 Gas Piping to Be Sloped

Piping for other than dry gas conditions shall be sloped not less than 1/4 inch in 15 feet (1.4 mm/m) to prevent traps. [NFPA 54:7.2.4]

CMC-1312.6-Each appliance connected to a piping system shall have an accessible, approved manual shutoff valve with a nondisplaceable valve member, or a listed gas convenience outlet. Appliance shutoff valves and convenience outlets shall serve a single appliance only. [NFPA 54:9.6.5] The shutoff valve shall be located within 6 feet (1829 mm) of the appliance it serves. [NFPA 54:9.6.5.1] Where a connector is used, the valve shall be installed upstream of the connector. A union or flanged connection shall be provided downstream from the valve to permit removal of appliance controls. [NFPA 54:9.6.5.1(A)]

Exceptions:

Shutoff valves serving decorative appliances in a fireplace shall not be located within the fireplace firebox except where the valve is listed for such use. [NFPA 54:9.6.5.1(B)]

Shutoff valves shall be permitted to be accessibly located inside wall heaters and wall furnaces listed for recessed installation where necessary maintenance is performed without removal of the shutoff valve

GAS SHEET NOTES

SHEET NOTES:

- 1 → GAS PIPE RISES TO CEILING LEVEL.
- 2 → GAS PIPE RISES TO ROOF.
- 3 → GAS PIPE RISES FROM BELOW.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
ROOF PLAN - GAS SUPPLY LAYOUT.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36:
1/8" = 1'-0"

DRAWING NO.

P 3 . 0 2

REV.

CALIFORNIA GAS CODE CHECKING:

GAS:

1208.7 Gas Meters. Gas meters shall be selected for the maximum expected pressure and permissible pressure drop. [NFPA 54:5.7.1]

1208.7.1 Location. Gas meters shall be located in ventilated spaces readily accessible for examination, reading, replacement, or necessary maintenance. [NFPA54:5.7.2.1]

1208.7.1.1 Subject to Damage. Gas meters shall not be placed where they will be subjected to damage, such as adjacent to a driveway; under a fire escape; n public passages, halls, or where they will be subject to excessive corrosion or vibration. [NFPA 54:5.7.2.2]

1208.7.1.2 Extreme Temperatures. Gas meters shall not be located where they will be subjected to extreme temperatures or sudden extreme changes in temperature or in areas where they are subjected to temperatures beyond those recommended by the manufacturer. [NFPA 54:5.7.2.3]

1208.7.2 Supports. Gas meters shall be supported or connected to rigid piping so as not to exert a strain n the meters. Where flexible connectors are used to connect a gas meter to downstream piping at mobile homes in mobile home parks, the meter shall be supported by a post or bracket placed in a firm footing or by other means providing equivalent support. [NFPA 54:5.7.3]

1208.7.3 Meter Protection. Meters shall be protected against overpressure, backpressure, and vacuum. [NFPA54:5.7.4]

1208.7.4 Identification. Gas piping at multiple meter installations shall be marked by a metal tag or other permanent means designating the building or the part of the building being supplied and attached by the installing agency. [NFPA 54:5.7.5]

1208.8 Gas Pressure Regulators. A line pressure regulator or gas appliance pressure regulator, as applicable, shall be installed where the gas supply pressure exceeds that at which the branch supply line or appliances are designed to operate or vary beyond design pressure limits. [NFPA 54:5.8.1]

1210.0 Gas Piping Installation.

1210.1 Piping Underground. Underground gas piping shall be installed with sufficient clearance from any other underground structure to avoid contact therewith, to allow maintenance, and to protect against damage from proximity to other structures. In addition, underground plastic piping shall be installed with sufficient clearance or shall be insulated from sources of heat to prevent the heat from impairing the serviceability of the pipe. [NFPA 54:7.1.1]

1212.6 Appliance Shutoff Valves and Connections.

Each appliance connected to a piping system shall have an accessible, approved manual shutoff valve with a non-displaceable valve member or a listed gas convenience outlet.

Appliance shutoff valves and convenience outlets shall serve a single appliance only. The shutoff valve shall be located within 6 feet (1829 mm) of the appliance it serves. Where a connector is used, the valve shall be installed upstream of the connector. A union or flanged connection shall be provided downstream from the valve to permit removal of appliance controls. Shutoff valves serving decorative appliances shall be permitted to be installed in fireplaces if listed for such use. [NFPA 54:9.6.5, 9.6.5.1 (A)(B)]

- Exceptions:**
- (1)

Shutoff valves shall be permitted to be accessible located inside or under an appliance where such appliance is removed without removal of the shutoff valve.
- (2)

Shutoff valves shall be permitted to be accessibly located inside wall heaters and wall furnaces listed for recessed installation where necessary maintenance is performed without removal of the shutoff valve.

TABLE 1208.4.1 APPROXIMATE GAS INPUT FOR TYPICAL APPLIANCES [NFPA 54: TABLE A.5.4.2.1]	
APPLIANCE	INPUT (Btu/h approx.)
Space Heating Units	
Warm air furnace	
Single family	100 000
Multifamily, per unit	60 000
Hydronic boiler	
Single family	100 000
Multifamily, per unit	60 000
Space and Water Heating Units	
Hydronic boiler	
Single family	120 000
Multifamily, per unit	75 000
Water Heating Appliances	
Water heater, automatic storage	
30 to 40 gallon tank	35 000
Water heater, automatic storage	
50 gallon tank	50 000
Water heater, automatic instantaneous	
Capacity at 2 gallons per minute	142 800
Capacity at 4 gallons per minute	285 000
Capacity at 6 gallons per minute	428 400
Water heater, domestic, circulating or side-arm	35 000
Cooking Appliances	
Range, freestanding, domestic	65 000
Built-in oven or broiler unit, domestic	25 000
Built-in top unit, domestic	40 000
Other Appliances	
Refrigerator	3000
Clothes dryer, Type 1 (domestic)	35 000
Gas fireplace direct vent	40 000
Gas log	80 000
Barbecue	40 000
Gaslight	2500

ALL GAS PIPES ARE METALLIC SHCD. 40	
THE TOTAL GAS PIPE LENGTH FROM THE MUNICIPALITY CONNECTION TO THE FARTHEST EQUIPMENT IS APPRX. 200 FEET.	
GAS UNITS AND MBH:	
ITEM	MBH
GWH-01	130
RTU-01	60
RTU-02	60
RTU-03	80
RTU-04	80
RTU-05	100
RTU-06	300
TOTAL =	810

ISOMETRIC GAS LAYOUT




TABLE 1215.2(1) SCHEDULE 40 METALLIC PIPE															Gas Piping Installations	
PIPE SIZE (inch)															Gas	Natural
Nominal															Inlet Pressure	Less than 2 psi
Actual ID															Pressure Drop	0.5 in. w.c.
Length (ft)															Specific Gravity	0.60
Capacity in Cubic Feet of Gas Per Hour																
10	131	273	514	1,060	1,580	3,050	4,860	8,580	17,500	31,700	51,300	105,000	191,000	303,000		
20	90	188	353	726	1,090	2,090	3,340	5,900	12,000	21,800	35,300	72,400	132,000	208,000		
30	72	151	284	583	873	1,680	2,680	4,740	9,660	17,500	28,300	58,200	106,000	167,000		
40	62	129	243	499	747	1,440	2,290	4,050	8,270	15,000	24,200	49,800	90,400	143,000		
50	55	114	215	442	662	1,280	2,030	3,590	7,330	13,300	21,500	44,100	80,100	127,000		
60	50	104	195	400	600	1,160	1,840	3,260	6,640	12,000	19,500	40,000	72,600	115,000		
70	46	95	179	368	552	1,060	1,690	3,000	6,110	11,100	17,900	36,800	66,800	106,000		
80	42	89	167	343	514	989	1,580	2,790	5,680	10,300	16,700	34,200	62,100	98,400		
90	40	83	157	322	482	928	1,480	2,610	5,330	9,650	15,600	32,100	58,300	92,300		
100	38	79	148	304	455	877	1,400	2,470	5,040	9,110	14,800	30,300	55,100	87,200		
125	33	70	131	269	403	777	1,240	2,190	4,460	8,080	13,100	26,900	48,800	77,300		
150	30	63	119	244	366	704	1,120	1,980	4,050	7,320	11,900	24,300	44,200	70,000		
175	28	58	109	224	336	648	1,030	1,820	3,720	6,730	10,900	22,400	40,700	64,400		
200	26	54	102	209	313	602	960	1,700	3,460	6,260	10,100	20,800	37,900	59,900		
250	23	48	90	185	277	534	851	1,500	3,070	5,550	8,990	18,500	33,500	53,100		
300	21	43	82	168	251	484	771	1,360	2,780	5,030	8,150	16,700	30,400	48,100		
350	19	40	75	154	231	445	709	1,250	2,560	4,630	7,490	15,400	28,000	44,300		
400	18	37	70	143	215	414	660	1,170	2,380	4,310	6,970	14,300	26,000	41,200		
450	17	35	66	135	202	389	619	1,090	2,230	4,040	6,540	13,400	24,400	38,600		
500	16	33	62	127	191	367	585	1,030	2,110	3,820	6,180	12,700	23,100	36,500		
550	15	31	59	121	181	349	556	982	2,000	3,620	5,870	12,100	21,900	34,700		
600	14	30	56	115	173	333	530	937	1,910	3,460	5,600	11,500	20,900	33,100		
650	14	29	54	110	165	318	508	897	1,830	3,310	5,360	11,000	20,000	31,700		
700	13	27	52	106	159	306	488	862	1,760	3,180	5,150	10,600	19,200	30,400		
750	13	26	50	102	153	295	470	830	1,690	3,060	4,960	10,200	18,500	29,300		
800	12	26	48	99	148	285	454	802	1,640	2,960	4,790	9,840	17,900	28,300		
850	12	25	46	95	143	275	439	776	1,580	2,860	4,640	9,530	17,300	27,400		
900	11	24	45	93	139	267	426	752	1,530	2,780	4,500	9,240	16,800	26,600		
950	11	23	44	90	135	259	413	731	1,490	2,700	4,370	8,970	16,300	25,800		
1,000	11	23	43	87	131	252	402	711	1,450	2,620	4,250	8,720	15,800	25,100		
1,100	10	21	40	83	124	240	382	675	1,380	2,490	4,030	8,290	15,100	23,800		
1,200	NA	20	39	79	119	229	364	644	1,310	2,380	3,850	7,910	14,400	22,700		
1,300	NA	20	37	76	114	219	349	617	1,260	2,280	3,680	7,570	13,700	21,800		
1,400	NA	19	35	73	109	210	335	592	1,210	2,190	3,540	7,270	13,200	20,900		
1,500	NA	18	34	70	105	203	323	571	1,160	2,110	3,410	7,010	12,700	20,100		
1,600	NA	18	33	68	102	196	312	551	1,120	2,030	3,290	6,770	12,300	19,500		
1,700	NA	17	32	66	98	189	302	533	1,090	1,970	3,190	6,550	11,900	18,800		
1,800	NA	16	31	64	95	184	293	517	1,050	1,910	3,090	6,350	11,500	18,300		
1,900	NA	16	30	62	93	178	284	502	1,020	1,850	3,000	6,170	11,200	17,700		
2,000	NA	16	29	60	90	173	276	488	1,000	1,800	2,920	6,000	10,900	17,200		

For SI: 1 inch = 25.4 mm, 1 foot = 304.8 mm, 1 pound per square inch = 6.895 kPa, 1-inch water column = 0.2488 kPa, 1 British thermal unit per hour = 0.2931 W, 1 cubic foot per hour = 0.0283 m3/h, 1 degree = 0.01745 rad.

- Notes:
1. NA means a flow of less than 10 cfh.

2. All table entries have been rounded to three significant digits.

CALIFORNIA PLUMBING CODE 2022 ®

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.


REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:


TITLE: GAS CODE CHECKING & ISOMETRIC RISER DIAGRAM.		
PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS

DRAWING NO. REV.


P 4 . 0 1




1 TYPICAL WASTE AND VENT RISERS
SCALE: NONE




2 TRAP PRIMER
SCALE: NONE




3 FLOOR DRAIN WITH TRAP SEAL PROTECTION
SCALE: NONE




ANTI-SCALD MIXING VALVE
NO SCALE




FLOOR SINK DETAIL
NO SCALE




FLOOR DRAIN DETAIL
NO SCALE




MOP SINK DETAIL
NO SCALE




TRAP PRIMER DETAIL
NO SCALE




FLOOR CLEANOUT DETAIL
NO SCALE




CONDENSATE DETAIL
NO SCALE



VENT THRU ROOF DETAIL
NO SCALE



WATER ENTRY DETAIL
NO SCALE



COND. ON FLOOR SINK DETAIL
NO SCALE

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:
PLUMBING GENERAL DETAILS.

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"

NTS

DRAWING NO. REV.

P 6 . 0 1

STATE OF CALIFORNIA

Electrical Power Distribution

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-ELC-E

This document is used to demonstrate compliance with mandatory requirements in 130.5, for electrical systems in newly constructed nonresidential and hotel/motel occupancies and 160.5 and 160.5.1 for electrical systems in newly constructed multifamily occupancies. Additions and alterations to electrical systems in nonresidential and hotel/motel occupancies will also use this document to demonstrate compliance per 141.0(a) or 141.0(b)(2) for alterations. For multifamily addition or alterations compliance will be documented per 180.1(a) or 180.2 (b)(4)(b).

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

A. GENERAL INFORMATION

01	Project Location (city)	Union City	02	Climate Zone	3
03	Occupancy Types Within Project:	All Other OccupanciesConvention CenterOfficeSupport Area			

B. PROJECT SCOPE

This table includes electrical systems that are within the scope of the permit application.

01	02	03	04	05	06	07
Electrical Service Designation/Description	Scope of Work/	Rating ¹ (kVA)	Utility Provided Metering System Exception to 130.5(a) / 160.6(a) ²	System subject to CA Elec Code Article 517 Exception to 130.5(a)and (b)	Demand Response Controls	Provides power to dwelling units/common living areas only in multifamily occupancy
Main	Add/Alt to feeders and branch circuits only	50	<input type="checkbox"/>	<input type="checkbox"/>	Where required, demand response controls must be specified which are capable of receiving and automatically responding to at least one standards based messaging protocol which enables demand response after receiving a demand response signal. Sections 130.2/160.3, 130.1/160.5, and 130.3/160.5, and mechanical, indoor lighting, and sign lighting Certificate of Compliance documents will indicate when demand response controls are required.	<input type="checkbox"/>

FOOTNOTES: Adding only new feeders and branch circuits triggers Voltage Drop 130.5(c)/160.6(c), no other requirements from 130.5/160.6 are required.

1 Common use areas in a multifamily are submetered, rating is for submeter size serving common use areas.

2 Applicable if the utility company is providing a metering system that indicates instantaneous kW demand and kWh for a utility-defined period.

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Electrical Power Distribution

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-ELC-E

This document is used to demonstrate compliance with mandatory requirements in 130.5, for electrical systems in newly constructed nonresidential and hotel/motel occupancies and 160.5 and 160.5.1 for electrical systems in newly constructed multifamily occupancies. Additions and alterations to electrical systems in nonresidential and hotel/motel occupancies will also use this document to demonstrate compliance per 141.0(a) or 141.0(b)(2) for alterations. For multifamily addition or alterations compliance will be documented per 180.1(a) or 180.2 (b)(4)(b).

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

C. COMPLIANCE RESULTS

Results in this table are automatically calculated from data input and calculations in Tables F through J. Note: If any cell on this table says "COMPLIES with Exceptional Conditions" refer to Table D. Exceptional Conditions for guidance or use applicable Table referenced below.

01	02	03	04	05	06				
Service Electrical Metering 130.5(a) / 160.6(a) (See Table F)	AND	Separation for Monitoring 130.5(b) / 160.6(b) (See Table G)	AND	Voltage Drop 130.5(c) / 160.6(c) (See Table H)	AND	Controlled Receptacles 130.5(d) / 160.6(d) (See Table I)	AND	Electric Ready 160.9 (See Table J)	Compliance Results
Yes	AND	Yes	AND	Yes	AND	Yes	AND	Yes	COMPLIES

D. EXCEPTIONAL CONDITIONS

This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

F. SERVICE ELECTRICAL METERING

This section does not apply to this project.

G. SEPARATION OF ELECTRICAL CIRCUITS FOR ENERGY MONITORING

This section does not apply to this project.

H. VOLTAGE DROP

This table includes entirely new or complete replacement electrical power distribution systems, or alterations that add, modify or replace both feeders and branch circuits to demonstrate compliance with 130.5(c) / 160.6(c). For alterations, only the altered circuits must demonstrate compliance per 141.0(b)(2)(iv) / 180.2(b)(4)(iv).

01	02	03	04	05
Electrical Service Designation/Description	Combined Voltage Drop on Installed Feeder/Branch Circuit Conductors Compliance Method	Location of Voltage Drop Calculations ¹	Sheet Number for Voltage Drop Calculations in Construction Documents	Field Inspector
				Pass Fail

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Electrical Power Distribution

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-ELC-E

This document is used to demonstrate compliance with mandatory requirements in 130.5, for electrical systems in newly constructed nonresidential and hotel/motel occupancies and 160.5 and 160.5.1 for electrical systems in newly constructed multifamily occupancies. Additions and alterations to electrical systems in nonresidential and hotel/motel occupancies will also use this document to demonstrate compliance per 141.0(a) or 141.0(b)(2) for alterations. For multifamily addition or alterations compliance will be documented per 180.1(a) or 180.2 (b)(4)(b).

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

H. VOLTAGE DROP

Main	<input checked="" type="checkbox"/>	Voltage drop less than 3%	<input type="checkbox"/>	Permitted by CA Elec Code (Exception to 130.5(c)) ¹	Attached	<input type="checkbox"/>	<input type="checkbox"/>
------	-------------------------------------	---------------------------	--------------------------	--	----------	--------------------------	--------------------------

FOOTNOTES: If "Permitted by CA Elec Code" is selected under Compliance Method above, please indicate where the exception applies in the space provided below.

1 FOOTNOTES: Voltage drop calculations may be attached to the permit application outside the construction documents if allowed by the Authority Having Jurisdiction. Select "attached" if applicable. If calculations will be the responsibility of the installing contractor, select "Contractor Responsible".

I. CIRCUIT CONTROLS FOR 120-VOLT RECEPTACLES AND CONTROLLED RECEPTACLES

This section does not apply to this project.

J. ELECTRIC READY BUILDINGS

This section does not apply to this project.

K. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION

Form/Title

NRCC-ELC-E - Must be submitted for all buildings

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Electrical Power Distribution

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-ELC-E

This document is used to demonstrate compliance with mandatory requirements in 130.5, for electrical systems in newly constructed nonresidential and hotel/motel occupancies and 160.5 and 160.5.1 for electrical systems in newly constructed multifamily occupancies. Additions and alterations to electrical systems in nonresidential and hotel/motel occupancies will also use this document to demonstrate compliance per 141.0(a) or 141.0(b)(2) for alterations. For multifamily addition or alterations compliance will be documented per 180.1(a) or 180.2 (b)(4)(b).

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name: Mohammad Nohayli

Signature Date: 2023-06-25

Address: 726 Foxbrough

City/State/Zip: Pleasanton CA94566

Documentation Author Signature: Mohammad Nohayli

Signature Date: 2023-06-25

Address: 726 Foxbrough

City/State/Zip: Pleasanton CA 94566

RESPONSIBLE PERSON'S DECLARATION STATEMENT

I certify the following under penalty of perjury, under the laws of the State of California:

- The information provided on this Certificate of Compliance is true and correct.
- I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer).
- The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design described on this Certificate of Compliance conform to the requirements of This 24, Part 1 and Part 6 of the California Code of Regulations.
- The building design features and performance specifications, materials, components, and manufactured devices for the building design or system design described on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.
- I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the documentation the builder provides to the building owner at occupancy.

Responsible Designer Name: Syed P. Alam

Signature Date: 2023-06-25

Address: 726 Foxbrough

City/State/Zip: Pleasanton CA 94566

Responsible Designer Signature: Syed P. Alam

Signature Date: 2023-06-25

Address: 726 Foxbrough

City/State/Zip: Pleasanton CA 94566

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

A. GENERAL INFORMATION

01	Project Location (city)	Union City	04	Total Conditioned Floor Area (ft²)	7,407	
02	Climate Zone	3	05	Total Unconditioned Floor Area (ft²)	0	
03	Occupancy Types Within Project (select all that apply):	06			# of Stories (Habitable Above Grade)	1
Convention Center • Office • Support Areas • All Other Occupancies						

B. PROJECT SCOPE

This table includes any lighting systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.6 / 170.2(c) or 141.0(b)(2) / 180.2(b)(4) for alterations.

01	02	03	04	05
Scope of Work	Conditioned Spaces	Unconditioned Spaces		
My Project Consists of (check all that apply):	Calculation Method	Area (ft²)	Calculation Method	Area (ft²)
<input type="checkbox"/> New Lighting System				
<input type="checkbox"/> New Lighting System - Parking Garage				
<input checked="" type="checkbox"/> Altered Lighting System	Area Category Method	7407	Area Category Method	0
Total Area of Work (ft²)		7407		

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

C. COMPLIANCE RESULTS

If any cell on this table says "DOES NOT COMPLY" or "COMPLIES with Exceptional Conditions" refer to Table D. for guidance.

Allowed Lighting Power per 140.6(b) / 170.2(c) (Watts)					Adjusted Lighting Power per 140.6(a) / 170.2(a) (Watts)					Compliance Results
01	02	03	04	05	06	07	08	09		
Lighting in conditioned and unconditioned spaces must not be combined for compliance per 140.6(b) / 170.2(c).	Complete Building 140.6(c)(1)	Area Category 140.6(c)(2) / 170.2(a)(4) (W)	Area Category Additional 140.6(c)(3) / 170.2(a)(4)(b) (+)	Tailored 140.6(c)(3) / 170.2(a)(4)(b) (+)	Total Allowed (Watts)	Total Designed (Watts)	Total Adjusted (+) (Watts) Includes Adjustments	05 must be >= 08 140.6 / 170.2(a)		
(See Table J) (See Table J) (See Table J) (See Table J)	5,165.5	0			5,166	2,456	0	2456	COMPLIES	
Conditioned									COMPLIES	
Unconditioned									COMPLIES	

D. EXCEPTIONAL CONDITIONS

This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

F. INDOOR LIGHTING FIXTURE SCHEDULE

This table includes all planned permanent and portable lighting other than dwelling unit / hotel / motel room lighting. Multifamily dwelling unit and hotel/motel room lighting is documented in Table F. If using Table F to document lighting in multifamily common use areas providing shared provisions for living, eating, cooking or sanitation, those luminaires are not included here.

Designed Wattage: Conditioned Spaces										
01	02	03	04	05	06	07	08	09	10	
Name or Item Tag	Complete Luminaire Description	Modular (Track) Fixture	Small Aperture & Other Change ¹	Watts per luminaire ²	How is Wattage determined	Total Number of Luminaires	Excluded per 140.6(a)(1) / 170.2(a)(2)(c)	Design Watts	Field Inspector	
L1	L1 - 2 x 4 Feet Surface Mount	No	NA	20	Mfg. Spec	116	No	2,320	<input type="checkbox"/>	<input type="checkbox"/>
L2	L2 - 12" Square Light	No	NA	4	No	136	No	136	<input type="checkbox"/>	<input type="checkbox"/>
Total Designed Watts: CONDITIONED SPACES						2,456				

FOOTNOTES: Design Watts for small aperture and solar changing luminaires which qualify per 140.6(a)(4) / 170.2(a)(2)(d) is adjusted to be 75% /80% of their rated wattage. Table F automatically makes this adjustment; the permit applicant should enter full rated wattage in column 05.

2: A highly housing jurisdiction may ask for Luminaire cut sheets to confirm wattage used for compliance per 130.6(c) / 160.5(b). Wattage used must be the maximum rated for the luminaire, not the lamp.

G. MODULAR LIGHTING SYSTEMS

This section does not apply to this project.

H. INDOOR LIGHTING CONTROLS (Not including PAFs)

This table includes lighting controls for conditioned and unconditioned spaces.

Building Level Controls		
01	02	03
Mandatory Demand Response 130.12(c)	Shut-off controls 130.1(c) / 160.5(b)(4)(c)	Field Inspector
Required >= 4,000W subject to multilevel	Whole Building Auto Time Switch	Pass Fail

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

H. INDOOR LIGHTING CONTROLS (Not including PAFs)

Area Level Controls

04	05	06	07	08	09	10	11	12		
Area Description	Complete Building or Area Category Primary Function Area	Manual Area Controls 130.1(a) / 160.5(b)(4)(A)	Multi-Level Controls 130.1(b) / 160.5(b)(4)(B)	Shut-Off Controls 130.1(c) // 160.5(b)(4)(C)	Primary/Daylighting 130.1(d) / 160.5(b)(4)(D)	Secondary Daylighting Systems 140.6(a)(1) / 160.5(b)(4)(E)	Interlocked Systems 140.6(a)(2) / 170.2(a)(2)(A)	Field Inspector		
		Pass	Pass	Pass	Pass	Pass	Pass	Pass Fail		
Multipurpose Room	Convention, Conference, Multipurpose and Meeting Center	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	Included	General	Included	No	<input type="checkbox"/>	<input type="checkbox"/>
Director Room	Office (>250 square feet)	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Corridor	Corridor	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: Rim < 24" Glazing 24" Glazing	NA: Rim < 24" Glazing 24" Glazing	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Restrooms	Restroom	Readily Accessible	NA: Restrooms	Occupancy Sensor	NA: Rim < 24" Glazing 24" Glazing	NA: Rim < 24" Glazing 24" Glazing	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Physical Therapy	Hospital - Physical Therapy	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Social Work	Office (<=250 square feet)	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Quiet Room	Office (<=250 square feet)	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Open Hall	Convention, Conference, Multipurpose and Meeting Center	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	Included	Included	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Partry	Restroom	Readily Accessible	NA: General Ltg <= 0.5W/SF	See Building Level	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Nursing	Hospital - Nursery	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: Licensed Healthcare	NA: Rim < 24" Glazing 24" Glazing	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Office Manager Room	Office (<=250 square feet)	Readily Accessible	NA: General Ltg <= 0.5W/SF	Occupancy Sensor	NA: General Ltg < 120W	NA: General Ltg < 120W	No	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

H. INDOOR LIGHTING CONTROLS (Not including PAFs)

Utility Room	Electrical Mechanical Telephone Room	Readily Accessible	NA: Enclosed area <100SF	Occupancy Sensor	NA: Rim < 24" Glazing 24" Glazing	NA: Rim < 24" Glazing 24" Glazing	No	<input type="checkbox"/>	<input type="checkbox"/>
							13		
Plan Sheet Showing Daylight Zones:									

I. LIGHTING POWER ALLOWANCE: COMPLETE BUILDING OR AREA CATEGORY METHODS

Each area complying using the Complete Building or Area Category Methods per 140.6(b) are included in this table. Column 06 indicates if additional lighting power allowances per 140.6(c) or adjustments per 140.6(d) are being used.

01	02	03	04	05	06
Area Description	Complete Building or Area Category Primary Function Area	Allowed Wattage (W/ft²)	Area (ft²)	Allowed Wattage (Watts)	Additional Allowance / Adjustment
Multipurpose Room	Convention, Conference, Multipurpose and Meeting Center	0.75	388	291	No
Director Room	Office (>250 square feet)	0.65	178	116.7	No
Corridor	Main Entry Lobby	0.7	200	140	No
Restrooms	Restroom	0.65	770	500.5	No
Physical Therapy	Hospital - Physical Therapy	0.75	597	447.8	No
Social Work	Office (<=250 square feet)	0.6	341	204.6	No
Quiet Room	Office (<=250 square feet)	0.65	150	97.5	No
Open Hall 01	Main Entry Lobby	0.7	1,129	790.3	No
Open Hall 02	Main Entry Lobby	0.7	1,500	1,050	No
Open Hall 03	Main Entry Lobby	0.7	1,210	847	No
Partry	Restroom	0.65	362	245.3	No
Nursing	Hospital - Nurse Station	0.85	384	326.4	No
Office Manager Room	Office (<=250 square feet)	0.65	153	99.4	No
Utility Room	Electrical Mechanical Telephone Room	0.4	35	14	No
TOTALS:			7,407	5,165.5	See Tables L, or P for detail

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2023.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

J. ADDITIONAL ALLOWANCE: AREA CATEGORY METHOD QUALIFYING LIGHTING SYSTEM

This section does not apply to this project.

K. TAILORED METHOD GENERAL LIGHTING POWER ALLOWANCE

This section does not apply to this project.

L. ADDITIONAL LIGHTING ALLOWANCE: TAILORED WALL DISPLAY

This section does not apply to this project.

M. ADDITIONAL LIGHTING ALLOWANCE: TAILORED FLOOR AND TASK LIGHTING

This section does not apply to this project.

N. ADDITIONAL LIGHTING ALLOWANCE: TAILORED DECORATIVE / SPECIAL EFFECTS

This section does not apply to this project.

O. ADDITIONAL LIGHTING ALLOWANCE: TAILORED VERY VALUABLE MERCHANDISE

This section does not apply to this project.

P. POWER ADJUSTMENT: LIGHTING CREDIT (POWER ADJUSTMENT FACTOR (PAF))

This section does not apply to this project.

Q. RATED POWER REDUCTION COMPLIANCE FOR ONE-FOR-ONE ALTERATIONS

This section does not apply to this project.

Registration Number:

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2023.0.000

Report Generated: 2023-06-25 13:50:23

Compliance ID: EnergyPro-50207-0623-0586

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Indoor Lighting

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-LTI-E

This document is used to demonstrate compliance with requirements in 130.9, 130.12(c), 130.2, 130.1, 140.6 and 141.0(b)(2) for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(c) and 180.2(b)(4) for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities.

Project Name: Adult Day Care

Report Page: 4 Union Square

Date Prepared: 6/25/2023

R. 80% LIGHTING POWER FOR ALL ALTERATIONS - CONTROLS EXCEPTIONS

This section does not apply to this project.

S. DAYLIGHT DESIGN POWER ADJUSTMENT FACTOR (PAF)

This section does not apply to this project.

T. DWELLING UNIT LIGHTING

This section does not apply to this project.

U. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION

Form/Title

NRCC-LTI-E - Must be submitted for all buildings

V. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE

Form/Title

NRCC-LTI-Q2-A - Must be submitted for occupancy sensors and automatic time switch controls.

NRCC-LTI-Q3-A - Must be submitted for automatic daylight controls.

NRCC-LTI-Q4-A - Must be submitted for demand responsive lighting

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 1 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

A. GENERAL INFORMATION

01	Project Location (city)	Union City	04	Total Conditioned Floor Area	7407
02	Climate Zone	3	05	Total Unconditioned Floor Area	0
03	Occupancy Types Within Project:		06	# of Stories (Habitable Above Grade)	1
■ Convention Center ■ Office ■ Support Areas ■ All Other Occupancies					

B. PROJECT SCOPE

This table includes mechanical systems or components that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, 170.2(b) or 141.0(b)2 and 180.2(b)2 for alterations.

01	02	03
Air System(s)	Water System Components	Dry System Components
<input checked="" type="checkbox"/> Heating Air System	<input type="checkbox"/> Water Economizer	<input type="checkbox"/> Air Economizer
<input checked="" type="checkbox"/> Cooling Air System	<input type="checkbox"/> Pumps	<input type="checkbox"/> Electric Resistance Heat
Mechanical Controls	System Piping	Fan Systems
<input checked="" type="checkbox"/> Mechanical Controls (existing to remain, altered or new)	<input type="checkbox"/> Cooling Towers	<input type="checkbox"/> Ductwork (existing to remain, altered or new)
	<input type="checkbox"/> Chillers	<input type="checkbox"/> Ventilation
	<input type="checkbox"/> Boilers	<input type="checkbox"/> Zonal Systems/ Terminal Boxes

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 2 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

C. COMPLIANCE RESULTS

Table C will indicate if the project data input into the compliance document is compliant with mechanical requirements. This table is not editable by the user. If this table says "DOES NOT COMPLY" or "COMPLIES with Exceptional Conditions" refer to Table D, or the table indicated as not compliant for guidance.

01	02	03	04	05	06	07	08	09
System Summary	Pumps	Fans/Economizers	System Controls	Ventilation	Terminal Box Controls	Distribution	Cooling Towers	Compliance Results
110.1, 110.2, 140.4, 170.2(c)	140.4(b), 170.2(c)(4)	140.4(c), 140.4(e), 170.2(c)	110.2, 120.2, 140.4(f), 170.2(c)	120.1, 160.2	140.4(c), 170.2(c)(4)	120.3, 140.4(i), 160.2, 160.3	110.2(c)(2)	
(See Table F)	(See Table G)	(See Table H)	(See Table I)	(See Table J)	(See Table K)	(See Table L)	(See Table M)	
AND	AND	AND	AND	AND	AND	AND	AND	COMPLIES
Mandatory Measures Compliance (See Table Q for Details)								
COMPLIES								

D. EXCEPTIONAL CONDITIONS

This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

01	02	03	04	05	06
----	----	----	----	----	----

E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

01	02	03	04	05	06
----	----	----	----	----	----

F. HVAC SYSTEM SUMMARY (DRY & WET SYSTEMS)

Space Conditioning System Information

01	02	03	04	05	06
System Name	Quantity	System Serving	System Status	Space Type	Utilizing Recovered Heat

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 3 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

G. PUMPS

This section does not apply to this project.

01	02	03	04	05	06	07	08	09	10	11
Name or Item Tag	Equipment Category per Tables 110.2, 140.4(i)(2) and 170.2(c)(3a)	Equipment Type per Tables 110.2 and 170.2(c)	Smallest Size Available ¹ 140.4(a)(4) & 170.2(c)(1)	Equipment Sizing per Mechanical Schedule (fBtu/h)	Heating Output ^{2,3} Per Design (fBtu/h)	Cooling Output ^{2,3} Per Design (fBtu/h)	Load Calculations ^{4,4} Total Heating Load (fBtu/h)	Total Sensible Cooling Load (fBtu/h)		

¹FOOTNOTES: Equipment shall be the smallest size, within the available options of the desired equipment line, necessary to meet the design heating and cooling loads of the building per 140.4(a) and 170.2(c)(1). Healthcare facilities are excepted.
²It is common practice to show rated output capacity on the equipment schedule. Sensible cooling output shown from specification sheet tables.
³If equipment is heating only, leave cooling output and load blank. If equipment is cooling only, leave heating output and load blank.
⁴Authority Having Jurisdiction may ask for load calculations used for compliance per 140.4(b) and 170.2(c).

H. FAN SYSTEMS & AIR ECONOMIZERS

This section does not apply to this project.

01	02	03	04	05	06
----	----	----	----	----	----

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 4 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

I. SYSTEM CONTROLS

This table is used to demonstrate compliance with mandatory controls in 110.2 and 120.2 and prescriptive controls in 140.4(f) and (h), 170.2(c)(4D) 170.2(c)(4L) or requirements in 141.0(b)2E, 180.2(b)2 for altered space conditioning systems.

01	02	03	04	05	06	07	08	09
System Name	System Zoning	Conditioned Floor Area Being Served (ft ²)	Thermostats 110.2(b) & (c), 120.2(a) 160.3(a)(2A) or 141.0(b)2E & 180.2(b)2	Shut-Off Control 120.2(g) & 160.3(a)(2)	Isolation Zone Controls 110.12, 120.2(b) & 160.3(a)(3)	Demand Response 110.12, 120.2(b) & 160.3(a)(3)	Supply Air Temp. Reset 140.4(f) & 170.2(c)(4D)	Window Interlocks per 140.4(f) & 170.2(c)(4D)

J. VENTILATION AND INDOOR AIR QUALITY

This table is used to demonstrate compliance with mandatory ventilation requirements in 120.1, 120.2(c)(3B) 140.4(f) and 140.4(c)2. For all nonresidential and hotel/motel and 141.0(b)2E, 160.2, 160.3(c)(3B), 170.2(c)(4D), 170.2(c)(4D) for high-rise residential occupancies. For alterations, only ventilation systems being altered within the scope of the permit application need to be documented in this table. In lieu of this table, the required outdoor ventilation rates and airflow may be shown on the plans or the calculations can be presented in a spreadsheet.

01	<input type="checkbox"/>	Check the box if the project is showing ventilation calculations on the plans, or attaching the calculations instead of completing this table.
02	<input checked="" type="checkbox"/>	Check this box if the project included Nonresidential, Hotel/Motel Spaces or Multifamily Common Use Spaces
03	<input type="checkbox"/>	Check the box if the project is using natural ventilation in any nonresidential or hotel/motel spaces to meet required ventilation rates per 120.1(c)(2).

Nonresidential and Hotel/ Motel Multifamily Common Use Ventilation Systems

04	05	06	07
System Name	RTU-01	System Design OA CFM Airflow ² 383	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided
08	09	10	11
		12	13
		14	15
		16	17

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 5 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

J. VENTILATION AND INDOOR AIR QUALITY

Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)
Multipurpose Room	Assembly, multiuse 388	194	0
Director Room	Office space 178	26.7	0
Corridor	Lobbies 200	100	0
17	Total System Required Min OA CFM	321	18
04	05	06	07
System Name	RTU-02	System Design OA CFM Airflow ² 385	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided
08	09	10	11
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)
Open Hall 01	Lobbies 1129	564.5	0
17	Total System Required Min OA CFM	564	18
04	05	06	07
System Name	RTU-03	System Design OA CFM Airflow ² 544	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided
08	09	10	11
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)
Physical Therapy	All others 597	89.6	0
Social Work	Office space 341	51.2	0
Quiet Room	Office space 150	22.5	0
17	Total System Required Min OA CFM	163	18

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 6 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

J. VENTILATION AND INDOOR AIR QUALITY

Restrooms	Toilet, public 770	0	0	0	0	DCV	NA: Not required per 120.1(d)(3)
17	Total System Required Min OA CFM	0	18	Ventilation for this System Complex?			Yes
04	05	06	07				
System Name	RTU-03	System Design OA CFM Airflow ² 544	System Design Transfer Air CFM 0	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided			
08	09	10	11				
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)				
Physical Therapy	All others 597	89.6	0				
Social Work	Office space 341	51.2	0				
Quiet Room	Office space 150	22.5	0				
17	Total System Required Min OA CFM	163	18				

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 7 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

J. VENTILATION AND INDOOR AIR QUALITY

System Name	RTU-04	System Design OA CFM Airflow ² 564	System Design Transfer Air CFM 0	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided		
08	09	10	11			
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)			
Open Hall 01	Lobbies 1129	564.5	0			
17	Total System Required Min OA CFM	564	18			
04	05	06	07			
System Name	RTU-05	System Design OA CFM Airflow ² 750	System Design Transfer Air CFM 0	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided		
08	09	10	11			
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)			
Open Hall 02	Lobbies 1500	750	0			
17	Total System Required Min OA CFM	750	18			

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 8 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

J. VENTILATION AND INDOOR AIR QUALITY

System Name	RTU-06	System Design OA CFM Airflow ² 1077	System Design Transfer Air CFM 0	Air Filtration per 120.1(c) 141.0(b)2 and 160.2(c)(2)1 ¹ Provided		
08	09	10	11			
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(c)(3) ¹ & 160.2(c)(3)	Exh. Vent per 120.1(c)(4) & 160.2(c)(4)	DCV or Sensor Controls per 120.1(d)(3), 120.1(d)(5), and 120.1(e)(3) ¹ 160.2(c)(5D) 160.2(c)(5E) 160.2(c)(5D)			
Open Hall 03	Lobbies 1200	600	0			
Pantry	Toilet, private 382	0	0			
Nursing	All others 384	57.6	0			
Office Manager Room	Office space 153	23	0			
Utility Room	All others 35	0	0			

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 9 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

J. VENTILATION AND INDOOR AIR QUALITY

17	Total System Required Min OA CFM	681	18	Ventilation for this System Complex?			Yes
¹ FOOTNOTES: System CFM should include both mechanical and natural ventilation for the zone/system ² Air filtration requirements apply to the following three system types per 120.1(c)(1A): space conditioning systems utilizing ducts to supply air to occupiable space; supply-only ventilation systems providing outside air to occupiable space; supply side of balanced ventilation systems including heat recovery and energy recovery ventilation systems providing outside air to occupiable space. ³ Uniform Mechanical Code may have more stringent ventilation requirements; the most stringent code requirement takes precedence. ⁴ See Standards Tables 120.1-A and 120.1-B. ⁵ For lecture halls with fixed seating, the expected number of occupants shall be determined in accordance with the California Building Code. ⁶ 120.2(c)(3) requires systems serving rooms that are required by 130.1(c) to have lighting occupancy sensing controls to also have occupancy sensing zone controls for ventilation. Examples of spaces which require lighting occupancy sensors include offices 250ft ² or smaller; multipurpose rooms less than 1,000ft ² ; classrooms, conference rooms, restrooms, aisles and open areas in warehouses, library book stock aisles, corridors, stairwells, parking garages, and loading and unloading zones, unless excepted by 130.1(c). ⁷ Multifamily Dwelling Unit Ventilation Systems <input type="checkbox"/> Check the box if the system is using continuous ventilation to meet the ventilation requirements per 160.2(b)(2)4mb2							
19	20	21	22	23	24	25	26
Space Name or Item Tag	Mechanical Ventilation Required per 120.1(b) & 160.2(b)2	Required Min OA CFM ¹	Supply Air CFM ²	Exhaust CFM ³	Local Exhaust	Air Filtration per 120.1(c) & 160.2(b)1	
28	Is this a balanced system?						29

¹FOOTNOTES: Uniform Mechanical Code may have more stringent ventilation requirements; the most stringent code requirement takes precedence.
²Kitchen range hood will be vented per 140.2.8.1.2 to outdoors model (y) and per 140.2.8.1.2 for ASHRAE.
³Air filtration requirements apply to the following three system types per 120.1(c)(1A): space conditioning systems utilizing ducts to supply air to occupiable space; supply-only ventilation systems providing outside air to occupiable space; supply side of balanced ventilation systems including heat recovery and energy recovery ventilation systems providing outside air to occupiable space.
⁴A balanced ventilation system provides ventilation airflow to each dwelling unit at a rate equal to or greater than the required minimum rate, but not more than twenty percent.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Mechanical Systems

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-MCH-4

This document is used to demonstrate compliance for mechanical systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.4, or 141.0(b)2 for alterations.

Project Name:

Adult Day Care

Report Page:

(Page 10 of 11)

Project Address:

4 Union Square

Date Prepared:

6/25/2023

K. TERMINAL BOX CONTROLS

This section does not apply to this project.

01	02	03	04	05	06
----	----	----	----	----	----

L. DISTRIBUTION (DUCTWORK AND PIPING)

This section does not apply to this project.

01	02	03	04	05	06
----	----	----	----	----	----

M. COOLING TOWERS

This section does not apply to this project.

01	02	03	04	05	06
----	----	----	----	----	----

N. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION

Form/Title

01	02	03	04	05	06
----	----	----	----	----	----

O. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE

There are no NRCA forms required for this project.

01	02	03	04	05	06
----	----	----	----	----	----

P. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION

There are no NRCA forms required for this project.

01	02	03	04	05	06
----	----	----	----	----	----

Q. MANDATORY MEASURES DOCUMENTATION LOCATION

This table is used to indicate where mandatory measures are documented in the plan set or construction documentation.

01	02	03	04	05	06
Compliance with Mandatory Measures documented through MCH	Yes	Plan sheet or construction document location			
Mandatory Measures Note Block		M-Sheets			

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000
Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0587
Report Generated: 2023-06-25 13:50:23

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name: Mohammad Nohayli	Documentation Author Signature: Mohammad Nohayli
Signature Date: 2023.06.25	Signature Date: 2023.06.25
Company: Innovelec, Inc	

STATE OF CALIFORNIA

Domestic Water Heating System

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-PUB-2

Project Name: Adult Day CareReport Page: (Page 2 of 6)

Project Address: 4 Union SquareDate Prepared: 6/25/2023

E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

F. DOMESTIC HOT WATER EQUIPMENT

This table is used to demonstrate compliance with mandatory equipment requirements in 110.1 and 110.3. Compliance with prescriptive requirements in 140.5(c) / 170.2(d) must also be demonstrated and with 141.0 / 180.1, 180.2 for addition and alteration scopes.

Equipment Schedule: Water Heating Efficiency and Standby Loss

03		04		05		06		
System Name	Standard Gas 50 gal or Less	Exception to 140.5(c) / 170.2(d)(3)		Gas Service Water Heating System >= 1MMBtu/h	Capacity-weighted Average Efficiency %	Efficiency Unit	Designed Standby Loss	Maximum Standby Loss
07	08	09	10	11	12	13	14	15
Name or Item Tag	Equipment Type	Volume (gal)	Rated Input Capacity (Btu/h)	Max GPM/ First Hour Rating (FHR)	Rated Efficiency	Minimum Efficiency Required		
Standard Gas 50 gal or Less	Commercial Gas Instantaneous Water Heater	34	200,000	FHR >=75	0.8	0.81	UEF	

FOOTNOTE: In systems >= 1MMBtu/h with multiple units, gas water heaters with input capacity > 100,000 Btu/h may meet 90% E1 requirements via an input capacity-weighted average.

Water Heating Equipment All Occupancies

	Yes	No	Not Applicable	Requirement
18	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Unfired storage tank insulation shall have Internal + External >=R-16 OR External >=R-3.5. Label required per 110.3(c)(3)
19	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	New state buildings 60% of energy for service water heating from site solar energy or recovered energy per 110.3(c)(5)
20	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Isolation valves for instantaneous water heater with input rating <=8 MBTUH or < 3 KW has been specified per 110.3(c)(6)
21	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	School buildings < 25,000 ft² and < 4 stories must install a heat pump water heating system per 140.5(a)(1). Water heating systems serving an individual bathroom space may be an instantaneous electric water heater.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000 Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0585

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Domestic Water Heating System

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-PUB-3

Project Name: Adult Day CareReport Page: (Page 3 of 6)

Project Address: 4 Union SquareDate Prepared: 6/25/2023

G. DOMESTIC HOT WATER DISTRIBUTION SYSTEM

This table is used to demonstrate compliance for nonresidential occupancies with distribution requirements in 120.3 and 140.5. For multifamily and hotel/motel occupancies, compliance is demonstrated with requirements 110.3(c), 160.4, 170.2(d).

Mandatory Pipe Insulation All Occupancies

13	<input type="checkbox"/>	For systems serving dwelling units, pipe insulation must meet the minimum insulation requirements in Table 160.4-A (see below) except: <ul style="list-style-type: none">Piping that penetrates framing members shall not be required to have pipe insulation for the distance of the framing penetration. Piping that penetrates metal framing shall use grommets, plugs, wrapping or other insulating material to assure that no contact is made with the metal framing. Insulation shall abut securely against all framing members.Piping installed in interior or exterior walls shall not be required to have pipe insulation if all of the requirements are met for compliance with Quality Insulation Installation (QII) as specified in the Reference Residential Appendix RA3.5.Piping surrounded with a minimum of 1 inch of wall insulation, 2 inches of crawlspace insulation, or 4 inches of attic insulation, shall not be required to have pipe insulation.
14	<input checked="" type="checkbox"/>	For systems serving nonresidential spaces, pipe insulation for the following applications is specified to comply with Table 120.3-A (see below) per 120.3: <ul style="list-style-type: none">Recirculating system piping, including supply and return piping of the water heater.The first 8 ft of hot and cold outlet piping, including between storage tank and heat trap, for a nonrecirculating storage system.Pipes that are externally heated. Insulation shall be protected from damage, including that due to sunlight, moisture, equipment maintenance, and wind. Insulation exposed to weather shall be installed with a cover suitable for outdoor service per 120.3(b) / 160.4(f). Pipe insulation buried below grade must be installed in a water proof and non-erodable casing or sleeve.

TABLE 120.3-A / 160.4-A PIPE INSULATION THICKNESS

Fluid Temperature Range (°F)	Conductivity Range (Btu-in per hour per ft² per °F)	Insulation Mean Rating Temp (°F)	Nominal Pipe Diameter (in)			
			< 1	1 to < 1.5	1.5 to < 4	1.5 to < 4 Multifamily & Hotel/Motel
105-140	0.22 - 0.28	100	Minimum Insulation Required			
			3.0 in or R-7.7	1.5 in or R-12.5	1.5 in or R-11	2.0 in or R-16

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000 Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0585

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Domestic Water Heating System

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-PUB-4

Project Name: Adult Day CareReport Page: (Page 4 of 6)

Project Address: 4 Union SquareDate Prepared: 6/25/2023

H. DOMESTIC HOT WATER CONTROLS

This table is used to demonstrate compliance with control requirements in 110.3 for all occupancies. For multifamily residential and hotel/motel occupancies, compliance is also demonstrated with requirements in 160.4(e) / 170.2(d).

	Yes	No	Not Applicable	Requirement
01	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Construction documents require manufacturer certification that service water heating systems are equipped with automatic temperature controls capable of adjusting temperature settings per 110.3(a).
02	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Systems with capacity > 167,000 BTUH equipped with outlet temperature controls per 110.3(c)(1) unless covered by California Plumbing Code 612.0.
03	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Controls for circulating pumps or electrical heat trace systems are capable of automatically turning off the system per 110.3(c)(2) unless systems serve healthcare facility.
04	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	For recirculation systems serving multiple dwelling units, design includes automatic pump controls per 170.2(d) or 180.1(b)(3) for additions.
05	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	For recirculation systems serving individual dwelling units, design includes manual on/off controls as specified in Reference Appendix RA4.4.9 per 170.2(d).
06	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Combustion air positive shut-off shall be provided per 160.4(3) for all newly installed commercial boilers as follows: <ul style="list-style-type: none">Boilers with input capacity >= 2.5 MMBtu/h, in which the boiler is designed to operate with a nonpositive vent static pressure.Boilers where gas flow serves two or more boilers with a total combined input capacity per stack of 2.5 MMBtu/h.
07	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Boiler combustion air fans with motor >= 10 hp shall meet one of the following: <ul style="list-style-type: none">The fan motor shall be driven by a variable speed drive ORThe fan motor shall include controls that limit the fan motor demand to <=30% of the total design wattage at 50% of the design air volume.
08	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Newly installed boilers with an input capacity (d.gtu) / 5MMBtu/h and a steady state full-load combustion efficiency < 90% shall maintain excess (stack gas) oxygen concentrations <= 1% by volume on a dry basis over firing rates of 25-100%. Combustion air volume shall be controlled with respect to firing rate or flue gas oxygen concentration. Use of a common gas and combustion air control linkage or jack-in fit is prohibited.

Form/Title

NRCC-PUB-E - Must be submitted for all buildings

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000 Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0585

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Domestic Water Heating System

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-PUB-5

Project Name: Adult Day CareReport Page: (Page 5 of 6)

Project Address: 4 Union SquareDate Prepared: 6/25/2023

I. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE

There are no forms required for this project.

K. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION

There are no forms required for this project.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000 Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0585

Report Generated: 2023-06-25 13:50:23

STATE OF CALIFORNIA

Domestic Water Heating System

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

NRCC-PUB-6

Project Name: Adult Day CareReport Page: (Page 6 of 6)

Project Address: 4 Union SquareDate Prepared: 6/25/2023

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name: Mohammad Nohayli

Signature Date: 7/20/23 06:25

Company: InnoDec, Inc.

Address: 728 Foothrough

City/State/Zip: Pleasanton CA 94566

Phone: (925) 885-1111

RESPONSIBLE PERSON'S DECLARATION STATEMENT

I certify the following under penalty of perjury, under the laws of the State of California:

1. The information provided on this Certificate of Compliance is true and correct.

2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer).

3. The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1, and Part 6 of the California Code of Regulations.

4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.

5. I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable inspections. I understand that a completed signed copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy.

Responsible Designer Name: Syed P. Alam

Signature Date: 2023-06-25

Company: InnoDec, Inc.

Address: 728 Foothrough

City/State/Zip: Pleasanton CA 94566

Phone: (925) 885-1111

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time: Report Version: 2022.0.000 Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-50207-0623-0585

Report Generated: 2023-06-25 13:50:23

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

T24-3

PROJ. NO.	PROJ. ENGR.	SCALE @ 24x36"
		NTS


DRAWING NO. REV.

T 2 4 . 3


HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-01	Floor Area 766
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Output (Btuh/sqft) 47.0	
Cooling System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Total Output (Tons) 3.0	
Total Output (Btuh/sqft) 47.0	
Total Output (sqft/Ton) 255.3	
Air System	
CFM per System 1,200	
Airflow (cfm) 1,200	
Airflow (cfm/sqft) 1.57	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 31.9%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)




COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)




HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-02	Floor Area 770
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Output (Btuh/sqft) 46.8	
Cooling System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Total Output (Tons) 3.0	
Total Output (Btuh/sqft) 46.8	
Total Output (sqft/Ton) 256.7	
Air System	
CFM per System 1,200	
Airflow (cfm) 1,200	
Airflow (cfm/sqft) 1.56	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 32.1%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)




COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)




HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-03	Floor Area 1,088
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 80,000	
Total Output (Btuh) 80,000	
Output (Btuh/sqft) 73.5	
Cooling System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Total Output (Tons) 3.0	
Total Output (Btuh/sqft) 33.1	
Total Output (sqft/Ton) 362.7	
Air System	
CFM per System 1,200	
Airflow (cfm) 1,200	
Airflow (cfm/sqft) 1.10	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 45.3%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)




COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)




HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-04	Floor Area 1,129
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 80,000	
Total Output (Btuh) 80,000	
Output (Btuh/sqft) 70.9	
Cooling System	
Output per System 36,000	
Total Output (Btuh) 36,000	
Total Output (Tons) 3.0	
Total Output (Btuh/sqft) 31.9	
Total Output (sqft/Ton) 376.3	
Air System	
CFM per System 1,200	
Airflow (cfm) 1,200	
Airflow (cfm/sqft) 1.06	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 47.0%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)




COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)




HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-05	Floor Area 1,500
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 100,000	
Total Output (Btuh) 100,000	
Output (Btuh/sqft) 66.7	
Cooling System	
Output per System 60,000	
Total Output (Btuh) 60,000	
Total Output (Tons) 5.0	
Total Output (Btuh/sqft) 40.0	
Total Output (sqft/Ton) 300.0	
Air System	
CFM per System 2,000	
Airflow (cfm) 2,000	
Airflow (cfm/sqft) 1.33	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 37.5%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)




COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)




HVAC SYSTEM HEATING AND COOLING LOADS SUMMARY

Project Name Adult Day Care	Date 6/25/2023
System Name RTU-06	Floor Area 2,154
ENGINEERING CHECKS	SYSTEM LOAD
Number of Systems 1	
Heating System	
Output per System 200,000	
Total Output (Btuh) 200,000	
Output (Btuh/sqft) 92.9	
Cooling System	
Output per System 120,000	
Total Output (Btuh) 120,000	
Total Output (Tons) 10.0	
Total Output (Btuh/sqft) 55.7	
Total Output (sqft/Ton) 215.4	
Air System	
CFM per System 4,000	
Airflow (cfm) 4,000	
Airflow (cfm/sqft) 1.86	
Airflow (cfm/Ton) 400.0	
Outside Air (%) 26.9%	
Outside Air (cfm/sqft) 0.50	
Note: values above given at ARI conditions	

HEATING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Heating Peak)



COOLING SYSTEM PSYCHROMETRICS (Airstream Temperatures at Time of Cooling Peak)



CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:

T24-4

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"

NTS

DRAWING NO. REV.

T 2 4 . 4

