

PROVIDE EQUIPMENT INDICATED ON THE DRAWINGS, AND AS REQUIRED FOR A COMPLETE FUNCTIONING SYSTEM.

WARRANTY: PROVIDE LABOR AND MATERIALS TO REPAIR OR REPLACE DEFECTIVE PARTS AND MATERIALS AS REQUIRED FOR ONE YEAR AFTER SUBSTANTIAL COMPLETION OR OWNER ACCEPTANCE OF THE COMPLETED PROJECT. PROVIDE A SEPARATE LINE ITEM DEDUCT AMOUNT ON THE PROPOSAL FORM TO DELETE WARRANTY SERVICE, AT THE OWNER'S OPTION.

PROVIDE OPERATION MANUALS, MAINTENANCE MANUALS AND SCHEMATICS FOR ALL MECHANICAL EQUIPMENT INSTALLED.

COORDINATION: COORDINATE WITH THE WORK OF OTHER SECTIONS, EQUIPMENT FURNISHED BY OTHERS, REQUIREMENTS OF THE OWNER, AND WITH THE CONSTRAINTS OF THE EXISTING CONDITIONS OF THE PROJECT SITE.

ROOF PENETRATIONS SHALL COMPLY WITH "SMACNA" AND "NRCA" STANDARDS, AND WITH THE REQUIREMENTS OF THE EXISTING ROOFING WARRANTY, IF APPLICABLE. DO NOT PERFORM ROOFING PENETRATIONS IN A MANNER WHICH WOULD VOID OR OTHERWISE LIMIT THE EXISTING ROOF WARRANTY.

DUCT DIMENSIONS: UNLESS OTHERWISE NOTED, DUCT DIMENSIONS ON THE DRAWINGS ARE INSIDE CLEAR DIMENSIONS.

SHEET METAL DUCTWORK: PROVIDE SHEET METAL DUCTWORK FABRICATED AND INSTALLED IN ACCORDANCE WITH ASHRAE AND SMACNA STANDARDS, FOR 1" W.G., PRESSURE CLASS, SEAL CLASS "A". SHEET METAL SHALL BE GALVANIZED SHEET STEEL OF LOCM FORMING QUALITY, WITH G90 ZINC COATING. SHEET STEEL SHALL COMPLY WITH ASTM A653 STANDARD SPECIFICATION FOR STEEL SHEET METAL, ZINC COATED (GALVANIZED) OR ZINC-IRON ALLOY-COATED (GALVANNEALED) BY THE HOT DIP PROCESS. SHEET METAL SHALL BE GALVANIZED OR GALVANNEALED EQUIVALENT FOR SHEET, METALLIC-COATED BY THE HOT DIP PROCESS. ALL ANGLE IRON USED FOR SUPPORT SHALL BE GALVANIZED. CONNECTIONS TO WALLS OR FLOOR SHALL BE AIR TIGHT WITH ANGLE IRON AND CAULKING. SEALS AT ALL DUCT SEAMS, TRANSVERSE AND LONGITUDINAL, AIR TIGHT. PROVIDE TURNING VANES AT ALL 90° ELBOWS.

TRAPEZE DUCT HANGERS: PROVIDE MINIMUM 1" X 2" X 1" X 18 GAUGE CHANNELS WITH MINIMUM 1" X 18 GAUGE STRAPS TO STRUCTURAL SUPPORT.

ROUND SHEET METAL DUCT: PROVIDE SPIRAL SEAM (ALL SIZES) OR SNAP LOCK (DUCT SIZES UP TO 10") GALVANIZED STEEL COMPLYING WITH SMACNA STANDARDS. SPIRAL SEAM DUCTWORK SHALL HAVE SMACNA SEAM TYPE RL-1.

FIBER GLASS DUCT BOARD IS AN ACCEPTABLE ALTERNATIVE IF APPROVED BY OWNER AND THE LOCAL BUILDING CODE OFFICIAL. PRODUCT AND INSTALLATION MUST MEET NAIMA STANDARDS AND OTHER APPLICABLE CODES AND REGULATIONS.

EXPOSED DUCTWORK: EXPOSED DUCTWORK SHALL BE CLEANED OF DEBRIS AND OIL, THEN WIPED DOWN WITH VINEGAR OR OTHER SURFACE PREPARING CHEMICAL TO PREPARE DUCT FOR PAINT.

DUCT SEALANT: PROVIDE POLYMERIC RUBBER TYPE SEALANT FOR USE ON BOTH INTERIOR LOCATED DUCTWORK AND DUCTWORK EXPOSED TO OUTDOOR CONDITIONS. SEALER SHALL HAVE HIGH BONDING STRENGTH FOR SURE, FIRST TIME SEALING OF JOINTS IN LOW, MEDIUM, AND HIGH PRESSURE DUCT SYSTEMS. SEALER SHALL BE HIGH IN SOLID CONTENT. PROVIDE A TWO PART TAPE SEALING SYSTEM, CONSISTING OF WOVEN FIBER TAPE IMPREGNATED WITH A GYPSUM MINERAL COMPOUND, AND A MODIFIED ACRYLIC/SILICONE ACTIVATOR THAT REACTS EXOTHERMICALLY WITH THE TAPE. TWO PART TAPE SEALING SYSTEM MUST BE RATED FOR BOTH INDOOR AND OUTDOOR APPLICATION. TAPE SHALL NOT CONTAIN ASBESTOS.

DUCT INSULATION: MATERIAL FOR SUPPLY AND RETURN AIR DUCT ABOVE CEILING INSIDE THE BUILDING SHALL HAVE THE EQUIVALENT THERMAL RESISTANCE OF MINIMUM R-6. THE REQUIRED R VALUES ARE FOR INSTALLED INSULATION WITH 25% COMPRESSION AT THE CORNERS. PROVIDE PINS AND WASHERS IN ACCORDANCE WITH SMACNA REQUIREMENTS AND AS REQUIRED TO PREVENT INSULATION FROM SAGGING. PROVIDE ADEQUATE INSULATION AT THE SUPPLY AIR DIFFUSERS TO PREVENT CONDENSATION.

FLEXIBLE DUCT - UL #181 LISTED, CLASS 1, AND CONTAIN A 0.1 PERM RATED POLYETHYLENE INNER LINER. WITH R-8 FIBERGLASS INSULATION. FLEXIBLE DUCT SHALL BE SECURED TO RIGID STRUCTURE METAL COLLARS AND AIR DIFFUSERS WITH NYLON TIE RODS. COLLARS SHALL WEAR GEAR STRAPS. SEAL ALL CONNECTIONS AND JOINTS AIRTIGHT. SUPPORT FLEXIBLE DUCTS FROM THE BUILDINGS STRUCTURE WITH MINIMUM 1" WIDE, 16 GAUGE, GALVANIZED STEEL STRAP AT MAXIMUM 4'-0" CENTERS. PROVIDE 4" WIDE SHEET METAL SADDLES AT EACH SUPPORT FOR EACH STRAP. SAG OF FLEXIBLE DUCT BETWEEN HANGERS SHALL NOT EXCEED 1/2" PER FOOT. SAG OF SUPPORT SPACING, RADIUS FOR TURNS OF FLEXIBLE DUCT SHALL BE MINIMUM 10'-0" IN LENGTH. SHALL BE THE SAME SIZE AS THE DUCT. SHALL NOT EXCEED 10'-0" IN LENGTH AND SHALL BE THE SAME SIZE AS THE DIFFUSER NECK CONNECTION.

ROUND VOLUME DAMPERS: PROVIDE MINIMUM 20 GAUGE GALVANIZED STEEL FRAME AND BLADES, MINIMUM 3/8" SQUARE STEEL AXLE, MOLDED SYNTHETIC BEARINGS, WITH LOCKING POSITION REGULATOR. REGULATOR SHALL BE POSITIONED WITH SHEET METAL BRACKET BEYOND DUCT COVERING, WHERE POSITIONING REGULATOR IS NOT ACCESSIBLE, PROVIDE COUPLING AND EXTENSION ROD WITH REGULATOR FOR CEILING OR WALL INSTALLATION, AS REQUIRED.

RECTANGULAR VOLUME DAMPERS: PROVIDE MINIMUM 16 GAUGE GALVANIZED STEEL CHANNEL FRAME. 16 GAUGE GALVANIZED STEEL BLADES, MINIMUM 1/2" HEXAGONAL AXLE, BOLDED SYNTHETIC BEARINGS, WITH 3/8" SQUARE PLATED STEEL CONTROL SHAFT. LINKAGES SHALL BE CONCEALED IN THE FRAME. OPERATING SHAFT SHALL EXTEND BEYOND FRAME AND DUCT TO A LOCKING QUADRANT WITH ADJUSTABLE LEVER. MAXIMUM BLADE WIDTH SHALL NOT EXCEED 6".

THE INTENT OF THESE PLANS AND SPECIFICATIONS IS TO INCLUDE ALL LABOR, EQUIPMENT, MATERIALS, AND SERVICES NECESSARY TO FURNISH, INSTALL, TEST, AND ADJUST A COMPLETE WORKABLE HEATING, VENTILATION, AND AIR CONDITIONING SYSTEM AS SHOWN, PRESCRIBED, OR REASONABLY IMPLIED BUT NOT LIMITED TO THAT EXPLICITLY INDICATED IN THE CONTRACT DOCUMENTS, BUT NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE INTENT THEREOF.

2. THE ENTIRE INSTALLATION SHALL CONFORM TO THE APPLICABLE CODES AND REGULATIONS REQUIRED BY AUTHORITIES HAVING JURISDICTION. IN THE EVENT OF CONFLICT BETWEEN SPECIFICATIONS, CODES, AND REGULATIONS, THE MORE RESTRICTIVE SHALL APPLY.

3. DRAWINGS FOR HVAC WORK ARE DIAGRAMATIC SHOWING THE GENERAL LOCATION, TYPE, LAYOUT, AND EQUIPMENT REQUIRED. THE DRAWINGS SHALL NOT BE SCALED FOR EXACT MEASUREMENT, REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSIONS. PROVIDE ALL DUCTWORK, MATERIALS, CONNECTIONS, ACCESSORIES, FITTINGS, OFFSETS, TRANSITIONS, DAMPERS AS REQUIRED FOR A COMPLETE WORKABLE SYSTEM.

4. ALL EQUIPMENT SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND APPROVED LISTING. ALL EQUIPMENT, PIPING AND SUPPORTS SHALL BE RESTRAINED IN ACCORDANCE WITH THE LATEST EDITION OF THE "GUIDELINES FOR SEISMIC RESTRAINTS OF MECHANICAL SYSTEMS AND PLUMBING PIPING SYSTEMS" BY THE SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION (SMACNA). ALL EQUIPMENT SHALL BE ANCHORED TO RESIST THE LATERAL FORCE REQUIREMENTS OF CHAPTER 16 OF THE 2012 INTERNATIONAL BUILDING CODE.

5. COORDINATE THE INSTALLATION OF THE HVAC SYSTEM WITH ALL OTHER TRADES PRIOR TO FABRICATION OR INSTALLATION. COORDINATE THE LOCATIONS OF PENETRATIONS AND FINAL LOCATION OF ALL EQUIPMENT WITH THE GENERAL CONTRACTOR. PROVIDE EQUIPMENT WEIGHTS, EQUIPMENT DIMENSIONS, PLATFORM SIZES & LOCATIONS, CURB SIZES & LOCATIONS, CONCRETE PAD SIZES AND LOCATIONS AS REQUIRED. COORDINATE LOCATIONS OF GAS & CONDENSATE LINES WITH PLUMBING CONTRACTOR. COORDINATE LOCATIONS OF POWER, DISCONNECTS, AND CONTROL CONDUIT WITH THE ELECTRICAL CONTRACTOR. COORDINATE LOCATIONS OF ALL DIFFUSERS, REGISTERS, AND GRILLES WITH ARCHITECTURAL PLANS, ELECTRICAL LIGHTING PLANS AND ARCHITECTURAL ELEVATIONS.

6. DETAILS FOR EQUIPMENT PADS, PLATFORMS, AND FLASHINGS SHALL BE AS INDICATED BY THE ARCHITECTURAL/STRUCTURAL/CIVIL DRAWINGS, UNLESS NOTED OTHERWISE.

7. ALL EQUIPMENT, DUCTS, PIPING, SUPPORTS, AND OTHER DEVICES OUTSIDE OF THE BUILDING OR EXPOSED TO WEATHER, SHALL BE COMPLETELY WEATHER-PROOFED.

8. OUTSIDE AIR INTAKES SHALL BE AT LEAST 10 FT. AWAY OR 3 FT. BELOW ANY VENT OR EXHAUST DISCHARGE.

9. ALL DUCT SIZES ARE CLEAR INSIDE DIMENSIONS. DUCTWORK SHALL BE CONSTRUCTED, ERECTED, INSULATED AND TESTED IN ACCORDANCE CHAPTER 6 OF THE 2012 INTERNATIONAL MECHANICAL CODE.

10. ALL EXHAUST FANS SHALL BE EQUIPED WITH A BACK DRAFT DAMPER.

11. DUCT AND AIR TRANSFER PENETRATIONS THRU BUILDING ASSEMBLIES REQUIRING PROTECTION SHALL BE PROTECTED WITH FIRE DAMPERS, SMOKE DAMPERS, COMBINATION SMOKE/FIRE DAMPERS AND CEILING RADIATION DAMPERS IN ACCORDANCE WITH SECTION 607 OF THE INTERNATIONAL MECHANICAL CODE. DUCTS NOT REQUIRING DAMPERS SHALL COMPLY WITH SECTION 714 & 717 OF THE 2019 CALIFORNIA BUILDING CODE.

12. INSTALL SMOKE DETECTORS AND PROVIDE FOR SMOKE DETECTION AND AUTOMATIC SHUT-OFF OF ALL AIR HANDLING EQUIPMENT IN ACCORDANCE WITH SECTION 606 OF THE 2019 CALIFORNIA MECHANICAL CODE.

13. UNLESS NOTED OTHERWISE, ALL LINE VOLTAGE WIRING, CONDUIT, FINAL CONNECTIONS, DISCONNECTS, STARTERS, AND OVER CURRENT PROTECTION DEVICES SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL CONTRACTOR AS INDICATED ON THESE MECHANICAL DRAWINGS AND/OR ELECTRICAL DRAWINGS AND/OR ELECTRICAL SECTION OF THE SPECIFICATIONS.

14. INSTALL ALL LOW VOLTAGE HVAC CONTROL WIRE AND DEVICES PER PLAN. ALL WIRE SHALL BE IN CONDUIT PROVIDED AND INSTALLED BY THE ELECTRICAL CONTRACTOR UNLESS NOTED OTHERWISE.

15. PROVIDE OWNER WITH THREE COPIES OF A CERTIFIED AIR BALANCE REPORT PREPARED IN BY A THIRD PARTY CERTIFIED BY THE AABC OR NEBB. TEST, ADJUST AND BALANCE THE HVAC SYSTEM IN ACCORDANCE WITH AABC OR NEBB PROCEDURES. PROVIDE START-UP/TEST REPORTS FOR ALL AIR HANDLING EQUIPMENT, FANS, AND REFRIGERATION EQUIPMENT. TEST AND VERIFY PROPER OPERATION OF ALL MAKE-UP AIR/EXHAUST AIR INTERLOCK SYSTEMS AND THEIR SEQUENCES OF OPERATION. BALANCE ALL AIR FLOWS WITHIN 5% OF DESIGN VALUES. PERMANENTLY MARK BALANCE POSITION OF ALL REGULATING DEVICES.

16. PROVIDE OWNER WITH THREE SETS OF AS-BUILT PLANS AND OPERATIONS AND MAINTENANCE MANUALS. CLEARLY IDENTIFY ALL EQUIPMENT WITH PERMANENT PLASTIC OR METAL LABELS/TAGS (PEN MARKING NOT ACCEPTABLE).

17. PROVIDE ONE YEAR WARRANTY ON ALL LABOR, PARTS AND MATERIALS

18. ANY CHANGE OR DEVIATION FROM THESE PLANS OR SPECIFICATIONS SHALL REQUIRE THE WRITTEN APPROVAL OF THE ENGINEER PRIOR TO COMMENCEMENT OF SUCH WORK.

19.0

a) DUCTS FOR DEMAND CONTROLLED VENTILATION SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE FAN MANUFACTURER'S INSTALLATION INSTRUCTIONS, THE PROVISIONS ASHRAE 62.2, TABLE 5.3, OR THE AIRFLOW SHALL BE MEASURED AS REQUIRED BY AND IN COMPLIANCE WITH ASHRAE 62.2, 5.4.

b) DUCTS FOR KITCHEN COOKTOPS OR RANGES SHALL BE SHOWN OF METAL WITH A SMOOTH INTERIOR. [CMC 504.3].

1) IDENTIFY THE DETAILED REQUIREMENTS OF CMC DRYER DUCTS. SPECIFY--

a) DUCTS FOR DOMESTIC CLOTHES DRYERS SHALL BE INSTALLED IN ACCORDANCE WITH CMC 504.0.

b) DUCTS FOR DOMESTIC CLOTHES DRYERS SHALL BE RIGID METALLIC DUCTS WITH A MINIMUM MILL THICKNESS OF 16 (0.016-INCH), SHALL HAVE A MINIMUM 4-INCH DIAMETER AND A SMOOTH INTERIOR. THE COMBINED HORIZONTAL AND VERTICAL LENGTH OF THE DUCTS OF THE DUCTS SHALL BE 14-FEET, WHICH SHALL BE REDUCED BY 2-FEET FOR EVERY 90-DEGREE ELBOW IN EXCESS OF TWO ELBOWS.

c) LISTED CLOTHES DRYER TRANSITION DUCTS NOT MORE THAN 6-FEET IN LENGTH SHALL BE PERMITTED TO CONNECT THE DRYER TO THE EXHAUST DUCTS AS LONG AS THEY ARE NOT CONCEALED WITHIN CONSTRUCTION, AND THEY ARE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS.

		DUCT WORK (WIDTHxDEPTH)
		LINED DUCT WORK (WIDTHxDEPTH DIMENSIONS ARE FOR I.D.)
		SUPPLY DUCT, SECTION
		RETURN DUCT, SECTION
		EXHAUST DUCT, SECTION
		RISE OR DROP IN DIRECTION OF AIR FLOW
	FLEX. CONN.	FLEXIBLE CONNECTION
		DUCT TRANSITION, ROUND AND RECTANGULAR
		SPLITTER DAMPER
		EXTRACTOR AT BRANCH DUCT
		TURNING VANES
		FLEXIBLE DUCT
		SINGLE LINE DUCT WORK
	AVD	AUTOMATIC VOLUME DAMPER
	MVD	MANUAL VOLUME DAMPER
	BDD	BACKDRAFT DAMPER
	MD	MODULATING DAMPER
	AFD	AUTOMATIC FIRE DAMPER
	AD	ACCESS DOOR
	SD	SUPPLY DIFFUSER
	RR	RETURN REGISTER
	ER	EXHAUST REGISTER
	SWR	SIDE WALL SUPPLY REGISTER
	SWE	SIDE WALL RETURN OR EXHAUST
	LD	LINEAR DIFFUSER
	DL	DOOR LOUVER
	UC	UNDER CUT DOOR
	VAV	VARIABLE AIR VOLUME
		THERMOSTAT
		DUCT SMOKE DETECTOR
	T/B	TO BELOW
	F/B	FROM BELOW
	T/A	TO ABOVE
	F/A	FROM ABOVE

1. ALL CONTRACTORS (GENERAL CONTRACTOR AND SUB-CONTRACTORS) BIDDING THIS PROJECT ARE REQUIRED TO VISIT THE JOB SITE AND VERIFY THE EXISTING CONDITIONS PRIOR TO SUBMITTING THEIR BID. CONTRACTORS ARE TO CAREFULLY REVIEW ALL CONSTRUCTION DOCUMENTS AND NOTE ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED AT THE JOB SITE PRIOR TO SUBMISSION OF ANY BID. THE BUILDING OWNER REPRESENTATIVE LISTED BELOW MAY BE CONTACTED FOR ACCESS TO THE JOB SITE.
2. CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO: GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.
3. ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED SHALL BE BROUGHT TO THE ATTENTION, IN WRITING, TO THE ARCHITECT AND/OR ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
4. NO WORK SHALL BE DONE ON ANY PART OF THE BUILDING BEYOND THE POINT INDICATED IN EACH SUCCESSIVE INSPECTION WITHOUT FIRST OBTAINING THE WRITTEN APPROVAL OF THE CODE OFFICIAL. NO CONSTRUCTION SHALL BE CONCEALED WITHOUT BEING INSPECTED AND APPROVED.

REV. NO.	DESCRIPTION	DATE	BY


PROJECT:

**TITLE:**  
**MECH LIST OF SYMBOLS**  
**AND GENERAL NOTES**


PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: NTS
-----------	-------------	-----------------------

DRAWING NO.	REV.
-------------	------

M 0.0



FIRST FLOOR PLAN



ROOF PLAN

GENERAL NOTES:

- MECHANICAL CONTRACTOR TO COORDINATE ROUTING AND LOCATION OF MECHANICAL COMPONENTS AND EQUIPMENT WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS PRIOR TO PERFORMING WORK.
- CONTRACTOR TO CUT AND PATCH AS REQUIRED TO PERFORM THE WORK.
- ACCESS DOORS ARE REQUIRED FOR ANY COMPONENT REQUIRING ACCESS ABOVE HARD LID CEILINGS. COORDINATE SIZE, LOCATION AND FINISH WITH ARCHITECT PRIOR TO PERFORMING WORK.
- REFER TO THE DIAGRAMS THAT APPLY TO THIS SHEET WHICH PROVIDE GENERAL GUIDANCE FOR INSTALLATION THOUGH NOT ALL COMPONENTS AND ACCESSORIES MAY BE SHOWN.
- PRIOR TO INSTALLATION, CONFIRM SPECIFIC LOCATION FOR ALL THERMOSTATS / SENSORS WITH ARCHITECT. MOUNT AT 48" A.F.F. OR IN ACCORDANCE WITH ADA REQUIREMENTS. PROVIDE LOCKING COVERS.
- COORDINATE AND CONFIRM BORDER, FRAME, FINISH, AND LOCATION WITH ARCHITECT PRIOR TO ORDERING.
- ANY PENETRATIONS THROUGH WALL STUDS, FLOOR JOISTS, OR ROOF TO BE IN ACCORDANCE WITH THE LATEST ADOPTED BUILDING CODE.
- DUCT DIMENSIONS SHOWN ARE CLEAR INSIDE DIMENSIONS.
- CONTRACTOR TO CONFIRM ADEQUATE RETURN AIR PATH BACK TO MAIN AIR HANDLING UNIT.

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS, UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
MECH. FIRST FLOOR,  
E.S & VENTIL. CALC.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: 3/16"=1'-0"
-----------	-------------	-------------------------------

DRAWING NO.

M 1 . 0

REV.



VENTILATION LOAD CALCULATION CMC 2019 TABLE 402.1							
OCCUPANCY	SF AREA	CFM/FT2	CFM	Pers.	CFM/Pers.	CFM	TOTAL CFM
101-RETAIL	1288	0.12	154.56	8	7.5	60	214.6
(E) AC-01 - TOTAL VENTILATION REQUIRED (CFM)							215

AC-01 (E) / BRYANT - 580JP08A125A2A0AAA CAN OPERATE UP TO 25% OA FROM THE SUPPLY.  
THE NOMINAL AC-01 (E) FLOW RATE IS 2400 CFM  
MAX. OA THE RTU CAN DELIVER IS = 2400 x 0.25 = 600 CFM  
600 CFM > 215CFM (req. OA)

VENTILATION LOAD CALCULATION CMC 2019 TABLE 402.1							
OCCUPANCY	SF AREA	CFM/FT2	CFM	Pers.	CFM/Pers.	CFM	TOTAL CFM
104-OFFICE	106	0.06	6.36	4	5	20	26.36
105-OFFICE	121	0.06	7.26	5	5	25	32.26
107-STORAGE CANNABIS	390	0.12	46.8	1	5	5	51.8
108-OFFICE	167	0.06	10.02	6	5	30	40.02
109-B-OFFICE	268	0.06	16.08	6	5	30	46.08
109-OFFICE	140	0.06	8.4	4	5	20	28.4
110-OFFICE	83	0.06	4.98	3	5	15	19.98
111-RECEIVING	87	0.06	5.22	2	5	10	15.22
112-IT EQUIPMENT	51	0.06	3.06	1	5	5	8.06
(E) AC-02 - TOTAL VENTILATION REQUIRED (CFM)							268.2

AC-02 (E) / BRYANT - 580JP08A125A2A0AAA CAN OPERATE UP TO 25% OA FROM THE SUPPLY FLOW.  
THE NOMINAL AC-02 (E) FLOW RATE IS 2400 CFM  
MAX. OA THE RTU CAN DELIVER IS = 24000 x 0.25 = 600 CFM  
600 CFM > 270 CFM (req. OA)

ROOF TOP UNIT SCHEDULE									
TAG	MANUFACTURER	MODEL	TOTAL COOLING (TONS)	HEATING UNIT INP./OUTP.(MBH)	AIRFLOW @0.5"W.G. (CFM)	EER	FLA	MAXIMUM FUSE SIZE (A)	VOLT/PH/HZ
AC-01 (E)	BRYANT	48HJD006	7.5	125.0 / 103.0	2400	11.0	46	60	208/230-3-60
AC-02 (E)	BRYANT	48HJD006	7.5	125.0 / 103.0	2400	11.0	46	60	208/230-3-60

\* RTU SHALL HAVE A FIELD INSTALLED OPERATION TO INCLUDE 25% OA FROM THE SUPPLY AIR FLOW.  
\* RTU-01 WILL BE EQUIPPED WITH ECONOMIZER FOR VENTILATION.

EXHAUST FAN SCHEDULE (EXISTING)	
TAG	EF-01, 02
LOCATION	RESTROOM#1
DESIGN SUPPLY VOLUME (CFM)	50
DESIGN PRESSURE DROP (INCH W.C.)	0.10
ELECTRICAL (V / PH / HZ)	115 / 1 / 60
POWER (BHP)	0.01

CEC 2019 -TABLE 150.2-A: DUCT INSULATION R-VALUE			
Climate Zone	1 through 10, 12 & 13	11, 14 through 16	
Duct R-Value	R-6	R-8	

ALL DUCTS INSULATION SHALL NOT BE LESS R6 |  
CEC2019-150.2A  
ALL DUCTS ARE GALVANIZED STEEL G90.

CMC 2019 - 603.4.1 Length Limitation:

[Not permitted for OSHPD 1, 1R, 2, 3, 4 & 5] Factory-made flexible air ducts and connectors shall be not more than 5 feet (1524 mm) in length and shall not be used in lieu of rigid elbows or fittings. Flexible air ducts shall be permitted to be used as an elbow at a terminal device.

CMC 2019 - 605.1 Smoke Dampers:

Smoke dampers shall comply with UL 555S, and shall be installed in accordance with the manufacturer's installation instructions where required by the California Building Code or California Residential Code.

CMC 2019 -603.10.1 Duct Leakage Tests:

Ductwork shall be leak-tested in accordance with the SMACNA HVAC Air Duct Leakage Test Manual. Representative sections totaling not less than 10 percent of the total installed duct area shall be tested. Where the tested 10 percent fail to comply with the requirements of this section, then 40 percent of the total installed duct area shall be tested. Where the tested 40 percent fail to comply with the requirements of this section, then 100 percent of the total installed duct area shall be tested. Sections shall be selected by the building owner or designated representative of the building owner. Positive pressure leakage testing shall be permitted for negative pressure ductwork. The permitted duct leakage shall be not more than the following:

Lmax = CLx(P)<sup>0.65</sup> (Equation 603.10.1)  
Where:  
Lmax = maximum permitted leakage, (ft3/min)/100 square feet [0.0001 (m3/s)/m2] duct surface area.  
CL = six, duct leakage class, (ft3/min)/100 square feet [0.0001 (m3/s)/m2] duct surface area at 1 inch water column (0.2 kPa).  
P = test pressure, which shall be equal to the design duct pressure class rating, inch water column (kPa).

310.1 Condensate Disposal

Condensate from air washers, air-cooling coils, condensing appliances, and the overflow from evaporative coolers and similar water-supplied equipment or similar air-conditioning equipment shall be collected and discharged to an approved plumbing fixture or disposal area. Where discharged into the drainage system, equipment shall drain by means of an indirect waste pipe. The waste pipe shall have a slope of not less than 1/8 inch per foot (10.4 mm/m) or 1 percent slope and shall be of approved corrosion-resistant material not smaller than the outlet size in accordance with Section 310.3 or Section 310.4 for air-cooling coils or condensing appliances, respectively. Condensate or wastewater shall not drain over a public way.

Fire and smoke dampers shall be provided with an approved means of access large enough to allow inspection and maintenance of the damper and its operating parts. The access shall not affect the integrity of the fire-resistance-rated assembly. The access openings shall not reduce the fire-resistance rating of the assembly. CMC 605.5

CPC 2016 - TABLE 814.3: MINIMUM CONDENSATE PIPE SIZE EQUIPMENT CAPACITY IN TONS OF REFRIGERATION		MINIMUM CONDENSATE PIPE (Inches)
Up to 20		3/4"
21 - 40		1"
41 - 90		1-1/4"
91 - 125		1-1/2"
126 - 250		2"

502.2.2 Product Conveying Ducts:

Ducts conveying explosive or flammable vapors, fumes, or dusts shall terminate not less than 30 feet (9144 mm) from a property line, 10 feet (3048 mm) from openings into the building, 6 feet (1829 mm) from exterior walls or roofs, 30 feet (9144 mm) from combustible walls or openings into the building that are in the direction of the exhaust discharge, and 10 feet (3048 mm) above adjoining grade.

Other product-conveying outlets shall terminate not less than 10 feet (3048 mm) from a property line, 3 feet (914 mm) from exterior walls or roofs, 10 feet (3048 mm) from openings into the building, and 10 feet (3048 mm) above adjoining grade.

Installed filters shall be clearly labeled by the manufacturer indicating the MERV 13 rating.  
CMC 2019 - 401.2.1

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
**MECH. E.S, VENTILATION  
AND CODE ANALYSIS.**

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: NTS
-----------	-------------	-----------------------

DRAWING NO.	REV.
-------------	------

M 2 . 0

Air System Information

Air System Name  
Equipment Class  
Air System Type

AC-1  
PKG ROOF  
SZCAV

Number of zones  
Floor Area  
Location

1  
1288.0 ft²  
Sacramento Metro, California

Sizing Calculation Information

Calculation Months  
Sizing Data

Jan to Dec  
Calculated

Zone CFM Sizing  
Space CFM Sizing

Sum of space airflow rates  
Individual peak space loads

Central Cooling Coil Sizing Data	
Total coil load	3.2 Tons
Total coil load	38.6 MBH
Sensible coil load	37.3 MBH
Coil CFM at Aug 1500	1419 CFM
Max block CFM	1419 CFM
Sum of peak zone CFM	1419 CFM
Sensible heat ratio	0.966
CFM/Ton	441.3
RT/Ton	460.5
BTU/(hr·ft²)	30.0
Water flow @ 10.0 °F rise	N/A
Load occurs at	Aug 1500
OA DB / WB	100.0 / 69.0 °F
Entering DB / WB	78.5 / 62.3 °F
Leaving DB / WB	54.1 / 52.6 °F
Coil ADP	51.4 °F
Bypass Factor	0.100
Resulting RH	45 %
Design supply temp.	58.0 °F
Zone T-stat Check	1 of 1 OK
Max zone temperature deviation	0.0 °F

Central Heating Coil Sizing Data	
Max coil load	15.6 MBH
Coil CFM at Des Htg	1419 CFM
Max coil CFM	1419 CFM
Water flow @ 20.0 °F drop	N/A
Load occurs at	Des Htg
BTU/(hr·ft²)	12.1
Entl. DB / Lvg DB	63.7 / 73.9 °F

Supply Fan Sizing Data	
Actual max CFM	1419 CFM
Standard CFM	1418 CFM
Actual max CFM/ft²	1.10 CFM/ft²
Fan motor BHP	2.00 BHP
Fan motor kW	1.66 kW

Outdoor Ventilation Air Data	
Design airflow CFM	215 CFM
CFM/ft²	0.17 CFM/ft²
CFM/person	29.80 CFM/person

Air System Information

Air System Name  
Equipment Class  
Air System Type

AC-2  
PKG ROOF  
SZCAV

Number of zones  
Floor Area  
Location

1  
1413.0 ft²  
Sacramento Metro, California

Sizing Calculation Information

Calculation Months  
Sizing Data

Jan to Dec  
Calculated

Zone CFM Sizing  
Space CFM Sizing

Sum of space airflow rates  
Individual peak space loads

Central Cooling Coil Sizing Data	
Total 1500	3.9 Tons
Total coil load	46.8 MBH
Sensible coil load	42.2 MBH
Coil CFM at Aug 1500	1678 CFM
Max block CFM	1678 CFM
Sum of peak zone CFM	1678 CFM
Sensible heat ratio	0.901
CFM/Ton	430.7
RT/Ton	382.6
BTU/(hr·ft²)	33.1
Water flow @ 10.0 °F rise	N/A
Load occurs at	Aug 1500
OA DB / WB	100.0 / 69.0 °F
Entering DB / WB	78.7 / 63.6 °F
Leaving DB / WB	55.4 / 54.0 °F
Coil ADP	52.8 °F
Bypass Factor	0.100
Resulting RH	50 %
Design supply temp.	58.0 °F
Zone T-stat Check	1 of 1 OK
Max zone temperature deviation	0.0 °F

Central Heating Coil Sizing Data	
Max coil load	15.4 MBH
Coil CFM at Des Htg	1678 CFM
Max coil CFM	1678 CFM
Water flow @ 20.0 °F drop	N/A
Load occurs at	Des Htg
BTU/(hr·ft²)	10.9
Entl. DB / Lvg DB	63.4 / 71.9 °F

Supply Fan Sizing Data	
Actual max CFM	1678 CFM
Standard CFM	1677 CFM
Actual max CFM/ft²	1.19 CFM/ft²
Fan motor BHP	2.00 BHP
Fan motor kW	1.66 kW

Outdoor Ventilation Air Data	
Design airflow CFM	268 CFM
CFM/ft²	0.19 CFM/ft²
CFM/person	9.31 CFM/person

Air System Information

Air System Name  
Equipment Class  
Air System Type

AC-1  
PKG ROOF  
SZCAV

Number of zones  
Floor Area  
Location

1  
1288.0 ft²  
Sacramento Metro, California

Sizing Calculation Information

Calculation Months  
Sizing Data

Jan to Dec  
Calculated

Zone CFM Sizing  
Space CFM Sizing

Sum of space airflow rates  
Individual peak space loads

Zone Terminal Sizing Data								
Zone Name	Design Supply Airflow (CFM)	Minimum Supply Airflow (CFM)	Zone CFM/ft²	Reheat Coil Load (MBH)	Reheat Coil Water gpm @ 20.0 °F	Zone Htg Unit Coil Load (MBH)	Zone Htg Unit Water gpm @ 20.0 °F	Mixing Box Fan Airflow (CFM)
Zone 1	1376	1376	1.07	0.0	-	0.0	-	0

Zone Peak Sensible Loads				
Zone Name	Zone Cooling Sensible (MBH)	Time of Peak Sensible Cooling Load	Zone Heating Load (MBH)	Zone Floor Area (ft²)
Zone 1	23.8	Sep 1400	12.6	1288.0

Space Loads and Airflows

Zone Name / Space Name	Mult.	Cooling Sensible (MBH)	Time of Peak Sensible Load	Air Flow (CFM)	Heating Load (MBH)	Floor Area (ft²)	Space CFM/ft²
Zone 1							
101-RETAIL	1	23.8	Sep 1400	1376	12.6	1288.0	1.07

Air System Information

Air System Name  
Equipment Class  
Air System Type

AC-2  
PKG ROOF  
SZCAV

Number of zones  
Floor Area  
Location

1  
1413.0 ft²  
Sacramento Metro, California

Sizing Calculation Information

Calculation Months  
Sizing Data

Jan to Dec  
Calculated

Zone CFM Sizing  
Space CFM Sizing

Sum of space airflow rates  
Individual peak space loads

Zone Terminal Sizing Data								
Zone Name	Design Supply Airflow (CFM)	Minimum Supply Airflow (CFM)	Zone CFM/ft²	Reheat Coil Load (MBH)	Reheat Coil Water gpm @ 20.0 °F	Zone Htg Unit Coil Load (MBH)	Zone Htg Unit Water gpm @ 20.0 °F	Mixing Box Fan Airflow (CFM)
Zone 1	1628	1628	1.15	0.0	-	0.0	-	0

Zone Peak Sensible Loads				
Zone Name	Zone Cooling Sensible (MBH)	Time of Peak Sensible Cooling Load	Zone Heating Load (MBH)	Zone Floor Area (ft²)
Zone 1	26.8	Sep 1400	10.8	1413.0

Space Loads and Airflows							
Zone Name / Space Name	Mult.	Cooling Sensible (MBH)	Time of Peak Sensible Load	Air Flow (CFM)	Heating Load (MBH)	Floor Area (ft²)	Space CFM/ft²
Zone 1							
104-OFFICE	1	1.8	Jun 1500	102	0.4	106.0	0.96
105-OFFICE	1	2.0	Jun 1500	118	0.2	121.0	0.98
107-STORAGE CANNABIS	1	4.2	Jun 1500	245	2.1	390.0	0.63
108-OFFICE	1	2.7	Jun 1400	154	0.2	167.0	0.92
108-B-OFFICE	1	6.2	Oct 1400	473	3.8	268.0	1.76
109-OFFICE	1	6.0	Oct 1400	348	2.8	140.0	2.47
110-OFFICE	1	1.4	Jun 1500	78	0.3	83.0	0.94
111-RECEIVING	1	1.3	Jun 1500	74	0.5	87.0	0.85
112-IT EQUIPMENT	1	0.7	Jul 1600	38	0.5	51.0	0.75

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
MECH. LOAD  
CALCULATIONS RESULTS








PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36:
		NTS

DRAWING NO.

REV.

M 3 . 0





CLIENT:  
ADDRESS:

**CONFIDENTIALITY STATEMENT:**  
  
ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

**NOTES:**  
1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.  
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.  
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.  
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
**MECHANICAL GENERAL DETAILS.**

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: NTS
-----------	-------------	-----------------------

DRAWING NO. <b>M 4 . 0</b>	REV.
-------------------------------	------

GENERAL ELECTRICAL NOTES	
#	DESCRIPTION
1	GENERAL CONTRACTOR SHALL VERIFY FIELD CONDITIONS BEFORE SUBMITTING BID.
2	ALL WORK SHALL BE DONE IN ACCORDANCE WITH 2019 NEC, AS AMENDED BY 2019 ELECTRICAL CODE, 2019 ENERGY CODE AND ANY ADDITIONAL STATE OR LOCAL CODES WHICH MAY APPLY.
3	GENERAL CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS, CERTIFICATES, ETC., REQUIRED.
4	GENERAL CONTRACTOR SHALL OBTAIN AND PAY FOR BOTH ROUGH AND FINAL UNDER-WRITERS OR OTHER APPROVED INSPECTION AGENCY CERTIFICATES "ELECTRICAL INSPECTION". THESE CERTIFICATES SHALL BE PRESENTED WITH REQUEST FOR FINAL PAYMENT.
5	IT IS THE INTENT OF THESE PLANS TO PROVIDE A COMPLETE OPERATING ELECTRICAL SYSTEM. THIS CONTRACTOR SHALL FURNISH AND INSTALL ALL WIRING, EQUIPMENT, MATERIAL, ETC., REQUIRED, EXCEPT WHERE SPECIFICALLY NOTED AS BEING FURNISHED BY OTHERS. SHOULD THERE BE ANY QUESTIONS CONCERNING RESPONSIBILITY, THEY SHALL BE ADDRESSED TO ARCHITECT PRIOR TO BID. NO EXTRA CHARGES WILL BE ALLOWED.
6	ELECTRICAL SERVICE SHALL BE COORDINATED WITH THE EXISTING FIELD CONDITIONS.
7	CONTRACTOR SHALL MAKE ALL FINAL CONNECTIONS TO ALL CONTROLS, OWNER-SUPPLIED EQUIPMENT, MECHANICAL AND PLUMBING EQUIPMENT AS REQUIRED.
8	REFER TO ARCHITECTURAL DRAWINGS FOR ELEVATION DETAILS. ALL FIXTURE AND DEVICE LOCATIONS SHOWN ON ARCHITECTURAL DRAWINGS SUPERSEDE THOSE SHOWN ON ELECTRICAL PLANS.
9	CIRCUIT NUMBER ON THE DRAWINGS ARE FOR IDENTIFICATION ONLY AND DO NOT INDICATE THE POSITION ON THE PANEL BOARD. CONNECT THE CIRCUITS WITH THE LIGHTEST LOADS AND THE RECEPTACLE CIRCUITS NEAR THE TOP OF THE PANEL, AND THE MORE HEAVILY LOADED CIRCUITS NEAR THE BOTTOM. BALANCE ALL CIRCUITS EVENLY BETWEEN PHASE SO THAT FEEDER WIRES CARRY APPROXIMATELY EQUAL CURRENT. ALL PHASES MUST BE BALANCED WITHIN 10% OR LESS. G.C. SHALL REBALANCE IF NECESSARY.
10	BRANCH CIRCUIT CONDUCTOR INSULATION SHALL BE COLOR CODED AND SHALL BE 600 VOLT. TYPE THHN/THWN.
11	CABLES IN HIGH TEMPERATURE AREAS SHALL HAVE INSULATION TYPE SUITABLE FOR THE TEMPERATURE. CABLES USED IN SPACES FOR ENVIRONMENTAL AIR SHALL CONFORM WITH APPLICABLE N.E.C. REQUIREMENTS.
12	ALL WIRING USED IN RETURN OR DISCHARGE AIR PLENUMS SHALL BE PLENUM RATED OR INSTALLED PER METHODS APPROVED BY THE LATEST EDITION OF THE N.E.C. FOR SUCH APPLICATION.
13	ALL WIRE AND CABLE CONDUCTORS SHALL BE COPPER WITH INSULATION RATED 600V. CONDUCTORS SIZED #10 AWG AND SMALLER SHALL BE SOLID OD STRANDED, AND CONDUCTORS SIZED LARGER THAN #10 AWG SHALL BE STRANDED WIRE.
14	BRANCH CIRCUITS FOR POWER AND LIGHTING SHALL NOT BE LESS THAN #12 AWG. OR AS NOTED. WIRES ARE TO BE SIZED FOR THE APPROPRIATE VOLTAGE DROPS. SEE WIRE SIZE SCHEDULE ON THIS SHEET.
15	ALL DATA CABLES SHALL BE CAT6, PLENUM RATED, TO BE PROVIDED BY OWNER SELECTED VENDOR. ELECTRICAL WORK SHALL BE TO PROVIDE OUTLET BOXES AND "RING AND STRING" FOR PULLING OF CABLES IN CONCEALED SPACES.
16	CONTROL WIRING SHALL NOT BE LESS THAN #14 AWG UNLESS OTHERWISE NOTED.
17	HOMERUNS SHOWN ARE SCHEMATIC. CONTRACTOR MAY ORIGINATE HOMERUNS FROM DIFFERENT LOCATIONS. ALL WIRE INCLUDING HOMERUNS SHALL BE DELINEATED ON AS-BUILT DRAWINGS.
18	ALL WIRING INSTALLED UNDER THIS CONTRACT SHALL BE TESTED FOR PROPER CONNECTIONS AND SHORT CIRCUITS PRIOR TO THE TURNING OVER OF WORK AS A COMPLETE UNIT.
19	PROVIDE ALL ELECTRICAL SYSTEM GROUNDING IN ACCORDANCE WITH N.E.C. REQUIREMENTS EVEN IF IT IS NOT SHOWN ON THE DRAWINGS. INCLUDE ADDITIONAL GROUNDING CONDUCTORS IN ALL RACEWAYS EVEN THOUGH THE DRAWINGS SHOW ONLY CIRCUIT AND/OR NEUTRALS CONDUCTORS. THE PLUMBING AND PIPING SYSTEM SHALL NOT BE USED AS A GROUND. ALL TRANSFORMER NEUTRALS SHALL BE GROUND TO BUILDING STEEL IN ACCORDANCE WITH NEC 250-70.
20	ALL CONDUITS PASSING THROUGH PARTITIONS ARE TO BE APPROPRIATELY SLEEVED AND SEALED.
21	FURNISH AND INSTALL ALL CONDUIT WITH PULL WIRES AS REQUIRED. ALL OUTLET BOXES SHALL BE STEEL, EXTRA DEEP WITH GROUNDING PIGTAILS. GROUNDING PUSH-CLIPS ARE NOT ACCEPTABLE.
22	ALL PENETRATIONS SHALL BE INSTALLED AND SEALED PER NATIONAL STATE AND LOCAL CODES
23	DO NOT MAKE ANY CHANGES OR SUBSTITUTIONS WITHOUT SPECIFIC WRITTEN APPROVAL FROM THE ARCHITECT OR ENGINEER.
24	GUARANTEE ALL WORK, MATERIAL AND EQUIPMENT FOR A PERIOD OF ONE YEAR FROM THE DATE OF APPROVAL AND FINAL ACCEPTANCE.
25	THIS DESIGN IS BASED ON INITIAL DESIGN DATA. GENERAL CONTRACTOR TO SUPPLY AND INSTALL FEEDERS, FUSES AND CIRCUIT BREAKERS TO MATCH THE NAMEPLATE RATING OF ALL EQUIPMENT. THIS SHALL BE INCLUDED IN THE INITIAL BID PROPOSAL AND NO EXTRAS SHALL BE ENTERTAINED.
26	LABEL ALL JUNCTION BOXES, OUTLETS, LIGHT SWITCH, ETC. WITH CIRCUIT NUMBER ON INTERIOR OR COVER PLATE. USE SELF-ADHESIVE "DYMO" LABEL 1/8" HIGH LETTERS.
27	GENERAL CONTRACTOR SHALL PROVIDE SEISMIC RESTRAINTS AND SUPPORTS FOR ALL FLOOR, WALL, AND CEILING MOUNTED ELECTRICAL EQUIPMENT TO RESIST EARTHQUAKE EFFECTS DETERMINED IN ACCORDANCE WITH THE BUILDING CODE.
28	THE G.C. SHALL PROVIDE ALL EQUIPMENT, MATERIALS AND LABOR TO COMPLETE ALL ELECTRICAL WORK IN A NEAT AND WORKMANLIKE MANNER AND IN ACCORDANCE WITH GOOD COMMERCIAL PRACTICE INCLUDING THE INSTALLATION OF ALL THE EQUIPMENT MATERIALS AND SYSTEMS AND THE FINAL CONNECTIONS TO THE OWNER'S EQUIPMENT AND FIXTURES AS REQUIRED BY THE OWNER. THE G.C. SHALL ALSO FURNISH TEMPORARY WIRING AND LIGHTING TO PROVIDE A MINIMUM OF 25 FC IN WORK AREAS FOR USE OF ALL THE TRADES DURING CONSTRUCTION AND THE INSTALLATION OF THE OWNERS FIXTURES. THE G.C. IS RESPONSIBLE TO REMOVE ALL TEMPORARY WIRING UPON COMPLETION OF CONSTRUCTION OF ALL TRADES.
29	THIS CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE AND INSTALL ALL SUPPLEMENTARY SUPPORT, INCLUDING SUPPORT STEEL AS REQUIRED TO HANG ALL EQUIPMENT AND LIGHTING FROM THE EXISTING STRUCTURE IN ACCORDANCE WITH THE ARCHITECTURAL/STRUCTURAL SUPPORT AND LOADING CRITERIA.
30	IT IS THE RESPONSIBILITY OF THIS CONTRACTOR TO PROVIDE FULLY DIMENSIONED COORDINATION DRAWINGS FOR ALL OF HIS RESPECTIVE WORK. THESE DRAWINGS MUST BE FULLY COORDINATED WITH ALL EXISTING CONDITIONS. ALL HVAC, PLUMBING, FIRE PROTECTION, ELECTRICAL, LIGHTING, STRUCTURAL AND ARCHITECTURAL SYSTEMS PRIOR TO PREPARING OR PREPARING MULTI-DISCIPLINE COORDINATION DRAWINGS.
31	ALL DISCONNECTING MEANS AND EQUIPMENT INDICATED ON THE DRAWING SHALL BE IDENTIFIED BY NAMEPLATE IN COMPLIANCE WITH THE NATIONAL ELECTRICAL CODE 110-22.
32	ALL WIRING FOR THE EMERGENCY LIGHTING AND EMERGENCY SYSTEMS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF THE NATIONAL ELECTRIC CODE ARTICLE 700.
33	THE WIRING METHODS AND MATERIALS INDICATED IN THE SPECIFICATIONS AND ON THE DRAWINGS SHALL BE INSTALLED AND CONNECTED IN ACCORDANCE WITH THE REQUIREMENTS OF THE NATIONAL ELECTRIC CODE ARTICLE 300.

GENERAL ELECTRICAL NOTES	
#	DESCRIPTION
33	THE WIRING METHODS AND MATERIALS INDICATED IN THE SPECIFICATIONS AND ON THE DRAWINGS SHALL BE INSTALLED AND CONNECTED IN ACCORDANCE WITH THE REQUIREMENTS OF THE NATIONAL ELECTRIC CODE ARTICLE 300.
34	THE ELECTRICAL SERVICE AND DISTRIBUTION SYSTEM AS INDICATED ON THE RISER DIAGRAM AND MATERIALS INDICATED IN THE SPECIFICATIONS SHALL BE IN COMPLIANCE WITH THE REQUIREMENTS OF THE NATIONAL ELECTRIC CODE ARTICLE 230, SERVICES.
35	ALL OVER CURRENT PROTECTION SHALL BE IN COMPLIANCE WITH THE NATIONAL ELECTRIC CODE SECTION 240, OVERCURRENT PROTECTION.
36	ALL GROUNDING REQUIREMENTS OF THE COMPLETE ELECTRICAL DISTRIBUTION SYSTEM AND AS INDICATED IN THE SPECIFICATIONS SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRIC CODE ARTICLE 250, GROUNDING AND BONDING.
37	PRIOR TO ANY REQUIRED CUTTING AND PATCHING OF CONCRETE FLOOR AND/OR CUTTING OF ROOF, CONTRACTOR SHALL COORDINATE WITH BUILDING ENGINEER.
38	FOR ALL LIGHTING FIXTURES MOUNTED IN HUNG CEILING THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL INDIVIDUAL SUPPORT AT EACH CORNER OF RECESSED LIGHTING TROFFER CONNECTED TO BUILDING STEEL ABOVE ALL CONDUIT AND MC CABLE MOUNTED ABOVE HUNG CEILING SHALL BE INDIVIDUALLY SUPPORTED IN THE SAME FASHION AS PER NEC REQUIREMENTS.
39	DO NOT SCALE FROM THESE DRAWINGS.
40	PLANS ARE PREPARED WITH REQUIRED BRANCH CIRCUITS INDICATED BY CIRCUITS NUMBERS. PROVIDE AND INSTALL ALL CONDUITS, CONDUCTORS, BOXES, MISCELLANEOUS FITTINGS, ETC. FOR A COMPLETE AND OPERABLE SYSTEM (HOME RUN SHOWN). BRANCH CIRCUIT INSTALLATION SHALL COMPLY WITH SPECIFICATIONS AND N.E.C.
41	ELECTRICAL RECEPTACLE, SWITCH AND CONTROL HEIGHTS: (CBC-1136A.1.1.) RECEPTACLE HEIGHTS: ELECTRICAL RECEPTACLE OUTLETS ON BRANCH CIRCUITS OF 30 AMPERES OR LESS AND COMMUNICATION SYSTEM RECEPTACLES SHALL BE LOCATED NO MORE THAN 48 INCHES (1219MM) MEASURED FROM THE TOP OF THE RECEPTACLE OUTLET BOX OR RECEPTACLE HOUSING NOR LESS THAN 15 INCHES (381MM) MEASURED FROM THE BOTTOM OF THE RECEPTACLE OUTLET BOX OR RECEPTACLE HOUSING TO THE LEVEL OF FINISHED FLOOR OR WORKING PLATFORM. IF THE REACH IS OVEN AN OBSTRUCTION (FOR EXAMPLE, A KITCHEN BASE CABINET) BETWEEN 20 AND 25 INCHES (508 AND 635MM) IN DEPTH, THE MAXIMUM HEIGHT MEASURED AT THE BOX IS REDUCED TO 44 INCHES (1118MM) FOR FORWARD APPROACH, OR 46 INCHES (1168MM) FOR SIDE APPROACH, PROVIDED THE OBSTRUCTION IS NO MORE THAN 24 INCHES (610MM) IN DEPTH. OBSTRUCTION SHALL NOT EXCEED MORE THAN 25 INCHES (635MM) FROM THE WALL BENEATH THE RECEPTACLE.
42	SWITCH AND CONTROL HEIGHTS: (CBC 1136A.2.) CONTROL OR SWITCHES INTENDED TO BE USED BY THE OCCUPANT OF THE ROOM OR AREA TO CONTROL LIGHTING AND RECEPTACLE OUTLETS, APPLIANCES, ALARMS OR COOLING, HEATING AND VENTILATING EQUIPMENT SHALL BE LOCATED NO MORE THAN 48 INCHES (1219MM) MEASURED FROM THE TOP OF THE OUTLET BOX NOR LESS THAN 15 INCHES (381MM) MEASURED FROM THE BOTTOM OF THE OUTLET BOX TO THE LEVEL OF THE FINISHED FLOOR OR WORKING PLATFORM. IF THE REACH IS OVER A PHYSICAL BARRIER OR AN OBSTRUCTION (FOR EXAMPLE, A KITCHEN BASE CABINET) BETWEEN 20 AND 25 INCHES (508 AND 635MM) IN DEPTH, THE MAXIMUM HEIGHT IS REDUCED TO 44 INCHES (1118MM) FOR FORWARD APPROACH, OR 46 INCHES (1168MM) FOR SIDE APPROACH, PROVIDED THE OBSTRUCTION IS NO MORE THAN 24 INCHES (610MM) IN DEPTH. PHYSICAL BARRIERS OR OBSTRUCTIONS SHALL NOT EXTEND MORE THAN 25 INCHES (635MM) FROM THE WALL BENEATH A CONTROL.

ELECTRICAL LEGEND	
SYMBOL	DESCRIPTION
S	LIGHT SWITCH – WALL MOUNTED @ +48" AFF UNLESS NOTED SUBSCRIPTS:  2 = 2-POLE SWITCH 3 = 3 WAY SWITCH
	RECEPTACLE, DUPLEX 20A, 120V GRD, NEMA 5-20R +18" AFF U.O.N.(WP=WEATHERPROOF, GFI=GROUND FAULT CIRCUIT INTERRUPTER
	RECEPTACLE DUPLEX 20A, 120V GRD NEMA 5-20R FLOOR MOUNTED.
	COMBINATION 4-PLEX RECEPTACLE, NEMA 5-20R DOUBLE DUPLEX (1 DUPLEX AUTO CONTROLLED BY OCCUPANCY SENSOR PER T24, (1) DUPLEX UNCONTROLLED), & TYPE 6 VOICE/DATA OUTLET, FLOOR MOUNTED. PROVIDE MIN. 3/4" TEL/DATA CONDUIT WITH PULL WIRES.
	GFI DUPLEX RECEPTACLE ABOVE COUNTER LEVEL, NEMA 5-20R.
	JUNCTION BOX CEILING MOUNTED, SIZE TO CODE, TAPE AND TAG WIRES.
	JUNCTION BOX WALL MOUNTED, SIZE TO CODE, TAPE AND TAG WIRES.
	ELECTRICAL PANELBOARD, SURFACE OR FLUSH MOUNTED (277/480V).
	ELECTRICAL PANELBOARD, SURFACE OR FLUSH MOUNTED (120/208V).
	SPECIAL PURPOSE ELECTRICAL PANELBOARD, SURFACE OR FLUSH MOUNTED.
	TRANSFORMER – DRY TYPE.
	FUSED DISCONNECT SWITCH WITH DUAL ELEMENT FUSES. SWITCH AND FUSES RATING PER NAMEPLATE OF SERVED UNIT.
	NON-FUSED DISCONNECT SWITCH, RATING PER NAMEPLATE OF SERVED UNIT.
	Smoke Detector
	Carbon Monoxide Detector
	COMBINATION 4-PLEX RECEPTACLE, NEMA 5-20R DOUBLE DUPLEX (1 DUPLEX AUTO CONTROLLED BY OCCUPANCY SENSOR PER T24, (1) DUPLEX UNCONTROLLED).
	TYPE 6 VOICE/DATA OUTLET, WALL MOUNTED. PROVIDE MIN. 3/4" TEL/DATA CONDUIT WITH PULL WIRES.
	LEGEND NOTES: 1. MOUNTING HEIGHT INDICATED ARE AFF TO CENTER OF PLATE. IN CASE OF CONFLICT, GENERAL NOTES 41 & 42 SHALL PREVAIL. 2. NOT ALL SYMBOLS AND ABBREVIATIONS ARE NECESSARILY USED IN THIS PROJECT.

WIRE SCHEDULE AND NOTES					
LOAD PER PH (KVA)	WIRE SIZE (AWG)	MAXIMUM LENGTH OF BRANCH CIRCUIT PER UTILIZATION VOLTAGE			NOTES AND REMARKS
		(120, 1PH, MAX V.D. 3%)	(240, 1PH, MAX V.D. 3%)	(240, 3PH, MAX V.D. 3%)	
< 1.92	#12	56 FT	85 FT	98 FT	5
	#10	94 FT	141 FT	163 FT	5
	#8	144 FT	217 FT	250 FT	5
	#6	230 FT	345 FT	398 FT	5
< 1.44	#12	75 FT	113 FT	130 FT	5
	#10	125 FT	188 FT	217 FT	5
	#8	192 FT	289 FT	334 FT	5
	#6	306 FT	460 FT	531 FT	5
< 1.26	#12	86 FT	129 FT	149 FT	
	#10	143 FT	215 FT	248 FT	
	#8	220 FT	330 FT	381 FT	
	#12	100 FT	150 FT	173 FT	
< 1.08	#10	167 FT	250 FT	289 FT	
	#8	256 FT	385 FT	445 FT	
	#12	120 FT	180 FT	240 FT	
	#10	200 FT	300 FT	347 FT	
< 0.9	#12	150 FT	225 FT	260 FT	
	#10	250 FT	376 FT	434 FT	
< 0.72					
#	NOTES				
1	CONTRACTOR SHALL REFER TO THIS TABLE PRIOR TO START OF BRANCH CIRCUIT ROUGH-IN.				
2	CONTRACTOR SHALL USE THE APPROPRIATE WIRE SIZE IN CONJUNCTION WITH THE LENGTH OF THE PROPOSED FIELD VERIFIED ROUTING OR BRANCH CIRCUIT WIRING (INCLUDING VERTICAL & LATERAL RUN, ROUTED PARALLEL/PERPENDICULAR TO THE BUILDING STRUCTURE).				
3	SEE PANEL SCHEDULE FOR THE CORRESPONDING KVA LOAD PER PHASE OF A PARTICULAR BRANCH CIRCUIT.				
4	RESISTANCE VALUES USED ARE FOR UNCOATED COPPER WIRES IN STEEL CONDUIT. 75 DEGREE C., OPERATING AT 60HZ.				
5	THE VALUES IN "120V, 1PH" COLUMN IS TO BE USED FOR GENERAL PURPOSE RECEPTACLE LOADS.				

ABBREVIATIONS AND TAGS			
ABB.	DESCRIPTION	ABB.	DESCRIPTION
EWB	ELECTRIC WATER HEATER	SD	SMOKE DETECTOR
(E)	EXISTING TO REMAIN	TEL	TELEPHONE
EC	ELECTRICAL CONTRACTOR	TX	TRANSFORMER
FA	FIRE ALARM	TV	TELEVISION
FMT	FLEXIBLE METALLIC TUBING	UAC	UNDER ANOTHER CONTRACT
GC	GENERAL CONTRACTOR	UAS	UNDER ANOTHER SECTION
GFCI	GROUND FAULT INTERUPTER	UON	UNLESS OTHERWISE NOTED
IG	ISOLATED GROUND	V.D.	VOLTAGE DROP
LL	LANDLORD	W	WIRE
LV	LOW VOLTAGE	WP	WEATHERPROOF
	MECHANICAL UNIT TAG. SEE MECHANICAL DRAWINGS FOR ADDITIONAL DESCRIPTION.		DETAIL TAG. REFER TO DETAIL 4 ON SHEET NUMBER E-4

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.  
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.  
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.  
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY
01	UPDATE	08/22	A.B

PROJECT:

TITLE: **ELECTRICAL SYMBOLS AND GENERAL NOTES**

PROJ. NO. PROJ. ENGR. SCALE @ 24X36: NTS

DRAWING NO. REV. **E . 0 1**



ELECTRICAL SPECIFICATIONS					
PART 1	GENERAL				
1.01	SCOPE OF WORK: Furnish and install all materials and equipment and provide all labor, tools, transportation, superintendence and services required and necessary to complete the work shown on the drawings and/or specified herein. Also include all other work and miscellaneous items, not specifically mentioned, but reasonably inferred for a complete installation including all accessories and appurtenances required for testing the system. It is the intent of the drawings and specifications that all systems be complete, and ready for operation.				
1.02	REGULATORY REQUIREMENTS: Code compliance is mandatory. Nothing in these Drawings and Specification permits work not conforming to these codes. Where work is shown to exceed minimum code requirements, comply with drawings and specifications. All work and materials shall comply with the latest rules, codes and regulations, including, but not limited to the following: 1. Occupational Safety and Health Act Standards (OSHA). 2. NFPA #70: National Electric Code (NEC). 3. NFPA #101: Life Safety Code. 4. State Fire Marshal. 5. Local Utilities Companies.				
1.03	LICENSES, FEES AND PERMITS: Electrical contractor shall pay for all licenses, permits and inspection fees required by the authority having jurisdiction and shall arrange for all required inspections.				
1.04	SAFETY AND INDEMNITY: The Contractor shall be solely and completely responsible for conditions of the job site, including safety of all persons and property during performance of work. This requirement will apply continuously and not be limited to normal working hours. No act, service, drawing review or construction review by the Owner, the Engineers or their Consultants, is intended to include review of the adequacy of the Contractor's safety measures, in, on, or near the construction site.				
1.05	DRAWINGS AND SPECIFICATIONS: All drawings and all Divisions of these specifications shall be considered as a whole and work of this Division shown anywhere therein shall be furnished under this Division. Drawings are diagrammatic and indicate the general arrangement of equipment and wiring. Most direct routing of conduits and wiring is not assured. Exact requirements shall be governed by conditions of the job. Consult all other drawings in preparation of the bid. Extra lengths of wiring or addition of pull or junction boxes, etc., necessitate by such conditions shall be included in the bid.				
1.06	CONDITIONS AT SITE: The electrical contractor shall have examined the site and familiarized themselves with all discernible existing conditions. No extra payment will be allowed for work required because of these conditions, whether specifically mentioned or not.				
1.07	WORKMANSHIP AND CONTRACTOR'S QUALIFICATIONS: Only quality workmanship will be accepted. Haphazard or poor installation will be cause for rejection of work.				
1.08	SHOP DRAWINGS AND MATERIALS LISTS: Submit to Owner in a single package six (6) copies of complete shop drawings and materials list, as noted below, for review within fifteen (15) days after award of contract. Submittals required as follows: 1. Wiring devices: switches, receptacles, device plates. 2. Enclosures for utility company metering. 3. Main fused disconnect switch. 4. Panelboards. 5. Disconnect switches. 6. Lighting fixtures, lamps and lighting control equipment.				
1.09	SUBSTITUTIONS: One or more makes of materials or methods may have been specified to establish the standard of quality, workmanship, finish and design required, but other materials or methods equal in quality, workmanship, finish, design, and guaranteed performance, will be accepted. However, all changes and substitutions shall be requested in letter form and shall be accompanied with a statement of the amount of money to be returned to the contract if the substitution is permitted. No work involving materials submitted for substitution shall proceed until written acceptance is received from the Owner. The Owner is the sole judge of acceptability of preferred substitutions. If a substitution item is permitted, and any re-design effort is thereby necessitated, the required redesign shall be at the Contractor's expense.				
1.10	COORDINATION: Coordinate work with other trades to avoid conflict and to provide correct rough-in and connection for equipment furnished by other trades that require electrical connections. Inform Contractors of other trades of the required access to and clearances around electrical equipment to maintain service ability and code compliance. Verify equipment dimensions and requirements with provisions specified under this Section. Check actual job conditions before fabricating work. Report necessary changes in time to prevent needless work. Changes or additions, subject to additional compensation, which are made without written authorization and an agreed price, shall be at the Contractor's risk and expense.				
1.11	CUTTING AND PATCHING: All cutting and patching required for work of this Division is included herein. Coordination with General Contractor and other trades is imperative. Contractor shall bear the responsibility for and the added expense of adjusting for improper holes, supports, etc.				
1.12	ACCEPTANCE DEMONSTRATION: Upon completion of the work, at a time to be designated by the Owner, the Contractor shall demonstrate for the Owner the operation of the electrical installation including any and all special items installed by him or installed under his supervision. Properly set automatic time switches to perform switching operations in accordance with schedules provided by the Owner's representative, and demonstrate (using the manufacturer's operating instructions) how to override and/or test time switches programming.				
1.13	RECORD DRAWINGS, EQUIPMENT DATA: Maintain one set of clear working drawings at the job site and enter daily such "as-built" information as feeder and service routes, pull box locations and changes in layout or arrangement which occur during construction. Deliver completed drawings to the Owner.				
1.14	CLEAN-UP: Rid the premises of scrap materials, trash and debris both during construction and at completion of the project. Leave the building and surrounding area in a clean and orderly condition.				
1.15	GUARANTEE: Guarantee the installation free from defects of workmanship and materials for a period of one year after Date of Certification of final payment and promptly remedy any defects developing during this period, without charge.				
1.16	TEMPORARY SERVICES: Provide adequate and safe temporary electrical power and lighting throughout the construction and finishing of the premises. In addition to special or unusual requirements, provide at least these items: 1. Three 20-amp circuits for construction power tools. Provide GFI temporary circuits with coverplates to meet OSHA requirements. 2. Three or more light strings suspended approximately one foot below the height of finish ceiling with lamps spaced not more than twelve feet on centers. Strings shall be run the length of the store space parallel to the demising walls, with one string within eight feet of each wall and one (or more) intermediate string(s) arranged to limit the spacing between rows to sixteen feet or less. 3. Flood lighting and task lighting for pointing and other finish work. When permanent electrical service is operable, disconnect and remove from the premises the materials and equipment used for temporary power and lighting, and restore modifications and repair damage caused by the installation, use or removal of temporary service provisions.				
PART 2	PRODUCTS				
2.01	MATERIAL APPROVAL: All materials must be new and bear Underwriter's Laboratories label. Materials that are not covered by UL testing standards shall be tested and approved by an independent testing laboratory or a governmental agency. Material not in accordance with these specifications may be rejected either before or after installation.				
2.02	CONDUITS AND OTHER RACEWAYS: A. Rigid Steel: Hot-dipped galvanized. B. Intermediate Metal Conduit (IMC): Hot-dipped galvanized. C. Electrical Metallic Tubing (EMT): Electro-galvanized. D. Wireway: Code gauge steel, with knockouts and hinged cover, corrosion resistant gray baked enamel finish. E. Provide fittings and accessories approved for the purpose equal in all respects to the conduit or raceway. EMT connectors and couplings shall be steel setscrew type indoors and steel compression type in wet locations and outdoors.				
2.03	WIRES AND CABLES: A. For power and lighting system 600V or less: 1. Conductor: minimum size #12 AWG. a. #12 and #10 AWG solid copper. b. #8 AWG and larger shall be stranded copper. 2. Insulation type: a. #12 to #1 AWG: THWN for wet or underground and THHN for dry locations. b. #1/0 through #4/0 AWG: XHHW (55 mils). c. #250 MCM and larger: XHHW (65 mils). d. Grounding wire: TW. B. For signal and communications circuit: 1. Special cables shall be as specified on drawings. 2. Conductors for general use shall be stranded copper conductor, #16 AWG minimum, with THWN insulation for underground or wet locations and THHN insulation for dry locations. C. Acceptable Products: General Electric, Amoco, Okonite, Paronite or Triangle products conforming or exceeding applicable IPCEA standards.				
2.04	OUTLET BOXES, JUNCTION AND PULL BOXES: A. Outlet boxes: 4" square x 1-1/2" deep (or larger) galvanized sheet steel KO-type with plaster ring and cover for general interior use and cast metal type FS or FD with matching screw covers for exterior and exposed interior locations (gasketed in damp or wet locations). B. Junction boxes shall be same as outlet boxes up to 42 cu. in. and codegauge steel in larger sizes with surface or flush-type screw-mounted trim covers, both boxes and covers inhibitor-primed and painted inside out. C. Pull boxes shall be same as junction boxes unless indicated otherwise on the drawings, with covers. D. Telephone outlet boxes shall be the type and size required by the serving telephone company but not smaller than 4-11/16" square x 2-1/8" deep with single-gang ring and Sierra #S-754N split plate bushing.				
2.05	WIRING DEVICES AND PLATES: Wiring devices and plates shall be by Pass and Seymour or approved equal. 1. Standard design: a. Switch and receptacles devices shall be plastic bodies, color per architect. b. Wall plates shall be metal type 430, stainless steel, color per architect. c. Isolated ground receptacles shall be white with orange triangle as required per NEC, manufactured by "Leviton" # 5362-IGW or approved equal.				
2.06	CONDUIT HANGERS: For individual conduit runs not directly fastened to the structure, use rod hangers manufactured by Caddy, Unistrut or Powerstrut. For multiple conduit runs, use Unistrut or Powerstrut trapeze type conduit support designed for maximum deflection not greater than 1/8".				
2.07	WIRE CONNECTORS: For wire sizes #8 AWG and smaller: Insulated pressure type (with live spring) rated 105 degrees C, 600V, for building wiring and 1000V in signs or fixtures. Scotchlok or Ideal. For wire size #6 AWG and larger: T & B or equivalent compression type with 3M #33+ or Plymouth "Slipknot Grey" tape insulation.				
2.08	PANELBOARDS: A. Construction: Cabinets shall be of code gauge, galvanized steel, surface or flush mounted as indicated. Doors shall be of cold-rolled steel with concealed hinges and flush catch and lock. All panels shall be keyed alike. Panels located adjacent to each other shall have identically sized enclosure and trim. Minimum panel width shall be 20". Finish exposed part with one coat of primer and one coat of light grey enamel suitable for overpainting in field if desired. B. Bus Bars: Provide ground block with full complement of terminals in addition to insulated neutral bus. Future breaker spaces shall have complete provision including busses and connecting hardware. C. Manufacturers: Panelboards shall be General Electric Type "AQ" or type "AE" or equivalent products of Eaton, Square-D or Siemens-ITE. D. Circuit Breakers: Shall be quick-make, quick-break, molded case type: 1. 120/240 Volt Panels: Shall be General Electric Type "Q" line, bolt-on type, with minimum symmetrical interrupting capacity as shown. 2. Provide multi-pole units with common trip element. 3. Circuit breakers used on "ON-OFF" control of fluorescent lighting (panelboard switching) shall be Underwriters' Laboratories listed and marked "SWD" to indicate their suitability. E. Identification: Provide screwed-on (no adhesives) bakelite or photo-etched metallic nameplate identification on outside of each panel showing panel designation, voltage and phase in minimum 1/8" high letters. Each panel shall contain a metal-framed circuit directory inside cover, with plastic protector. Complete shop drawings are required. See Article 1.08. F. Individually mounted motor controllers: A. For Polyphase Motors: Combination motor circuit protector and magnetic starter, with 3-leg overload protection. Provide two interlock contacts of the interchangeable open-close type. Provide hand-off-automatic selector switch, motor running pilot light and reset button in cover. Circuits 300V and over shall be provided with 120V control transformers. B. Starters for fractional horsepower 120V motors shall be manual type unless shown otherwise, equipped with built-in overload protection. C. Acceptable manufacturers: General Electric, Siemens, Square D, Eaton, and Westinghouse.				
2.10	LIGHTING: A. Furnish and install all fixtures complete, including lamps and ballast ready for service. B. Supports: Proper supports and mounting accessories, such as hangers, stems, yokes, plaster frames, etc. shall be provided as required by the type of ceiling installed. Where switch canopies or ball aligners are specified, they shall cause fixture to hang plumb regardless of ceiling slope. C. Fixture Designation: Fixture types are designated on drawings. Where only one fixture designation is shown, it applies to all fixtures in that room or area. For exact fixture count and location refer to reflected ceiling plan. D. Wire 1-lamp and 3-lamp fluorescent fixtures in tandem where required by code. E. Ballasts: Advance, GE, or Approved high frequency electronic, full light output, energy saving, Class "P", high power factor, ETL certified, sound rating "A" or as indicated on drawings.				
2.11	MISCELLANEOUS MATERIALS: A. Safety Switches: Heavy duty type, 600V, horsepower rated for motors, fused or non-fused as required. Mount in enclosure with NEMA rating as required for the specific application General Electric, Square D or Westinghouse.				
PART 2	PRODUCTS				
2.12	DRY TYPE TRANSFORMERS: General: Equipment shall conform to or exceed requirements of NEMA, ANSI Standard C89.2 for Dry Type Transformers for General Applications. Acceptable products are those of General Electric Company's "QL" Line or equivalent Square D, Siemens-ITE, or Eaton. Electrical Ratings: 1. Primary windings voltage: 480 Volts, 3-Phase, delta. Secondary windings voltages: 240Y/120 Volts, 3-Phase grounded. Frequency: 60 Hz. KVA rating: As shown on drawings. Taps: Six (6) 2.5% full capacity taps: 2 above and 4 below, rated voltage. Impedance: For transformers larger than 75 KVA, 4.5% minimum, 5.75% maximum. Winding temperature rise shall be 150 degrees Centigrade in accordance with UL Specification Article 506. 3. Transformer shall be capable of operating at 100% of nameplate rating continuously while in an ambient temperature not exceeding 40 degrees Centigrade. 4. Transformer shall meet the daily overload requirements of ANSI Standard C57.96. Vibration Isolation, Factory-installed: Provide neoprene rubber pads to isolate core and coil assembly from transformer enclosure. Installation: 1. Anchor transformer securely with minimum 1/2" diameter bolts. Strength of bolts used to secure the transformer shall be sufficient to resist shear and uplift produced by force equal to 1/2 of the equipment mass applied horizontally at center of gravity. 2. Provide 1" thick high resiliency pads to isolate transformer from floor or platform. Korlund "Elasto Rib" or equivalent. 3. Use flexible conduits at least 24" long for electrical connections. 4. Provide grounding of each transformer secondary including all conduits, wires, and connectors in accordance with NEC 250-26 and any local additional regulations.				
PART 3	EXECUTION				
3.01	GENERAL: A. Electric system layouts indicated on the drawings are generally diagrammatic and shall be followed as closely as actual construction and work of other trades will permit. Govern exact routing of cable and wiring and the locations of outlets by the structure and equipment served. Take all dimensions from architectural drawings. B. Consult all other drawings, verify scales and report any dimensional discrepancies or other conflicts with Owner before submitting bid. C. All home runs to panelboards are indicated as starting from the outlet nearest the panel and continuing in the general direction of that panel. Continue such circuits to the panel as though the routes were completely indicated. Terminate homeruns of signal, alarm, and communication systems in a similar manner. D. Avoid cutting and boring holes through structure or structural members wherever possible. Obtain prior approval of Owner and conform to all structural requirements when cutting or boring the structure is necessary and permitted. E. Furnish and install all necessary hardware, hangers, blocking, brackets, bracing, runners, etc. required for equipment specified under this Section. F. Provide necessary backing required to insure rigid mounting of outlet boxes.				
3.02	WIRING METHODS: A. Install all wiring in raceway or use MC cable. Where approved by all Applicable codes, Conduit shall be rigid steel, IMC or EMT as follows: 1. Above ground: Use rigid steel, IMC or EMT. a. Wet locations: Rigid steel or IMC only. b. Locations subject to mechanical injury: Rigid steel or IMC only. c. Dry locations and not subject to mechanical injury: EMT, IMC or rigid steel conduit. 2. Underground: Use rigid steel. B. Use flexible conduits in the following applications: 1. Recessed lighting fixtures. 2. Motor connections. 3. At building joints. At wet locations, flexible conduit shall be liquid tight type.				
3.03	INSTALLATION OF CONDUITS: A. General: 1. Run all conduit concealed unless otherwise noted or shown. 2. Run all conduit parallel to or at right angles to center lines of columns and beams. 3. Conduits above ceilings shall not obstruct removal of ceiling tiles, lighting fixtures, air diffusers, etc. 4. Conduits shall not cross any duct shaft or area designated as future duct shaft horizontally. Conduit risers when allowed in duct shaft must be coordinated with Mechanical work to avoid any conflict. B. Conduit Supports: 1. Support conduits with Underwriter's Laboratories listed steel conduit supports designed for the rating of the equipment. Wire or sheet metal strips are not acceptable for conduit support. Use conduit hangers for all conduits not directly fastened to structure and for all multiple conduit runs. Do not attach any conduit to mechanical ducts or pipes. 2. Individual conduits 1/2" and 3/4" size for lighting may be supported from ceiling support wires with Caddy clips only if acceptable to local code. Only one conduit is permitted to be attached to any ceiling support wire. Hang such conduit so as not to affect level of ceiling. 3. Avoid attaching conduit to fan plenums. When it is necessary to support conduit from fan plenum, provide a length of flexible conduit between portion attached fan plenum and portion attached to the building to minimize transmission of vibration to the building structure.				
3.04	CONNECTIONS TO EQUIPMENT: A. General: 1. Furnish and install required power supply conduit and wiring to all equipment. See below for other wiring required. 2. Furnish and install a disconnect switch immediately ahead of and adjacent to each magnetic motor starter or appliance unless the motor appliance is located adjacent and within sight of the serving panelboard, circuit breaker or switch. Verify all equipment nameplate current ratings prior to installation. 3. Install all rough-in work for equipment from approved shop drawings to suit the specific requirements of the equipment. 4. Furnish and install manual thermal protection for all motors not integrally equipped with thermal protection. 5. Furnish 120 Volt power to each control panel and time switch requiring a source of power to operate.				
3.05	WIRE COLOR CODE: Color coding shall be continuous for wire #12 through #10 AWG. Phase conductors #8 and larger and nonconductors of any size in cable assemblies may have colored phasing tape at terminations. Color code wires as follows: Voltage 120/208V 277/480V Phase A Black Brown Phase B Red Orange Phase C Blue White Neutral White Yellow Gray Ground Green Green				
PART 3	EXECUTION				
3.06	INSTALLATION OF WIRES: A. Pull no wire into any portion of the conduit system until all construction work which might damage the wire has been completed. B. Install all wire continuous from outlet to outlet or terminal to terminal. Splices in cables when required shall be made in handholes, pull boxes or junction boxes. Make branch circuit splices in outlet boxes with 8" of correctly color-coded tails left in the box. C. Splices in wires and cables shall be made utilizing materials and methods described herein before. D. Make all ground, neutral and line connections to receptacle and wiring device terminals as recommended by manufacture. Provide ground jumper from outlet box to ground terminal of devices when the device is not approved for grounding through the mounting screws. E. Provide Brady wire markers where number of conductors in a box exceeds four. F. Megger and record insulation resistance of all 600 Volt insulated conductors size #4/0 and larger using 500 Volt megger for one minute. Make tests with circuits isolated from source and load.				
3.07	IDENTIFICATION: A. Provide nameplates for switchgears, panelboards, and all similar devices. Nameplates shall be screwed (no adhesives) engraved bakelite or photo-etched metallic nameplate identification showing panel designation, voltage and phase in minimum 1/4" high letters. B. Provide dymo labels on all lighting switches and convenience and special purpose receptacles to show panel and circuit number to which the device is connected. C. Each panelboard shall contain a metal-framed circuit directory inside cover, with plastic protector. D. Panelboard Schedule: After completion of work, provide typewritten updated panelboard schedules for all panelboards.				
3.08	REMODELING WORK: A. Existing electrical wiring which will not be made obsolete and which will be disturbed due to construction changes required by this contract shall be restored to operating condition. Where construction changes require, outlets and conduit runs shall be relocated. Extend conduits and pull in new wiring or install junction boxes and splice in new wiring. B. Outlets from which fixtures, switches, receptacles, and/or other electrical devices are moved and which are not replaced or reused shall be removed, where outlets boxes, etc., are completely removed, the contractor shall cut off conduits and remove wiring. C. Where conduits extending through floors are to be abandoned, the contractor shall cut and cap or plug conduit, and the conduit shall not protrude above the floor. D. Where existing conduit is to be abandoned, the conduit shall be removed if it is exposed, in a crawl space or in accessible ceiling. Where it is impossible to remove the conduit, it shall be cut off and capped or plugged. E. Remove all existing wiring not reused or required to maintain continuity circuits to remain. F. The contractor shall be held fully responsible for the proper restoration of all existing surfaces requiring patching, plastering, painting and/or other repairs due to the installation of electrical work under the terms of this specification. Close all openings, repair all surfaces, etc., as required. G. Maintain circuit continuity to areas outside of this work. Provide new conduit and conductors as required to maintain continuity and maintain area as existing.				
3.09	GROUNDING: A. Electrical service and separately derived alternating current system shall be grounded in accordance with NEC Article 250-3 to 250-26, inclusive. B. Ground non-current carrying metal parts of electrical equipment enclosures, frames, conductor raceways or cable trays to provide a low impedance path for line-to-ground fault current and to bond all non-current carrying metal parts together. Provide ground conductor in each raceway system in addition to conductors shown. Equipment ground conductor shall be electrically and mechanically continuous from the electrical circuit source to the equipment to be grounded. Size ground conductors per NEC Article 250-95 unless larger conductors are shown on drawings. C. Grounding conductors shall be identified with green insulation. Where green insulation is not available on larger sizes, black insulation shall be used and suitable identified with green tape at each junction box or device enclosure.				
	END OF SECTION				

**CONFIDENTIALITY STATEMENT:**

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

**NOTES:**

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.  
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.  
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.  
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY
01	UPDATE	08/22	A.B


PROJECT:

TITLE: ELECTRICAL SPECIFICATIONS

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36:
		NTS


DRAWING NO.	REV.
E . 0 2	





LIGHTING PLAN

LIGHTING PLAN



POWER PLAN

SHEET NOTES:

- POWER FOR LOGO. MOUNT RECEPTACLE AT 6'-6" TO BOTTOM OF RECEPTACLE BOX. USE RECESSED RECEPTACLE BOX. REFER TO SPECSHEET
- ROUTE (1) CAT 6 CABLE FOR DATA TO LOW CURRENT CABINET
- PROVIDE NON-FUSED DISCONNECT SWITCH FOR GAS WATER HEATER
- PROVIDE NON-FUSED DISCONNECT SWITCH FOR ELEVATOR
- PROVIDE NON-FUSED DISCONNECT SWITCH FOR ROOF TOP UNIT
- OUTLET FOR AIR CURTAINS
- OUTLET FOR ELECTRIC DOOR



RECESSED RECEPTACLE BOX

SHEET NOTES:  
1 JUNCTION OUTLET FOR STIP LED

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY
01	UPDATE	08/22	A.B

PROJECT:


TITLE: **FIRST FLOOR AND LIGHTING AND POWER LAYOUTS**

PROJ. NO. PROJ. ENGR. SCALE @ 24X36"  
3/16"=1'-0"

DRAWING NO. REV.

**E . 0 3**





ROOF PLAN

SHEET NOTES:

- 1 → POWER FOR LOGO INSTALLED AT 6 FEET ABOVE FLOOR
- 2 → ROUTE (1) CAT 6 CABLE FOR DATA TO LOW CURRENT CABINET
- 3 → PROVIDE NON-FUSED DISCONNECT SWITCH FOR GAS WATER HEATER
- 4 → PROVIDE NON-FUSED DISCONNECT SWITCH FOR ELEVATOR
- 5 → PROVIDE NON-FUSED DISCONNECT SWITCH FOR ROOF TOP UNIT

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL  
UNITS, UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN  
CONJUNCTION WITH ALL RELEVANT DESIGNER,  
ENGINEER OR SPECIALIST DRAWINGS AND  
SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL  
DIMENSION AT SITE BEFORE COMMENCING  
WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR  
PROVIDING ALL NECESSARY TEMPORARY  
SUPPORT TO THE BUILDING AND ANY  
ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY
01		UPDATE	08/22	A.B

PROJECT:

TITLE: **ROOF POWER LAYOUTS**


PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		3/16"=1'-0"

DRAWING NO.

**E . 0 4**

REV.

LIGHT SCHEDULE

ID	SYMBOL	TYPE	LOCATION	PRODUCT NAME	URL	DIMENSIONS	FINISH	BULB PER FIXTURE / TYPE	MAXIMUM WATTS PER FIX	QUANTIT Y FIXTURES	UL LISTING	DIMABLE	WET LOCA TION	NOTE
LT 01		EXTERIOR SCONCE	MAIN ENTRANCE	Simplicity Bar Shaped LED Wall Mounted Light Metal	<a href="https://www.litfad.com/">https://www.litfad.com/</a>	47" BY 2"	BLACK	1 - LED	47	2	UL Listed	Dimmable when used with a ELV Dimmer	YES	
LT 02		EXTERIOR FLUSHMOUNTED	ABOVE THE 3 ENTRY DOORS	KOS ROUND LED FLUSH MOUNT	<a href="https://www.lumens.com/">https://www.lumens.com/</a>	6" BY 5"	BLACK	1 - LED	11 WATTS	6	UL Listed	Dimmable when used with a ELV Dimmer	YES	
LT 11		PENDANT	RETAIL (ABOVE ROUND DISPLAYS)	Large pendant by Gubi for Bonderup	<a href="https://www.lumens.com/">https://www.lumens.com/</a>	Height 11.8" Diameter 23.6" Weight 2.7Lbs	White	1	60 Watt 120 Volt E26	8	ETL Listed	Dimmable when used with a ELV Dimmer	N/A	
LT 12		FLUSHMOUNT	RETAIL (MAIN ARCHITECTURAL LIGHT)	Exo Dual Flush Mount TECH LIGHTING	<a href="https://www.circalighting.com/exo-dual-flush-mount-700fmexod/">https://www.circalighting.com/exo-dual-flush-mount-700fmexod/</a>	Length: 10.4" Width: 5.2" Height: 6.1"	Matte Black	2	2 x14 watt	15	UL Listed	Dimmable with most LED compatible ELV	N/A	CONFIRM NUMBER PER ARCHITECT LOCATION VIF
LT 13		TRACK	- FRONT WINDOWS - CASH HANDLING	NT-304 8" One-Circuit Track  Nora Track head: NTH-920 PAR20 Architectural Cylinder	<a href="https://noraaighting.com/product/nt-304/">https://noraaighting.com/product/nt-304/</a>  <a href="https://noraaighting.com/product/nth-920/">https://noraaighting.com/product/nth-920/</a>	TRACK 8FT  HEAD: 7"(H) x 5" x 3" (D)	Black	1	700 Lumens - LED PAR20 - 8.5 Watt -2700 Kelvin Snap System Compatible - 10 Deg. Spot - 120 Volt - Soraa 08793	8 TRACKS WITH 4 HEADS EACH	UL Listed	Dimmable	N/A	COLOR TBD
LT 14		RECESS SPOT	ENTRY VESTIBULE ATM RECESS	2" ELEMENT Remodel Adjustable Square Flanged Housing	<a href="https://www.circalighting.com/">https://www.circalighting.com/</a>	N/A	WHITE	1 (INCLUDED )		2			N/A	CONFIRM PER ARCHITECT
LT 15		TRACK	ART INSTALLATION	NT-2331 12" Two-Circuit Track	<a href="https://noraaighting.com/product/nt-2331/">https://noraaighting.com/product/nt-2331/</a>	12 feet long	silver	N/A	N/A	3	UL Listed	Dimmable	N/A	
LT-15B		TRACK HEADS	ART INSTALLATION	tellium spotlight track head by tech lighting	<a href="https://www.lumens.com/">https://www.lumens.com/</a>	3" head, 6" extension	brushed nickel or black	included	integrated 12 volt	18	UL Listed	Dimmable	N/A	
LT 16		LINEAR PENDANT	AT POS COUNTER		<a href="https://www.wayfair.com/">https://www.wayfair.com/</a>	3ft by 1"	wood	1- LED	18 watts	2	UL Listed	NO	N/A	CONFIRM PER ARCHITECT
LT 17		FLUSHMOUNT	- SIDE WINDOWS (PRODUCTS AND WINDOW DISPLAY)	Exo Flush Mount TECH LIGHTING	<a href="https://www.circalighting.com/">https://www.circalighting.com/</a>	5" BY 6"	WHITE	1 - LED	14 WATT	n/a	UL Listed	Dimmable	N/A	CONFIRM PER ARCHITECT
LT 18		PENDANT	PRODUCT BACKWALL SHELVES (RETAIL)	Lab White Glass Bottle Minimalist Pendant Light	WWW.TUDOANDCO.COM	14cm diameter, 24cm heigh	Glass and polyethylene	1 - LED	40W MAX E27 SCREW ON (NOT INCLUDED) LED BULB 2.2 - 3W (TBD)	10	UL Listed	Dimmable	N/A	standing among products on the shelves PRODUCT LIGHTING / ACCEST
LT 19		SMALL PENDANT	LUNCH COUNTER AT STAFF ROOM	TBD	<a href="https://www.wayfair.com/">https://www.wayfair.com/</a>	N/A	BRASS	1 LED	12 WATTS E27 Screw on	3	UL Listed	Dimmable	N/A	
LT 20		FLUSHMOUNT	OFFICE AREA	PER OWNER						6				
LT 21		LED STRIP	RETAIL SHELVES IN REAR OF STORE	PER GC				N/A	2700K LED STRIP LIGHT	2 LOCATIO NS				CONFIRM PER ARCHITECT
LT 22		EXISTING SURFACE MOUNTED	PRODUCT STORAGE, RECEIVING & IT EQUIPMENT			2' BY 4'				7				
		EM1	WALL MOUNTED EMERGENCY LIGHTING FIXTURE WITH S SEMI RECESS LAMP HEADS, WHITE HOUSING, LEAD CALCIUM BATTERY, BATTERY CHARGER, AND SELF DIAGNOSTICS											
		EX1	LED EXIT LIGHT WITH EGRESS LIGHTING UNIVERSAL CEILING MOUNT, RED LETTERS ON STENCIL FACE, PRISMATIC DIFFUSER, WHITE ALUMINUM HOUSING. NICKEL CADMIUM BATTERY BACKUP, BATTERY CHARGER, AND SELF DIAGNOSTICS											
			DIRECTIONAL EGRESS SIGNAGE WALL MOUNTED DIRECTIONAL. POINT TOWARD EXIT PATH											

1

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL  
UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN  
CONJUNCTION WITH ALL RELEVANT DESIGNER,  
ENGINEER OR SPECIALIST DRAWINGS AND  
SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL  
DIMENSION AT SITE BEFORE COMMENCING  
WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR  
PROVIDING ALL NECESSARY TEMPORARY  
SUPPORT TO THE BUILDING AND ANY  
ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY
01		UPDATE	08/22	A.B

PROJECT:

TITLE: LIGHTING SHCHEDULE

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS

DRAWING NO.

E . 0 5

REV.



Branch Panel: A				Volts: 120/208				A.I.C Rating: 22kA					
Location: Cash Handling & Order Pick-up				Phases: 3				Mains Type: MCCB					
Supply From: Utility Meter				Wires: 3+1				Mains Rating: 200A					
Mounting:Surface													
Enclosure Type 1				Feeder Size: 4-3/0 AWG THHN, 1-#1 GND THHN IN 2-1/2" PVC									
CKT	CIRCUIT DESCIRPTION	TRIP	POLES	A		B		C		POLES	TRIP	CIRCUIT DESRIPTION	CKT
1	Lighting Retail	15A	1	548	224					1	15A	Lighting Retail	2
3	Lighting Retail	15A	1			366	237			1	15A	Lighting Retail	4
5	Lighting Entry Vestibule	15A	1					154	152	1	15A	Lighting Cash Handling & Order Pick-up	6
7	EMERGENCY AND EXIT LIGHTS	15A	1	25	140					1	15A	Fire Alarm	8
9	Receptacles Retail	20A	1			800	800			1	20A	Receptacles Retail	10
11	Air Curtians	20A	1					400	800	1	20A	Receptacles Retail	12
13	Receptacles Retail	20A	1	800	400					1	20A	Air Curtians	
15	Receptacles Retail	20A	1			800	800			1	20A	Receptacles Retail	16
17	Receptacles Retail	20A	1					1400	600	1	20A	Receptacles Cash Handling & Order Pick-up	18
19	ATM	20A	1	700	400					1	20A	POS	20
21	POS	20A	1			400	400			1	20A	POS	22
23	Logo	20A	1					400	400	1	20A	Logo	24
25	Logo	20A	1	400	11850					3	100A	Panel B	26
27	Existing RTU	60A	3			5517	12497						28
29								5517	7817				30
31													
33											34		
35	Electric Door	20A	1					300	300	1	20A	Electric Door	36
TOTAL CONNECTED LOAD (VA)				21004		22617		18240					
TOTAL CONNECTED CURRENT (A)				175		188		152					
Legend:													
Load Classification		Connected Load (VA)		Demand Factor		Estimated Demand (VA)				Panels Totals			
Lighting		1846		125.00%		2308							
Receptacles		11300		40.00%		4520				Total Conn. Load (kVA):		61.861	
Kitchen Equipment Non Dwelling Unit		0		65.00%		0				Total Est. Demand (kVA):		49.0159	
Mechanical Equipment		16551		80.00%		13240.8				Total Conn. Current (A) Per 1 Phase:		171.8361	
Panels		32164		90.00%		28947.6				Total Est. Demand Current (A) Per 1 Phase:		136.1553	

Branch Panel: B				Volts: 120/208				A.I.C Rating: 10kA					
Location: Kitchen				Phases: 3				Mains Type: MCCB					
Supply From: Utility Meter				Wires: 3+1				Mains Rating: 100A					
Mounting:Surface													
Enclosure Type 1				Feeder Size: 4-1/0 AWG THHN, 1-#4 GND THHN IN 2-1/2" PVC									
CKT	CIRCUIT DESCIPTION	TRIP	POLES	A		B		C		POLES	TRIP	CIRCUIT DESCIPTION	CKT
1	Lighting IT Equipment, Receiving & Product Storage	15A	1	240	193					1	15A	Lighting Hall	2
3	Lighting Hall & Kitchen	15A	1			352	228			1	15A	Lighting Offices	4
5	Spare	15A						0		1	15A	Spare	6
7	Receptacles Product Storage Cannabis	15A	1	1200	1200					1	15A	Receptacles Receiving	8
9	Receptacles IT Equipment	15A	1			1200	1200			1	15A	Receptacles Office 104	10
11	Receptacles Hall	20A	1					800	600	1	20A	Receptacles Office 110	12
13	Receptacles Office 108	20A	1	1200	800					1	20A	Receptacles Office 108	14
15	Receptacles Office 108	20A	1			600	400			1	20A	Drinking Fountain	16
17	SPARE	20A	1						400	1	20A	Drinking Fountain	18
19	Receptacles Kitchen	20A	1	600	400					1	20A	Receptacles Refrigerator	20
21	Receptacles Kitchen	20A	1			1500	1500			1	20A	Receptacles Kitchen	22
23	Existing RTU	60A	3					5517	500	1	20A	Gas Water Heater	24
25				5517	500					1	20A	Gas Water Heater	26
27						5517	0			1	20A	Spare	22
TOTAL CONNECTED LOAD (VA)				11850		12497		7817					
TOTAL CONNECTED CURRENT (A)				99		104		65					
Legend:													
Load Classification		Connected Load (VA)		Demand Factor		Estimated Demand (VA)				Panels Totals			
Lighting		1013		125.00%		1266							
Receptacles		10600		40.00%		4240				Total Conn. Load (kVA):		31.664	
Kitchen Equipment Non Dwelling Unit		3000		65.00%		1950				Total Est. Demand (kVA):		21.09705	
Mechanical Equipment		17051		80.00%		13640.8				Total Conn. Current (A) Per 1 Phase:		87.95556	
										Total Est. Demand Current (A) Per 1 Phase:		58.60292	
Notes													

1

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS, UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY
01		UPDATE	08/22	A.B

PROJECT:

TITLE: **PANEL BOARD SCHEDULE**

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS

DRAWING NO.



REV.

**E . 0 6**

GENERAL NOTES

- A. ALL EXISTING COMPONENTS OF THIS ELECTRICAL DIAGRAM ARE TO REMAIN AS INSTALLED AND ARE SHOWN FOR REFERENCE ONLY.
- B. ALL WORK SHALL CONFORM TO THE LATEST EDITION OF THE NATIONAL FIRE PROTECTION
- C. ASSOCIATION (NFPA) 70, NATIONAL ELECTRICAL CODE. ALL ITEMS ARE ON AN OR EQUAL BASIS.
- D. ALL SINGLE PHASE BRANCH CIRCUITS (RECEPTACLES, LIGHTING, ETC.; ARE 1/2" CONDUIT OR EMT WITH THIN, 90C WIRING, UNLESS NOTED OTHERWISE. ALL OTHER CONDUIT AND WIRING SHALL BE AS INDICATED ON THE PLANS. ACTUAL ROUTING AND HOME RUN GROUPINGS ARE TO BE DETERMINED IN THE FIELD.
- E. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC EXCEPT FOR DETAILS AND ELEVATIONS. DO NOT SCALE FROM DIAGRAMMATIC DRAWINGS. EXACT LOCATIONS OF DEVICES AND PANELS ARE TO BE DETERMINED AND ROUGHED-IN DURING CONSTRUCTION TO AVOID INTERFERENCE, TO MEET USER REQUIREMENTS, TO PROVIDE ADEQUATE MOUNTING, AND TO MEET NEC LINEAR ACCESS AND CLEARANCE REQUIREMENTS.
- F. BACK TO BACK MOUNTING OF RECEPTACLES IS NOT PERMITTED.
- G. IN ADDITION TO THE NEC REQUIREMENTS FOR GFCI PROTECTION FOR RECEPTACLES, THE FOLLOWING RECEPTACLES SHALL ALSO HAVE GFCI PROTECTION: (1)-ALL RECEPTACLES LOCATED WITHIN 8 FEET OF A SINK, (2)-ALL RECEPTACLES WHICH ARE PROVIDED FOR CONVENIENCE IN SERVICING HVAC EQUIPMENT REGARDLESS OF LOCATION.AS REQUIRED TO ACCOMMODATE CONDUCTOR PULLING EASE, FIELD LIFE SAFETY.
- H. PROVIDE A LAMICOID NAMEPLATE (WHITE LETTERS ON BLACK BACKGROUND; ON EACH PANELBOARD, MOTOR STARTER,CONTACTOR, TRANSFORMER, ETC. LETTERS SHALL BE 0.75 INCH MAINIMUM.
- I. CONTRACTOR SHALL CUT AS REQUIRED TO INSTALL ELECTRICAL EQUIPMENT REPAIR OF FLOOR OR WALLS SHALL BE COORDINATED WITH GENERAL CONTRACTOR CONTRACTOR SHALL ALSO REPAIR ALL OPENINGS LEFT DUE TO EQUIPMENT REMOVAL.
- J. CONDUCTORS ARE COPPER UNLESS OTHERWISE SHOWN. ALL CONDUCTORS LARGER THAN #10 SHALL BE STRANDED.
- K. PANELBOARDS SHALL CONTAIN A TYPEWRITTEN DIRECTORY WITH A PLASTIC COVER AFFIXED TO THE INSIDE DOOR.

- L. ALL FIXTURES, DEVICES, CONDUIT, AND EQUIPMENT SHALL BE SECURED WITH APPROVED HANGERS AND ANCHORS AND IN ACCORDANCE WITH APPROVED STANDARDS OF INSTALLATION.
- M. ALL BREAKERS SHOWN IN THE PANELBOARD SCHEDULE SHALL BE RATED AS SHOWN FOR BOTH CIRCUIT CAPACITY AND FAULT CURRENT INTERRUPTING CAPACITY.
- N. ALL PANELBOARDS, DISCONNECT SWITCHES, MOTOR STARTERS, AND CONTACTORS SHALL BE NEMA 1, UNLESS OTHERWISE NOTED.
- O. ELECTRICAL CONTRACTOR MUST BE AVAILABLE AT TIME OF DBS INSPECTION. COORDINATE WITH GENERAL CONTRACTON.
- P. FIELD VERIFY THE AVAILABLE FAULT CURRENT AT THE LANDLORD'S EXISTING PANEL AND PROVIDE A NEW, FULLY RATED, PANEL TO MATCH EXISTING.
- Q. CONTRACTOR TO MAKE FINAL CONNECTIONS IN EMS PANEL FOR LANDLORD PROVIDED LIGHTING CIRCUITS. 50% OF THE GENERAL LIGHTING CIRCUITS SHOULD BE ROUTED THROUGH THE CUSTOMER CONTROL ZONE .



NOTES

- CONTRACTOR TO INCLUDE IN THE CONTRACT ALL ONE TAP CHARGERS AND FEES FROM THE POWER COMPANY, AND COORDINATE WITH THE POWER COMPANY.
- PROVIDE PLAQUE STATING LOCATION OF DISCONNECTING MEANS.
- PANEL BOARD TO HAVE FULLY RATED BREAKERS UNLESS NOTED OTHERWISE.

ONE LINE DIAGRAM

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

- ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS, UNLESS STATED OTHERWISE.
- THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
- THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY
01		UPDATE	08/22	A.B

PROJECT:

TITLE: **ELECTRICAL GENERAL DETAILS.**

PROJ. NO. PROJ. ENGR. SCALE @ 24X36" NTS


DRAWING NO.

REV.

**E . 0 7**



Building 1 · Story 1 · Room 1 (Emergency light scene)  
Working plane (Room 1)



Properties	E	E <sub>min</sub>	E <sub>max</sub>	g <sub>1</sub>	g <sub>2</sub>
Working plane (Room 1)	7.96 lx	4.02 lx	12.6 lx	0.51	0.32
Perpendicular illuminance (adaptive)					
Height: 0.000 m, Wall zone: 0.000 m					

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV.	NO.	DESCRIPTION	DATE	BY
01		UPDATE	08/22	A.B

PROJECT:		
TITLE: LIGHTING CALCULATION		
PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36"
		NTS
DRAWING NO.		REV.
E . 0 8		

PLUMBING SPECIFICATIONS

THE WORK INCLUDES MODIFICATION TO THE EXISTING PLUMBING SYSTEM AND PROVIDING NEW MATERIALS, FITTINGS AND ACCESSORIES NECESSARY FOR A COMPLETE FUNCTIONING PLUMBING SYSTEM. THE WORK ALSO INCLUDES ROUGH-IN AND FINAL CONNECTIONS TO FOOD SERVICE EQUIPMENT AND BEVERAGE DISPENSING EQUIPMENT PROVIDED BY OTHERS. ALL WORK SHALL BE IN ACCORDANCE WITH LOCAL CODES AND/OR ORDINANCES AND IS SUBJECT TO INSPECTION.

HOOK-UP CHARGES, PERMITS AND ALL OTHER EXPENSES RELATED TO A COMPLETE AND FUNCTIONING PLUMBING SYSTEM ARE INCLUDED AS A PART OF THIS SECTION.

WARRANTY: PROVIDE LABOR AND MATERIALS TO REPAIR OR REPLACE DEFECTIVE PARTS AND MATERIALS AS REQUIRED FOR ONE YEAR AFTER SUBSTANTIAL COMPLETION OR OWNER ACCEPTANCE OF THE COMPLETED PROJECT. PROVIDE A SEPARATE LINE ITEM DEDUCT AMOUNT ON THE PROPOSAL FORM TO DELETE WARRANTY SERVICE, AT THE OWNER'S OPTION.

THE INTENT OF THE DRAWINGS IS TO INDICATE THE GENERAL EXTENT OF WORK REQUIRED FOR THE PROJECT. THE DRAWINGS FOR PLUMBING WORK ARE DIAGRAMMATIC, SHOWING THE GENERAL LOCATION, TYPE, FIXTURES AND EQUIPMENT REQUIRED. THE DRAWINGS SHALL NOT BE SCALED FOR EXACT MEASUREMENTS. REFER TO MANUFACTURER'S STANDARD ROUGH-IN DRAWINGS FOR PLUMBING FIXTURE INSTALLATION REQUIREMENTS. COMPLY WITH ALL APPLICABLE ADA INSTALLATION REQUIREMENTS.

COORDINATE WITH THE WORK OF OTHER SECTIONS, EQUIPMENT FURNISHED BY OTHERS, AND WITH THE CONSTRAINTS OF THE EXISTING CONDITIONS OF THE PROJECT SITE.

PIPING SYSTEMS - GENERAL: ALL PIPING SHALL BE RUN PARALLEL TO BUILDING LINES AND SUPPORTED AND ANCHORED AS REQUIRED TO FACILITATE EXPANSION AND CONTRACTION. ALL PIPING SHALL BE CONCEALED EXCEPT IN UNFINISHED SPACES. INSTALL AS REQUIRED TO MEET ALL CONSTRUCTION CONDITIONS AND TO ALLOW FOR INSTALLATION OF OTHER WORK SUCH AS DUCTS AND ELECTRICAL CONDUIT. AT ALL CONNECTIONS BETWEEN FERROUS PIPING AND NONFERROUS PIPING, PROVIDE AN ISOLATING DIALECTIC UNION. ALL HANGERS SHALL BE COMPATIBLE WITH PIPING MATERIAL TO PREVENT CORROSION.

PROVIDE ALL FITTINGS, ACCESSORIES, OFFSETS, AND MATERIALS NECESSARY TO FACILITATE THE PLUMBING SYSTEMS FUNCTIONING AS INDICATED BY THE DESIGN AND THE EQUIPMENT INDICATED.

FIXTURES/EQUIPMENT FURNISHED BY OTHERS: PLUMBING CONTRACTOR SHALL PROVIDE UTILITY CONNECTIONS REQUIRED SUCH AS WATER, GAS, AIR, SUPPLIES, WASTE OUTLET, TRAPS, ETC. AT ALL PLUMBING TYPE FIXTURES OR EQUIPMENT FURNISHED BY OWNER, GENERAL CONTRACTOR, FOOD SERVICE CONTRACTOR, EQUIPMENT SUPPLIER, ETC. INCLUDED ARE STOP VALVES, ESCUTCHEONS, AND CHROME PLATED BRASS TUBING WITH COMPRESSION FITTINGS.

SEWER AND WASTE PIPING: PROVIDE ALL DRAINS AND SEWERS WITHIN THE SPACE WITH CONNECTION TO THE EXISTING DRAINAGE SYSTEMS ON-SITE. SANITARY DRAINAGE PIPING ABOVE FLOOR SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE, FITTINGS AND CONNECTIONS. SANITARY DRAINAGE PIPING BELOW GRADE SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE WITH SOLVENT WELD FITTINGS MAY BE USED (WHERE PERMITTED BY CODE/LOCAL AUTHORITIES). ALL DRAINAGE PIPING SHALL BE UNIFORMLY PITCHED, 1/4" PER FOOT UNLESS OTHERWISE REQUIRED BY EXISTING CONDITIONS, OR INDICATED ON THE DRAWINGS.

VENTS: PROVIDE A COMPLETE SYSTEM OF STANDARD WEIGHT CAST IRON NO-HUB VENT RISERS WHERE THE CEILING SPACE IS USED AS A RETURN AIR PLENUM OR USE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE (WHERE PERMITTED BY CODE/LOCAL AUTHORITIES) WHERE THERE IS A DUCTED RETURN AIR SYSTEM. DO NOT USE PVC PIPE IN RETURN AIR PLENUM SPACES. THE VENT SYSTEM SHALL BE CARRIED THROUGH THE ROOF WITH APPROPRIATE FLASHING.

CONDENSATE AND INDIRECT DRAIN PIPING: PIPING ABOVE FLOOR SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE, FITTINGS AND CONNECTIONS. PIPING BELOW GRADE SHALL BE CO-EXTRUDED PVC DWV (SCHEDULE 40) PIPE WITH SOLVENT WELD FITTINGS.

CLEANOUTS: PROVIDE CLEANOUTS AT THE END OF EACH HORIZONTAL RUN, AND AT THE BASE OF ALL VERTICAL WASTE AND DRAIN PIPES. CLEANOUTS SHALL BE OF THE SAME SIZE AS THE PIPES THEY SERVE, CONFORMING TO CODE REQUIREMENTS. PROVIDE SUITABLE WALL OR FLOOR CLEANOUTS WITH ACCESSORIES TO OBSOURE FROM VIEW.

WATER DISTRIBUTION PIPING: LAYOUT WATER PIPING SO THAT THE ENTIRE SYSTEM CAN BE DRAINED. HOT AND COLD WATER PIPING SHALL BE 1/2" MIN. CPVC PIPE WITH SOLVENT FITTING. PROVIDE WATER HAMMER ARRESTERS AT EACH FIXTURE OR GROUP OF FIXTURES AS REQUIRED. INSTALL CHROME PLATED BRASS ESCUTCHEON PLATES AT ALL PENETRATIONS THROUGH FINISHED SURFACES (INCLUDING CABINET INTERIORS).

PIPE INSULATION: INSULATE (AS ALLOWED BY CODE) ALL LISTED SERVICE PIPING AS FOLLOWS. DOMESTIC COLD/HOT WATER, HOT WATER RETURN, STORM WATER PIPING. PROVIDE 1" PREFORMED FIBERGLASS, AS/JSS-11, FLAME SPREAD 25, SMOKE DEVELOPED 50, ASTM C-547. FOR CONDENSATE PIPING PROVIDE 1/2" THICK INSULATION OF SAME CHARACTERISTICS AS LISTED FOR 1" ABOVE, WHERE PERMITTED BY LOCAL CODES. PROVIDE 1/2" SELF-ADHESIVE UNICELLULAR FOAM PIPE INSULATION WITH PRE-FORMED PVC FITTING COVERS - EQUAL TO SELF-ADHESIVE ARMSTRONG 2000 WITH K FACTOR OF 0.27 AT 75 DEGREES MEAN TEMPERATURE. INSULATE ANY EXPOSED CONDENSATE PIPING WITH WASTE TEMPERATURE BELOW 60 DEGREES F.

SHUTOFF VALVES, WITH UNIONS SHALL BE PROVIDED FOR SERVICE TO EACH PLUMBING FIXTURE, FOOD SERVICE EQUIPMENT ITEM OR OTHER EQUIPMENT ITEM. TO FACILITATE ISOLATION FOR REPAIR OR REPLACEMENT. VALVES SHALL BE EQUAL TO JENKINS #902-T BALL VALVE, CHROME-FINISHED BRONZE, TEFLON SEATS AND PACKING, 400 LB. W.O.G., SOLDER END.

ACCESS PANELS SHALL BE PROVIDED WHERE CONCEALED CONTROL DEVICES, VALVES, ETC. ARE CONCEALED WITHIN WALLS. WHERE ACCESS FOR ADJUSTMENT AND MAINTENANCE IS POSSIBLE THROUGH LAY-IN SUSPENDED CEILINGS, ACCESS PANELS ARE NOT REQUIRED.

PIPING SYSTEM- PVC SCHEDULE 40, SCHEDULE 80 AND CPVC PIPE WITH SOLVENT FITTINGS SHALL BE USED WHERE PERMITTED BY CODE/LOCAL AUTHORITIES.

INSTALLATION: THOROUGHLY CLEAN ITEMS BEFORE INSTALLATION. CAP PIPE OPENINGS TO EXCLUDE DIRT UNTIL FIXTURES ARE INSTALLED AND FINAL CONNECTIONS HAVE BEEN MADE. PROCEED AS RAPIDLY AS CONSTRUCTION WILL PERMIT. SET FIXTURES LEVEL AND IN PROPER ALIGNMENT. INSTALL SUPPLIES IN PROPER ALIGNMENT WITH FIXTURES. INSTALL SILICONE SEALANT BETWEEN FIXTURES AND ADJACENT MATERIAL, FOR SANITARY JOINT, AND OMIT ESCUTCHEONS.

REPAIR EXISTING PLUMBING SYSTEM COMPONENTS DAMAGED BY CONSTRUCTION OPERATIONS AND RESTORE TO ORIGINAL CONDITIONS.

TEST WATER SYSTEM UNDER 150 PSIG HYDROSTATIC PRESSURE, FOR FOUR (4) HOURS MINIMUM. WHEN TESTING INDICATES MATERIALS OR WORKMANSHIP IS DEFICIENT, REPLACE OR REPAIR AS REQUIRED, AND REPEAT TEST UNTIL STANDARDS ARE ACHIEVED.

ROOF PENETRATIONS SHALL COMPLY WITH "SMACNA" AND "NRC4" STANDARDS, AND WITH THE REQUIREMENTS OF THE EXISTING ROOFING WARRANTY, IF APPLICABLE. DO NOT PERFORM ROOFING PENETRATIONS IN A MANNER WHICH WOULD VOID OR OTHERWISE LIMIT THE EXISTING ROOFING WARRANTY.

GENERAL NOTES

1. THE INTENT OF THESE PLANS AND SPECIFICATIONS IS TO INCLUDE ALL LABOR, EQUIPMENT, MATERIALS, AND SERVICES NECESSARY TO FURNISH, INSTALL, TEST, AND ADJUST A COMPLETE WORKABLE PLUMBING INSTALLATION AS SHOWN, PRESCRIBED, OR REASONABLY IMPLIED BUT NOT LIMITED TO THAT EXPLICITLY INDICATED IN THE CONTRACT DOCUMENTS, BUT NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE INTENT THEREOF.
2. THE ENTIRE INSTALLATION SHALL CONFORM TO THE REQUIREMENTS OF THE 2006 UNIFORM PLUMBING CODE, 2006 INTERNATIONAL BUILDING CODE, 2006 INTERNATIONAL ENERGY CONSERVATION CODE AND ALL OTHER APPLICABLE CODES AND REGULATIONS REQUIRED BY AUTHORITIES HAVING JURISDICTION. IN THE EVENT OF CONFLICT BETWEEN SPECIFICATIONS, CODES, AND REGULATIONS, THE MORE RESTRICTIVE SHALL APPLY.

3. COORDINATE ENTIRE INSTALLATION OF THE PLUMBING SYSTEM WITH THE WORK OF OTHER TRADES PRIOR TO ANY FABRICATION OR INSTALLATION. FIELD VERIFY ALL DIMENSIONS AND CONDITIONS. REPORT ANY DISCREPANCIES, IN WRITING, TO THE ENGINEER PRIOR TO COMMENCEMENT OF WORK.

4. CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS WITH ALL CHANGES NOTED THEREON AT THE COMPLETION OF THE PROJECT IN ACCORDANCE WITH THE SPECIFICATIONS.

5. PROVIDE ONE YEAR WARRANTY ON ALL PARTS AND LABOR.

6. THE DRAWINGS ARE DIAGRAMMATIC AND INTENDED TO SHOW SCOPE. CONTRACTOR SHALL COORDINATE HIS WORK WITH OTHER TRADES TO PROVIDE THE BEST ARRANGEMENT OF ALL DUCT, PIPE, CONDUIT, ETC.

7. ALL CUTTING AND PATCHING OF THE EXISTING STRUCTURE SHALL BE PROVIDED UNDER OTHER SECTIONS OF THE WORK. PROVIDE NECESSARY REQUIREMENTS TO THE PROJECT SUPERINTENDENT.

8. ALL HOT WATER PIPING AND RECIRCULATION PIPING (EXCEPT RUNOUTS 12 FT. OR SHORTER TO INDIVIDUAL FIXTURES) SHALL BE INSULATED TO MEET THE REQUIREMENTS OF THE 2006 INTERNATIONAL ENERGY CONSERVATION CODE.
9. CONDENSATE DRAINS SHALL BE PROVIDED FOR EACH AIR CONDITIONING UNIT. HORIZONTAL CONDENSATE DRAINS ABOVE ANY CEILING SHALL BE INSULATED WITH MIN. 3/8" THICK CLOSED CELL INSULATION.

10. PIPING:
- A. WASTE, VENT, AND STORM DRAIN PIPING SHALL BE CO-EXTRUDED PVC SCHEDULE 40) PIPE
- B. WATER PIPE SHALL BE CPVC PIPE

- C. CONDENSATE PIPING SHALL BE CO-EXTRUDED PVC (SCHEDULE 40) PIPE
- D. INSIDE GAS PIPING SHALL BE BLACK IRON SCHEDULE 40 WITH MALLEABLE IRON FITTINGS. OUTSIDE SHALL BE GALVANIZED IRON SCHEDULE 40 WITH GALVANIZED FITTINGS. GAS LINE TO BE PAINTED GRAY IN COLOR. A 24 HOUR METERED GAS TEST SHALL BE REQUIRED.

- E. ALL PIPING NOT ENCLOSED IN CONDITION SPACE OR AT EXTERIOR WALLS SHALL BE INSULATED.

- F. PIPING: PVC SCHEDULE 40, SCHEDULE 80 AND CPVC PIPING WITH SOLVENT WELD FITTINGS SHALL BE USED WHERE PERMITTED BY CODE/LOCAL AUTHORITIES

11. ALL VENTS OR EXHAUSTS SHALL BE AT LEAST 10 FT. AWAY OR 3 FT. ABOVE ANY WINDOW, DOOR, OPENING, OR AIR INTAKE.

12. CLEANOUTS SHALL BE INSTALLED PER THE UNIFORM PLUMBING CODE.

13. PROVIDE WATER TIGHT FLASHINGS WHEREVER PIPES PASS THROUGH EXTERIOR WALLS, ROOFS, OR FLOORS.

14. PROVIDE ISOLATION FOR ALL PIPES THAT COME IN CONTACT WITH THE STRUCTURE.

15. LOCATION OF EXISTING UTILITIES AND POINTS OF CONNECTION ARE APPROXIMATE. CONTRACTOR SHALL VERIFY EXACT LOCATIONS AND DEPTHS OF EXISTING UTILITIES AND SERVICES PRIOR TO STARTING WORK OF THIS SECTION. IF INDICATED POINTS OF CONNECTION CANNOT BE MADE TO EXISTING UTILITIES AS FOUND, THE CONTRACTOR SHALL NOTIFY THE ENGINEER PRIOR TO INSTALLING ANY WORK WHICH MAY BE AFFECTED.

16. VALVES SHALL BE NIBCO, JENKINS, HAMMOND, RED & WHITE OR APPROVED EQUAL. SERVICE PRESSURE SHALL BE SUITABLE FOR SERVICE INTENDED. THE MAIN WATER SHUT OF VALVE SHALL BE A FULL PORT BALL TYPE AND APPROVED FOR SERVICE INTENDED.

17. CONTRACTOR SHALL PROVIDE ALL SHUT OFF VALVES AS NECESSARY TO ISOLATE ANY EQUIPMENT, PLUMBING ITEMS, OR FIXTURES THAT MAY NEED SERVICING OR ARE SUBJECT TO FAILURE WHETHER OR NOT SUCH VALVES ARE SHOWN ON THE DRAWINGS.

18. PROVIDE HANGERS AND SUPPORTS AS REQUIRED. PLUMBERS TAPE AND WIRE ARE NOT ACCEPTABLE.

19. CONTRACTOR IS RESPONSIBLE FOR HIS OWN TRENCHING, BACKFILL, AND COMPACTION OF TRENCHES NECESSARY TO COMPLETE HIS SCOPE OF WORK. BACKFILLED TRENCHES SHALL BE RETURNED TO THEIR ORIGINAL GRADE UNLESS NOTED OTHERWISE.

20. CONTRACTOR SHALL AFFIX A MAINTENANCE LABEL TO ALL EQUIPMENT REQUIRING ROUTINE MAINTENANCE AND SHALL PROVIDE MAINTENANCE AND OPERATIONAL MANUALS IN ACCORDANCE WITH THE SPECIFICATIONS.

21. ALL EQUIPMENT THAT REQUIRES KEYS OR SPECIAL TOOLS TO OPERATE SHALL SUPPLY THE OWNER WITH TWO OF ANY SUCH KEYS OR TOOLS FOR EACH PIECE OF EQUIPMENT THAT REQUIRE THE SAME.

25. ANY CHANGE OR DEVIATION FROM THESE PLANS OR SPECIFICATIONS SHALL REQUIRE THE APPROVAL, IN WRITING, OF THE ENGINEER PRIOR TO COMMENCEMENT OF SUCH WORK.

26. ALL PLUMBING, ELECTRICAL, AND GAS LINES SHALL BE CONCEALED WITHIN THE BUILDING STRUCTURE TO AS GREAT EXTENT AS POSSIBLE. ALL LINES NOT CONCEALED SHALL BE SECURED 6" OFF THE FLOOR AND 3/4" FROM THE WALLS USING STANDOFF BRACKETS.

27. AN APPROVED BACKFLOW PREVENTOR SHALL BE PROPERLY INSTALLED UPSTREAM OF ANY POTENTIAL HAZARD BETWEEN THE POTABLE WATER SUPPLY AND SOURCE OF CONTAMINATION.

28. WATER SUPPLY CARBONATORS SHALL BE PROTECTED BY AN APPROVED REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTOR. THE RELIEF VALVE SHALL DRAIN IN-DIRECTLY TO A FLOOR SINK WITH A 1" MIN. AIR GAP.

PLUMBING LEGEND		
SYMBOL	ABBREV	DESCRIPTION
	SS or W	NEW SEWER OR WASTE
	V	NEW VENT
	CW	NEW COLD WATER
	HW	NEW HOT WATER
	G	NEW GAS
	CD	NEW CONDENSATE DRAIN
	CA	COMPRESSED AIR
	FCO	FLOOR CLEANOUT
	WCO	WALL CLEANOUT
	FD	FLOOR DRAIN
	FS	FLOOR SINK
	TP	TRAP PRIMER & TRAP PRIMER PIPING
	SOV	SHUT-OFF VALVE
	CV	CHECK VALVE
	PRV	BACKFLOW PREVENTER W SOV'S
	T & P	
	DN	PIPE DOWN
	UP	PIPE UP
	POC	POINT OF CONNECTION
	-	PLUMBING NOTE CALL-OUT
	ABV	ABOVE
	AFF	ABOVE FINISH FLOOR
	AP	ACCESS PANEL
	BEL	BELOW
	BLDG	BUILDING
	CLG	CEILING
	CONT	CONTINUATION
	EL	ELEVATION
	FIN	FINISH
	FL	FLOOR
	GR	GRADE
	NTS	NOT TO SCALE
	OC	ON CENTER
	S= %	SLOPE AT A PERCENTAGE
	SHT	SHEET
	TYP	TYPICAL
	VTR	VENT THRU ROOF

PLUMBING / GENERAL NOTES

BATHTUBS AND WHIRLPOOL BATHTUBS. THE MAX. HOT WATER TEMPERATURE DISCHARGING SHALL BE LIMITED TO 120 DEGREES. CPC 414/2019

BATHTUBS WASTE OPENING IN FLOOR OVER CRAWL SPACES SHALL BE PROTECTED BY A METAL SCREEN NOT EXCEEDING 12" OR SOLID COVER. CPC 313.12-4/2019

SHOWERS AND TUB-SHOWERS COMBINATIONS IN ALL BUILDINGS SHALL BE PROVIDED WITH INDIVIDUAL CONTROL VALVES OF THE PRESSURE BALANCE, THERMOSTATIC, OR COMBINATION OF BOTH THAT PROVIDE SCALD AND THERMAL SHOCK PROTECTION. VALVES SHALL BE ADJUSTED TO DELIVER A MAXIMUM MIXED WATER SETTING OF 120 DEGREES FAHRENHEIT. THE WATER HEATER THERMOSTAT SHALL NOT BE CONSIDERED A SUITABLE CONTROL FOR MEETING THIS PROVISION. 418.0 CPC2019

VERIFY AND WHERE WATER PRESSURE EXCEEDS 80 PSI AN APPROVED PRESSURE REGULATOR PRECEDED BY AN ADEQUATE STRAINER SHALL BE INSTALLED 608.2 CPC / 2019

1-INSTALL TEMPERATURE AND PRESSURE RELIEF VALVE WITH MINIMUM 3/4" DRAIN PIPE AND TERMINATE TO THE EXTERIOR OF THE BUILDING OVER WINDOW, DOOR OR VISIBLE LOCATION. DISCHARGE FROM A RELIEF VALVE INTO A WATER HEATER PAN SHALL BE PROHIBITED CPC 608.5, 510.8.

2-PROVIDE (ON THE PLANS) A GAS PIPING DIAGRAM OF THE GAS PIPING SYSTEM THAT INCLUDES ALL PIPE SIZES, PIPE LENGTHS AND BTU RATINGS.

- 3-SUBMIT GAS LOAD CALCULATIONS IN ACCORDANCE WITH CPC TABLE 12-8 TO VERIFY THE PIPE SIZES ARE ADEQUATE FOR THE MAXIMUM DELIVERY CAPACITY OF CUBIC FEET OF GAS PER HOUR.
- 4- A WHOLE HOUSE HAS TEST IS REQUIRED UPON COMPLETION OF THE INSTALLATION, ALTERATION, OR REPAIR OF ANY GAS PIPING.
- THE CITY SHALL BE NOTIFIED WHEN GAS PIPING IS READY FOR INSPECTION.
- 5- 2 GPM SHOWER FIXTURE, MAX 1.5 GPM BATHROOM FAUCET, MAX. 2 GPM KITCHEN FAUCET, AND MAX 1.28 WATER CLOSET TO CONFORM TO CITY GREEN REQUIREMENTS.

BATHROOMS: PROVIDE AN EXHAUST FAN (AT LEAST 50 CFM) DUCTED TO THE OUTSIDE (MINIMUM 4" DIAMETER FLEX DUCT WITH A MAXIMUM LENGTH OF 70' WITH A MINIMUM VENTILATION RATE OF 100 CFM. IDENTIFY THE REQUIREMENT FOR A BACKDRAFT DAMPER ON THE DUCT, AN ENERGY STAR COMPLIANT EXHAUST FAN THAT IS CONTROLLED BY A HUMIDITY SENSOR THAT IS CAPABLE OF BEING ADJUSTED BETWEEN ≤ 50-PERCENT TO 80-PERCENT HUMIDITY; AND A SEPARATE SWITCH FROM THE LIGHT UNLESS THE FAN IS ALLOWED TO OPERATE WITH THE LIGHT SWITCHED OFF.

6-NOTE THAT ALL PLUMBING VENTS SHALL TERMINATE NOT LESS THAN 6" ABOVE ROOF NOR LESS THAN 1' FROM ANY VERTICAL SURFACE. VENTS SHALL TERMINATE NOT LESS THAN 10" FROM OR 3' ABOVE ANY WINDOW, DOOR OPENING AIR INTAKE, OR VENT SHAFT NOR 3' FROM LOT LINE. (2019 CPC 906) IF WATER PRESSURE EXCEEDS 80 PSI, AND EXPANSION TANK AND AN APPROVED PRESSURE REGULATOR SHALL BE INSTALLED. (2019 CPC608.2)

NON-REMOVABLE BACK FLOW PRE-VENTER OR RIBB-TYPE VACUUM BREAKER WILL BE INSTALLED ON ALL EXTERIOR HOSE BIBS. (2019 CPC603.4.7)

HOT WATER RE-CIRCULATING SYSTEM IS INSTALLED, THE ENTIRE LENGTH OF HOT WATER PIPES SHALL BE INSULATED. (2008 CALIFORNIA ENERGY REGULATIONS 150 (J)) HOT WATER PIPE FROM THE WATER HEATER TO THE KITCHEN WILL BE INSULATED. (2008 CALIFORNIA ENERGY REGULATIONS 151(F)8 D)

NOTES:

- 1-PROJECTS WHICH DISTURB LESS THAN ONE ACRE OF SOIL SHALL MANAGE STORM WATER DRAINAGE DURING CONSTRUCTION BY ONE OF THE FOLLOWING: A. RETENTION BASINS. B. WHERE STORM WATER IS CONVEYED TO A PUBLIC DRAINAGE SYSTEM, WATER SHALL BE FILTERED BY USE OF A BARRIER SYSTEM, WATTLE OR OTHER APPROVED METHOD.
- 2-SITE GRADING OR DRAINAGE SYSTEM WILL MANAGE ALL SURFACE WATER FLOWS TO KEEP WATER FROM ENTERING BUILDINGS (SWALES, WATER COLLECTION, FRENCH DRAINS, ETC.), CGC SECTION 4.106.3. EXCEPTION: ADDITIONS NOT ALTERING THE DRAINAGE PATH.
- 3-WHEN A SHOWER IS PROVIDED WITH MULTIPLE SHOWER HEADS, THE SUM OF FLOW TO ALL THE HEADS SHALL NOT EXCEED 1.8 GPM @ 80 PSI, OR THE SHOWER SHALL BE DESIGNED SO THAT ONLY ONE HEAD IS ON AT A TIME. CGC SECTION 4.303.1.3.2.
- 4-LANDSCAPE IRRIGATION WATER USE SHALL HAVE WEATHER OR SOIL BASED CONTROLLERS. CGC SECTION 4.304.1.
- 5-THE PLANS THAT A MINIMUM OF 65% OF CONSTRUCTION WASTE IS TO BE RECYCLED. CGC SECTION 4.408.1.
- 6-THE CONTRACTOR SHALL SUBMIT A CONSTRUCTION WASTE MANAGEMENT PLAN, PER CGC SECTION 4.408.2.
- 7-THE BUILDER IS TO PROVIDE AN OPERATION MANUAL (CONTAINING INFORMATION FOR MAINTAINING APPLIANCES, ETC.) FOR THE OWNER AT THE TIME OF FINAL INSPECTION. CGC SECTION 4.410.1.
- 8-THE GAS FIREPLACE(S) SHALL BE A DIRECT-VENT SEALED- COMBUSTION TYPE. WOODSTOVE OR PELLET STOVES MUST BE US EPA PHASE II RATED APPLIANCES. CGC SECTION 4.503.1.

WATER SAVING STANDARDS.

THE WATER SAVING PERFORMANCE STANDARDS FOR A PLUMBING FIXTURE ARE THOSE ESTABLISHED BY THE AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI), CURRENT OR THE FOLLOWING STANDARDS, WHICHEVER ARE THE MORE RESTRICTIVE

- 1.THE MAXIMUM FLOW FROM A SINK OR LAVATORY FAUCET OR A FAUCET AERATOR SHALL NOT EXCEED 0.5 GALLONS OF WATER PER MINUTE AT A PRESSURE OF 60 POUNDS PER SQUARE INCH WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES
- 2.THE MAXIMUM VOLUME OF WATER PER FLUSH FROM A TOILET SHALL NOT EXCEED AN AVERAGE OF 1.28 GALLONS WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES
3. THE MAXIMUM VOLUME OF WATER PER FLUSH FROM A URINAL AND THE ASSOCIATED FLUSH VALVE, IF ANY, SHALL NOT EXCEED AN AVERAGE OF ONE GALLON WHEN TESTED IN ACCORDANCE WITH ANSI TESTING PROCEDURES

SPECIAL NOTICE TO CONTRACTORS

1. ALL CONTRACTORS (GENERAL CONTRACTOR AND SUB-CONTRACTORS) BIDDING THIS PROJECT ARE REQUIRED TO VISIT THE JOB SITE AND VERIFY THE EXISTING CONDITIONS PRIOR TO SUBMITTING THEIR BID. CONTRACTORS ARE TO CAREFULLY REVIEW ALL CONSTRUCTION DOCUMENTS AND NOTE ANY DISCREPANCIES BETWEEN THE CONSTRUCTION DOCUMENTS AND THE CONDITIONS OBSERVED AT THE JOB SITE PRIOR TO SUBMISSION OF ANY BID. THE BUILDING OWNER REPRESENTATIVE LISTED BELOW MAY BE CONTACTED FOR ACCESS TO THE JOB SITE.
2. CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO, GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.
3. CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO, GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.
4. CONTRACTORS ARE RESPONSIBLE FOR VERIFYING THE LOCATION AND CONDITION OF ALL POINTS OF CONNECTION, LOCATION AND CONDITION OF ALL BUILDING (ROOF/FLOOR/CEILING) PENETRATIONS, LOCATION AND CONDITION OF ALL UTILITIES AND BUILDING SYSTEMS INCLUDING, BUT NOT LIMITED TO, GAS, WATER, SEWER, VENT, ELECTRICAL, BUILDING MECHANICAL SYSTEMS, DUCT CONNECTIONS, EXHAUST/OUTSIDE AIR CONNECTIONS, SECURITY, FIRE ALARM, DATA, AND PHONE PRIOR TO SUBMISSION OF THEIR BID.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS

APPEARING HEREIN CONSTITUTE THE

ORIGINAL AND UNPUBLISHED WORK OF THE

DESIGNER AND THE SAME MAY NOT BE

DUPLICATED, USED OR DISCLOSED WITHOUT

CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.


REV. NO.	DESCRIPTION	DATE	BY

PROJECT:


TITLE:  
PLUMBING LIST OF SYMBOLS  
AND GENERAL NOTES

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36:
		NTS
DRAWING NO.		REV.
P O . O		





FIRST FLOOR PLAN



FIRST FLOOR PLAN

GENERAL NOTES:

1. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
2. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
3. REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
4. CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
5. CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
6. ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
7. ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
8. ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
9. CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
10. ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT 1/4" PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT 1/8" PER FOOT.
11. ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT 1/8" PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
12. VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
13. REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

SANITARY SHEET NOTES:

- 1 → WASTE DROP AND 2" VENT RISE.
- 2 → 2" VENT RISE TO HIGH LEVEL.
- 3 → 1-1/2" VENT RISE TO HIGH LEVEL.
- 4 → 3" VENT STACK TO ABOVE TERMINATED NOT LESS THAN 6 INCHES ABOVE THE ROOF NOR LESS THAN 1 FOOT FROM A VERTICAL SURFACE.
- 5 → 4" FLOOR CLEAN-OUT.
- 6 → OUTDOOR FLOOR CLEAN-OUT. REFER TO DWG FOR PIPE SIZE.
- 7 → 3" FLOOR DRAIN.
- 8 → 4" WASTE DROP FROM FLOOR ABOVE
- 9 → 3" ROOF VENT CAP
- 10 → 4" WASTE DROP TO FLOOR BELOW
- 11 → 2" FROM FLOOR SINK
- 12 → 3" WASTE DROP TO FLOOR BELOW

WATER SUPPLY SHEET NOTES:

- 1 → DCW/DHW/DHWR TO ABOVE FLOOR.
- 2 → DCW & DHW DROP IN WALL.
- 3 → DCW/DHW/DHWR FROM BELOW FLOOR.
- 4 → DCW/DHW/DHWR TO BELOW FLOOR.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
PLUMBING. FIRST FLOOR LAYOUTS.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: 3/16"=1'-0"
-----------	-------------	-------------------------------

DRAWING NO. P 1 . 0	REV.
------------------------	------

PLUMBING PIPING MATERIAL SCHEDULE		
PIPING SYSTEM	LOCATION	ACCEPTABLE PIPING MATERIAL
WASTE & VENT	BELOW AND ABOVE GRADE	ASTM D 2665 PVC SCHEDULE 40, SOCKET FITTINGS DWV
	FROM SECOND TO FIRST FLOOR	ASTM A 888 CAST IRON, NO HUB SYSTEM

AS PER CPC 708.1  
ALL PIPE BELOW 4"Ø PIPE SIZE TO BE SLOPED 2%.  
ALL PIPES GREATER THAN 4"Ø PIPE SIZE SHALL BE SLOPED 1%.

As per CPC 906.1, ABS/PVC vent terminations up through the roof exposed to sunlight are required to be protected by water based synthetic latex paints."

Cleanouts are required at the upper most terminals of all horizontal waste lines. Please provide cleanouts location within the floor plan. CPC 707.4.

All Plumbing Works shall comply with 2019 California Plumbing Code, 2019 California Green Building Code and 2019 California Energy Code.

FIXTURE TYPE	MAXIMUM FLOW RATE
Water closets	1.28 gallons/flush
Urinals (wall mounted)	0.125 gallons/flush
Showers	1.8 gpm @ 80 psi
Lavatory faucets-nonresidential	0.5 gpm @60 psi
Kitchen faucets	1.8 gpm @ 60 psi
Metering faucets	gallons/cycle

Cleanouts are required at the upper most terminals of all horizontal waste lines. Please provide cleanouts location within the floor plan. CPC 707.4

FIXTURE TYPE	DRAINAGE F.U VALUE AS LOAD FACTORS
LAVATORY	1
TOILET, PRIVATE	3
BATHTUB	2
LAUNDRY TRAY	2
FLOOR DRAIN 3 INCH TRAP SIZE	3
KITCHEN SINK, DOMESTIC	2

Dia of Pipe (Inches)	MAXIMUM NUMBER OF DRAINAGE FIXTURE UNITS (dfu)			
	Total for Horizontal Branch	Stacks Total Discharge into one branch interval	Total for stack of three branch Intervals or less	Total for stack greater than three branch intervals
1 1/2	3	2	4	8
2	6	6	10	24
2 1/2	12	9	20	42
3	20	20	48	72
4	160	90	240	500
5	360	200	540	1,100
6	620	350	960	1,900

MINIMUM PIPE SIZE PER FIXTURE		
FIXTURE UNIT	DR (INCH)	VENT (INCH)
SHOWER	3	2
WATER CLOSET	4	2
LAVATORY	1-1/2	2
KITCHEN SINK	2	2
HAND SINK	2	2
MOP SINK	2	2
DISHWASHER	1-1/2	2
BATHTUB	3	2
LAUNDRY MACHINE	1-1/2	2

PLUMBING PIPING MATERIAL SCHEDULE		
PIPING SYSTEM	LOCATION	ACCEPTABLE PIPING MATERIAL
DOMESTIC WATER	BELOW GRADE	ASTM B 88 TYPE K SOLDERED COPPER
	ABOVE GRADE	PEX A COMPRESSION JOINT

BUILDING WATER LOAD			
DESCRIPTION	LOAD		PIPE SIZE
	FU	GPM	PEX
DCW	20	14.3	1"
DHW	3	3	3/4"
TOT. COMBINED	21.2	14.8	1-1/4"

POTABLE WATER SUPPLY TO BEVERAGE DISPENSERS  
CORBONATED BEVERAGE DISPENSERS, OR COFFEE MACHINES  
MUST BE PROTECTED BY AN AIR GAP OR VENTED BACK-FLOW PREVENTER. (CPC 603.5.12)

the water heater thermostat shall not be considered a control for meeting this provision" Also see CRFC section 113953 (c) :Handwashing facilities shall be equipped to provide warm water under pressure for a minimum of 15 seconds through a mixing valve or combination faucet. If the Temperature of water provided to a handwashing sink is not readily adjustable at the faucet, the temperature of the water shall be at least 100°F, but not greater than 108°F.

CPC 609.11 & ES 150.0(j):  
Hot Water Piping will have a Minimum Insulation for the following pipe sizes:  
- ½" pipe (½" insulation)  
- ¾" pipe (1" insulation)  
- 1"- 1 ½" pipes (1 ½" insulation)  
- 2" pipes are larger (2" insulation)

Water Heater will be adequately braced to resist seismic forces.  
Provide two straps. One strap at top 1/3 of the tank and one strap at bottom 1/3 of the tank. CPC 507.2

CPC 408.3, 409.4.  
- Public use lavatories limited to 110 degrees F  
- Bathtubs, bidets, and showers 120 degrees F

MINIMUM PIPE SIZE PER FIXTURE

FIXTURE UNIT	CWP (INCH)	HWP (INCH)
SHOWER	1/2	1/2
URINAL	3/4	-
WATER CLOSET	1	-
LAVATORY	1/2	1/2
KITCHEN SINK	3/4	3/4
DISHWASHER	-	3/4
BATHTUB	1/2	1/2
LAUNDRY MACHINE	1/2	1/2

SCHEDULE No. 1  
(E) GAS WATER HEATER SCHEDULE

TAG	GWH-01
LOCATION	SECOND FLOOR
MANUFACTURER	AO SMITH
MODEL	GSP-100
TYPE	GAS
RATED STORAGE (gal.)	33
MAX. NATURAL GAS (BTU/hr)	100,000
UEF	0.90
APPROX. WEIGHT (lbs)	150
DIAMETER (in)	22"
HEIGHT (in)	48.5"
MIN. RECOVERY (GPH)	129
CW/HW CONNECTION SIZE	1"
GAS INLET CONNECTION	-

DOMESTIC WATER PIPE SIZING TABLE

BC PLUMBING CODE (2018) SECTION 2.6.3.1  
DOMESTIC WATER PIPE SIZING IN ACCORDANCE WITH ASPE PLUMBING ENGINEERING DESIGN HANDBOOK VOL. 2.  
BC PLUMBING CODE (2018) SECTION 2.6.3.2.  
THIS TABLE IS TO BE USED IN CONJUNCTION WITH THE HYDRAULIC LOAD REQUIREMENTS FOR EACH FIXTURE.  
BC PLUMBING CODE (2018) SECTION 2.6.3.5.  
DOMESTIC WATER PIPE SIZING IN ACCORDANCE WITH THE MAXIMUM PERMITTED WATER VELOCITIES AS RECOMMENDED BY THE PIPE AND FITTING MANUFACTURER.  
\* PEX VALUES ARE BASED UPON UPONOR AQUAPEX.

PIPE MATERIAL		PEX*			PEX*		DUCTILE IRON & STAINLESS STEEL			COPPER (TYPE L)			COPPER (TYPE K)			COPPER (TYPE K)	
POTABLE WATER SYSTEM		DCW / DHW			DHWR		DCW / DHW			DCW			DHW			DHWR	
MAXIMUM ALLOWABLE VELOCITY		2.4 m/s (8 ft/s)			0.6 m/s (8 ft/s)		2.4 m/s (8 ft/s)			1.5 m/s (5 ft/s)			1.2 m/s (4 ft/s)			0.9 m/s (3 ft/s)	
[MM]	[INCH]	L/S	GPM	FU	L/S	GPM	L/S	GPM	FU	L/S	GPM	FU	L/S	GPM	FU	L/S	GPM
15 MM	1/2"	0.28	4.4	4.5	0.07	1.1	0.36	5.7	7	0.23	3.6	3.5	0.18	2.9	2.5	0.06	1
20 MM	3/4"	0.55	8.8	11.5	0.14	2.2	0.77	12.2	17	0.48	7.6	9	0.38	6.0	7.5	0.32	5
25 MM	1"	0.92	14.5	20.5	0.23	3.6	1.26	20.0	30	0.81	12.8	18	0.65	10.3	14	0.60	9.5
32 MM	1-1/4"	1.36	21.8	34	0.34	5.4	1.80	28.5	54	1.24	19.7	29	0.99	15.7	22	1.01	16
40 MM	1-1/2"	1.91	30.3	55	0.48	7.5	2.80	44.4	102	1.75	27.7	46	1.40	22.2	34	1.51	24
50 MM	2"	3.27	51.9	138	0.82	12.9	4.92	78.0	265	3.04	48.2	120	2.43	38.5	81	2.59	41

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
PLUMBING EQUIPMENT SCHD.  
AND CODE ANALYSIS.

PROJ. NO.

PROJ. ENGR.


SCALE @ 24X36:  
NTS

DRAWING NO.  
P 2 . 0

REV.



Design calculation sheet

Project no:	Date:	20/5/2022	Sheet no.:	1	of	1	Computed by:	Innodez
Subject: Redwood City Dispensary							Checked by:	Innodez
Hot Water Calculation							Approved by:	Innodez
Application Type		Office Building						
Water Temperature		Tin	=	50 °F = 10 °C				
		Tout	=	140 °F = 60 °C				
		ΔT	=	90 °F = 50 °C				
Fixture		GPH		QTY.				
Kitchen Sink		20		x	1	=	20	gph
Basin, Public lavatory		6		x	2	=	12	gph
Service Sink		20		x	1	=	20	gph
Other		GPH		QTY.				
		Maximum Possible Demand		=	52	gph		
		Demand Factor (Custom)		=	0.25	gph		
		Maximum Probable Demand		=	13	gph		
		Maximum Probable Demand		=	0.22	gpm		
				=	0.01	L/s		
		Heater Recovery Capacity		=	0.22	gpm		
		Storage Factor (Custom)		=	0.6			
		Storage Tank Capacity		=	7.8	gal		
					29.5	liters		
				Actual Selection		30 Liters		
Heater or Coil		=	500	x	gpm	x	ΔT	/ Efficiency
Capacity		=	500	x	0.22	x	90	/ 0.9 = 11,000 btu/hr
								= 3.3 kW
				Actual Selection		= 4 kW		

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

- NOTES:
- 1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS, UNLESS STATED OTHERWISE.
  - 2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
  - 3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
  - 4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:


TITLE:  
WATER HEATER  
CALCULATIONS.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36:
		NTS


DRAWING NO.	REV.
P 3 . 0	

EXISTING WATER HEATERS TO REMAIN

Non-Condensing Models  
On-Demand Water Heater  
Troubleshooting Guide



110 Indoor (T-KJr2-IN)  
310 Indoor (T-K4-IN)  
510 Indoor (T-D2-IN)



110 Outdoor (T-KJr2-OS)  
310 Outdoor (T-K4-OS)  
510 Outdoor (T-D2-OS)

A.O. Smith Water Products Company  
500 Tennessee Waltz Parkway  
Ashland City, TN 37015  
Toll Free: 1-877-737-2840

Table of Contents

Troubleshooting Guide

1. SPECIFICATIONS.....3

2. INTRODUCTION.....4

3. NORMAL OPERATION.....5

    Activation.....5

    Operation.....5

    Shutdown.....5

4. INSTALLATION.....6

    Venting.....6

    Gas Line.....6

    Water Line.....6

    Power Supply.....6

5. TROUBLESHOOTING.....7

    Preliminary Checklist.....7

    General Problems.....8

    Error Codes.....12

    Procedures.....19

        Verifying proper Dipswitch settings.....19

        Draining the unit.....21

        Cleaning the filter.....21

        Checking for a Cross Connection.....21

        Check for Reverse Connection.....21

        Check gas supply pressure.....21

        Purge the gas line of air.....22

        Adjusting manifold pressure.....22

        Resetting the computer board.....23

        Checking the OHCF.....24

6. MAINTENANCE.....25

    Rod Assembly.....25

    Burner & Rod Assembly.....26

    Heat Exchanger.....29

    Flow Sensor.....31

    Descaling the Unit.....32

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL  
UNITS, UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN  
CONJUNCTION WITH ALL RELEVANT DESIGNER,  
ENGINEER OR SPECIALIST DRAWINGS AND  
SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL  
DIMENSION AT SITE BEFORE COMMENCING  
WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR  
PROVIDING ALL NECESSARY TEMPORARY  
SUPPORT TO THE BUILDING AND ANY  
ADJACENT STRUCTURES.


REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
WATER HEATER  
CATALOG.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: NTS
-----------	-------------	-----------------------

DRAWING NO. P 3 . 1	REV.
------------------------	------




FIRST FLOOR PLAN

(VERIFY LOCATION IN FIELD)

(E) G/M

ALL GAS LINES ARE EXISTING TO REMAIN.  
NO CHANGE.



ROOF PLAN

GENERAL NOTES:

1. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
2. PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
3. REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
4. CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
5. CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
6. ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
7. ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
8. ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
9. CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
10. ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT  $\frac{1}{4}$ " PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT  $\frac{1}{8}$ " PER FOOT.
11. ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT  $\frac{1}{8}$ " PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
12. VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
13. REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS  
APPEARING HEREIN CONSTITUTE THE  
ORIGINAL AND UNPUBLISHED WORK OF THE  
DESIGNER AND THE SAME MAY NOT BE  
DUPLICATED, USED OR DISCLOSED WITHOUT  
CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS, UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY


PROJECT:

TITLE:  
GAS FIRST FLOOR AND  
ROOF LAYOUTS

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36: $\frac{3}{16}"=1'-0"$
-----------	-------------	---

DRAWING NO. <b>P 4 . 0</b>	REV.
-------------------------------	------





ALL GAS PIPES ARE METALLIC SCHEDULE 40  
THE TOTAL GAS PIPE LENGTH FROM GAS METER TO THE FARTHEST EQUIPMENT IS APPRX. 180 FEET.

ALL GAS LINES ARE EXISTING TO REMAIN.  
NO CHANGE.

### GAS ISOMETRIC RISER DIAGRAM

**1315.1 Pipe Sizing Methods:**

Where the pipe size is to be determined using a method in Section 1315.1.1 through Section 1315.1.3, the diameter of each pipe segment shall be obtained from the pipe sizing tables in Section 1315.2 or from the sizing equations in Section 1315.3. [NFPA 54:6.1]

**1314.4 Size of Piping Outlets**

The size of the supply piping outlet for a gas appliance shall be not less than 1/2 of an inch (15 mm).

The size of a piping outlet for a mobile home shall be not less than 3/4 of an inch (20 mm).

**1313.6.2 Piping Systems Allowed to Be Purged Indoors or Outdoors**

The purging of piping systems shall be in accordance with the provisions of Section 1313.6.2.1 where the piping system meets both of the following:

The design operating pressure is 2 psig (14 kPag) or less.

The piping being purged is constructed entirely from pipe or tubing not meeting the size and length criteria of Table 1313.6.1. [NFPA 54:8.3.2]

**1313.6.1.4 Combustible Gas Indicator**

Combustible gas indicators shall be listed and calibrated in accordance with the manufacturer's instructions. Combustible gas indicators shall numerically display a volume scale from 0 percent to 100 percent in 1 percent or smaller increments. [NFPA 54:8.3.1.4]

**1313.3 Test Pressure**

This inspection shall include an air, CO<sub>2</sub>, or nitrogen pressure test, at which time the gas piping shall stand a pressure of not less than 10 psi (69 kPa) gauge pressure. Test pressures shall be held for a length of time satisfactory to the Authority Having Jurisdiction but in no case less than 15 minutes with no perceptible drop in pressure. For welded piping, and for piping carrying gas at pressures in excess of 14 inches water column (3.5 kPa) pressure, the test pressure shall be not less than 60 psi (414 kPa) and shall be continued for a length of time satisfactory to the Authority Having Jurisdiction, but in no case for less than 30 minutes. For CSST carrying gas at pressures in excess of 14 inches water column (3.5 kPa) pressure, the test pressure shall be 30 psi (207 kPa) for 30 minutes. These tests shall be made using air, CO<sub>2</sub>, or nitrogen pressure and shall be made in the presence of the Authority Having Jurisdiction. Necessary apparatus for conducting tests shall be furnished by the permit holder. Test gauges used in conducting test shall be in accordance with Section 1303.3.3.1 through Section 1303.3.3.4.

**1313.5 Piping System Leak Test**

Leak checks using fuel gas shall be permitted in piping systems that have been pressure-tested in accordance with Section 1313.0. [NFPA 54:8.2.1]

**1313.5.1 Turning Gas On**

During the process of turning gas on into a system of new gas piping, the entire system shall be inspected to determine that there are no open fittings or ends and that all valves at unused outlets are closed and plugged or capped. [NFPA 54:8.2.2]

**1313.5.2 Leak Check**

Immediately after the gas is turned on into a new system or into a system that has been initially restored after an interruption of service, the piping system shall be checked for leakage. Where leakage is indicated, the gas supply shall be shut off until the necessary repairs have been made. [NFPA 54:8.2.3]

**1313.4 Detection of Leaks and Defects**

The piping system shall withstand the test pressure specified without showing any evidence of leakage or other defects. Any reduction of test pressures as indicated by pressure gauges shall be deemed to indicate the presence of a leak unless such reduction can be readily attributed to some other cause. [NFPA 54:8.1.5.1]

**1313.4.1 Detecting Leaks**

The leakage shall be located by means of an approved gas detector, a noncorrosive leak detection fluid, or other approved leak detection methods. [NFPA 54:8.1.5.2]

**1313.4.2 Repair or Replace**

Where leakage or other defects are located, the affected portion of the piping system shall be repaired or replaced and retested. [NFPA 54:8.1.5.3]

**1313.2.4 Designed for (Less Than) Operating Pressures**

Where the piping system is connected to appliances or equipment designed for operating pressures of less than the test pressure, such appliances or equipment shall be isolated from the piping system by disconnecting them and capping the outlets. [NFPA 54:8.1.3.4]

**1313.1.5 Regulators and Valves**


Regulator and valve assemblies fabricated independently of the piping system in which they are to be installed shall be permitted to be tested with inert gas or air at the time of fabrication. [NFPA 54:8.1.1.6]

**1313.1.6 Test Medium**

The test medium shall be air, nitrogen, carbon dioxide, or an inert gas. OXYGEN SHALL NEVER BE USED. [NFPA 54:8.1.2]

**1312.9 Sediment Trap**

Where a sediment trap is not incorporated as a part of the appliance, a sediment trap shall be installed downstream of the appliance shutoff valve as close to the inlet of the appliance as practical, but before the flex connector, where used at the time of appliance installation. The sediment trap shall be either a tee fitting with a capped nipple in the bottom outlet, as illustrated in Figure 1312.9 or other device recognized as an effective sediment trap. Illuminating appliances, ranges, clothes dryers, decorative appliances for installation in vented fireplaces, gas fireplaces, and outdoor grills shall not be required to be so equipped.



BUILDING GAS LOAD	
ITEM	MBH
GWH-01&2	200
AC-01	125
AC-02	125
TOTAL =	550


### GENERAL NOTES:

- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE EXACT PIPE SIZES, INVERT ELEVATIONS, PRESSURES FOR LOCATIONS OF ANY SEWER, WATER PIPING AND WATER METER WITH CIVIL UTILITIES DRAWINGS, AND ANY OTHER ENGINEER AS APPLICABLE.
- PRIOR TO PERFORMING WORK, CONTRACTOR TO COORDINATE PIPE ROUTING WITH ALL OTHER TRADES AND EXISTING FIELD CONDITIONS.
- REFER TO MECHANICAL PLANS FOR PLUMBING SPECIFICATION OF MATERIAL, INSULATION AND INSTALLATION REQUIREMENTS.
- CONTRACTOR IS RESPONSIBLE FOR ROUGH-IN COORDINATION AND LOCATIONS. REFER TO ARCHITECTURAL PLANS FOR LOCATIONS AND FIXTURES.
- CONTRACTOR IS RESPONSIBLE FOR ANY REQUIRED CUTTING AND PATCHING.
- ALL NOTCHING, BORING, AND CUTTING OF HOLES IN WALL STUDS AND FLOOR JOISTS SHALL BE PERFORMED BASED ON THE LATEST ADOPTED AND APPROVED EDITION OF THE BUILDING CODE.
- ALL PLUMBING FIXTURES SHALL BE OF WATER CONSERVATION TYPE AS REQUIRED BY LOCAL AUTHORITY HAVING JURISDICTION.
- ALL WATER PIPING SHALL BE INSTALLED ON INTERIOR SIDE OF THE BUILDING WALL INSULATION.
- CONTRACTOR SHALL PROVIDE VALVES LOCATED ABOVE LAY-IN CEILING OR 24"x24" CEILING ACCESS PANEL COORDINATE FINAL LOCATION AND SIZE WITH ARCHITECT. PROVIDE BALANCING VALVES FOR HOT WATER RETURN SYSTEM AS REQUIRED.
- ALL SANITARY DRAINAGE PIPING 3" AND SMALLER SHALL BE SLOPED AT 4" PER FOOT. PIPING 4" AND LARGER SHALL BE SLOPED AT 8" PER FOOT.
- ALL CONDENSATE DRAIN PIPING SHALL BE SLOPED AT 8" PER FOOT AND PROVIDE ACCESSIBLE CLEANOUTS AT ALL CHANGES OF DIRECTION.
- VENTS THAT TERMINATE AT THE ROOF SHALL BE A MINIMUM OF 10' FROM ANY FRESH AIR INTAKE.
- REFER TO THE PLUMBING DIAGRAMS FOR GUIDANCE OF INSTALLATION INTENT. CONTRACTOR IS TO PROVIDE ALL COMPONENTS NECESSARY TO MEET THE DESIGN INTENT, WHETHER SHOWN IN DIAGRAM OR NOT.


### GAS PIPING INSTALLATIONS

TABLE 402.4(1) SCHEDULE 40 METALLIC PIPE														Gas		Natural	
														Inlet Pressure		Less than 2 psi	
														Pressure Drop		0.3 in. w.c.	
														Specific Gravity		0.60	
PIPE SIZE (inch)																	
Nominal	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	5	6	8	10	12			
Actual ID	0.622	0.824	1.049	1.380	1.610	2.067	2.469	3.068	4.026	5.047	6.065	7.981	10.020	11.938			
Length (ft)	Capacity in Cubic Feet of Gas Per Hour																
10	131	273	514	1,060	1,580	3,050	4,860	8,580	17,500	31,700	51,300	105,000	191,000	303,000			
20	90	188	353	726	1,090	2,090	3,340	5,900	12,000	21,800	35,300	72,400	132,000	208,000			
30	72	151	284	583	873	1,680	2,680	4,740	9,660	17,500	28,300	58,200	106,000	167,000			
40	62	129	243	499	747	1,440	2,290	4,050	8,270	15,000	24,200	49,800	90,400	143,000			
50	55	114	215	442	662	1,280	2,030	3,590	7,330	13,300	21,500	44,100	80,100	127,000			
60	50	104	195	400	600	1,160	1,840	3,260	6,640	12,000	19,500	40,000	72,600	115,000			
70	46	95	179	368	552	1,060	1,690	3,000	6,110	11,100	17,900	36,800	66,800	106,000			
80	42	89	167	343	514	989	1,580	2,790	5,680	10,300	16,700	34,200	62,100	98,400			
90	40	83	157	322	482	928	1,480	2,610	5,330	9,650	15,600	32,100	58,300	92,300			
100	38	79	148	304	455	877	1,400	2,470	5,040	9,110	14,800	30,300	55,100	87,200			
125	33	70	131	269	403	777	1,240	2,190	4,460	8,080	13,100	26,900	48,800	77,300			
150	30	63	119	244	366	704	1,120	1,980	4,050	7,320	11,900	24,300	44,200	70,000			
175	28	58	109	224	336	648	1,030	1,820	3,720	6,730	10,900	22,400	40,700	64,400			
200	26	54	102	209	313	602	960	1,700	3,460	6,260	10,100	20,800	37,900	59,900			
250	23	48	90	185	277	534	851	1,500	3,070	5,550	8,990	18,500	33,500	53,100			
300	21	43	82	168	251	484	771	1,360	2,780	5,030	8,150	16,700	30,400	48,100			
350	19	40	75	154	231	445	709	1,250	2,560	4,630	7,490	15,400	28,000	44,300			
400	18	37	70	143	215	414	660	1,170	2,380	4,310	6,970	14,300	26,400	41,200			
450	17	35	66	135	202	389	619	1,090	2,230	4,040	6,540	13,400	24,400	38,600			
500	16	33	62	127	191	367	585	1,030	2,110	3,820	6,180	12,700	23,100	36,500			
550	15	31	59	121	181	349	556	982	2,000	3,620	5,870	12,100	21,900	34,700			
600	14	30	56	115	173	333	530	937	1,910	3,460	5,600	11,500	20,900	33,100			
650	14	29	54	110	165	318	508	897	1,830	3,310	5,360	11,000	20,000	31,700			
700	13	27	52	106	159	306	488	862	1,760	3,180	5,150	10,600	19,200	30,400			
750	13	26	50	102	153	295	470	830	1,690	3,060	4,960	10,200	18,500	29,300			
800	12	26	48	99	148	285	454	802	1,640	2,960	4,790	9,840	17,900	28,300			
850	12	25	46	95	143	275	439	776	1,580	2,860	4,640	9,530	17,300	27,400			
900	11	24	45	93	139	267	426	752	1,530	2,780	4,500	9,240	16,800	26,600			
950	11	23	44	90	135	259	413	731	1,490	2,700	4,370	8,970	16,300	25,800			
1,000	11	23	43	87	131	252	402	711	1,450	2,620	4,250	8,720	15,800	25,100			
1,100	10	21	40	83	124	240	382	675	1,380	2,490	4,030	8,290	15,100	23,800			
1,200	NA	20	39	79	119	229	364	644	1,310	2,380	3,850	7,910	14,400	22,700			
1,300	NA	20	37	76	114	219	349	617	1,260	2,280	3,680	7,510	13,700	21,800			
1,400	NA	19	35	73	109	210	335	592	1,210	2,190	3,540	7,270	13,200	20,900			
1,500	NA	18	34	70	105	203	323	571	1,160	2,110	3,410	7,010	12,700	20,100			
1,600	NA	18	33	68	102	196	312	551	1,120	2,030	3,290	6,770	12,300	19,500			
1,700	NA	17	32	66	98	189	302	533	1,090	1,970	3,190	6,550	11,900	18,800			
1,800	NA	16	31	64	95	184	293	517	1,050	1,910	3,090	6,350	11,500	18,300			
1,900	NA	16	30	62	93	178	284	502	1,020	1,850	3,000	6,170	11,200	17,700			
2,000	NA	16	29	60	90	173	276	488	1,000	1,800	2,920	6,000	10,900	17,200			







1 TYPICAL WASTE AND VENT RISERS  
SCALE: NONE




2 TRAP PRIMER  
SCALE: NONE




3 FLOOR DRAIN WITH TRAP SEAL PROTECTION  
SCALE: NONE




ANTI-SCALD MIXING VALVE  
NO SCALE




FLOOR SINK DETAIL  
NO SCALE




FLOOR DRAIN DETAIL  
NO SCALE




TRAP PRIMER DETAIL  
NO SCALE




FLOOR CLEANOUT DETAIL  
NO SCALE




CONDENSATE DETAIL  
NO SCALE



VENT THRU ROOF DETAIL  
NO SCALE



WATER ENTRY DETAIL  
NO SCALE



COND. ON FLOOR SINK DETAIL  
NO SCALE

CLIENT:

ADDRESS:

CONFIDENTIALITY STATEMENT:

ALL DRAWINGS AND WRITTEN MATERIALS APPEARING HEREIN CONSTITUTE THE ORIGINAL AND UNPUBLISHED WORK OF THE DESIGNER AND THE SAME MAY NOT BE DUPLICATED, USED OR DISCLOSED WITHOUT CONSENT OF THE DESIGNER.

NOTES:

1. ALL DIMENSIONS HEREIN ARE IN IMPERIAL UNITS. UNLESS STATED OTHERWISE.
2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL RELEVANT DESIGNER, ENGINEER OR SPECIALIST DRAWINGS AND SPECIFICATIONS.
3. THE CONTRACTOR MUST CHECK ALL DIMENSION AT SITE BEFORE COMMENCING WORK.
4. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY TEMPORARY SUPPORT TO THE BUILDING AND ANY ADJACENT STRUCTURES.

REV. NO.	DESCRIPTION	DATE	BY

PROJECT:

TITLE:  
PLUMBING GENERAL  
DETAILS.

PROJ. NO.	PROJ. ENGR.	SCALE @ 24X36:
		NTS

DRAWING NO. REV.

P 5 . 0