CONTINUOUS FLOW CARTON
CASE ELEVATOR & LOWERATOR

Continuous flow elevating with no reciprocating action

Universal mounts for any type of infeed and outfeed conveyor

Quick access maintenance panel

Comprehensive guiding

Available in multiple heights, capacities and payload sizes

Available in Aluminium and Stainless Steel frame

MODU System Continuous Flow Elevator / Lowerator is commonly used to convey food and beverage cases, bagged products, trays, and other similar items. It is designed for high speed and large payload capacity. Continuous Flow Elevators / Lowerator frees up floor space in case/carton palletizing lines, warehousing, or in work-in-progress storage applications by transferring products to an overhead conveyor section. This machine is idle to create aisleways, clearance for forklifts, transfer product between floors and etc.

modu®

MODU System

the Modular Conveyor Company   www.mymodu.com

Specification

- ✓ **Power:** 230VAC or 415VAC, 3-Phase
- ✓ **Compressed Air:** 5bar
- ✓ **Payload:** 4.5kg - 30kg
- ✓ **Min Infeed Height:** 550mm
- ✓ **Outfeed Height:** 2400mm or variable
- ✓ **Throughput:** up to 20 cases/min

Order Guideline

- ⚙ **Standard infeed height:** 750, 900mm or please specify
- ⚙ **Standard outfeed height:** 2400, 3000mm or please specify
- ⚙ **Maximum product size:** 400x400x400 mm

Customized configuration available upon request. Please consult MODU System representative for further information.

Outfeed (Infeed)

Infeed (Outfeed)

Continuous Elevator - at work

modu®

A Global Brand