




CHIUSURE PNEUMATICHE - PNEUMATIC CLAMPS


Chiusura Pneumatica
Pneumatic Clamp **CPR25**



Diam. 25mm
Clamp. 30Nm
Hold. 75Nm
Ang. 15-105°
Weight. 2,0Kg.

[PDF Catalogue](#)

Chiusura Pneumatica
Pneumatic Clamp **CPL40**



Diam. 40mm
Clamp. 140Nm
Hold. 380Nm
Ang. 2-135°
Weight. 2,2-2,7Kg.

[PDF Catalogue](#)


Chiusura Pneumatica
Pneumatic Clamp **CPL50/63**



EU Norm
Diam. 50/63mm
Clamp. 250/420Nm
Hold. 1.300/1.700Nm
Ang. 2,5-135°
Weight. 4,0/5,0Kg.

[PDF Catalogue](#)


Chiusura Pneumatica
Pneumatic Clamp **CPL80**



NEW
EU Norm
Diam. 80mm
Clamp. 1.000Nm
Hold. 2.500Nm
Ang. 3-135°
Weight. 14Kg.

[PDF Catalogue](#)


Chiusura Pneumatica
Pneumatic Clamp **CPR50/63**



HeavyDuty
SteelBody
Diam. 50/63mm
Clamp. 270/420Nm
Hold. 1.000
Ang. 15-120°
Weight. 5,0/5,5Kg.

[PDF Catalogue](#)


Chiusura Pneumatica
Pneumatic Clamp **DL63**



HeavyDuty
SteelBody
Diam. 63mm
Clamp. 400Nm
Hold. 600Nm
Ang. 45-90°
Weight. 10,0Kg.

[PDF Catalogue](#)

Chiusura Pneumatica
Pneumatic Clamp **CPN50/63**




NAAMS Standard
Diam. 50/63mm
Clamp. 250/420Nm
Hold. 1.300/1.700Nm
Ang. 2,5-135°
Weight. 4,0/5,0Kg.

NAAMS

[PDF Catalogue](#)

Chiusura Pneumatica
Pneumatic Clamp **CPN80**




NEW
NAAMS Standard
Diam. 80mm
Clamp. 1.000Nm
Hold. 2.500Nm
Ang. 3-135°
Weight. 11,5Kg.

NAAMS

[PDF Catalogue](#)

Chiusura Manuale
Manual Clamp **MC**




HeavyDuty
SteelBody
Manual
Hold. 160Nm
Ang. 60-120°
Weight. 4,3Kg.

[PDF Catalogue](#)

GRIPPER PNEUMATICI - PNEUMATIC GRIPPERS


Gripper pneumatico
Pneumatic Gripper **B32A/B**



Diam. 32mm
Clamp. 850N/250N
Ang. 22,5-160°
Weight. 1,3-1,5Kg.

[PDF Catalogue](#)


Gripper pneumatico
Pneumatic Gripper **B40A/B**
B40VA/B



Diam. 40mm
TolleranceComp. (V)
Clamp. 1.400/600N
Clamp(V). 1.050/460N
Ang. 22,5-160°
Weight. 2,5Kg.

[PDF Catalogue](#)


Gripper pneumatico
Pneumatic Gripper **G40.1**



Diam. 40mm
Clamp. 130Nm
Hold. 200Nm
Ang. 15-105°
Weight. 1,8Kg.

[PDF Catalogue](#)

Gripper per Transfer
Transfer Gripper **G20**



Diam. 22mm
Clamp. 20Nm
Hold. 50Nm
Ang. 15-90°
Weight. 0,8Kg.

[PDF Catalogue](#)

DISPOSITIVI DI CENTRAGGIO - LOCATOR DEVICE


Disp. Centraggio
Locator Device **DCP30.1**



Diam. 30mm
Stroke. 20-40mm
PushForce. 350N
PullForce. 250N
RadialForce. 70N
AxialTorque. 4Nm
Weight. 0,8-1,1Kg.

[PDF Catalogue](#)


Disp. Centraggio
Locator Device **DCP40**



Diam. 40mm
Stroke. 20-60mm
PushForce. 600N
PullForce. 500N
RadialForce. 150N
AxialTorque. 4-6Nm
Weight. 1,7-2,0Kg.

[PDF Catalogue](#)


Disp. Centraggio
Locator Device **DCP63.1**



Diam. 63mm
Stroke. 20-60mm
PushForce. 1500N
PullForce. 1400N
RadialForce. 200N
AxialTorque. 4-6Nm
Weight. 2,8-3,1Kg.

[PDF Catalogue](#)

Disp. Centraggio
Locator Device **DCP40**
(CNOMO STANDARD)




NEW
Diam. 40mm
Stroke. 25-50mm
PushForce. 600N
PullForce. 500N
RadialForce. 150N
AxialTorque. 4-6Nm
Weight. 1,7-2,0Kg.

CNOMO

[PDF Catalogue](#)


Disp. Centraggio
Locator Device **DCPD40W**



Diam. 40mm
Stroke. 20-40mm
PushForce. 600N
PullForce. 500N
RadialForce. 80N
Ma. 6Nm
Mb. 3Nm
Weight. 1,1-1,2Kg.

[PDF Catalogue](#)

Disp. Centraggio
Locator Device **DCPD63.1**



Diam. 63mm
Stroke. 20-60mm
PushForce. 1500N
PullForce. 1350N
RadialForce. 200N
Ma. 60Nm
Mb. 30Nm
Weight. 3,6-3,8Kg.

[PDF Catalogue](#)

Disp. Centraggio
Locator Device **DCPD50U**




NEW
Toggle Lock System
Diam. 50mm
Stroke. 40mm
PushForce. 1000N
PullForce. 800N
RadialForce. 400N
Ma/Mb 40/80Nm
Weight. 6,7-7,0Kg.

[PDF Catalogue](#)





Cancelare la cache del web browser per essere sicuri di scaricare l'ultima versione dei cataloghi o dei 3Ds / Cancel your web browser cache in order to be sure to download the last release catalogues or 3Ds




SUBLEVELS - UNDERBODYCLAMPS

<p>Sublevel UnderbodyClamp DCA50.1</p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN HighStrengthPin PinØ. 20-40mm Weight. 5,7Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63V.2</p>  <p>SteelBody Toll.Comp.(V). 3mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin PinØ. 20-40mm Weight. 7,0Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63CV</p>  <p>NEW SteelBody Pin-Hole Gap Comp. Toll.Comp.(V). 3mm Diam. 63mm Clamp. 220-280dN Hold. 330dN HighStrengthPin Weight. 7,5Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA63.1</p>  <p>HeavyDuty SteelBody Diam. 63mm Clamp. 700dN Hold. 770dN HighStrengthPin PinØ. 20-40mm Weight. 7,3Kg.</p> <p>PDF Catalogue</p>
<p>Sublevel Orizzontale Horiz. UnderbodyClamp DCA50Z</p>  <p>Horizontal LayOut AluBody Diam. 50mm Clamp. 200dN Hold. 330dN HighStrengthPin PinØ. 18-30mm Weight. 3,0Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA50R</p>  <p>SteelBody Diam. 50mm Clamp. 250dN Hold. 380dN HighStrengthPin PinØ. 18-40mm Weight. 3,4Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DCA40G</p>  <p>LightWeight AluBody Diam. 40mm Clamp. 110dN Hold. 200dN HighStrengthPin PinØ. 16-32mm Weight. 1,8Kg.</p> <p>PDF Catalogue</p>	<p>Sublevel UnderbodyClamp DPA50</p>  <p>SteelBody Diam. 50mm Clamp. 400dN Hold. 470dN Weight. 6,2Kg.</p> <p>PDF Catalogue</p>

RIBALTATORI PNEUMATICI - PIVOT UNITS

<p>Ribaltatore Pneumatico Pivot Unit RFM.2/RF.2</p>  <p>SBI Brake System Hydraulic Control Angles Changeable D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Pneumatico Pivot Unit RCM.2/RC.2</p>  <p>Angles Changeable Hydraulic Control D. 100-125-160-200 Ang. 15°-129° 190-800Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Pneumatico Pivot Unit RP80.2</p>  <p>Diam. 80 Flat Cylinder Ang. 15-135° 100Nm (90°)</p> <p>PDF Catalogue</p>	<p>Ribaltatore Elettrico Electric Pivot Unit GRE</p>  <p>NEW ServoMotor 400V ServoAxis Controlled Ang. 0-135° Torque: 500Nm Hold: 2.000Nm 3,5 Sec. 0°->135° Weight: 61Kg.</p> <p>PDF Catalogue</p>
--	---	--	--

UNITA' LINEARI - LINEAR UNITS

<p>Unità Lineare Linear Unit SLD.1</p>  <p>SBI Lock System 2 Work Positions Stroke Changeable D. 40-50-63-80-125 Stroke. 1-500mm Payload. 40-600Kg. Weight. 9,5-305 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLDS.1</p>  <p>Clamps Lock System 2 Work Positions Stroke Changeable Diam. 63-80-125 Stroke. 1-500mm Payload. 150-600Kg. Weight. 54-285 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLG40</p>  <p>LightWeight Pin Lock System 2 Work Positions Stroke Changeable Diam. 40 Stroke. 1-300 mm Payload. 25 Kg. Weight. 6,5-9,0 Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Linear Unit SLCP63</p>  <p>Togle Lock System 1 Work Positions Stroke Changeable Diam. 63 Stroke. 5-90 mm Payload. 15 Kg. Weight. 8,0 Kg.</p> <p>PDF Catalogue</p>
<p>Unità Lineare Elettrica Servo Linear Unit SLDE</p>  <p>Servo Unit SBI Lock System 4 Work Positions Stroke Changeable Sizes. 63-80 Stroke. 0-500mm Payload. 150-250Kg.</p> <p>PDF Catalogue</p>	<p>Unità Lineare Elettrica Servo Linear Unit SE80</p>  <p>NEW ServoMotor 400V ServoAxis Controlled Stroke 0-250mm 3,0 Sec. 0-250mm Stroke 0-500mm 4,5 Sec. 0-500mm Payload. 250Kg.</p> <p>PDF Catalogue</p>		

MOLTIPLICATORI DI FORZA - FORCE MULTIPLIERS

Moltiplicatore di Forza Force Multipliers **FM100**



SteelBody
Diam. 100mm
FwStroke. 50-200mm
PwStroke. 8mm
FW Force. 460daN
PW Force. 4.500daN
Weight. 20,5-26,5Kg.

[PDF Catalogue](#)