



TTT-SOLF-25

1 DESCRIPTION

TTT-SOLF-25 is a high temperature body low bio-persistence fiber that utilizes a unique spinning technology to create a special fiber with superior thermal and mechanical properties. This fiber is made from a blend of calcium, silica and magnesium and can be exposed to temperatures up to 2192°F.

2 APPLICATIONS

TTT-SOLF-25 is intended for use in removable insulation, cable trays, batteries, expansion joints, ovens, process furnace linings, structural steel fire protection, fire barriers, and more.

3 ADVANTAGES

The unique properties of TTT-SOLF-25 make it flexible, lightweight, inorganic, thermal shock, chemical attack and corrosion resistant with a low level of thermal conductivity and a high tensile strength for low heat storage. TTT-SOLF-25 is also a cost effective alternative to refractory ceramic fiber for applications to 2200°F. TTT-SOLF-25 also has excellent sound absorption, is high heat reflective and easy to fabricate and install.

4 PROPERTY DATA

Characteristics:	Method:	English Values:	Metric Values:
Thickness	ASTM-D-1777	1" +/- 10%	25.4 mm +/- 10%
Temperature Resistance	N/A	Max: 2200°F Operating: 2000°F	Max: 1200°C Operating: 1100°C
Linear Shrinkage	2000°F/24 hrs	0-1.5%	
Specific Heat	(Btu/lbs/F)	0.27	
Color:	N/A	White	

***All values are nominal unless otherwise specified. All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without warranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.