



## TTT-TUFFCOAT-2000

### 1 DESCRIPTION

TTT-TUFFCOAT-2000 is a silicone/fiberglass composite that contains a thick, rugged, coating engineered specifically for removable pads, flanges and valve covers.

### 2 APPLICATIONS

TTT-TUFFCOAT-2000 is intended for preheating blankets, kneeling pads, protective hoses, cables, welding neck protectors, low-temperature heating blankets, and welding gloves.

### 3 ADVANTAGES

Our TTT-TUFFCOAT-2000 material has high-temperature and chemical exposure capabilities, excellent flexibility, is easily sewn, and has a durable construction.

### 4 PROPERTY DATA

<b>Characteristics:</b>	<b>Method:</b>	<b>English Values:</b>	<b>Metric Values:</b>
Weight	N/A	20 oz/yd <sup>2</sup>	680 g/m <sup>2</sup>
Thickness	N/A	0.018 in	0.46 mm
Tensile Strength	N/A	Warp: 370 lbs/in Fill: 310 lbs/in	Warp: 3240 N/50 mm Fill: 2714 N/50 mm
Temperature Resistance	N/A	480°F Continuous Service	249°C Continuous Service
Color	N/A	Gray	

\*\*\*All values are nominal unless otherwise specified. All statements herein are expressions of opinion that we believe to be accurate and reliable but are presented without guaranty or responsibility on our part. Statements concerning the possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.