

# SATIN WEAVE SILICA FABRIC

## PRODUCT & COMPANY IDENTIFICATION

**Product Identifier:** TTT-SIL-3600

**Common Name:** Satin Weave Silica Fabric

**SDS Number:** 

**Revision Date:** 2025

**Supplier Details:** Thermal Tech & Temp Inc.

P.O Box 1304

Crown Point, Indiana 46308

**Contact:** Thermal Tech & Temp Inc.

Phone: 1.800.674.9284

Email: info@thermaltechtemp.com

sales@thermaltechtemp.com

Website: www.thermaltechtemp.com

## HAZARDS IDENTIFICATION

GHS Classification In Accordance with 29 CFR 1910 (OSHA HCS): **Classification of Substance:** 

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 B

Health, Specific target organ toxicity - Single exposure, 3

**GHS Label Elements, Including Precautionary Statements:** 

**GHS Signal Word: WARNING GHS Hazard Pictograms:** 



#### **GHS Hazard Statements:**

H315 - Causes skin irritation H320 - Causes eye irritation

H335 - May cause respiratory irritation

#### **GHS Precautionary Statements:**

P264 - Wash \_ thoroughly after handling.

P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.

P337 - If eye irritation persists: Get medical advice/attention.

P337+313 - Get medical advice/attention.

Hazards not Otherwise Classified (HNOC) or not covered by GHS:

Route of Entry. This material may enter the body through inhalation of nuisance dust

Target Organs: Respiratory system Inhalation: Sore, raspy throat

Skin Contact: Redness and possible rash; itching

Eye Contact: Itching and redness

Ingestion: N/A

**Chemical Ingredients** 

CAS # % Chemical Name

7631-86-9 Silica Fabric

**Silica Fabric:** (CAS 7631-86-9)

**Exposure Limits:** OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1/fcc

## 4 FIRST AID MEASURES

**Inhalation:** Remove person to fresh air. If condition persists, seek medical attention.

**Skin Contact:** Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.

**Eye Contact:** Rinse with water. Do not rub eyes. Seek medical attention.

**Ingestion:** Not applicable.

## 5 FIRE FIGHTING MEASURES

Flash Point (Method Used): >250 C by TOC Flammable Limits
Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.

**Unusual Fire and Explosion Hazards: None** 

## ACCIDENTAL RELEASE MEASURES

Material is solid in roll form. If accidentally released, rewind the material back onto the roll.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Use adequate material handling equipment.

Storage Requirements: Store in a dry place. Use may be at temperature extremes based on product data, but storage should be at

ambient temperature.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust; dust collection
Personal Protective Equipment: HMIS PP, B | Safety Glasses, Gloves

Safety Glasses; cotton gloves; long sleeve clothing Wash thoroughly with soap and water after handling

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Tan Fabric **Physical States:** Solid Specific Gravity or Density: 2.2 **Boiling Point:** N/A Vapor Pressure N/A Potential Hydrogenii: N/A Odor. No odor Solubility: Negligible Freezing or Melting Point: > 3000 degrees F

Vapor Density: N/A

## 10 STABILITY AND REACTIVITY

Chemical Stability:Material is stableConditions to Avoldentification:None known.

Materials to Avoldentification: Strong oxidizing agents.

**Hazardous Decomposition:** Carbon monoxide; carbon dioxide.

Hazardous Polymerization: Will not occur.

## TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

### 12 ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

## 13 DISPOSAL CONSIDERATIONS

Incineration is preferred in a federal, state, or local approved facility.

## 14 TRANSPORT INFORMATION

None special required.

#### 15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Silica fabric (7631-86-9) [n/a%] MASS, NJHS, PA, TSCA

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List NJHS =

NJ Right-to-Know Hazardous Substances

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

#### 16 OTHER INFORMATION

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

**HMIS PPE:** B - Safety Glasses, Gloves

Disclaimer. Although reasonable care has been taken in the preparation of this document, we extend no warranties

> and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the

information for their particular purpose(s).