



# SAFETY DATA SHEET

THERMAL TECH & TEMP



## MARITEX FIBERGLASS FABRIC

1

### PRODUCT & COMPANY IDENTIFICATION

**Revision Date:** 2025  
**Supplier Details:** Thermal Tech & Temp Inc.  
P.O Box 1304  
Crown Point, IN 46308  
**Phone:** 1.800.674.9284  
**Email:** info@thermaltechtemp.com  
sales@thermaltechtemp.com  
**Website:** www.thermaltechtemp.com

2

### HAZARDS IDENTIFICATION

**Classification of Substance:** GHS Classification In Accordance with 29 CFR 1910 (OSHA HCS):  
Health, Respiratory or skin sensitization, 1 Skin  
Health, Skin corrosion/irritation, 2  
Health, Serious Eye Damage/Eye Irritation, 2 B  
Health, Specific target organ toxicity - Single exposure, 3

**GHS Label Elements, Including  
Precautionary Statements:** GHS Signal Word: WARNING  
GHS Hazard Pictograms:



GHS Hazard Statements:  
H317 - May cause an allergic skin reaction  
H315 - Causes skin irritation  
H320 - Causes eye irritation  
H335 - May cause respiratory irritation

GHS Precautionary Statements:  
P264 - Wash \_ thoroughly after handling.  
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.  
P337 - If eye irritation persists: \_  
P337+313 - Get medical advice/attention.

**Hazards not Otherwise Classified  
(HNOC) or not Covered by GHS:** Route of Entry: This material may enter the body through inhalation of nuisance dust.  
Target Organs: Respiratory System.  
Inhalation: Sore, raspy throat.  
Skin Contact: Redness and possible rash; itching.  
Eye Contact: Itching and redness.  
Ingestion: N/A



# SAFETY DATA SHEET

THERMAL TECH & TEMP



## MARITEX FIBERGLASS FABRIC

3

### COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS #	%	Chemical Name
65997-17-3	-	Fibrous Glass

Fibrous Glass (CAS 65997-17-3) (65%-75%)

Exposure Limits: OSHA PEL 15 mg/m3 (total), 5 mg/m3 (respirable). ACGIH TLV 1 f/cc

4

### FIRST AID MEASURES

Inhalation:	Remove person to fresh air. If condition persists, seek medical attention.
Skin Contact:	Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.
Eye Contact:	Rinse with water. Do not rub eyes. Seek medical attention.
Ingestion:	Not applicable.

5

### FIRE FIGHTING MEASURES

Flash Point (Method Used):	>250 C by TOC Flamable
Flammable Limits:	LEL: N/A UEL: N/A
Extinguishing Media:	Water, carbon dioxide, or dry chemical.
Special Fire Fighting Procedures:	Thermal decomposition of fiber coating may produce an irritating mixture of smoke and fumes.
Unusual Fire and Explosion Hazards:	None.

6

### ACCIDENTAL RELEASE MEASURES

Material is a solid in roll form. If accidentally released, rewind material back onto roll.

7

### HANDLING AND STORAGE

Handling Precautions:	Use adequate material handling equipment.
Storage Requirements:	Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

8

### EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls:	Local exhaust; dust collection.
Personal Protective Equipment:	HMISS PP, B   Safety Glasses, Gloves. Safety glasses; cotton gloves; long sleeve clothing. Wash thoroughly with soap and water after handling.



# SAFETY DATA SHEET

THERMAL TECH & TEMP



## MARITEX FIBERGLASS FABRIC

9

### PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Light tan fabric
Physical States:	Solid
Specific Gravity or Density:	2.5
Boiling Point:	N/A
Vapor Pressure	N/A
Potential Hydrogenii:	N/A
Odor:	No odor
Solubility:	Negligible
Freezing or Melting Point:	> 1000°F
Vapor Density:	N/A

10

### STABILITY AND REACTIVITY

Chemical Stability:	Material is stable.
Conditions to Avoid Identification:	None known.
Materials to Avoid Identification:	Strong oxidizing agents.
Hazardous Decomposition:	Carbon monoxide; carbon dioxide.
Hazardous Polymerization:	Will not occur.

11

### TOXICOLOGICAL INFORMATION

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to fibers, while others are not.

12

### ECOLOGICAL INFORMATION

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

13

### DISPOSAL CONSIDERATIONS

Incineration is preferred in a federal, state, or local approved facility

14

### TRANSPORT INFORMATION

None special required.



# SAFETY DATA SHEET

THERMAL TECH & TEMP



## MARITEX FIBERGLASS FABRIC

15

### REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Fibrous Glass (65997-17-3) [N/A%]- TCSA

Regulatory CODE Descriptions

TSCA= Toxic Substances Control Act

16

### OTHER INFORMATION

**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).