



# GHS Safety Data Sheet

Thermal Tech & Temp Inc.

# SDS

---

TTT 1700 SRC

---

**Section 1**

**PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier:** TTT 1700 SRC  
**Common Name:** Silicone Coated Glass Fabric  
**SDS Number:**  
**Revision Date:** 05/07/2019

**Supplier Details:** Thermal Tech & Temp Inc.  
880 North Madison Street  
Crown Point, Indiana 46307

**Contact:** Thermal Tech & Temp Inc.  
**Phone:** 1.800.674.9284  
**Email:** info@thermaltechtemp.com  
sales@thermaltechtemp.com

**Website:** www.thermaltechtemp.com

**Classification of Substance****GHS Classification In Accordance with 29 CFR 1910 (OSHA HCS):**

Health, Skin corrosion/irritation, 2  
 Health, Serious Eye Damage/Eye Irritation, 2 B  
 Health, Specific target organ toxicity - Single exposure, 3

**GHS Label Elements, Including Precautionary Statements****GHS Signal Word: WARNING****GHS Hazard Pictograms:****GHS Hazard Statements**

H315 - Causes skin irritation  
 H320 - Causes eye irritation  
 H335 - May cause respiratory irritation

**GHS Precautionary Statements:**

P264 - Wash \_ thoroughly after handling.  
 P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.  
 P337 - If eye irritation persists: \_  
 P337+313 - Get medical advice/attention.

**Hazards not Otherwise Classified (HNOC) or not Covered by GHS****Route of Entry:** This material may enter the body through inhalation of nuisance dust**Target Organs:** Respiratory system

**Inhalation:** Sore, raspy throat  
**Skin Contact:** Redness and possible rash; itching  
**Eye Contact:** Itching and redness  
**Ingestion:** N/A

**Chemical Ingredients**

CAS#	%	Chemical Name
65997-17-3		Fibrous Glass
68037-59-2	25-31%	Compounded Silicone Coating

**Silica Fabric:** (CAS 65997-17-3)**Exposure Limits:** OSHA PEL 15 mg/m<sup>3</sup> (total), 5mg/m<sup>3</sup> (respirable). ACGIH TLV 1/fcc (69-75%)v

**Inhalation:** Remove person to fresh air. If condition persists, seek medical attention.  
**Skin Contact:** Rinse with copious quantities of cool water. If rash or itching persists, seek medical attention.  
**Eye Contact:** Rinse with water. Do not rub eyes. Seek medical attention.  
**Ingestion:** Not applicable.

**Section 5 FIRE FIGHTING MEASURES**

Flash Point (Method Used): &gt;250 C by TOC                      Flamable Limits

LEL: N/A                      UEL: N/A

Extinguishing Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Thermal decompiston of fiber coating may produce an irritating mixture of smoke and fumes.

Unusual Fire and Explosion Hazards: None

**Section 6 ACCIDENTAL RELEASE MEASURES**

Material is a solid in roll form. If accidently released, rewind material back onto roll

**Section 7 HANDLING AND STORAGE**

**Handling Precautions:**                      Use adequate material handling equipment.

**Storage Requirements:**                      Store in dry place. Use may be at temperature extremes based on product data, but storage should be at ambient temperature.

**Section 8 EXPOSURE CONTOL/PERSONAL PROTECTION**

**Engineering Controls:**                      Local exhaust; dust collection

**Personal Protective Equipment:**                      HMIS PP, B | Safety Glasses, Gloves

**Equipment:**                      Safety Glasses; cotton gloves; long sleeve clothing

Wash ththoroughly with soap and water after handling

**Section 9 PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Silver-Grey Ruber Coating On Fabric	<b>Odor:</b>	No odor
<b>Physical State:</b>	Solid	<b>Solubility:</b>	Negligible
<b>Specific Gravity or Density:</b>	2.4	<b>Freezing or Melting Point:</b>	>1000 degrees F
<b>Boiling Point:</b>	N/A	<b>Vapor Density:</b>	N/A
<b>Vapor Pressure:</b>	N/A		
<b>Potential Hydrogenii:</b>	N/A		

**Section 10 STABILITY AND REACTIVITY**

**Chemical Stability:**                      Material is stable

**Conditions to Avoid:**                      None Known.

**Materials to Avoid:**                      Strong oxidizing agents.

**Hazardous Decomposition:**                      Carbon monoxide, carbon dioxide

**Hazardous Polymerization:**                      Will Not Occur

**Section 11 TOXOLOGICAL INFORMATION**

Direct contact with fiberglass materials or exposure to airborne fiberglass dust may irritate the skin, eyes, nose and throat. Fiberglass can cause itching due to mechanical irritation from the fibers. This is not an allergic reaction to the material. Breathing fibers may irritate the airways resulting in coughing and a scratchy throat. Some people are sensitive to the fibers, while others are not.

**Section 12 ECOLOGICAL INFORMATION**

No known hazards except for airborne fibers caused by nuisance dust. 10 milligrams per cubic meter for fiber diameters less than 7 microns.

**Section 13 DISPOSAL INFORMATION**

Incineration preferred in a federal, state, or local approved facility.

**Section 14 TRANSPORT INFORMATION**

None special required.

**Section 15 REGULATORY INFORMATION**

Component (CAS#) [%] - CODES

-----  
 Compounded Silicone Coating (68037-59-2) [25-31%] [n/a%]  
 Regulatory CODE Descriptions  
 -----

MASS = MA Massachusetts Hazardous Substances List  
 NJHS = NJ Right-to-Know Hazardous Substances  
 PA = PA Right-To-Know List of Hazardous Substances  
 TSCA = Toxic Substances Control Act

**Section 16 OTHER INFORMATION**

**NFPA:** Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

**HMIS III:** Health = 1, Fire = 0, Physical Hazard = 0

**HMIS PPE:** B - Safety Glasses, Gloves



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).