



FIRE BLANKET

1

DESCRIPTION

FIRE BLANKET IS A PLAIN WEAVE FIBERGLASS FABRIC COATED ON TWO SIDES WITH YELLOW ACRYLIC. THE FABRIC AND FIRE-RESISTANT COATING ARE SPECIFICALLY DESIGNED TO RESIST SLAG, SPARKS AND INCIDENTAL FLAME FROM CUTTING TORCHES.

2

APPLICATIONS

THE MAIN APPLICATION FOR THIS PRIDUCT IS FOR USE AS A VERTICAL WELDING CURTAIN FOR SPARK CONTAINMENT, FLASH BARRIERS AND HEAT SHEILDS. IT CAN ALSO BE USED FOR PROTECTIVE CLOTHING APPLICATIONS SUCH AS APRONS AND GLOVES.

3

ADVANTAGES

STANDARD COLORS FOR THE COATING INCLUDE YELLOW, BLUE AND BLACK. SPECIALTY COLORS CAN BE MADE WITH A MINIMUM QUANTITY PURCHASE.

4

PROPERTY DATA

VALUES

WEIGHT:	23.0 oz/sy +/- 10%	FLAME RESISTANCE:	Char Length 1/8" inch max
THICKNESS:	0.034 inches +/- 1-%		Afterglow 1 sec. max.
			Flame out 1sec. max.
TENSILE STRENGTH:	Warp 200 lbs./inch Fill 200 lbs./inch	TEMPERATURE RESISTANCE:	-40 F to +1000F
TEAR STRENGTH:	Warp 45 lbs. Fill 35 lbs.		
BURST STRENGTH:	340 psi		

***All values are nominal unless otherwise specified. All statements herein are expressions of opinion that we believe to be accurate and reliable but are presented without guarantee or responsibility on our part. Statements concerning the possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.