

Artwork Specifications

GENERAL ARTWORK SPECIFICATIONS

ALL FILES SHOULD BE SUPPLIED AS PRINT READY PDFs

IMAGE RESOLUTION

Photos and Illustrations should be 150dpi (or greater) at finished size.

COLOUR

Convert all colours to CMYK (no PMS colours, RGB, LAB etc).

FONTS

Fonts should be embedded or outlined.

BLEED

Minimum 2mm bleed. Crop marks are optional.

SIZE

Trim size of your document should match the order specifications.

CUTLINES

Any cut or crease lines are overlaid onto the artwork as a spot colour named CUT and set to overprint. Crease lines need to be set up the same way and named CREASE.

PAGE COUNT

Page count should matche the order specifications and all pages combined into 1 PDF file per kind of artwork.

DOUBLE SIDED BANNERS

Double sided banners with pockets need to have artwork set up so that the fold matches on the reverse - please request specific artwork specs if you are unsure of the set up.

VINYL CUT LETTERING

All vinyl cut lettering and shapes need to have minimum 2mm bleed. The cutlines overlaid onto the artwork as a spot colour named CUT and set to overprint. If you are having issues with this, please let us know so we can assist.

FILE NAMING CONVENTION

Please follow this naming convention where possible: substrate_your file name_size_double or single sided_quantity







Please check your artwork before submitting it to PrinterHQ.













How to check your Artwork from Adobe Acrobat DC


All colours are converted to CMYK (no PMS colours, RGB, LAB etc).





How to check: Print Production tool > Output Preview

Fonts should be embedded or outlined.



How to check:

- Go to File menu
- Properties
- In **Document Properties**, choose **Fonts**

Crop marks included, minimum 2mm bleed.




Trim size of your document matches the order specifications.



How to check:


- Go to Print Production tool
- Set Page Boxes
- Margin Controls box menu
- Apply to Trim Box

Any cutlines (or crease lines) are overlaid onto the artwork as a spot colour and set to overprint.



How to check: Print Production tool > Output Preview
To see cutlines, you can uncheck the Simulate Overprinting.

- Page count matches the order specifications and is combined into 1 PDF file per kind of artwork.
 - eg. 2 kinds of posters printed 2 sides = 2 PDF files with 2 pages each.



1

All vinyl cut lettering and shapes need to have minimum 2mm bleed. The cutlines overlaid onto the artwork as a **spot colour** named **CUT** and set to overprint.

2

