



RED EXTENDED LIFE ANTIFREEZE

DESCRIPTION:

TECHNICAL PRODUCT INFORMATION

Extended Life Antifreeze & Coolant is an ethylene glycol-based coolant for heavy duty diesel, gasoline and natural powered engines that protects your complete cooling system with no added supplemental coolant additives or testing required. EL Truck Antifreeze & Coolant is available as a concentrate and as a 50/50 pre-diluted.

FEATURES/ BENEFITS

- Improved performance
- 600,000 miles or 12,000 hours of service
- Excellent heat transfer properties
- Less maintenance and reduced costs
- Silicate free formula reduces seal wear
- Improved water pump seal life
- No regular supplemental coolant additives or testing required
- Contains a special long life inhibitor complex for extended drain life
- Contains Bitterant for animal and child protection

RECOMMENDATIONS

Extended Life Antifreeze & Coolant is suitable for use where the following specifications are recommended:

ASTM D3306, D4985, D6210

Caterpillar EC-1

Cummins

Volvo

Detroit Diesel

Navistar

TMC RP 329

TMC RP 338

Extended Life Antifreeze & Coolant Pre-diluted 50/50 is suitable for use where the following specifications are recommended:

ASTM D 4656, D5345, D6210

TMC RP 329

TMC RP 338

APPLICATIONS

Extended Life Antifreeze & Coolant Pre-diluted 50/50 is a fully formulated engine coolant suitable for heavy duty diesel engines found in on-road, off-road, marine, farm, mining and construction equipment.

SPECIAL HANDLING, NOTICES OR WARNINGS

Take precautions when handling all chemicals. Specifically, the workplace must be well ventilated and safety glasses should be worn at all times. Avoid skin contact. These products contain bitterant, which reduces the chance of accidental ingestion. The products are based on mono ethylene glycol and should be kept away from children and animals to prevent exposure.

TYPICAL CHARACTERISTICS

Extended Life Antifreeze (Red)		
Properties	Typical Concentrate	Typical Pre-Diluted 50/50
Appearance	Red	Red
Specific Gravity	1.130	1.06
Freeze Point, °F, (ASTM D1177)	-34°F Diluted 50/50	-34°F as sold
pH, 1:2 dilution with water	8.3 Diluted 50/50	8.3 as sold
Reserve Alkalinity	6.0	3.0 as sold
Silicate, % (as Anhydrous Alkali Metasilicate)	None	None