



GREEN ANTIFREEZE

DESCRIPTION:

Green Antifreeze / Coolant is a premium, ethylene glycol antifreeze / coolant for use year-round in both aluminum and conventional metal engine cooling systems of automobiles, trucks, marine and stationary equipment and heavy-duty diesel engines (with the use of SCAs). Formulated with a low silicate type rust and corrosion inhibitor system which alleviates problems of gel formation and prevents loss of radiator heat transfer capacity. Green Antifreeze pre-diluted 50/50 is a 50/50 mixture of Green Antifreeze / Coolant with deionized water. For child and animal protection, Varouh Oil Green Antifreeze / Coolant contains bitterant.

FEATURES/ BENEFITS

- Universal formula for both automotive and heavy-duty diesel engines (ASTM D 3306 and ASTM D 4985)
- Excellent heat transfer properties
- Premium anti-foam characteristics
- Premium corrosion protection for aluminum, brass, copper, solder, steel and cast iron
- Low silicate formulation
- Amine-free and borax-free
- Concentrate mixes readily with clean tap water
- Pre-diluted product is ready to use and requires no mixing top-up and initial fill
- Compatible with cooling system filters
- Compatible with heavy duty diesel supplemental coolant additives
- Compatible with conventional brands of coolant
- 100% biodegradable in its pure, unused form
- Contains bitterant for child and animal protection

APPLICATIONS

Our Green Antifreeze / Coolant is formulated to meet the stringent aluminum corrosion protection requirements of today's automotive engines. Due to its low concentration of silicate, it also complies with Cummins and other heavy duty diesel engine manufacturer's requirements. This product is also designed for use in industrial internal combustion engines which require an antifreeze / coolant to provide protection against freezing, boil over, and corrosion. Our Green Antifreeze / Coolant is suitable for use where the following specifications are required:

- AAMV
- General Motors GM 1825M
- ASTM D 3306 incl. D 4340
- ASTM D 4985
- ASTM D 6210
- Chrysler MS-7170
- Cummins 90T8-4
- Federal Specification A-A-870
- Ford ESE-M97B44-A
- Mack Truck
- Detroit Diesel 7SE298
- Freightliner
- General Motors GM1899M
- (Performance corresponding to GM6038M)
- Caterpillar EC-I
- J.I. Case JIC501
- John Deere H24B1
- John Deere H24C1
- PACCAR
- SAEJ1034

- TMC RP329
- TMC of ATA RP-302A

RECOMMENDATIONS OR APPROVALS/ LICENSES

Green Antifreeze / Coolant meets:

ASTM D 3306 for automotive service

ASTM D 4985 for heavy duty diesel service

Green Antifreeze / Coolant Pre-diluted 50/50 meets:

ASTM D 4656 for pre-blend automotive service

ASTM D 5345 for pre-blend heavy duty diesel service

TECHNICAL PRODUCT INFORMATION

SPECIAL HANDLING, NOTICES OR WARNINGS

Varouh Oil Green Antifreeze / Coolant has an approximate shelf life of 18 months.

Concentrate product should be mixed prior to use. Always dispose of coolant in accordance with local, state and federal guidelines. These products are not to be used to protect the inside of portable water systems against freezing.

Appearance	Fluorescent Green	Fluorescent Green
Specific Gravity 60 / 60 °F	1.13	1.06
Freezing Point, °F (ASTM D 1177) 50 vol % q.s. aqueous solution	-9	-34
pH (ASTM D 1287), 1:2 dilution with water	10.5	10.3
Reserve Alkalinity (ASTM D 1121), as received	12	6
Silicate, % (as Anhydrous Alkali Metasilicate)	0.09	0.045
Metasilicate)		