



MOLY EP #2

DESCRIPTION:

Varouh Oil, Inc.'s MOLY EP 2 is a lithium based lubricating grease formulated with the highest quality virgin base oils. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties. In addition, MOLY EP 2 has been fortified with Molybdenum Disulfide to provide protection against seizure under high loads and severe shock load conditions.

Typical Properties

NLGI Grade - 2

Soap Type - Lithium

Texture - Smooth

Color - Moly Gray

Worked Penetration, ASTM

D-217, 77°F, 60 Stocks - 265-295

Dropping Point, ASTM

D-2265, ° F Min 350

Oxidation Stability, ASTM

D-942, psi Drop 100 Hrs. Max- 10

Rust & Corrosion, ASTM

D-1743- Pass

Water Washout, ASTM

D-1264, 175° F, Max 10%

Timkin, ASTM D-2509,

OK Load, MIN 40

Four Ball EP, ASTM D-2596

Weld Point Kg, 250

Four Ball Wear, ASTM D-2666

Scar Dia. mm, 40kg, 0.60

Base Oil Viscosity

SUS @ 100° F 900-1100

cSt @ 100° C 15.5-17.5

cSt @ 40° C 180-210

Viscosity Index 88
Pour Point °F 0