



AXIS

VERSATILITY
AND EFFICIENCY
MEET AT THIS
AXIS POINT.



Introducing the Gravely Axis, a multi-tool machine that puts a heavy emphasis on “multi.” It performs a ton of jobs but its main one is maximizing a crew’s time in the field. With its list of attachments and capabilities, it’s not a machine that will sit idle. On the 200 Series models you can also customize its hydraulics to put its brawn where and when you need it. Welcome the Axis, where you’re the pivot point to all its power.



200DW

MODEL - 950012

25 HP / Kubota® D1105

200DT

MODEL - 950010

25 HP / Kubota® D1105

200DTN

MODEL - 950011

25 HP / Kubota® D1105

VERSATILITY Due to compact design

POWERFUL DIESEL ENGINES Models feature Kubota D1105 25 HP Diesel engines.

TIRES OR TRACKS Models include big 18 x 8.5 x 8 bar style tires, 7” or 9” embedded steel rubber tracks.

DRIVER PLATFORM Stand-on position for easy dismount and dash panel access.

SELF-LEVELING BOOM The automatic self-leveling booms that will keep the bucket, pallet forks or attachment level so the operator does not need to keep making adjustments when raising or lowering the boom to allow for more efficient operation.

VARIABLE FLOW SYSTEM Variable Flow control allows precise adjustment of the hydraulic flow to allow inching when trenching.

	200DW	200TN	200T
MODEL NUMBER	950012	950011	950010
DESCRIPTION	DIESEL WHEELED	DIESEL NARROW TRACK	DIESEL WIDE TRACKED
DRIVE TIRES	18 X 8.5 X 8 BAR TREAD TIRES	N/A	N/A
TRACKS	N/A	7"	9"
DIMENSIONS AND WEIGHT			
LENGTH W/STD BUCKET		79.8 IN.	
LENGTH W/O STD BUCKET		63.3 IN.	
WIDTH W/STD BUCKET	42 IN.	36 IN.	42 IN.
WIDTH W/O BUCKET	41 IN.	35.5 IN.	41.5 IN.
WEIGHT W/O STD BUCKET	2,100 LBS.	2,500 LBS.	2,600 LBS.
HEIGHT			
OVERALL OPERATING HEIGHT	84 IN.		85 IN.
HEIGHT AT 45 DEGREE DUMP ANGLE	47.8 IN.		48.8 IN.
GROUND CLEARANCE		6.0 IN.	
ENGINE			
MAKE		KUBOTA	
MODEL		D1105	
FUEL TYPE		DIESEL	
FUEL TANK CAPACITY		10 GALLON	
GROSS HP		25 HP	
COOLING SYSTEM		LIQUID	
MAX INCLINE ANGLE		72 DEGREES	
PERFORMANCE			
MAX LIFT CAPACITY	631 LBS. @ 50% OF TIPPING LOAD	497 LBS. @ 35% OF TIPPING LOAD	489 LBS. @ 35% OF TIPPING LOAD
TIPPING CAPACITY	1,262 LBS.	1,420 LBS.	1,397 LBS.
TOP SPEED	3.2 MPH		3.5 MPH
OPERATIONAL			
STEERING		SINGLE PALM HAND STEERING	
LIFT		SINGLE JOYSTICK	
CURL		SINGLE JOYSTICK	
HYDRAULIC SYSTEM			
AUX SYSTEM FLOW		14 GPM	
LOW FLOW		5.5 GPM	
SYSTEM PRESSURE		3,000 PSI	
GROUND PRESSURE	4.2 PSI	4.2 PSI	4.2 PSI
TANK CAPACITY		11 GALLON	
ATTACHMENTS OFFERED			
36' BUCKET		X	
42" BUCKET	X	X	X
PALLET FORKS	X	X	X
WARRANTY			
UNIT	1 YEAR/1000 HOUR COMMERCIAL, 3 YEAR ENGINE		

