

GRAVELY

PRO TURN 300

COMFORT AND DURABILITY, YARD AFTER YARD...

Taking mowing to the next level thanks to its innovative features and superior cutting performance.

5YR
FIVE YEAR OR 1250 HOUR
WARRANTY



FULLY WELDED TUBULAR FRAME

One glance and you can see its strength and ruggedness. Its wide front rail distributes weight for superior balance. Also supports the deck lift for easy engagement. Includes a limited lifetime warranty.

PARKER TRANSAXLES

Parker HTJ transaxles deliver a top speed of 11mph and have a 12cc pump. Filters are easily accessed from the rear for easy maintenance. This is one complete system which eliminates the need for additional parts, saving both time and money.

X-FACTOR® 3 DECK

The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

DIAL HEIGHT ADJUSTMENT

The dial wheel allows easy height adjustment between one and five inches. Toolless adjustable foot pedal with internal assist springs helps lift the deck with little effort.



52"

MODEL - 992528

25.5 HP / Kawasaki® FX801 Engine

60"

MODEL - 992529

29.5 HP / Kawasaki® FX850 EFI Engine

72"

MODEL - 992526

31 HP / Kawasaki® FX921V Engine

MODEL - 992525

31 HP / Kawasaki® FX921V Engine

★ MADE IN THE UNITED STATES ★
★ WITH GLOBALLY SOURCED PARTS ★

PRO-TURN® 300



See your professional Gravelly® dealer for complete warranty details.

	352	360	360	372
MODEL NUMBER	992528	992529	992526	992525
ENGINE	KAWASAKI FX801	KAWASAKI FX801 EFI	KAWASAKI FX921V	KAWASAKI FX921V
HORSEPOWER	25.5 HP	29.5 HP	31 HP	31 HP
DISPLACEMENT	852 CC	852 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTJ TRANSMISSION			
FUEL CAPACITY	12.5 GAL			
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	11 MPH / 5 MPH			
DECK				
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT			
DECK CONSTRUCTION	X-FACTOR® 3 DECK			
NUMBER OF SPINDLES	3			
BLADE TIP SPEED (FPM)	18,000			
SPINDLE HOUSING MATERIAL	LARGE SERVICEABLE FORGED ALUMINUM BEARING			
SPINDLE BEARINGS	DOUBLE ROLLER BEARINGS			
DECK ENGAGEMENT	OGURA GT2.75	OGURA GT3.5		
CUTTING WIDTH	52 IN	60 IN	60 IN	72 IN
CUTTING HEIGHTS	1.0 IN - 5.5 IN			
CUTTING POSITIONS	19			
WHEELS				
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES			
FRONT	15 X 6-6 SEMI-PNEUMATIC			
REAR	24 X 12-16 BIAS PLY TURF			
FEATURES				
SEAT	SUSPENSION PLUSH SEAT WITH ARM RESTS			
FOLDABLE ROPS	STANDARD			
MACHINE				
WEIGHT	1320 LBS	1346 LBS	1350 LBS	1472 LBS
LENGTH	83 IN			
WIDTH (w/o CHUTE)	55 IN	63 IN		75 IN
WIDTH (w/ CHUTE)	67 IN	75 IN		87 IN
HEIGHT (w/ ROPS EXT/DOWN)	76.0 IN /47.8 IN			
WARRANTY				
UNIT	5 YEAR/1250 HOUR COMMERCIAL/NO HOUR LIMIT FIRST 2 YEARS- SEE YOUR PROFESSIONAL GRAVELY DEALER FOR COMPLETE WARRANTY DETAILS			
DECK SHELL & FRAME	LIMITED LIFETIME			

ATTACHMENTS & ACCESSORIES

- MULCHING KIT
- ELECTRIC DECK LIFT KIT
- TRAILER KIT KIT
- LED HEADLIGHT KIT
- POWERED BAGGER KIT
- OCDC KIT
- SUNSHADE KIT
- REAR TWEEL KIT
- RADIAL DRIVE CONVERSION KIT
- WHEEL COVER KIT
- LASEREDGE BLADE KIT
- TUNE UP KIT

