


A TRUE COMMERCIAL-QUALITY MOWER BUILT FOR PROFESSIONALS.

This is a commercial-grade mower for professionals who want rugged durability without sacrificing features and performance.





One glace and you can see its strength and ruggedness. Its wide front rail distributes weight for superior balance. Also supports the deck lift for easy engagement. Includes a limited lifetime warranty.

PARKER® TRANSAXLES

Parker® HTG transaxles deliver a top speed of 11mph and have a 12cc pump. Filters are easily accessed from the rear for easy maintenance. This is one complete system which eliminates the need for additional parts, saving both time and money.

X-FACTOR® 3 DECK

The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

AIR RIDE SEAT

Isolated mounting absorbs more shock while the high-back seat with lumbar support and padded armrests deliver cushioned comfort.

52"

MODEL - 992510

27 HP / Kawasaki® FX850V Engine

GRAVE

60"

MODEL - 992511

31 HP / Kawasaki® FX921V Engine

MODEL - 992530

 $38.5~\mathrm{HP}$ / Kawasaki $^{\circ}$ FX1000V EFI Engine

72"

MODEL - 992512

31 HP / Kawasaki® FX921V Engine

MODEL - 992531

38.5 HP / Kawasaki® FX1000V EFI Engine

** MADE UNITED STATES**

** WITH GLOBALLY SOURCED PARTS **

PRO-TURN 500



See your professional Gravely® dealer for complete warranty details.

	552	560	560	572	572	
MODEL NUMBER	992510	992511	992530	992512	992531	
ENGINE	KAWSAKI FX850V	KAWASAKI FX921V	KAWASAKI FX1000 EFI	KAWASAKI FX921V	KAWASAKI FX1000 EFI	
HORSEPOWER	27 HP	31 HP	38.5 HP	38.5 HP	31 HP	
DISPLACEMENT	852 CC	999 CC	999 CC	999 CC	999 CC	
DRIVE SYSTEM	PARKER® HTG TRANSMISSION					
FUEL CAPACITY	12.5 GAL					
GROUND SPEED (APPROX. Mph) (Forward/ Reverse)	15 MPH / 6 MPH					
DECK						
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT					
DECK CONSTRUCTION	X-FACTOR® 3 DECK					
NUMBER OF SPINDLES	3					
BLADE TIP SPEED (FPM)	18,000					
SPINDLE HOUSING MATERIAL	LARGE SERVICEABLE FORGED ALUMINUM BEARING					
SPINDLE BEARINGS	IMPROVED DOUBLE ROLLER BEARINGS					
DECK ENGAGEMENT	OGURA® GT3.5					
CUTTING WIDTH	52 IN.	60 IN.	60 IN.	72 IN	72 IN	
CUTTING HEIGHTS	1.0 IN 5.5 IN					
CUTTING POSITIONS	19					
WHEELS						
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES					
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC					
REAR	26 X 12-16 RADIAL TURF					
FEATURES						
SEAT	AIR RIDE PLUSH SEAT WITH ARM RESTS					
FOLDABLE ROPS	STANDARD					
MACHINE						
WEIGHT	1447 LBS	1487 LBS	1580 LBS	1477 LBS	1580 LBS	
LENGTH	84 IN	84 IN	84 IN	86.2 IN	86.2 IN	
WIDTH (w/o CHUTE)	51 IN	63 IN	63 IN	75 IN	75 IN	
WIDTH (w/ CHUTE)	63 IN	75 IN	75 IN	87 IN	87 IN	
HEIGHT (w/ ROPS EXT/DOWN)	76.0 IN/47.8 IN					
WARRANTY						
UNIT	5 YEAR/1500 HOUR C	5 YEAR/1500 HOUR COMMERCIAL/NO HOUR LIMIT FIRST 2 YEARS- SEE YOUR PROFESSIONAL GRAVELY DEALER FOR COMPLETE WARRANTY DETAILS				
DECK SHELL & FRAME		LIMITED LIFETIME				

ATTACHMENTS & ACCESSORIES

MULCHING KIT
ELECTRIC DECK LIFT KIT
TRAILER KIT KIT
LED HEADLIGHT KIT
POWERED BAGGER KIT
OCDC KIT, SUNSHADE KIT
REAR TWEEL KIT
RADIAL DRIVE CONVERSION KIT
WHEEL COVER KIT
LASEREDGE BLADE KIT
TUNE UP KIT

