

MEET YOUR NEW EMPLOYEE OF THE MONTH.

When you add a Pro-Turn 600 to your crew, you cut faster and more efficiently, handling more work in less time.



DIAL-A-HEIGHT

This lets the operator easily adjust the deck height by quarter-inch increments.

PARKER HTG TRANSMISSION

Warranty that matches the machine warranty and allows up to 15 mph operation. Making the Pro-Turn 600 a very efficient mower for any crew trying to get work out of every daylight hour.

X-FACTOR® 3 DECK

The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

OPERATOR POD SYSTEM

Separates the operator from the mower's bouncing and jostling. You'll feel like you're floating as you mow faster and more comfortably, without sacrificing control.

52"

MODEL - 992505

35 HP / Kawasaki® FX1000V Engine

60"

MODEL - 99201

35 HP / Kawasaki® FX1000V Engine

MODEL - 992503

 $38.5~\mathrm{HP}$ / Kawasaki $^{\circ}$ FX1000V EFI Engine

72"

MODEL - 992502

 $35~\mathrm{HP}$ / Kawasaki $^{\circ}$ FX1000V Engine

MODEL - 992504

38.5 HP / Kawasaki® FX1000V EFI Engine

** MADE UNITED STATES**

** WITH GLOBALLY SOURCED PARTS **

PRO-TURN 600



See your professional Gravely® dealer for complete warranty details.

	652	660	660	672	672
MODEL NUMBER	992505	992501	992503	992502	992504
ENGINE	KAWASAKI® FX1000V	KAWASAKI° FX1000V	KAWASAKI* FX1000V-EFI	KAWASAKI° FX1000V	KAWASAKI° FX1000V-EF
HORSEPOWER	35 HP	35 HP	38.5 HP	35 HP	38.5 HP
DISPLACEMENT	999 CC	999 CC	999 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION				
FUEL CAPACITY	12.7 GAL				
GROUND SPEED (APPROX. Mph) (Forward/ Reverse)	15 MPH / 6 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	X-FACTOR® 3 DECK				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	LARGE SERVICEABLE FORGED ALUMINUM				
SPINDLE BEARINGS	DOUBLE ROLLER BEARINGS				
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH				
CUTTING WIDTH	52 IN	60 IN	60 IN	72 IN	72 IN
CUTTING HEIGHTS	1.0 IN - 5.5 IN				
CUTTING POSITIONS	19				
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC				
REAR	26 X 12-16 RADIAL TURF				
FEATURES					
SEAT	HIGH BACK BOLSTERED WITH SUSPENSION OPERATEOR POD SYSTEM				
FOLDABLE ROPS	STANDARD				
MACHINE					
WEIGHT	1551 LBS	1586 LBS	1601 LBS	1646 LBS	1661 LBS
LENGTH	83 IN				
WIDTH (w/o CHUTE)	55 IN	63 IN	63 IN	75 IN	75 IN
WIDTH (w/ CHUTE)	63 IN	75 IN	75 IN	87 IN	87 IN
HEIGHT (w/ ROPS EXT/DOWN)	71.5 IN / 47.8 IN				
WARRANTY					
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS				
DECK SHELL & FRAME	LIMITED LIFETIME				

ATTACHMENTS & ACCESSORIES

MULCHING KIT TRAILER HITCH KIT LED HEADLIGHT KIT STRIPING KIT POWERED BAGGER KIT OCDB KIT SUNSHADE KIT REAR TWEEL KIT RADIAL DRIVE CONVERSION KIT LASEREDGE BLADES TUNE UP KIT POLY SIDE GRASS CATCHER **ELECTRIC DECK LIFT** ENTRY ASSIST HANDLE FRONT TWEFLS GRAVELY EQUIPMENT COVER FRONT WEIGHT KIT

