



# Z-STANCE<sup>®</sup>



## STAND TALL ON THE TURF

You'll ride with pride as you deliver that perfect Gravely cut on the Z-stance. This powerful commercial stand-on mower is easy to maneuver and a breeze to maintain. It's three deck sizes make quick work of a corporate campus or a gated backyard. You take a stand for comfort, ingenuity, and durability when you're on a Z-stance.

**4YR**  
FOUR YEAR OR 750 HOUR  
WARRANTY

## 32"

**MODEL - 994160**

18.5 HP / KAWASAKI<sup>®</sup> FS600

V-TWIN Engine

## 48"

**MODEL - 994159**

22 HP / KAWASAKI<sup>®</sup> FS651

V-TWIN Engine

## 52"

**MODEL - 994158**

22 HP / KAWASAKI<sup>®</sup> FS651

V-TWIN Engine

**ADJUSTABLE CRUISE BAR** Allows the operator to limit and expand the unit's maximum speed in tight working environments.

**THREE DECKS TO CHOOSE FROM** 10 gauge 48" and 52" X-Factor III decks or 32" deck in 7 gauge for added weight.

**POWERFUL V-TWIN ENGINES** 18.5 HP with the 32" or 22 HP on the 48" and 52" models.

**ADDED EFFICIENCY** Ingenious design allows quick and easy access to the fuel tank.

**HEIGHT-OF-CUT SYSTEM** Simple lever control for fast adjustments

**LOWERED CENTER OF GRAVITY**  
Reshaped geometry and redistributed weight provide increased hillside stability and confidence in your ride.

# Z-STANCE®



See your professional Gravelly® dealer for complete warranty details.

	32	48	52
<b>MODEL NUMBER</b>	<b>994160</b>	<b>994159</b>	<b>994158</b>
<b>ENGINE</b>	KAWASAKI® FS600 V-TWIN		KAWASAKI® FS651 V-TWIN
<b>HORSEPOWER</b>	18.5 HP		22 HP
<b>DISPLACEMENT</b>	603 CC		726 CC
<b>DRIVE SYSTEM</b>	HYDRO-GEAR® ZT-3100 TRANSAXLE		
<b>FUEL CAPACITY</b>	4.5 GAL.		
<b>GROUND SPEED (APPROX. Mph)</b> <i>(Forward/Reverse)</i>	7 MPH / 3 MPH		
<b>STARTER</b>	ELECTRIC		
<b>DECK</b>			
<b>DECK MATERIAL</b>	7 GA.		10 GA.
<b>DECK CONSTRUCTION</b>	X-FACTOR® II		X-FACTOR® 3
<b>NUMBER OF SPINDLES</b>	2		3
<b>BLADE TIP SPEED (FPM)</b>	18,220	18,000	18,500
<b>SPINDLE HOUSING MATERIAL</b>	FORGED ALUMINUM		
<b>SPINDLE SHAFT</b>	STEEL		
<b>SPINDLE BEARINGS</b>	BALL BEARING		
<b>DECK ENGAGEMENT</b>	ELECTRIC CLUTCH		
<b>DECK LIFT SYSTEM</b>	MANUAL		
<b>CUTTING WIDTH</b>	32 IN.	48 IN.	52 IN.
<b>CUTTING HEIGHTS</b>	2.0 IN. - 5.0 IN.		1.5 IN. - 5.0 IN.
<b>CUTTING POSITIONS</b>	13		15
<b>WHEELS</b>			
<b>FRONT</b>	11 X 5-6 PNEUMATIC		
<b>REAR</b>	20 X 6.50 - 8 TURF		
<b>MACHINE</b>			
<b>WEIGHT</b>	669 LBS.	744 LBS.	763 LBS.
<b>LENGTH</b>	65.5 IN.		
<b>WIDTH (w/o CHUTE)</b>	32.8 IN.	49.5 IN.	55 IN.
<b>WIDTH (w/ CHUTE)</b>	44.8 IN.	61 IN.	66.75 IN.
<b>HEIGHT</b>	47.5 IN.		
<b>WARRANTY</b>			
<b>UNIT</b>	4 YEAR / 500 HOUR COMMERCIAL		
<b>ATTACHMENTS &amp; ACCESSORIES</b>			
MULCHING KIT, OPERATOR CONTROLLED DISCHARGE BAFFLE, HEADLIGHT KIT, TWEEL KIT, BLADE KIT, GRASS CATCHER			

