

DNS Series

Dual MPPT, Single Phase



Technical Data	GW3000D-NS	GW3600D-NS	GW4200D-NS	GW5000D-NS
PV String Input Data				
Max. DC Input Power (W)	4000	4800	5600	6650
Max. DC Input Voltage (V)	600	600	600	600
MPPT Range (V)	80~550	80~550	80~550	80~550
PV Input Operating Voltage Range (V)	80~600	80~600	80~600	80~600
Start-up Voltage (V)	120	120	120	120
Nominal DC Input Voltage (V)	360	360	360	360
Max. Input Current (A)	11/11	11/11	11/11	11/11
Max. Short Current (A)	13.8/13.8	13.8/13.8	13.8/13.8	13.8/13.8
Maximum Inverter Backfeed Current to Array (A)	0	0	0	0
No. of MPP Trackers	2	2	2	2
No. of Input Strings per Tracker	1	1	1	1
AC Output Data				
Nominal Output Power (W)	3000	3680	4200	4999
Max. Output Apparent Power (VA)	3000	3680	4200	4999
Nominal Output Voltage (V)	220/230	220/230	220/230	220/230
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60
Max. Output Current (A)	13.6	16	19	21.7
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)			
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%
Efficiency				
Max. Efficiency	97.8%	97.8%	97.8%	97.8%
European Efficiency	97.5%	97.5%	97.5%	97.5%
Protection				
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated
Protective Class	Protective Class I	Protective Class I	Protective Class I	Protective Class I
General Data				
Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Convection			
User Interface	LCD & LED	LCD & LED	LCD & LED	LCD & LED
Communication	RS485 or WiFi*1 or LAN	RS485 or WiFi*1 or LAN	RS485 or WiFi*1 or LAN	RS485 or WiFi*1 or LAN
Weight (kg)	13	13	13	13
Size (Width*Height*Depth mm)	354*433*147	354*433*147	354*433*147	354*433*147
Protection Degree	IP65	IP65	IP65	IP65
The Decisive Voltage Class (DVC)	DVC-C	DVC-C	DVC-C	DVC-C
Night Self Consumption (W)	<1	<1	<1	<1
Topology	Transformerless	Transformerless	Transformerless	Transformerless

*: Only compatible with 2.4Ghz network.

*: Please visit GoodWe website for the latest certificates.