



STYLE

7500 / 7500R

7500 - BLACKOUT FABRIC

7500R - RESIDENTIAL
BLACKOUT FABRIC

WEAVING
EXCELLENCE
WITH
INNOVATION



Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 7500 - BLACKOUT							
R13	Ice	0	68	32	0	0.24	0.20
R22	Midnight	0	68	32	0	0.24	0.20
R99	Midnight x2	4	9	87	0	0.57	0.36
S97	Orient x2	4	13	83	0	0.56	0.35
STYLE 7500R - BLACKOUT							
R44	Ice	0	68	32	0	0.24	0.20
R55	Midnight	0	68	32	0	0.24	0.20



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



STYLE 7500

TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values,
test references and technical
definitions visit us at phifer.com.

STYLE 7500

R13 Ice



R39 Cloud




R40 Porcelain



R17 Dune




R19 Stone




R41 Limestone




R97 Mist



R42 Nimbus



R43 Tundra



R20 Odyssey



R21 Orient



S97 Orient x2



R22 Midnight



R99 Midnight x2




STYLE 7500R RESIDENTIAL


R44 Ice



R45 Cloud




R46 Porcelain



R51 Dune




R52 Stone



R47 Limestone




R48 Mist



R49 Nimbus



R50 Tundra



R53 Odyssey



R54 Orient



R55 Midnight



STYLE 7500 / 7500R SPECIFICATIONS

This attractive blackout fabric maintains high quality at an economical price. Style 7500 is presented in a classic range of neutral colors with a unique PVC-free composition and is ideal for commercial applications. SheerWeave Style 7500 is an excellent option when total light blockage is needed and all Style 7500 colors have an off-white backing.

New Style 7500R, a companion to the Style 7500 range, maintains the same look and feel as its namesake at substantial cost savings and is designed specifically for residential use where commercial fire certifications are not required.

STYLE 7500 FIRE CLASSIFICATION	California U.S. Title 19 (small scale)	NFPA 701 TM#1 (small scale)
	CAN/ULC-S 109 (large and small scale)	IBC Section 803.1.1 (Class A Rating)
	CAN/CGSB2-4.162-M80	BS 5867 Part 2 Type B Performance
	NFPA 101 (Class A Rating)	

STYLE 7500R FIRE CLASSIFICATION	California Technical Bulletin 117	IBC Section 803.1.1 (Class B Rating)
	NFPA 101 (Class B Rating)	

Fire classifications are subject to change. Please go to phifer.com for the most current information.

BACTERIA AND FUNGAL RESISTANCE	ASTM E2180	ASTM G21
---------------------------------------	------------	----------

ENVIRONMENTAL CERTIFICATION	GREENGUARD	GREENGUARD Gold
	Certified to these standards for low chemical emissions into indoor air during product usage	

SAFE USE	ANSI/WCMA A 100.1-2007 for lead content	RoHS Compliant	REACH Compliant
	US Consumer Product Safety Commission Section 101		

WARRANTY 5-year interior

ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with	
	ASTM C423-09a	

UV PROTECTION SheerWeave sun control fabrics are an effective way to reduce harmful UV rays. Phifer Incorporated is a proud member of the Skin Cancer Foundation's Corporate Council.

CLEANING INSTRUCTIONS Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

Railroading this fabric is not recommended.

Colors may vary slightly from swatch samples. All variations are within industry standards.

STYLE	7500	7500R
WIDTHS	118" 300 cm	118" 300 cm
ROLL LENGTH	30 Linear Yards 27.4 Linear Meters	30 Linear Yards 27.4 Linear Meters
COMPOSITION	100% Polyester with Acrylic Coating	100% Polyester with Acrylic Coating
MESH WEIGHT	12.14 oz/yd ² 412 g/m ²	10.7 oz/yd ² 363 g/m ²
FABRIC THICKNESS	0.016 in 0.40 mm	0.012 in 0.305 mm
OPENNESS FACTOR	Opaque	Opaque
ACOUSTICAL VALUE	NRC .00 / SAA .03	NRC .00 / SAA .03

