

FEATURES
BTD5, BTD10, BTD25 BTD50

- ◆ Strong Chemical Resistance.
- ◆ Fully autoclavable @ 121°C.
- ◆ Adjustable control through knob makes setting the volume easy.
- ◆ Made of PTFE, FEP, BSG, PP.
- ◆ Vapor pressure Max. 500mbar, viscosity max. 500mm²/s,
Temperature max. 40°C, density max. 2.2g/cm³.
- ◆ 5 Standard Adaptor dia.

Adaptor dia 45 / 40mm.
 Adaptor dia 45 / 32mm.
 Adaptor dia 45 / 38mm.
 Adaptor dia 32 / 25mm.
 Adaptor dia 32 / 28mm.


SPECIFICATIONS
HSN : 90275090

PRODUCT NAME	BOTTLE TOP DISPENSER - CHEMICAL RESISTANCE			
MODEL	BTD5	BTD10	BTD25	BTD50
Volume	0.5-5ml	1.0-10ml	2.5-25ml	5.0-50ml
Sub Division	0.1ml	0.2ml	0.5ml	1.0ml
Accuracy (±)	0.50% 25µl	±0.50% 50µl	±0.50% 125µl	±0.50% 250µl
Precision (≤)	0.10% 5µl	0.10% 10µl	0.10% 25µl	0.10% 50µl
Vapor Pressure	Max. 500mbar			
Solvent Resistance	Strong Chemical Resistance			
Material	PTFE, FEP, BSG, PP			
Auto clavable	@ 121°C			
Bottle	NA			
Standard Adaptor dia	5 sizes			
Density max.	2.2g/cm ³			
Adjustable knob control	Yes			
Dimension (LxWxH) & Gross Weight	290 × 210 × 95 mm & Weight 1.5kg			

* Specifications are subject to change without Notice