

FEATURES
DV60, DV209

- ◆ Microprocessor Based.
- ◆ LCD display.
- ◆ Selectable Speed.
- ◆ Temperature Monitoring.
- ◆ Optional Accessory - Low Viscosity Adaptor (0 Spindle).
- ◆ Instrument has a % of full scale function, which allows the user to select the spindle and speed to measure the liquid.

Applications:

It widely used to determine solvent-based adhesives, latex, Bio Chemicals, Paints, Coatings, Cosmetics, Inks, Pulp, food, etc.


SPECIFICATIONS
HSN : 90278910

PRODUCT NAME	DIGITAL VISCOMETER	
MODEL	DV60	DV209
Measuring Range	50 mPas to 20,00,000 mPas	50 mPas to 60,00,000 mPas
No of speed	8	9
Speed Option	0.3, 0.6, 1.5, 3, 6, 12, 30, 60 rpm	0.1, 0.3, 0.6, 1.5, 3, 6, 12, 30, 60 rpm
Measuring Accuracy	±2% (Newtonian liquid)	
No of Spindle	4	
0 Spindle	Optional 0 Spindle, for 1 ~ 50mPas	
Ambient Temperature	10°C to 85°C	
Interface	RS232C	
Display	LCD	
Power supply	Using Adaptor, AC 220V/50Hz	
Packing Dimension (LxWxH)	380 × 335 × 280 mm	
Net / Gross weight	4.8 kg / 7.4kg	

* Specifications are subject to change without Notice