

FEATURES
MS100S & MS280H

- ◆ Digital LCD display.
- ◆ Control through Knob.
- ◆ Maximum Stirring Volume 2L.
- ◆ Stirring - MS100S.
- ◆ Heating & Stirring - MS280H.

Magnetic stirrer is mainly suitable for liquid mixing, it can simultaneously do heating and stirring of low viscosity liquids or solid liquid mixtures. Its used as an experimental tool in various Universities, Environmental Protection, Sanitation, Epidemic Prevention, Chemical Tap Water, Medical and Other Units.


MS280H
HSN : 84798200
SPECIFICATIONS

PRODUCT NAME	MAGNETIC STIRRER	
MODEL	MS100S	MS280H
Function	Stirring only	Heating & Stirring
Temp. Range & Accuracy	NA	280°C & Acc.±1°C (<100°C)± 3°C(<280°C)
Heating Power (W)	NA	300W
Plate Type	Acrylic	Ceramic
Display Indication	Time & Speed	Temperature, Time & Speed
Speed Range	200-1500rpm	
Maximum Stirring Volume	2000ml	
Timing range	0-999min	
Display	LCD	
Control method	Knob type	
Plate size	130mm Ø	
Power Supply	AC 220V / 50-60Hz	
Dimension & Weight	345 x 225 x160mm & Weight 2kg	

* Specifications are subject to change without Notice