


FEATURES
PS650

- ◆ Touch screen display - 4.3 inches TFT.
- ◆ User Password Protection available.
- ◆ Microprocessor controlled and completely programmable.
- ◆ Large LCD display with Time setting .
- ◆ Temperature Indicator and controller.
- ◆ Auto-tuning for convenience and optimal processing efficiency.
- ◆ Variable Power Output control.
- ◆ Auto frequency tracking.
- ◆ Output amplitude 0-100% adjustment.
- ◆ Automatic fault alarm.


SPECIFICATIONS
HSN : 84798200

PRODUCT NAME	PROBE SONICATOR
MODEL	PS650
Frequency	20-25KHz - Automatic tracking
Process capacity	0.5-500ml (approx.)
Standard Probd (Titanium Alloy)	6mm (1/4") Standard
Display	4.3 inches TFT
Display Function	Temperature, Power, Time, etc.
Temperature range(°C)	0-99°C
Timer (Selectable)	Yes
Overload Protection	Yes
User Password Protection	Available
Input method & Data Memory	Touch screen control & 20 groups
Output Power	6.5-650W (adjustable)
Power supply	AC 220V /50HZ
Dimension LxWxH & Weight	490 x 370 x 280mm & 10 kg + 5kg (Sound Proof Enclosure)

Optional Probe : 2mm, 3mm, 8mm, 10mm, 12mm

* Specifications are subject to change without Notice