

FEATURES
SVP20, SVP50, SVP100, SVP200, SVP1000, SVP5M, SVP10M

- ◆ An ergonomic handle hook design for easy grip in the palm.
- ◆ Unique design for the tip eject button.
- ◆ A clear reading window.
- ◆ The pipette can be half autoclaved at 121°C.
- ◆ A tip one made of durable chemical materials, with excellent chemical corrosion resistance.
- ◆ Ease of calibration and maintenance.
- ◆ Availability for high temperature and high pressure. disinfection of part of the device.


SPECIFICATIONS
HSN : 90275090

PRODUCT NAME SINGLE CHANNEL DIGITAL PIPETTES																						
MODEL	SVP20			SVP50			SVP100			SVP200			SVP1000			SVP5M			SVP10M			
Volume Range	2-20μl			5-50μl			10-100μl			20-200μl			100-1000μl			1-5ml			1-10ml			
Increment	0.5μl			0.5μl			1μl			1μl			5μl			0.05ml			0.1ml			
Test Volume	μl			μl			μl			μl			μl			ml			ml			
	20	10	2	50	25	5	100	50	10	200	100	20	1000	500	100	5	2.5	1	10	5	1	
Accuracy % ±	0.90	1.20	3	0.60	0.90	2	0.80	1	3	0.60	0.80	3	0.60	0.70	1.5	0.50	0.60	0.70	0.60	0.8	3	
Accuracy μl ±	0.18	0.12	0.06	0.3	0.225	0.1	0.8	0.5	0.3	1.2	0.8	0.6	6	3.5	2	25	15	7	60	60	30	
Precision % ≤	0.40	1.00	2.00	0.30	0.60	2	0.15	0.40	1.50	0.15	0.30	1.00	0.20	0.25	0.70	0.15	0.30	0.30	0.20	0.30	0.60	
Precision μl ≤	0.08	0.1	0.04	0.15	0.15	0.1	0.15	0.2	0.15	0.3	0.3	0.2	2	1.25	0.7	7.5	7.5	3	20	15	6	
Dimension	275 ×75×45 mm																					
Gross weight	190g																					

The DIGITAL PIPETTE is a continuously adjustable, General purpose pipette for sampling and dispensing accurate liquid volumes. It Operates on an air displacement principle and uses detachable, disposable tips. The adjusted delivery volume is displayed digitally on a numeric readout window on the handle.

* Specifications are subject to change without Notice