

FEATURES
TEC3 & TEC4

- ◆ Ip67 Waterproof level, can float on the water surface
- ◆ Electrode module can be replaced, Long Life Usage.
- ◆ Auto OFF Function.
- ◆ Double Line LCD Display.
- ◆ Temperature Compensation.
- ◆ TEC3 - For Pure Water Measurement.
- ◆ TEC4 - For Normal Solution Measurement.

TEC3

TEC4

Applications

Laboratories, Environmental Monitoring, Food processing, conventional water or sewage, chemical industry Hydroponics, aquaculture, aquariums, swimming pools, spa, resorts, etc...

SPECIFICATIONS
HSN : 90275090

PRODUCT NAME	POCKET CONDUCTIVITY TESTER	
MODEL	TEC3	TEC4
Conductivity Range	0.0-199.9 $\mu\text{S}/\text{cm}$	0-1999 $\mu\text{S}/\text{cm}$
Resolution	0.1 $\mu\text{S}/\text{cm}$	1 $\mu\text{S}/\text{cm}$
Calibration Point	146 μS (0.1mol/KCL)	1413 μS (0.01mol/KCL)
Precision	$\pm 1.5\%$ FS	
Temp.Range & Resolution	0.0-99.9°C & 0.1°C	
Temperature Accuracy	$\pm 0.5^\circ\text{C}$	
Temperature Compensation	Yes	
Non Volatile Memory	Yes (Last Measurement)	
Ambient temperature	10°C-50°C	
Display	Double-line LCD display	
Battery	4 x 1.5V coin cell batteries	
Packing Dimension (LxWxH)	170 x 37 x 37mm	
Gross Weight	90g	

* Specifications are subject to change without Notice