

FEATURES

- ◆ Ip67 Waterproof level, can float on the water surface.
- ◆ Electrode module can be replaced, Long Life Usage.
- ◆ Auto OFF Function.
- ◆ Double Line LCD Display.
- ◆ Temperature Compensation.

Applications

Laboratories, Environmental Monitoring, Food processing, conventional Water or sewage, chemical industry Hydroponics, aquaculture, Aquariums, Swimming Pools, Spa resorts, etc...

TTDS5

TSA6

HSN : 90275090
SPECIFICATIONS

PRODUCT NAME	POCKET TDS TESTER	
MODEL	TTDS5	TSA6
Detection Parameters	TDS /°C	Salinity /°C
TDS Range	0-1000 mg/l (ppm)	0.0 - 50 ppt
Resolution	1 mg/l (ppm)	0.1 ppt
Accuracy	±1.5% FS	± 5% FS
Calibration Data	73.3mg/l, (0.001mol/l KCl)	6.7ppt (0.1mol/l, KCl) 0-20ppt
		46.3ppt (5% NaCl) >20ppt
Temp. range & Resolution	0.0-99.9°C & 0.1°C	
Temperature Accuracy	± 0.5°C	
Temperature compensation	Yes	
Ambient Temperature	10-50°C	
Display	Double-line LCD display	
Battery	4 x 1.5V coin cell batteries	
Dimension & Weight	170 x 37 x 37mm & 90g	

* Specifications are subject to change without Notice