

PRODUCT LITERATURE 2024

Ultrasonic Cleaner - UC SERIES

FEATURES

- Inner Tank & Outer body made of Stainless Steel.
- Digital Control.
- RED LED display.
- Heating Temperature RT+5 ~ 80°C.
- Temperature with timer function.
- Drainage and cool fan available in 6L to 24L.
- LID & Basket as Standard Supply.





UC3, UC6, UC9, UC12, UC25

SPECIFICATIONS HSN: 84562000

MODEL	UC3	UC6	UC9	UC12	UC25
Tank Capacity (Approx.)	2.5L	5L	8L	11L	24L
Tank Size (mm)	240x140x100	300×155×150	300×240x150	330×300×150	500×300×200
Overall Size (mm)	270x170x240	330×180×310	330×270×310	360×330×310	550×330×360
Ultrasonic Power	100W	150W	200W	300W	500W
Heating power	100W	300W	300W	400W	500W
Tank Drain	NA Drain Valve				
Time Setting	1-99 min.				
Heating Temp.	RT. +5 ~ 80°C				
Display	Digital RED LED				
Frequency	40kHz				
Lid Material & Inner Tank Material	SS 304				
Outer Tank Material	SS 201				
Power Supply	AC 220V / 50 Hz				
Weight (approx.)	4 kg	7.5 kg	9 kg	12 kg	17 kg

Ultrasonic Cleaners available from 2.5ltrs to 24trs capacity