

ENGINE OIL SAE 10W40

(High performance Semi-Synthetic Engine Oil)



DESCRIPTION

PATROL Semi Synthetic Motor Oil series are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

APPLICATIONS

PATROL Semi Synthetic Motor Oil are formulated to give you confidence of protection beyond that of conventional oils. Particularly recommended for Latest gasoline engine technologies, Passenger cars, SUV's, light trucks and vans, Normal to severe operating conditions, Turbo-Chargers & High-Performance Engines.

PROPERTIES

PATROL Semi Synthetic Motor Oil are high performance industry proven product, so you can trust that you will get the performance you want from your vehicle. Low friction semi-synthetic formulation increases engine efficiency and offers greater fuel economy & also helps to promote long engine life.

PRODUCT BENEFITS

- Superior engine protection during start-up
- Superior engine wear protection
- Minimizes sludge formation
- Reduces wear by controlling soot deposits
- Extension of engine's lifetime
- Reduced high temperature engine deposits
- Reduces wear due to advanced base oils
- Can be used in both Diesel & LPG engines
- Provides improved fuel economy
- Suitable for hydraulically actuated injectors
- Safe for wet clutch motorcycles
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures



RECOMMENDATIONS / SPECIFICATIONS

MEETS OR EXCEEDS

API SL

TYPICAL TECHNICAL PROPERTIES

| Kinematic Viscosity at 40°C, mm²/s, ASTM D445 | 92 |
|---|------|
| Kinematic Viscosity at 100°C, mm²/s, ASTMD445 | 14.4 |
| Viscosity Index, ASTM D2270 | 154 |
| Flash Point (COC), °C, ASTM D92 | 230 |
| Pour Point, °C, ASTM D97 | -36 |
| Total Base Number, mg KOH/g, ASTM D2896 | 8.7 |
| Sulphated Ash, %wt., ASTM D874, max | 1.25 |
| | |

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.













