

PATROL OIL PCMO

SAE 10W-40 API SL



PRODUCT DESCRIPTION

Patrol Oil SAE 10W-40 API SL is a high-quality multigrade gasoline engine oil formulated to provide reliable protection and performance in passenger cars and light-duty vehicles. It offers good wear protection, engine cleanliness, and oxidation resistance under a wide range of operating conditions.

APPLICATIONS

- Gasoline passenger car engines
- Light commercial vehicles
- Engines operating under normal to severe driving conditions
- Suitable where API SL or earlier gasoline specifications are recommended

FEATURES & BENEFITS

- Good protection against engine wear and deposits
- Maintains engine cleanliness and performance
- Good oxidation and thermal stability
- Reliable performance over extended drain intervals
- Good low-temperature flow and high-temperature protection

PERFORMANCE STANDARDS / OEM REFERENCES

- API SL
- ACEA A3 / B3, A3 / B4
- Mercedes-Benz MB 229.1
- Volkswagen VW 501 01 / 505 00
- BMW Special Oil
- Renault RN 0700 / 0710 (earlier requirements)

TYPICAL PROPERTIES

PROPERTY	METHOD	UNIT	TYPICAL VALUE
SAE Grade	SAE J300	-	10W-40
Kinematic Viscosity @ 40°C	ASTM D445	cSt	85–95
Kinematic Viscosity @ 100°C	ASTM D445	cSt	13.5–15.0
Viscosity Index	ASTM D2270	-	150–160
Flash Point (COC)	ASTM D92	°C	220–235
Pour Point	ASTM D97	°C	-30
Density @ 15°C	ASTM D4052	kg/m ³	860–870

Note: These characteristics are typical of current production. While future production will conform to PATROL's specification, variations in these characteristics may occur.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment

